

RESTRICTED USE PESTICIDE

Due to Acute Toxicity and because this product contains arsenic compounds some types of which have been associated with tumor development in humans.

For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators certification.

HICKSON

Arsenic Acid 75%

KEEP OUT OF REACH OF CHILDREN

DANGER



POISON

CAUSES SEVERE EYE AND SKIN BURNS. FATAL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED.

FIRST AID:

EYE CONTACT: Immediately flush with large amounts of water for at least 15 minutes. Immediately seek medical aid.

SKIN CONTACT: Immediately flush area with large amounts of water. Remove contaminated clothing. Immediately seek medical aid.

INHALATION: Remove from exposure. If breathing has stopped or is difficult, administer artificial respiration or oxygen as indicated. Seek medical aid.

INGESTION: Immediately seek medical aid. Do not induce vomiting. Give 1 glass of milk or 1 to 2 oz. (30 to 60 g) of activated charcoal in water to victims as tolerated. Do not attempt to give anything by mouth to an unconscious person.

INGREDIENTS:

Active Ingredients:	
Arsenic Acid H ₃ AsO ₄	75.00%
Inert Ingredients: Water	25.00%
Total:	100.00%

(Total Arsenic, expressed as metallic, all in water soluble form 39.58%)

EPA Reg. No. 62190-7

EPA Est.-No. 62150-GA-001
Conley, Georgia

EPA Est.-No. 62100-IN-001
Valparaiso, Indiana

EPA Est. No. 62190-WA-001
Kalama, Washington

NET CONTENTS:

POUNDS

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

DANGER

Do not get in eyes, on skin or on clothing.

Wear face shield, plastic gown with long sleeves and plastic gloves when handling. In case of contact, immediately remove all contaminated clothing, including shoes, and flush skin with plenty of water for at least 15 minutes.

Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure limits.

Provide wash skin thoroughly with soap and water after handling.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g., cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves and boots, impervious to the wood treatment formulation.

In addition, individuals who enter pressure-treatment cylinders must wear properly fitting, well-maintained, high efficiency filter respirators, MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10ug/m³) averaged over an 8-hour work period.

Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

Wash thoroughly after skin contact and before eating, drinking, use of tobacco products or using restrooms.

Protective clothing* must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots and equipment at the plant. Worn out protective clothing and workshoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with state and Federal regulations.

*Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets and boots) required during application and handling of inorganic arsenicals are vinyl polyvinyl chloride (PVCs), neoprene, NBR (Buna-N) and polyethylene.

AIR QUALITY MONITORING
Individuals in the work area of an arsenical wood treatment plant must wear properly fitting, well maintained, high efficiency filter respirators, MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10ug/m³) averaged over an 8-hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

ENVIRONMENTAL HAZARDS
Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge

Elimination Systems (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Contents for use only in pressure-treating wood products when mixed with other components in accordance with the American Wood Preservers Association Standards. Cannot be used in concentrated form. DO NOT attempt to use without reading the product Technical Data Sheet, and having the necessary safety equipment.

Refer to label attachment. Permissible Exposure Limit (PEL) Monitoring Program for additional information concerning the use of this product.

STORAGE

STORAGE: Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame. Close container after each use.

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant it to be fit for the normal purposes for which such goods are used. We assume no responsibility that this material is fit for any particular purposes outside the general purposes of goods of the description.

Hickson Corporation
1955 Lake Park Dr., Ste. 250,
Smyrna, GA 30080
MADE IN U.S.A.

Medical Emergencies 404-616-9000 Reg. No. 62190-7
Others call: 404-363-6300

ACCEPTED

JUL - 6 1999

Under the Federal Insecticide, Fungicide, and
Herbicide Act as amended, for the
pesticide registered under

62190-7

PM 34

62190-7

7-6-99

104