

4/5/96

PM 21

62190-8

Pg 1/2

Please read instructions on reverse before completing form. Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States Environmental Protection Agency Washington, DC 20460

<input type="checkbox"/>	Registration
<input type="checkbox"/>	Amendment
<input checked="" type="checkbox"/>	Other

OPP Identifier Number	251674
-----------------------	--------

Application for Pesticide - Section I

1. Company/Product Number Hickson Corporation/62190-8	2. EPA Product Manager Connie Welch/Team 21	3. Proposed Classification <input type="checkbox"/> None <input checked="" type="checkbox"/> Restricted
4. Company/Product (Name) Wolman Concentrate 72%/Tanalith (CCA Type C).	PM# 21	
5. Name and Address of Applicant (Include ZIP Code) Hickson Corporation 3941 Bonsal Road Conley, Georgia 30027 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

NOTIFICATION APR 23 1996

Explanation: Use additional page(s) if necessary. (For section I and Section II.)
Notification to add Spanish language to the Tanalith (CCA Type C) Concentrate 72% label and To add Portuguese to its alternative Wolman label. Spanish and Portuguese portions of the two brand names for this product are generic and interchangeable between the two labels.

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Metal Plastic Glass Paper Other (Specify) _____		
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container		
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Freda Griffis	Title Environmental, Health & Safety Engineer	Telephone No. (Include Area Code) 404/362-3970
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Vice President, Technical & Environmental Services	
4. Typed Name William J. Baldwin	5. Date 2/1/96	

282

HICKSON

Wolman® Concentrate 72%

For Industrial Use Only
KEEP OUT OF REACH OF CHILDREN

DANGER



POISON

RESTRICTED USE PESTICIDE

DUE TO ACUTE TOXICITY AND BECAUSE THIS PRODUCT CONTAINS ARSENIC AND/OR CHROMIUM COMPOUNDS SOME TYPES OF WHICH HAVE BEEN ASSOCIATED WITH TUMOR DEVELOPMENT IN HUMANS

For retail sale to and use only by certified applicators or persons under their direct supervision and only for those uses covered by the certified applicator certification.

APPLICATOR SAFETY

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g., cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves and boots, impervious to the wood treatment formulation. In addition, individuals who enter pressure-treatment cylinders must wear properly fitting well maintained high efficiency filter respirators, MSHA/NIOSH - approved for inorganic arsenic, of the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10 µg/m³) averaged over an 8 hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

Wash thoroughly after skin contact and before eating, drinking, use of tobacco product or using restrooms.

Protective clothing* must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots and equipment at the plant. Worn out protective clothing and workshoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with state and Federal regulations.

*Examples of acceptable protective clothing (e.g., gloves, overalls, jackets and boots) required during application and handling of inorganic arsenicals are vinyl, polyvinyl chloride (PVC), neoprene, NBR (Buna-N) and polyethylene.

AIR QUALITY MONITORING

Individuals in the work area of an arsenical wood treatment plant must wear properly fitting, well maintained high efficiency filter respirators. MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10 µg/m³) averaged over an 8 hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Processes used only to apply inorganic arsenical formulations shall leave no visible surface deposits on the wood, as defined by AWPB Standard C-1 and AWPB Standards LP2 and LP22. (Visible surface deposits means a surface residue or crystallization on the treated wood. Small isolated or infrequent spots of chemical on otherwise clean wood shall be allowed.)

Refer to label attachment, "Permissible Exposure Limit (PEL) Monitoring Program" for additional information concerning the use of this product.

FATAL IF SWALLOWED, ABSORBED THROUGH THE SKIN, OR THE MIST BREATHED IN. CAUSES SEVERE BURNS TO THE EYES AND SKIN.

Directions:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Contents for use only in pressure-treating forest products. Cannot be used in concentrated form. DO NOT attempt to use without reading the manual and having the necessary safety equipment. To be used only in pressure impregnation of forest products utilizing water solutions having concentrations ranging from 0.6 percent to 10.0 percent by weight. Impregnation procedures must rigidly adhere to the current specifications by Hickson Corporation and/or those of the American Wood Preservers Association.

Pressure treatment of forest products with time-tested Wolman Preservative provides wood in all its forms with "built-in" protection against termites, ascomycetes, white rot, brown rot and dry rot.

Ingredients:

Active Ingredients:

Chromic Acid (CrO ₃)	34.20%
Cupric Oxide (CuO)	13.32%
Arsenic Pentoxide (As ₂ O ₅)	24.48%

Inert Ingredients:

Water	28.00%
Total	100.00%

Arsenic content is 15.98% as elementary As.

E.P.A. Reg. No. 62190-8

E.P.A. Est. 62190-GA-001

Spills:

In case of spillage, treat with 99 pounds (45 kg.) of lime and 375 pounds (170 kg.) of cement per 100 kg. of spill. Dispose of in accordance with local, state, and federal applicable regulations.

STORAGE AND DISPOSAL

STORAGE: Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations. Do not contaminate water, food, or feed by storage and disposal.

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact you State Pesticide or Environmental Control Agency, or the Hazardous Waste representatives at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

Triple rinse (or equivalent). Then offer recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS - DANGER -

Do not get in eyes, on skin, on clothing. Wear face shield, plastic gown with long sleeves and plastic gloves when handling. WASH THOROUGHLY AFTER USING. Avoid breathing mist. Keep container closed. USE ONLY WITH ADEQUATE VENTILATION.

FIRST AID:

CALL A PHYSICIAN.


If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

In case of contact, immediately remove all contaminated clothing and shoes while flushing the skin or eyes with plenty of water for at least 15 minutes. Call a physician immediately.


If inhaled, remove to fresh air. Call a physician immediately.

ENVIRONMENTAL HAZARDS:

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.



NET CONTENTS



WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant it to be fit for the normal purposes for which such goods are used. We assume no responsibility that this material is fit for any particular purpose outside of the general purposes of goods of the description.

Sold by Hickson Corporation, Atlanta, GA 30342
MEDICAL EMERGENCIES: 1-404-616-9000 OTHERS CALL: 1-404-363-6300

MADE IN U.S.A. HCPL15-R003-2-96