



Office of Pesticide Programs
Registration Division (M7505C)
401 "M" St., S.W.
Washington, D.C. 20460

Number:
62190-14 03/08/96

Term of Issuance:
Conditional

Name of Pesticide Product:
Wolmanac Concentrate
60%

NOTICE OF PESTICIDE:
 X Registration
 Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the following label changes:

a. Revise the EPA Registration Number to read, "EPA Reg. No. 62190-14".

b. Since the percentage of arsenic pentoxide in this product is less than that in Wolmanac Concentrate 72%, the statement of arsenic content which appears below the ingredients statement must be revised to indicate the correct percentage of arsenic as elementary arsenic for this product. (continued on page 2)

Signature of Approving Official:

Connie B. Welch
Connie Welch, Product Manager 21

Date:

March 8, 1996

293

Page 2
EPA Reg. No. 62190-14

3. Submit five copies of the revised final printed label for the record.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

323

HICKSON

Wolmanac

Talith[®] (CCA Type C)
Concentrate 72%
60%

RESTRICTED USE
DUE TO ACUTE TOXICITY AND
CONTAINS ARSENIC AND/OR CH
TYPES OF WHICH HAVE BEEN
DEVELOPMENT IN HUMANS
For retail sale to and use only by
under their direct supervision and or
certified applicator certification.

For Industrial Use Only
KEEP OUT OF REACH OF CHILDREN

DANGER  **POISON**

FATAL IF SWALLOWED, ABSORBED THROUGH THE SKIN, OR
THE MIST BREATHED IN. CAUSES SEVERE BURNS TO THE
EYES AND SKIN.

Directions:
It is a violation of Federal law to use this product in a manner in-
consistent with its labeling.

Contents for use only in pressure-treating forest products. Can-
not be used in concentrated form. DO NOT attempt to use
without reading the manual and having the necessary safety
equipment. To be used only in pressure impregnation of forest
products utilizing water solutions having concentrations ranging
from 0.5 percent to 10.0 percent by weight. Impregnation pro-
cedures must rigidly adhere to the current specifications by
Hickson Corporation and/or those of the American Wood Pres-
ervers Association.

Pressure treatment of forest products with time-tested Wolman
Preservative provides wood in all its forms with "built-in"
protection against termites, ascomycetes, white rot, brown rot
and dry rot.

Ingredients:

Active Ingredients:	
Chromic Acid (CrO ₃)	28.50% 31.00%
Cupric Oxide (CuO)	20.40% 13.33%
Arsenic Pentoxide (As ₂ O ₅)	1.10% 2.00%
Inert Ingredients:	
Water	40.00% 53.67%
Total	100.00%

Arsenic content is 15.96% as elementary As.
E.P.A. Reg. No. 62190-B
E.P.A. Est. 62190-GA-001

Spills:
In case of spillage, treat with 99 pounds (45 kg.) of lime and 375
pounds (170 kg.) of cement per 100 kg. of spill. Dispose of in ac-
cordance with local, state, and federal applicable regulations.

STORAGE AND DISPOSAL

STORAGE: Keep closures tight and upright to prevent leakage. Keep
container closed when not in use. In case of spillage, absorb and
dispose of in accordance with local applicable regulations. Do not
contaminate water, food, or feed by storage and disposal.

PESTICIDE DISPOSAL:
Pesticide wastes are acutely hazardous. Improper disposal of excess
pesticide, spray mixture, or rinsate is a violation of Federal Law. If
these wastes cannot be disposed of by use according to label in-
structions, contact your State Pesticide or Environmental Control
Agency, or the Hazardous Waste representative at the nearest EPA
Regional Office for guidance.

CONTAINER DISPOSAL:
Triple rinse (or equivalent). Then offer recycling or reconditioning,
or puncture and dispose of in a sanitary landfill, or by other pro-
cedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS:

**HAZARDS TO HUMANS AND DOMESTIC
ANIMALS - DANGER -**
Do not get in eyes, on skin, on clothing. Wear face shield, plastic
gown with long sleeves and plastic gloves when handling. WASH
THOROUGHLY AFTER USING. Avoid breathing mist. Keep con-
tainer closed. USE ONLY WITH ADEQUATE VENTILATION.

FIRST AID:
CALL A PHYSICIAN.
If swallowed, drink promptly a large quantity of milk, egg whites,
gelatin solution or if these are not available, drink large quantities
of water. Avoid alcohol. Call a physician immediately.
In case of contact, immediately remove all contaminated clothing
and shoes while flushing the skin or eyes with plenty of water for
at least 15 minutes. Call a physician immediately.
If inhaled, remove to fresh air. Call a physician immediately.

ENVIRONMENTAL HAZARDS
Do not discharge effluent containing this product into lakes,
streams, ponds, estuaries, oceans or other waters unless in
accordance with the requirements of a National Pollutant
Discharge Elimination System (NPDES) permit and the permitting
authority has been notified in writing prior to discharge. Do not
discharge effluent containing this product to sewer systems
without previously notifying the local sewage treatment plant
authority. For guidance contact your State Water Board or
Regional Office of the EPA.

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass
in the trade for goods within the description, and further warrant it to be fit for the normal purposes for which such goods are used. We assume no
responsibility that this material is fit for any particular purpose outside of the general purposes of goods of the description.

Sold by Hickson Corporation, Atlanta, GA 30342

MEDICAL EMERGENCIES: 1-404-616-9000 OTHERS CALL 1-404-363-6300

MADE IN U.S.A.

BEST AVAILABLE COPY

APPLICATOR SAFETY

Applicators must wear gloves impervious
situations where dermal contact is expected
and manually opening cylinder doors).

Individuals who enter pressure treatment
that is contaminated with the wood treat-
operation or are not free of the treatment
including overalls, jacket, gloves and boots
formulation. In addition, individuals who
must wear properly fitting well maintained
NIOSH-approved for inorganic ar-
the plant is unknown or exceeds 10 micro-
averaged over an 8-hour work period. Air
record retention and submission must
instructions on the attached labeling material.

Applicators must not eat, drink, or use toilet
Application process that may expose them
(e.g., manually opening/closing cylinders,
mixing chemicals, and handling freshly

Wash thoroughly after skin contact and
product or using restrooms.

Protective clothing must be changed
Applicators must leave protective clothing
ment at the plant. Wear out protective clothing
left at the plant and disposed of in a manner
in accordance with state and Federal regulations.

Examples of acceptable protective clothing
boots) required during application and handling
polyvinyl chloride (PVC), neoprene, NBR

AIR QUALITY MONITORING

Individuals in the work area of an air
properly fitting, well maintained high efficiency
approved for inorganic arsenic, if the level
unknown or exceeds 10 micrograms per
over an 8-hour work period. Air moni-
toring and submission must be conducted
on the attached labeling material.

Processes used only to apply inorganic
visible surface deposits on the wood.
AWPB Standards LP2 and LP22 (Vis-
residue or crystallization on the treated
of chemical on otherwise clean wood surface.

Refer to label attachment, "Permissible
gram" for additional information.
In EPA 1

3-8

Under the Fe
Fungicide, and
ag. amended.
Registered only
68190

HOPL45-R002-795