

U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (7505C) 401 "M" St., S.W. Washington, D.C. 20460

EPA Reg. Number:

Date of Issuance:

62190-15 Term of Issuance: 08/14/96

NOTICE OF PESTICIDE:

<u>x</u> Registration

Reregistration

(under FIFRA, as amended)

Conditional

Name of Pesticide Product:

Hickson TuBor

Name and Address of Registrant (include ZIP Code):

Hickson Timber Protection Hickson Corporation Technical Center 3941 Bonsal Road Conley, GA 30027

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

- Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
 - Make the following label changes:
 - a. Revise the EPA Registration Number to read, "EPA Reg. No. 62190-15".
 - b. On the front panel, add the appropriate signal word beneath Keep Out of Reach of Children. Note that both the signal word and Keep Out of Reach of Children are required on the front panel and must be of the type size stated in the regulations (40 CFR 156.10).

Signature of Approving Official:

Connie B. Welch

August 14, 1996

page 2 EPA Reg. No.

- c. Under Environmental Hazards, delete the references to effluents. Effluent statements are appropriate only for manufacturing use products. There would be no effluent of this product when used according to label directions.
- 3. Submit five copies of the revised final printed label for the record.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped "Accepted" copy of the label will be provided for your records as soon as you submit your label revised according to the conditions identified above, and it is reviewed a determined to be acceptable.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION

Harmful if swallowed or absorbed through skin.
Causes eye 'trilation. Avoid contact with skin, eyes or clothing. Wash thoroughly with scap and water after handling.

STATEMENT OF PRACTICAL TREATMENT IF SWALLOWED: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce wornling. Do not induce vornifing or attempt to give anything to an unconscious person.

IF IN EYES: Flush with large amounts of water. Call a physician if irritation persists.

IF ON SKIN: Wash with scap and water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS

Do not coalaminate water when disposing of equipment or washwaters. For guidance, contact your local or State Water Board or Regional Office of the EPA...


STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store in a dry place. Do not store where children or animals may gain access. In case of spli, sweep or scoop up and remove.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on-site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Completely empty packaging and dispose of it in a sanitary landfit or by incineration.



registered under EPA Reg. No. ()

Hickson TuBor

A REMEDIAL POLE TREATMENT FOR PREVENTION AGAINST FUNGAL DECAY AND WOOD EATING INSECTS FOR COMMERCIAL USE ONLY

Active ingredient:
Boric Acid (H₃BO₃) 100.00%
[Boric Oxide (B₂O₃) Equivalent 58.3%]

100% boric acid contained in water soluble packaging to be used as a treatment for poles in service.

NET CONTENTS POUNDS

Manufactured by: Hickson Corporation 1955 Lake Park Drive Suite 250 Smyrna, Georgia 30080

EPA Registration No.: 62190-15 EPA Establishment No: 62190-GA-001

Manufactured at: Hickson Corporation 2852 Raystone Drive Valparaiso, Indiana 46384

Establishment No.: 62190-IN-001

See side panels for precautionary statements, environmental hazards, and directions for use.

KEEP OUT OF REACH OF CHILDREN

CAUTION

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its tabeling.

WOOD AND WOOD PRODUCTS

HICKSON TuBor gel caps and paper tubes encapsulating this pesticide are designed for use as remedial protection of wood and wood products (e.g. poles, crossties, timbers, pillings) against fungal decay and wood eating insects.

The rate of application for TuBor is dependent upon the volume of wood to be treated. In general, the rate of application for TuBor is 8.0 ounces Boric Acid Equivalent per cubic foot for the remedial treatment of wood and 2.0 ounces Boric Acid Equivalent per cubic foot for the preventive treatment of wood. TuBor contains 1.0 ounce of Boric Acid Equivalent per ounce. TuBor is designed to be placed inside the wood to be treated. The method is as follows:

- Drill the predetermined number of holes 1/16" larger than TuBor
- Insert the correct amount of TuBor needed into the pre-drilled holes (determined from area to be treated)
- Close holes with treated plugs, caulk, or filler.

Locations for placement of TuBor should be in the general vicinity of the greatest potential for decay to occur. In structural wood, TuBor should be inserted in a staggered pattern over the affected length of the wood to be treated.