PM

SEP 27 1999

Under the Federal Insecticide, Fungicida, and Rodenticide Act, as amended, for the pesticide

registered under BPA Reg. No. 6 03

2190-19

62190 - 19 Hickson BA

page 121

A Component for the Preparation of Hickson Wood Shield Wood Preservative ACCEPTED For Industrial Use Only

INGREDIENTS:

Active Ingredients:

Boric Acid

100%

9/27/49

KEEP OUT OF REACH OF CHILDREN

CAUTION

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Call a physician or Poison Control Center. 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. If person is unconscious, do not give anything by mouth and do not induce vomiting.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

IF ON SKIN: Wash thoroughly with soap and water. Wash contaminated clothing before reuse.

IF IN EYES: Flush eyes with plenty of water. Call a physician if irritation persists.

NET CONTENTS: 100 pounds

To be used with Hickson BX and water to formulate treating solutions of Hickson Wood Shield

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Contents fr yse only in pressure-treating wood products. To be used c in vacuum pressure impregnation of wood products utilizing water solutions and Hickson BX having concentrations of Hickson BA and BX ranging from 1.5 percent to 3.0 percent by weight. Impregnation procedures must rigidly adhere to the current specifications of Hickson Corporation and/or the American Wood-Preservers' Association.

Processes used to apply Hickson BA formulations shall leave no visible surface deposits on the wood, as defined by AWPA Standard P5-96. Visible surface deposits means a surface residue or crystallization on the treated wood. Small isolated or infrequent spots of chemical on otherwise clean wood shall be allowed.

Pressure treatment of wood products with this boric acid wood preservative provides wood with protection against termites, ascomycetes, white rot, brown rot and dry rot.

STORAGE AND DISPOSAL: Store in a cool, dry and wellventilated area. Keep in tightly closed containers. Store away from incompatible materials. Protect containers from physical damage. Observe all applicable local, state, federal guidelines for storage and disposal. PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS'



Harmful if swallowed or inhaled. Causes eye irritation. Avoid contact with eyes or clothing. Avoid breathing dust. Wash thoroughly with soap and water after handling. Remove contaminated clothing before use.

Good industrial hygiene practices, such as eye protection from dust, fumes or splashes, general or local exhaust ventilating, use of a full face respirator where needed, and washing hands with soap and water before eating, drinking or smoking, should be followed. Protective equipment, such as coveralls or aprons and gloves to prevent contamination of clothing and skin contact is recommended.

ENVIRONMENTAL HAZARDS: Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of EPA.

EPA Registration No.: 62190-19 Establishment No.: 62190-GA-001

Manufactured by Hickson Corporation, Smyrna, GA 30027 404-363-6300 Made in the USA

FOR MEDICAL EMERGENCIES: 1-800-837-0496 Outside USA: 404-616-9000

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant it to be fit for the normal purposes for which such goods are used. We assume no responsibility that this material is fit for any particular purpose outside of the general purposes of goods of the description.