



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

SEP 1 0 2014

Shelly Turula Regulatory Specialist Lonza Inc. 90 Boroline Road Allendale, NJ 07401

Subject:

Amended Reregistration Label

AntiBlu XP64

EPA Registration Number 62190-25

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the reregistration of the above referenced product in connection with the Propiconazole (REDs) and has concluded that your submission is acceptable.

NOTE: This product is not being reregistered under sections (c) 5 and 4(g) of FIFRA at this time.

Please note that the record for this product currently contains the Confidential Statements of Formulation (CSFs) listed below. Any previously dated CSFs are superseded.

Basic Formulation, dated 7/29/13

A copy of your label stamped "Accepted" is enclosed along with copies of the acute toxicity and product chemistry reviews completed for the subject product. Products shipped after 12 months from the date of this amendment or the next printing of the label whichever occurs first, must bear the new revised label. Your release for shipment of the product bearing the amended label constitutes acceptance of the conditions. If these conditions are not compiled with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e).

If you have any question about this letter, please contact Drusilla Copeland at copeland.drusilla@epa.gov.

Acting Product Manager 31
Regulatory Management Branch 1
Antimicrobials Division (7510P)

Enclosure: stamped label

NOW Lahur

AntiBlu® XP64

For the control of sapstain and mold on freshly sawn and seasoned wood and wood products

ACTIVE INGREDIENTS:

Propiconazole	4.0%
3-lodo-2-propynyl butylcarbamate	
Alkyl (60%C14, 30%C16, 5%C12, 5%C18) dimethyl benzyl ammonium chloride	25.0%
Alkyl (68%C12, 32%C14) dimethyl ethylbenzyl ammonium chlorides	25.0%
OTHER INGREDIENTS:	<u>40.0%</u>
TOTAL .	100.0%

DANGER

FIRST AID

IF IN EYES: Hold eye(s) open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue to rinse eye(s). Call a Poison Control Center or doctor for treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison Control Center or doctor for further treatment advice.

Have the product container or label with you when calling a Poison Control Center or doctor, or when going for treatment.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.


IN CASE OF EMERGENCY CALL: 1-800-654-6911

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA REG. NO. 62190-25 EPA EST NO. xxxxx-yy-zz

MANUFACTURED BY:
ARCH WOOD PROTECTION, INC.
360 Interstate North Parkway, Suite 450
Atlanta, GA 30339

NET CONTENTS: BATCH CODE: XXXXXX



Antiblu XP64 EPA Reg. No: 62190-25 EPA Draft Label: 2014-06-25

Page 1 of 4

4/6

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application. Not for food grade/food contact paper or paper board.

For Industrial and Commercial Use

APPLICATION DIRECTIONS

AntiBlu® XP64 may be applied to wood and wood products by immersion or spray methods according to the dilutions provided below. Dilution levels may vary widely and will depend on application methods, wood species, seasonal changes in exposure conditions, length of protection desired, and wood storage and transport conditions.

For spray applications: Mix one gallon of AntiBlu® XP64 to 10-50 gallons of water.

For immersion applications: Mix one gallon of AntiBlu® XP64 to 50-300 gallons of water.

For best results, apply AntiBlu XP64 to recently felled and fresh sawn or peeled wood ensuring total coverage. Allow treated wood to drain in a contained area before storage, and ensure that freshly treated wood is not allowed to remain unprotected in heavy rains.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Open dumping is prohibited. Keep container closed when not in use. Store in a dry, well ventilated area away from food or feed.

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING:

{Container less than or equal to 5 gallons}

Nonrefillable Container. Do not refill or reuse container. Triple rinse as follows: Fill container 1/4 full with water and recap. Shake for 10 seconds. Drain for 10 seconds after the flow begins to drip. Empty the rinsate into the application equipment or mix tank or store rinsate for later use or disposal. Repeat procedure two more times. Then offer for recycling or reconditioning. If not available, puncture and dispose in a sanitary landfill.

{5 gallons or more}

Nonrefillable Container. Do not refill or reuse container. Triple rinse as follows: Fill container 1/4 full with water. Tip container on its side and roll it back and forth, ensuring at least one complete revolution for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling or reconditioning. If not available, puncture and dispose in a sanitary landfill.

Antiblu XP64 EPA Reg. No: 62190-25 EPA Draft Label: 2014-06-25

Page 2 of 4

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: CORROSIVE, CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS. May be fatal if swallowed. Harmful if inhaled or absorbed through the skin. Do not get in eyes, on skin, or on clothing. Wear protective eyewear (goggles, face shield or safety glasses), protective clothing and gloves. Do not breathe vapor or spray mist. Wash thoroughly with soap and water after handling, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse.

Personal Protective Equipment (PPE)

Applicators and other handlers must wear:

- Coveralls over long-sleeved shirt and long pants,
- Chemical resistant footwear and socks,
- Chemical resistant gloves that are waterproof (such as: Barrier Laminate, or any of the following gloves at ~14 mils thickness: butyl nitrile, neoprene rubber, polyvinyl chloride or Viton)
- Protective eyewear: Goggles or face shield
- Dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21 C) or a NIOSH approved respirator with any N, R, P, or HE filter.
- When mixing, loading and cleaning equipment wear a chemical resistant apron. For overhead exposure wear chemical resistant head gear.

USER SAFETY REQUIREMENTS

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this products concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separate from other laundry.

USER SAFETY RECOMMENDATIONS

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing/PPE immediately if pesticide gets inside, then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic invertebrates. Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Observe the most restrictive of the labeling limitations and precautions of all products used in mixtures. Treated lumber must be stored under cover, or indoors, or at least 100 feet from any ponds, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored outdoors within 100 feet of a pond, lake, stream, or river must be either covered with plastic or surrounded by berm to prevent surface water runoff into the nearby water way. If a berm is used around the site, it must consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

Antiblu XP64 EPA Reg. No: 62190-25 EPA Draft Label: 2014-06-25

PHYSICAL OR CHEMICAL HAZARDS

Combustible. Do not use or store near heat or open flame. Incompatible with the oxidizing agent, 10% potassium permanganate and compatible with the other tested materials: zinc powder, ammonium phosphate, turpentine, carbon dioxide, and water.