

U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs Antimicrobials Division (7510P) 1200 Pennsylvania Ave., N.W. Washington, D.C. 20460

62190-44

Date of Issuance:

EPA Reg. Number:

7/17/25

NOTICE OF PESTICIDE:	:
----------------------	---

X Registration Reregistration

(under FIFRA, as amended)

Unconditional

Term of Issuance:

Name of Pesticide Product:

Wolmanac OD23

Name and Address of Registrant (include ZIP Code):

Arch Wood Protection Inc.

3941 Bonsal Road, Conley, GA 30288

Electronic Transmittal: teri.muchow@arxada.com

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA).

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is unconditionally registered in accordance with FIFRA section 3(c)(5) provided that you:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:	Date:	
Hoather a Yamie		
Heather Garvie, Senior Regulatory Advisor		
Regulatory Management Branch II, Antimicrobials Division	7/17/25	
(7510P)	, ,	

Page 2 of 2 EPA Reg. No. 62190-44 Action Case No. 00643180

- 2. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, "EPA Reg. No. 62190-44."
- 3. Submit one copy of the revised final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

• Basic CSF dated 5/01/2025

If you have any questions, please contact Kasey Chambers by phone at 202-566-0743, or via email at chambers.katelyn@epa.gov.

Enclosure: Stamped Final Label

HAZARD TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive. Causes irreversible eye damage and skin burns. May be fatal if inhaled. Harmful if swallowed. Harmful if absorbed through the skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Do not breathe vapors. Wear coveralls worn over long sleeve shirt and long pants, chemical-resistant footwear plus socks, rubber gloves, and protective eyewear. Wear a minimum of a NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and a combination R, or P filter, OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air-purifying respirator with OV cartridges and combination HE filters. When mixing and loading wear a chemical resistant apron. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

NOTE TO USER: Examples of acceptable materials for protective clothing (e.g., overalls, jackets, and boots) required during application and handling of Wolmanac OD23 are polyvinyl acetate (PVA), heavy PVC, butyl-viton, neoprene, nitrile, and rubber. In addition, plastic-coated disposable coveralls impervious to dust are acceptable for dust protections. Examples of acceptable chemical resistant gloves are Barrier Laminatte, Nitrile Rubber ≥ 14 mils, Neoprene Rubber ≥ 14 mils, and Viton≥ 14 mils.

USER SAFETY REQUIREMENTS

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them. Eating, drinking, and smoking are prohibited in the treatment cylinder load-out area, drip pad area, and engineering control room of the wood treatment facilities. EXCEPTION: Where treating operator control rooms are isolated from the treating cylinders, drip pad, and work tanks, eating, drinking, and smoking (depending on local restrictions) are permitted.

USER SAFETY INSTRUCTIONS

Users must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users must remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination Systems (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS

COMBUSTIBLE. Do not use or store near open flames. Close container after each use.

ACCEPTED

Batch Code:

07/17/2025

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 62190-44

Draft Label = 1/28/2025 6219

WOLMANAC ® OD23

ANTIMICROBIAL – WOOD PRESERVATIVE For the Industrial pressure/vacuum treatment of wood.

KEEP OUT OF REACH OF CHILDREN

DANGER/PELIGRO

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it

	to you in actait.)	
FIRST AID		
If in Eyes:	Hold eye open and rinse slowly and gently with water for 15-20 min. Remove contact lenses, if present, after first 5min. then continue rinsing eye. Call a poison control center or doctor for treatment advice	
If on Skin:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 min. Call a poison control center or doctor for further advice	
In Inhaled:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth. Call a poison control center or doctor for further advice.	
If Swallowed:	Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.	

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. For general information on product use, etc., call the National Pesticides Information Center at 1-800-858-7378. In case of an emergency, call CHEMTREC toll free at 1-800-424-9300. You may also contact the poison control center at 1-800-222-1222 for emergency medical treatment information.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

See side panel for additional precautionary statements

Manufactured by: Arch Wood Protection, Inc. 3941 Bonsal Road, Conley GA 30288

EPA Reg. No. 62190-XX EPA Est. No.: xxxxx

Net Contents: xxx gallons

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For use as a wood preservative to protect treated wood from fungi and subterranean termites. This product is a concentrate and must be diluted with solvent(s) such as benzyl alcohol, fuel oil, mineral spirits, diesel, biodiesel, or petroleum distillates prior to use

PRESSURE/VACUUM TREATMENT

Use Wolmanac OD23 in the pressure/vacuum treatment of wood products intended for ground contact applications, such as utility poles, distribution poles, cross arms, railroad ties, transportation (road or rail) bridge timbers, posts, crossties, switchties, glued laminated or mechanically fastened timber. Mix Wolmanac OD23 with solvent(s) to obtain 1.0% to 3.0% DCOIT in the final treatment solution. For example, to prepare a 1,000-gallon solution containing 3.0% DCOIT, combine 952 lbs of Wolmanac OD23 with enough solvent to make a 1,000 gallon solution. The minimum target retention is 0.1 pounds per cubic foot (pcf) DCOI in the wood.

All wooden members must be free of bark before receiving treatment.

At the conclusion of treatment, the cylinder must be ventilated by purging the post-treatment cylinder through fresh air exchange. The ventilation process is considered complete after a minimum of 2 volume exchanges based on the empty treatment cylinder volume. The exhaust pipe of the vacuum system or any air moving device utilized in conducting the air purge must terminate into a containment vessel such as a treating solution work tank or water/effluent tank.

The ventilation process may be accomplished by one of the following methods: 1) activating an air purge system that operates while the cylinder door remains closed; or 2) using a device to open and hold open the cylinder door (no more than 6 inches) to allow adequate ventilation and activating the vacuum pump. If the second method is utilized, at the conclusion of the treatment, no personnel may be located within 15 feet of the cylinder when open (cracked) until the cylinder has been ventilated. In the event of equipment malfunction, or to place the spacer to hold the door open during venting, only personnel wearing specified PPE are permitted within 15 feet of the cylinder prior to ventilation. After ventilation is complete, the cylinder door may be completely opened.

The treatment process must include a final vacuum to remove excess preservative from the wood. The final vacuum must attain a vacuum equal or greater than the initial vacuum. This vacuum must be held for an appropriate time based on wood species, retention levels, and commodity treated to remove excess preservative from the wood.

For elevated temperature pressure treatment with Wolmanac OD23, automatic, remotely operated devices must be used to open, close, lock and unlock cylinder doors. For ambient Wolmanac OD23 treatments, an automatic locking/unlocking device must be used to accomplish locking and unlocking of the cylinder door.

Cylinder openings and door pits must use grating and additional measures such as sumps, dams or other devices which prevent or remove spillage of the preservative.

Personnel must not directly handle the charge cables, poles or hooks used to retrieve charge cables, or other equipment that has contacted the preservative without wearing chemical resistant gloves.

Mechanical methods must be used to place/remove bridge rails.

POST TREATMENT HANDLING: After treatment, wood must be moved to a drip pad capable of recovering excess preservative until the wood is drip free.

NOTE: This product cannot be used to treat wood intended for direct continuous saltwater immersion. Wood treated with this product must not be used in interior applications, for packaging or other uses which will result in contact with food or feed, or in the manufacture of beehives.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment.

PESTICIDE STORAGE: Store in original container, preferably in a locked storage area inaccessible to children and pets. Keep away from heat and open flame. Keep product from freezing.

SPILL CONTAINMENT: In case of a spill or leak contain with absorbent materials and collect in suitable and properly labeled containers.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Triple rinse container promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with solvent. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.