ease read Instructions on reverse	before completing f		Form App	rovec	I. OMB No. 2070	0-0060	Approval expires 11-30-93
[^] "	Inited States Environr Office of Pesticide Washingto Applicatio	mental Protection Programs (H750 n, DC 20460 n for Pesti	Agency <u>Southan</u> SC) Cide:	- •	Registrati Amendmo Other	ion ent	OPP Identifier Number
		Section I					
Company/Product Number		2.	EPA Product Ma	nager		3. Pr	oposed Classification
62207-1			R. Douglas				
Company/Product (Name)		РМ	#			Ĺ	None Hestricted
Fex-Chlor			32				
Name and Address of Applicant (Inc. Fox Packaging; Co. 51 East Maryland Avenu St. Paul, NN 55117-46	i lude ZIP Code) 1e 515	6. (b) to EF	Expedited Re (i), my product	vlew. Is sin	. In accordanc nilar or identica	e with al in co	FIFRA Section 3(c)(3) emposition and labeling
Check if this is a new ac	ddress	D					
		Pro	DOUCT NAME				
	S						<u> </u>
Amondment - Explain below			Final printed	labeis r date	in response to d		
Resubmission in response to Age	ncy letter dated			dinati	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		
					J. 1.		
	· · · · · · · · · · · · · · · · · · ·		Other - explai	in bek	ow.		
Aseniment of Sfilldent	Discharge La	beling Sta	tement per		Motice 93	10.	
Material This Product Will Be Pac	Discharge La Se kaged In:	beling Sta	tement per	P:2	Motice 93	10.	
Material This Product Will Be Pac hild-Resistant Packaging Unit Pack	Discharge La Se kaged In: kaging	beling: Sta ection III Water Solu	tenent per		Motice 93	1().	
Material This Product Will Be Pac hild-Resistant Packaging Unit Pack	Discharge La Se kaged In: aging s	ection III Water Solu	tenent per		Motice 93	ntainer	
Material This Product Will Be Pac hild Resistant Packaging Unit Pack	Discharge La Se kaged In: saging s	ection III Water Solu Yes No	tement per		Motice 93	ntainer etal lassic	
Material This Product Will Be Pac hild-Resistant Packaging Unit Pack Yes* Yes No If "Yes,"	Discharge La Se kaged In: aging s No. pe	ection III Water Solu Yes No	tenent per ble Packaging No	P:R	Motice 93	ntainer letal lassc lass aper ther (S	Decity)
Allemant of shird went Material This Product Will Be Pack hild Resistant Packaging Yes* No Certification must be Unit Pack	Diachange La Se kaged In: kaging s No. pe age wgt. contain	ection III Water Solu Yes No er If "Yes," Package w	tenent per ble Packaging gt. cont	P:2	Motice 93	ntainer etal lastic lass aper ther (S	pecity}
Adventional of shirld went Material This Product Will Be Pac hild Resistant Packaging Yes* No Certification must be Submitted. Location of Net Contents Information	Diachange La Se kaged In: taging s age wgt. No. pe contain n 4. Size(s)	ection III Water Solu Yes No Package w	tement per ble Packaging gt. cont ner	per ainer	Motice 93	ntainer etal lastic lass aper ther (S	pecity}
Allemant of shird went Material This Product Will Be Pac hild Resistant Packaging Yes* No Certification must be submitted. Location of Net Contents Information Label Container	Diachange La Se kaged In: aging s age wgt. No. pe contain n 4. Size(s)	ection III Water Solu Yes No If "Yes," Package w	ble Packaging No gt. cont	per ainer	Notice 93	ntainer etal lassic lass aper ther (S	pecity)
Allemant of child went Material This Product Will Be Pac hild Resistant Packaging Yes* No Certification must be submitted. Location of Net Contents Information Label Container Manner in Which Label Is Affixed To	Diachange La Se kaged In: taging s age wgt. Contain n 4. Size(s) o Product Lit	ection III Water Solu Yes No er If "Yes," Package w i of Retail Contai	ble Packaging gt. Othe	per ainer	Motice 93	ntainer letal lastic lass aper ther (S I Direct accom	pecity} ions ipanying product
Material This Product Will Be Paci- hild Besistant Packaging Unit Pack Yes* Yes No If *Yes,* Unit Pack Submitted. Location of Net Contents Information Label Container Manner in Which Label Is Affixed To	Diachange La Se kaged In: saging s age wgt. No. pe contain n 4. Size(s) p Product Lit St	ection III Water Solu Yes No Package w of Retail Contai thograph aper glued enciled	ble Packaging gt. Cont ner Othe	per ainer	Motice 93	ntainer letal lassic lass aper ther (S I Direct	pecity) ions ipanying product
Alight control of the shift went Material This Product Will Be Pac hild Resistant Packaging Yes* No Certification must be Submitted. Location of Net Contents Information Label Container Manner in Which Label Is Affixed To	Diacharge La Se kaged In: age wgt. No. pe contain n 4. Size(s) p Product Lit Pa St	ection III Water Solu Ves No rr If 'Yes," Package w of Retail Contai thograph aper glued enciled Section IV	tement per ble Packaging gt. cont ner Othe	per ainer	Motice 93	ntainer etal lassic lass aper ther (S	pecify}ions
Adventionent of shift went Material This Product Will Be Pac hild Resistant Packaging Yes* No Certification must be Submitted. Location of Net Contents Information Label Container Manner In Which Label Is Affixed To Contact Point (Complete items direction)	Diaghange La Se kaged In: kaged In:	ection III Water Solu Yes No r If *Yes,* Package w of Retail Contai thograph aper glued enciled Section IV ation of individua	tement per ble Packaging gt. cont ner Dothe	per ainer 5 (Motice 93	ntainer letal lastic lass aper ther (S I Direct accom	pecity
Alientation of shirl aent Material This Product Will Be Pac hild Resistant Packaging Yes* No Certification must be submitted. Location of Net Contents Information Label Container Manner In Which Label Is Affixed To Contact Point (Complete items direct ame Jacquelfine A, Hogue	Se kaged In: taging s age wgt. No. pe contain n 4. Size(s) p Product Lit Pa St Ctly below for identific	ection III Water Solu Yes No er If Yes," Package w of Retail Contai thograph aper glued enciled Section IV vation of individua Title Agent	tement per ble Packaging gt. cont ner Dothe	per ainer	Motice 93	ntainer etal lastic lass aper ther (S I Direct accom	pecity) ions ipanying product sepplication / e No. (Include Area Code) {/858228
Material This Product Will Be Pach hild-Resistant Packaging Unit Pack Yes* Yes* No If "Yes," Certification must be Unit Pack Submitted. Unit Pack Location of Net Contents Information Label Label Container Manner In Which Label Is Affixed To Contact Point (Complete items direct ame Jacquel'ine Jacquel'ine	Diachange La Se kaged In: kaging s No. pe contain A. Size(s) Product Lit Pa St Certifica	ection III Water Solu Yes No r If Yes," Package w of Retail Contai thograph aper glued enciled Section IV ation of individua Title Agent	tement per ble Packaging gt. cont ner Dothe	per ainer 5 (Motice 93	ntainer etal lastic lass aper ther (S I Direct accom	pecity} ions ipanying product ipanying product ipan
Adventionation of all fill went Material This Product Will Be Pack hild-Resistant Packaging Yes* No Certification must be Submitted. Location of Net Contents Information Label Container Manner in Which Label Is Affixed To Contact Point (Complete items direct ame Jacquel'ine A, Hogue f certify that the statements I have m I acknowledge that any knowingly for both under applicable law.	Se kaged In: saging s No. pe age wgt. contain n 4. Size(s) p Product Lit Pa St Certifica hade on this form and alse or misleading sta	ection III Water Solu Yes No I of Retail Contai thograph aper glued enciled Section IV ation of individua Title Agent Agent	ble Packaging gt. cont ner Dtb be contacted hereto are true, a bunishable by fin	per ainer 5 (; if ne	Motice 93	ntainer letal lastic lass aper ther (S I Direct accom	pecity) ions ipanying product sepplication f eNo. (include Area Code) {858228 5. Date Application Received - (Sta.r.p.z.J)
Adventionant of shift went Material This Product Will Be Pack hild Resistant Packaging Yes* No Certification must be submitted. Location of Net Contents Information Label Container Manner in Which Label Is Affixed To Contact Point (Complete items direct ame Jacquel'ine A. Hogue f certify that the statements I have m I acknowledge that any knowingly for both under applicable law. Signature	Diacharge La Se kaged In: taging s age wgt. No. pe age wgt. contain n 4. Size(s) o Product Lit Product Lit Certifica sade on this form and alse or misleading state	ection III Water Solu Yes No I of Retail Contai thograph aper glued enciled Section IV ation of individua Title Agent Ition all attachments the etement may be p	tement per ble Packaging gt. cont ner Dothe <i>I to be contacted</i>	per ainer 5. (er (Motice 93	ntainer letal lassc lass aper ther (S l Direct accom	pecity) ions ipanying product supplication / e'No. (include Area Code) {7858228 6. Date Application Received (Sta.r.p.a.)
Adventional of shift went Material This Product Will Be Pact hild Resistant Packaging Yes* No Ves* No If *Yes,* Unit Pack Submitted. Location of Net Contents Information Label Container Manner In Which Label Is Affixed To Contact Point (Complete items direct ame Jacquel'ine A, Hogue I certify that the statements I have m I acknowledge that any knowingly for both under applicable law. Signature Macapueline A, Macapueline M	Se harge La	ection III Water Solu Yes No r If *Yes * Package w of Retail Contai thograph aper glued enciled Section IV sation of individua Title Agrent atlan all attachments the ctement may be p	tement per ble Packaging gt. cont ner Othe <i>I to be contacted</i> hereto are true, a bunishable by fin resident	per ainer 5 1 er (Motice 93	ntainer etal lassic lass aper ther (S I Direct accom	pecity) ions ipanying product period product period product period product period product period product period product period product period product period product pecity) supplication / e No. (Include Area Code) */858228 f. Date Application Received - (Sta.r.p.z.d)
Material This Product Will Be Pack hild Besistant Packaging Unit Pack Yes* Yes No If "Yes," Unit Pack Unit Pack submitted. Unit Pack Location of Net Contents Information Label Label Container Manner In Which Label Is Affixed To Contact Point (Complete items direation Jacquelfine A. Hogue I certify that the statements I have m I acknowledge that any knowingly ft both under applicable law. Signature Macquelie Macquelie	Diacharge La Se kaged In: taging s age wgt. No. pe age wgt. contain n 4. Size(s) o Product Lit Product Lit Certifica tade on this form and alse or misleading sta July July	ection III Water Solu Yes No r If Yes," Package w r of Retail Contai thograph aper glued enciled Section IV ation of individua Title Agent all attachments the tement may be p 3. Title Vice P 5. Date	tement per ble Packaging gt. cont ner Dothe <i>I to be contacted</i> hereto are true, a punishable by fin resident	PR per ainer 5 I Fr (Motice 93	ntainer letal lastic lass aper ther (S I Direct accom	pecity) ions ipanying product supplication f eNo. (include Area Code) {7858228 6. Date Application Received (Sta.r.p.z.j)

PACKAGE LABEL

- 120

FRONT PANEL

. '

Hypochlorite Solution

.

FOX-CHLOR

KEEP OUT OF REACH OF CHILDREN DANGER

STATEMENT OF PRACTICAL TREATMENT (FIRST AID)

IF CONTACT WITH EYES OCCURS, flush with water for at least 15 minutes. Get prompt medical attention.

IF CONTACT WITH SKIN OCCURS, wash with plenty of soap and water.

IF SWALLOWED, drink large quantities of water. DO NOT induce vomiting. Call a physician or poison control center immediately.

(See additional precautions on side panel.)

Net Contents:

FOX PACKAGING CO. 137 South Robert Street . St. Paul, MN 55107

EPA. Reg. No. 62207-1 EPA. Est. 62207-MN-1

Authorized by USDA for use in federally inspected meat, poultry, and food egg plants.

GIDE PANEL

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, may cause severe skin and eye irritation or chemical burns to broken skin. Causes eye damage. Wear safety glasses or goggles and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until strong odors have dissipated.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL OR CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (e.g. unine, feces, etc.) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

SIDE PANEL

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

NOTE: This product degrades with age. Use a chlorine test kit and increase dosage, as necessary, to obtain the required level of available chlorine.

STORAGE AND DISPOSAL

Store this product in a cool dry area, away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water. Product or rinsates that cannot be used should be diluted with water before disposal in a sanitary sewer. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incineratione or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES

CLEAN-IN-PLACE METHOD - Thoroughly clean equipment after use. Prepare a volume of 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment by mixing the product in a ratio of 5 oz. product with 10 gallons of water. Pump solution clrough the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 10 minutes to insure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

SANITIZATION OF POROUS FOOD CONTACT SURFACES

FINSE METHOD - Prepare a 500 ppm solution by thoroughly mixing 15 oz. of this product with 10 gallons of water. Clean surfaces in the normal manner. Rinse all surfaces thoroughly with the 600 ppm solution, maintaining contact with the sanitizer for at least 2 minutes. Prepare a 200 ppm sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution. Do not rinse and do not soak equipment overnight.

DISINFECTION OF DRINKING WATER (PUBLIC/INDIVIDUAL SYSTEMS) PUBLIC SYSTEMS - Mix a ratio of 1 or. of this product to 100 gallons of water. Begin feeding this solution with a hypochlorinator until a free available chlorine residual of at least 0.2 ppm and no more than 0.6 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details. 4-1 20

SWIMMING POOL WATER DISINFECTION

For a new pool or spring start-up, superchlorinate with 128 to 256 oz. of product for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Adjust and maintain pool water pH to between 7.2 to 7.6. Adjust and maintain the alkalinity of the pool to between 50 to 100 ppm.

To maintain the pool, add manually or by a feeder device 25 oz. of this product for each 10,000 gallons of water to yield an available chlorine residual between 0.6 to 1.0 ppm by weight. Stabilized pools should maintain a residual of 1.0 to 1.5 ppm available chlorine. Test the pH, available chlorine residual and alkalinity of the water frequently with appropriate test kits. Frequency of water treatment will depend upon temperature and number of swimmers.

Every 7 days, or as necessary, superchlorinate the pool with 128 to 256 oz. of product for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Do not reenter pool until the chlorine residual is between 1.0 and 3.0 ppm.

At the end of the swimming pool season or when water is to be drained from the pool, chlorine must be allowed to dissipate from treated pool water before discharge. Do not chlorinate the pool within 24 hours prior to discharge.

WINTERIZING POOLS - While water is still clear and clean, apply 8 or. of product per 1000 gallons, while filter is running, to obtain a 3 ppm available chlorine residual, as determined by a suitable test kit. Cover pool, prepare heater, filter and heater components for winter by following manufacturers' instructions.

FOX-CHLOF is also registered for the following: FRUIT AND VEGETABLE WASHING, PROCESSING AND CHILL WATER FOR POULTRY PROFESSIVE, and FOOD EGG SAMITIZATION; SAMITIZATION OF POROUS FOOD CONTACT SURFACES; SAMITIZATION OF NONPOROUS FOOD CONTACT SURFACES; DISINFECTION OF DRINKING WATER (PUBLIC/INDIVIDUAL SYSTEMS); COOLING TOWER/EVAPORATIVE CONDENSER WATER; and many other uses.

Please write or call Fox Packaging and a Product Bulletin will be sent.

5.120

AND CONTRACTOR AND AND CONTRACTOR OF A

6-120

FRONT PANEL

Hypochlorite Solution Household Bleach

FOX-CHLOR

No Phosphorus

KEEP OUT OF REACH OF CHILDREN DANGER

STATEMENT OF PRACTICAL TREATMENT (FIRST AID)

IF CONTACT WITH EYES OCCURS, flush with water for at least 15 minutes. Get prompt medical attention.

IF CONTACT WITH SKIN OCCURS, wash with plenty of soap and water.

IF SWALLOWED, drink large quantities of water. DO NOT induce vomiting. Call a physician or poison control center immediately.

(See additional precautions on side panel.)

Net Contents:

FOX PACKAGING **20**. 51 East Maryland Avenue . St. Paul, MN 55117-4615

EPA. Reg. No. 62207-1 EPA. Est. 62207-MN-1

Authorized for use in federally inspected meat, poultry, and food egg plants.

SIDE PANEL

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, may cause severe skin and eye irritation or chemical burns to broken skin. Causes eye damage. Wear safety glasses or goggles and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until strong odors have dissipated.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL OR CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (e.g. urine, feces, etc.) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

This product is not to be used as a terminal sterilant/high-level disinfectant on any surface or instrument that (1) is introduced directly into the human body, either into or in contact with the bloodstream or normally sterile areas of the body, or (2) contacts intact mucous membranes but which does not ordinarily penetrate the blood barrier or otherwise enter normally sterile areas of the body. This product may be used to preclean or decontaminate critical or semi-critical medical devices prior to sterilization or high-level disinfection.

STORAGE AND DISPOSAL

Store this product in a cool dry area, away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water. Product or rinsates that cannot be used should be diluted with water before disposal in a sanitary sewer. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or punctureand dispose of in a sanitary landfill or by incineration or, if allowed by state and local authorities, by burning. If burned stay out of smoke. Do not contaminate food or feed by storage, disposal or cleaning of equipment. NOTE: This product degrades with age. Use a chlorine test kit and increase dosage, as necessary, to obtain the required level of available chlorine.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES

RINSE METHOD - A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 2.5 oz. of this product with 10 gallons of water. If no test kit is available, prepare a sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water to provide approximately 200 ppm available chlorine by weight.

Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient product to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment and do not soak equipment overnight.

Sanitizers used in automated systems may be used for general cleaning a may not be reused for sanitizing purposes.

IMMERSION METHOD - A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 2.5 oz. of this product with 10 gallons of water. If no test kit is available, prepare a sanitizing solution by thoroughly mixing 5 oz. of this product with 12 gallons of water to provide approximately 200 ppm available relarine by weight.

Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient product to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment.

Sanitizers used in automated systems may be used for general cleaning but may not be reused for sanitizing purposes.

FLOW/PRESSURE METHOD - Disassemble equipment and thoroughly clean after use. Assemble equipment in operating position prior to use. Prepare a volume of 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment by mixing the product in a ratio of 5 oz. product with 10 gallons of water. Pump solution through the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 2 minutes to insure contact with all internal surfaces. Here the solution trom drain valve and test with a chlorine test fit. Repeat entire cleaning/sanitizing process 1. effluent contains less than 50 ppm available chlorine. CLEAN-IN-PLACE METHOD - Thoroughly clean equipment after use. Prepare a volume of 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment by mixing the product in a ratio of 5 oz. product with 10 gallons of water. Pump solution through the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 10 minutes to insure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

SPRAY/FOG METHOD - Preclean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution to control bacteriophage. Prepare a 200 ppm sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 5 oz. product with 10 gallons of water. Prepare a 600 ppm solution by thoroughly mixing the product in a ratio of 15 oz. product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces treated with a 600 ppm solution with a 200 ppm solution.

SANITIZATION OF POROUS FOOD CONTACT SURFACES RINSE METHOD - Prepare a 600 ppm solution by thoroughly mixing 15 oz. of this product with 10 gallons of water. Clean surfaces in the normal manner. Rinse all surfaces thoroughly with the 600 ppm solution, maintaining contact with the sanitizer for at least 2 minutes. Prepare a 200 ppm sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution. Do not rinse and do not soak equipment overnight.

IMMERSION METHOD - Prepare a 600 ppm solution by thoroughly mixing, in an immersion tank, 15 oz. of this product with 10 gallons of water. Clean equipment in the normal manner. Immerse equipment in the 600 ppm solution for at least 2 minutes. Prepare a 200 ppm sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water. Prior to using equipment, immerse all surfaces with a 200 ppm available chlorine solution. Do not rinse and do not soak equipment overnight.

SPRAY/FOG METHOD - Preclean all surfaces after use. Prepare a 600 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 15 oz. product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution. Prepare a 200 ppm sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water.

9-120

SANITIZATION OF NONPOROUS NON-FOOD CONTACT SURFACES

RINSE METHOD - Prepare a sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD - Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 5 oz. of this product with 10 gallons of water to provide approximately 200 ppm available chlorine by weight. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

SPRAY/FOG METHOD - Preclean all surfaces after use. Prepare a 200 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 5 oz. product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

DISINFECTION OF NONPOROUS NON-FOOD CONTACT SURFACES RINSE METHOD - Prepare a disinfecting solution by thoroughly mixing 15 oz. of this product with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the disinfecting solution, maintaining contact with the solution for at least 10 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD - Prepare a disinfecting solution by thoroughly mixing, in an immersion tank, 15 oz. of this product with 10 gallons of water to provide approximately 600 ppm available chlorine by weight. Prior to use, immerse equipment in the disinfecting solution for at least 10 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

BANITIZATION OF POROUS NON-FOOD CONTACT SURFACES RINSE METHOD - Prepare a sanitizing solution by thoroughly mixing 15 oz. of this product with 10 gallons of water to provide approximately 600 available chlorine by weight. Clean surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD - Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 15 oz. of this product with 10 gallons of water to provide approximately 600 available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

والمراوح والمراوح والمراوح والمعالية والمعالية والمراجع المراجع المراجع المحافية والمحافية والمحافي والمحاف

10 1 20

SPRAY/FOG METHOD - After cleaning, sanitize non-food contact surfaces with 600 pps available chlorine by thoroughly mixing the product in a ratio of 15 pz. of this product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate for at least 2 hours.

1.0020

AGRICULTURAL USES

FOOD EGS SANITIZATION - Thoroughly clean all eggs. Thoroughly mix 5 oz. of this product with 10 gallons of warm water to produce a 200 ppm available chlorine solution. The sanitizer temperature should not exceed 130° F. Spray the warm sanitizer so that the eggs are thoroughly wetted. Allow the eggs to thoroughly dry before casing or breaking. Do not apply a potable water rinse. The solution should not be reused to sanitize eggs.

FRUIT & VEGETABLE WASHING - Thoroughly clean all fruits and vegetables in a wash tank. Thoroughly mix 12 oz. of this product in 200 gallons of water to make a sanitizing solution of 25 ppm available chlorine. After draining the tank, submerge fruit or vegetables for 2 minutes in a second wash tank containing the recirculating sanitizing solution. Spray rinse vegetables with the sanitizing solution prior to packaging. Rinse fruit with potable water only prior to packaging.

PROCESSING AND CHILL WATER FOR POULTRY PROCESSING - Follow guidelines of local water authority for water potability treatment.

Continuous feed: Using automatic metering device, continuously feed this product into the water to obtain and/or maintain a level of available chlorine that is in accordance with USDA guidelines. Confirm target chlorine level with either a chlorine test kit or an automatic testing device. When the available chlorine level reaches 20 ppm, notify the USDA plant inspector.

Intermittent feed: Start up by adding 2.5 oz. of this product per 1,000 gallons of water for each 1 ppm of available chlorine needed. For subsequent doses, check chlorine level with a chlorine test kit, add enough of this product to maintain the target chlorine level, and confirm this level with a chlorine test kit. Do not pour this product directly on poultry product in the water.

FARM PREMISES

Remove all animals, poultry and feed from premises, vehicles and enclosures. Remove all litter and manure from floors, walls and surfaces of barns, pens, stalls, chutes, and other facilities occupied or traversed by animals or poultry. Empty all troughs, racks and other feeding and watering appliances. Thoroughly clean all surfaces with soap or detergent and rinse with water. To disinfect, saturate all surfaces with a solution of at least 1000 ppm available chlorine for a period of 10 minutes. A 1000 ppm solution can be made by thoroughly mixing 25 oz. of this product with 10 gallons of water. Immerse all halters, ropes and other types of equipment used in handling and restraining animals or poultry, as well as the cleaned forks, shovels and scrapers used for removing litter and manure. Ventilate buildings, cars, boats and other closed spaces. Do not house livestock or poultry or employ equipment until chlorine has been dissipated. All treated feed racks, mangers, iroughs, automatic feeders, fountains and waterers must be rinsed with potable water before reuse.

n 1995 and a line and a state and a state of a state and and an an an and a state of a state of an an an an an

When the contract of the second state

AQUACULTURAL USES

1: -7 20

FISH PONDS - Remove fish from ponds prior to treatment. Thoroughly mix 256 oz. of this product to 10,000 gallons of water to obtain 10 ppm available chlorine. Add more product to the water if the available chlorine level is below 1 ppm after 5 minutes. Return fish to pond after the available chlorine level reaches zero.

FISH POND EQUIPMENT - Thoroughly clean all equipment price to treatment. Thoroughly mix 5 oz. of this product to 10 gallons of water to obtain 200 ppm available chlorine. Porous equipment should soak for one hour.

MAINE LOBSTER FONDS - Remove lobsters, seaweed, etc. from ponds prior to treatment. Drain the pond. Thoroughly mix 15,400 oz. of this product to 10,000 gallons of water to obtain at least 600 ppm available chlorine. Apply so that all barrows, gates, rocks and dams are treated with product. Permit high tide to fill the pond and then close gates. Allow water to stand for 2 to 3 days until the available chlorine level reaches zero. Open gates and allow 2 tidal cycles to flush the pond before returning lobsters to pend.

CONDITIONING LIVE OYSTERS - Thoroughly mix 13 oz. of this product to 10,000 gallons of water at 50 to 70°F to obtain 0.5 ppm available chlorine. Expose oysters to this solution for at least 15 minutes, monitoring the available chlorine level so that it does not fall below 0.05 ppm. Repeat entire process if the available chlorine level drops below 0.05 ppm or the temperature falls below 50°F.

CONTROL OF SCAVENGERS IN FISH HATCHERY PONDS - Prepare a solution containing 200 ppm of available chlorine by mixing 5 oz. of product with 10 gallons of water. Pour into drained pond potholes. Repeat if necessary. Do not put desirable fish back into refilled ponds until chlorine residual has dropped to zero, as determined by a test kit.

BOAT BOTTOMS

To control slime on boat bottoms, sling a plastic tarp under boat, retaining enough water to cover the fouled bottom but not allowing water to enter enclosed area. This envelope should contain approximately 500 gallons of water for a 14 foot boat. Add 40 oz. of this product to this water to obtain a 35 ppm available chlorine concentration. Leave immersed for 8 to 12 hours. Repeat if necessary. Do not discharge the solution until the free chlorine level has dropped to zero, as determined by a swimming puol test kit.

ARTIFICIAL SAND BEACHES

To sanitize the sand, spray a 500 ppm available chlorine solution containing 13 pz. of this product per 10 gallons of water at frequent intervals. Small areas can be sprinkled with a watering can.

ASPHALT OR WOOD ROOFS AND SIDING

To control fungus and mildew, first remove all physical soil by brushing and hosing with clean water, and apply a 5000 ppm available chlorine solution. Mix 13 oz. of this product per gallon of water and brush or spray roof or siding. After 30 minutes, rinse by hosing with clean water.

DISINFECTION OF DRINKING WATER (PUBLIC/INDIVIDUAL SYSTEMS) PUBLIC SYSTEMS - Mix a ratio of 1 oz. of this product to 100 gallons of water. Begin feeding this solution with a hypochlorinator until a free available chlorine residual of at least 0.2 ppm and no more than 0.6 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details.

12420

INDIVIDUAL SYSTEMS: DUG WELLS - Upon completion of the casing (lining) wash the interior of the casing (lining) with a 100 ppm available chlorine solution using a stiff brush. This solution can be made by thoroughly mixing 2.5 oz. of this product into 10 gallons of water. After covering the well, pour the sanitizing solution into the well through both the pipesleeve opening and the pipeline. Wash the exterior of the pump cylinder also with the sanitizing solution. Start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After the hours flush well until all traces of chlorine have been removed from the water. Consult your local Health Department for further details.

INDIVIDUAL SYSTEMS: DRILLED, DRIVEN & BORED WELLS - Run pump until water is as free from turbidity as possible. Four a 100 ppm available chlorine sanching solution into the well. This solution can be made by thoroughly isong 2.7 c. of this product into 12 gallons of water. Add 5 to 12 gallons of clean, chlorinated water to the well in order to force the panitizer into the rock formation. Wash the exterior of the pump cylinder with the sanctizer. Drop pipeline into well, start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours flush well until all traces of chlorine have been removed from the water. Deep wells with high water levels may nacessitate the use of special methods for introduction of the sanitizer into the well. Consult your local Health Department for further details.

INDIVIDUAL SYSTEMS: FLOWING ARTESIAN WELLS - Artesian wells generally do not require disinfection. If analyses indicate persistent contamination, the well should be disinfected. Consult your local Health Department for further defails.

PUBLIC WATER SYSTEMS

FESEPVOIRS: ALGAE CONTROL - Hypochlorinate streams feeding the reservoir. Suitable feeding points should be selected on each stream at least 50 gards upstream from the points ocentry into the reservoir.

MAINS - Thoroughly flush section to be sanitized by discharging from hydrants. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of a hypochlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water. NEW TANKS, BASINS, ETC. - Remove all physical soil from surfaces. Place 52 oz. of this product for each 5 cubic feet of working capacity (500 ppm available chlorine). Fill to working capacity and allow to stand for at least 4 hours. Drain and flush with potable water and return to sufface.

11.120

NEW FILTER SAND - Apply 208 oz. of this product for each 150 c aic feet of sand. The action of the product dissolving as the wat. passes through the bed will aid in sanitizing the new sand.

NEW WELLS - Flush the casing with a 50 ppm available chlorine solution of water containing 12 oz. of this product for each 100 gallons of water. The solution should be pumped or fed by gravity into the well after thorough mixing with agitation. The well should stand for several hours or overnight under chlorination. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary.

EXISTING EQUIPMENT - Remove equipment from service and thoroughly clean surfaces of all physical soil. Sanitize by placing 53 oz. of this product for each 5 cubic feet capacity (approximately 500 ppm available chlorine). Fill to working capacity and let stand at least 4 hours. Drain and place in service. If the previous treatment is not practical, surfaces may be sprayed with a solution containing 6 oz. of this product for each 5 gallons of water (approximately 1000 ppm available chlorine). After drying, flush with water and return to service.

COOLING TOWER/EVAPORATIVE CONDENSER WATER

SEUG FEED METHOD - Initial Dose: When system is noticeably fouled, apply 128 to 256 or. of this product per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 25 oz. of this product per 10,000 gallons of water in the system daily, or as needed to calibration control and keep the chlorine residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

INTERMITTENT FEED METHOD - Initial Dose: When system is noticeably fouled, spply 128 to 256 oz. of this product per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add 25 oz. of this product per 10,000 gallons of water in the system to obtain a 1 ppm residual. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD - Initial Dose: When system is noticeably fouled, apply 128 to 256 oz. of this product per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine.

Subsequent Dose: Maintain this treatment level by starting a continuous eed of 2 oz. of this product per 1,000 gallons of water lost by blowdown to maintain a 1 ppm residual. Badly fouled systems must be cleaned before treatment is begun.

EMERGENCY DISINFECTION AFTER FLOODS

15-120

WELLS - Thoroughly flush contaminated casing with a 500 ppm available chlorine solution. Prepare this solution by mixing 13 oz. of this product with 10 gallons of water. Backwash the well to increase yield and reduce turbidity, adding sufficient chlorinating solution to the backwash to produce a 10 ppm available chlorine residual, as determined by a chlorine test kit. After the turbidity has been reduced and the casing has been treated, add sufficient chlorinating solution to produce a 50 ppm available chlorine residual. Agitate the well water for several hours and take a representative water sample. Retreat well if water samples are biologically unacceptable.

RECERVOIRS - In case of contamination by overflowing streams, establish hypochlorinating stations upstream of the reservoir. Chlorinate the inlet water until the entire reservoir obtains a 0.2 ppm available chlorine residual, as determined by a suitable chlorine test kit. In case of contamination from surface drainage, apply sufficient product directly to the reservoir to obtain a 0.2 ppm available chlorine residual in all parts of the reservoir.

BASINS, TANKS, FLUMES, ETC. - Thoroughly clean all equipment, then apply 52 cz. of product per 5 cu. ft. of water to obtain 500 ppm available chlorine, as determined by a suitable test kit. After 24 hours drain, flush, and return to service. If the previous method is not suitable, spray or flush the equipment with a solution containing 13 cz. of this product for each 5 gallons of water (1000 ppm available chlorine). Allow to stand for 2 to 4 hours, flush, and return to service.

FILTERS - When the sand filter needs replacement, apply 208 oz. of this product for each 150 to 200 cubic feet of sand. When the filter is severely contamonated, additional product should be distributed over the surface at the rate of 208 cz. per 20 sq. ft. Water should stand at a depth of 1 foot above the surface of the filter bed for 4 to 24 hours. When filter beds can be backwashed of mud and silt, apply 208 oz. of this product per each 50 sq. ft., allowing the water to stand at a depth of 1 foot above the filter sand. After 32 minutes, drain water to the level of the filter. After 4 to 5 hours drain and proceed with normal backwashing.

DISTRIBUTION SYSTEM - Flush repaired or replaced section with water. Establish a hypochlorinating station and apply sufficient product until a consistent available chlorine residual of at least 100 ppm remains after a 24 hour retention time. Use a chlorine test kit.

EMERGENCY DISINFECTION AFTER FIRES

CROCE CONNECTIONS of PERCENCY CONNECTIONS - Hypochlorination or gravity feed equipment should be set up near the intake of the untreated water cupply. Apply sufficient product to give a chlorine residual of at least 0.1 to 0.2 ppm at the point where the untreated supply enters the regular distribution system. Use a chlorine test kit.

EMERGENCY DISINFECTION AFTER DROUGHTS

. .

10 120

SUPPLEMENTARY WATER SUPPLIES - Gravity or mechanical hypochlorite feeders should be set up on a supplementary line to dose the water to a minimum chlorine residual of 0.2 ppm after a 20 minute contact time. Use a chlorine test kit.

WATER SHIFPED IN BY TANKS, TANK CARS, TRUCKS; ETC. - Thoroughly clean all containers and equipment. Spray with a 500 ppm available chlorine solution and rinse with potable water after 5 minutes. This solution is made by mixing 13 oz. of this product for each 10 gallons of water. During the filling of the containers, dose with sufficient amounts of this product to provide at least a 0.2 ppm chlorine residual. Use a chlorine test kit.

EMERGENCY DISINFECTION AFTER MAIN BREAKS

MAINS - Before assembly of the repaired section, flush out mud and soil. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of a hypochlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.

PULP AND PAPER MILL PROCESS WATER SYSTEMS SUVE FEED METHOD - Initial Dose: When system is noticeably fouled, apply 128 to 206 or. of this product per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 25 oz. of this product per 10,020 gallons of water in the system daily, or as needed to matchal: control and keep the chlorine residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

INTERMITTONI FLED MOTHOD - Initial Bose: When system is noticeably fouled, Apply 128 to 056 bb, of this product per 12,000 gallons of mater in the system to obtain 5 to 10 ppm available chlorine. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add 25 oz. of this product per 10,000 gallons of water in the system to obtain a 1 ppm residual. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown. Badly fould systems much be cleaned before treatment is begun.

CONTINUOUS FEED METHOD - Initial Dose: When system is noticeably fouled, apply 128 to 256 oz. of this product per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine.

Subsequent Dose: Maintain this treatment level by starting a continuous feed of 2 oz. of this product per 1,000 gallons of water lost by blowdown to maintain a 1 ppm residual. Badly fouled systems must be cleaned before treatment is begun.

SEWAGE & WASTEWATER EFFLUENT TREATMENT

17.4:20

The disinfection of sewage effluent must be evaluated by determining the total number of coliform bacteria and/or fecal coliform bacteria, as determined by the Most Probable Number (MPN) procedure, of the chlorinated effluent that has been reduced to or below the maximum permitted by the controlling regulatory jurisdiction.

On the average, satisfactory disinfection of secondary wastewater effluent can be obtained when the chlorine residual is 0.5 ppm after 15 minutes contact. Although the chlorine residual is the critical factor in disinfection, the importance of correlating chlorine residual with bacterial kill must be emphasized. The MPN of the effluent, which is directly related to the water quality standards requirements, should be the final and primary standard and the chlorine residual should be considered an operating standard valid only to the extent verified by the coliform quality of the effluent.

The following are critical factors affecting wastewater disinfection.

1. Mixing: It is imperative that the product and the wastewater be instantaneously and completely flash mixed to assure reaction with every chemically active soluble and particulate component of the wastewater.

2. Contacting: Upon flash mixing, the flow through the system must be maintained.

3. Dosage/Residual Control: Successful disinfection is extremely dependent on response to fluctuating chlorine demand to maintain a predetermined desirable chlorine level. Secondary effluent should contain 0.2 to 1.0 ppm chlorine residual after a 15 to 30 minute contait time. A reasonable average of residual chlorine is 0.5 ppm after 15 minutes contact time.

SEWAGE & WASTEWATER TREATMENT

EFFLUENT SLIME CONTROL - Apply a 100 to 1000 ppm available chlorine solution at a location which will allow complete mixing. Prepare this solution by mixing 23 to 227 oz. of this product with 100 gallons of water. Once control is evident, apply a 15 ppm available chlorine solution. Prepare this solution by mixing 8 oz. of this product with 100 gallons of water.

FILTER BEDS SLIME CONTROL - Remove filter from service, drain to a depth of 1 foot above filter, and add 187 pz. of product per 20 sq. ft. evenly over the surface. Wait 30 minutes before draining water to a level that is even with the top of the filter. Wait for 4 to 6 hours before completely draining and backwashing filter.

SWIMMING POOL WATER DISINFECTION

18 120

For a new pool or spring start-up, superchlorinate with 128 to 256 oz. of product for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Adjust and maintain pool water pH to between 7.2 to 7.6. Adjust and maintain the alkalinity of the pool to between 50 to 100 ppm.

To maintain the pool, add manually or by a feeder device 25 oz. of this product for each 10,000 gallons of water to yield an available chlorine residual between 0.6 to 1.0 ppm by weight. Stabilized pools should maintain a residual of 1.0 to 1.5 ppm available chlorine. Test the pH, available chlorine residual and alkalinity of the water frequently with appropriate test kits. Frequency of water treatment will depend upon temperature and number of swimmers.

Every 7 days, or as necessary, superchlorinate the pool with 128 to 256 oz. of product for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Do not reenter pool until the chlorine residual is between 1.0 and 3.0 ppm.

At the end of the swimming pool season or when water is to be drained from the pool, chlorine must be allowed to dissipate from treated pool water before discharge. Do not chlorinate the pool within 24 hours prior to discharge.

WINTERIZING POOLS - While water is still clear and clean, apply 8 oz. of product per 1000 gallons, while filter is running, to obtain a 3 ppm available chlorine residual, as determined by a suitable test kit. Cover pcol, prepare heater, filter and heater components for winter by following manufacturers' instructions.

SPAS, HOT-TUES, IMMERSION TANKS, ETC.

SPAS/HOT-TUBE - Apply 13 oz. of product per 1000 gallons of water to obtain a free available chlorine concentration of 5 ppm, as determined by a suitable chlorine test kit. Adjust and maintain pool water pH to between 7.0 and 7.8. Some cils, lotions, fragrances, cleaners, etc. may cause foaming or cloudy water as well as reduce the efficiency of the product.

To maintain the water, apply 13 bz. of product per 1000 gallons of water over the surface to maintain a chlorine concentration of 5 ppm.

After each use, shock treat with 21 oz. of this product per 500 gallons of water to control odor and algae.

During extended periods of disuse, add 8 oz. of product daily per 1000 gallons of water to maintain a 3 ppm chlorine concentration.

EUDBARD AND IMMERSION TANKS - Add 13 oz. this product per 200 gallons of water before patient use to obtain a chlorine residual of 25 ppm, as determined by a suitable test kit. Adjust and maintain the water pH to between 7.2 and 7.6. After each use drain the tank. Add 13 oz. to a bucket of water and circulate this solution through the agitator of the tank for 15 minutes and then rinse out the solution. Clean tank thoroughly and dry with clean cloths.

HYDROTHERAPY TANKS - Add 2 oz. of this product per 1000 gallons of water to obtain a chlorine residual of 1 ppm, as determined by a suitable chlorine test kit. Pool should not be entered until the chlorine residual is below 3 ppm. Adjust and maintain the water pH to between 7.2 and 7.6. Operate pool filter continuously. Drain pool weekly and clean before refilling.

LAUNDRY SANITIZERS

Household Laundry Sanitizers

IN SOAKING SUDS - Thoroughly mix 5 oz. of this product to 10 gallons of wash water to provide 200 ppm available chlorine. Wait 5 minutes, then add soap or detergent. Immerse laundry for at least 11 minutes prior to starting the wash/rinse cycle.

IN WASHING SUDS - Thoroughly mix 5 cz. of this product to 10 gallons of wash water containing clothes to provide 200 ppm available chlorine. Wait 5 minutes, then add scap or detergent and start the wash/rinse cycle.

Commercial Laundry Sanitizers

Wet fabrics on clothes should be spun dry prior to sanitization. Thoroughly mix 5 oz. of this product with 10 gallons of water to provide 200 ppm available chlorine. Fromptly after mixing the sanitizer, add the solution to the prewash prior to washing fabrics/clothes in the regular wash cycle with a good detergent. Test the level of available chlorine if solution has been allowed to stand. Add more of this product if the available chlorine level has dropped below 200 ppm.

SANITIZATION OF DIALYSIS MACHINES

Flush equipment thoroughly with water prior to using this product. Thoroughly mix 15 oz. of this product to 10 gallons of water to obtain at least 600 ppm available chlorine. Immediately use this product in the bemodialyeste system allowing for a minimum contact time of 15 minutes at 20°C. Dealn system of sanitizing solution and thoroughly rinse with water. Discard and DO NOT reuse the spent sanitizer. Rinsate must be monitored with a suitable test kit to insure that no available chlorine remains in the system.

This product is recommended for decontaminating single and multipatient hemodialysate systems. This product has been shown to be an effective disinfectant (vinucide, fungicide, bactericide, pseudomonicide) when tested by AOAC and EPA test methods. This product may not totally eliminate all vegetative microorganisms in hemodialysate delivery systems due to their construction and/or assembly, but can be relied upon to reduce the number of microorganisms to acceptable levels when used as directed. This product should be used in a disinfectant program which includes bacteriological monitoring of the hemodialysate delivery system. This product is NOT recommended for use in hemodialysate or reverse osmosis (RO) membranes.

Consult the guidelines for hemodialysate systems which are available from the Hepatitis Laboratories, CDC, Phoenix, AZ 85021.

DIRECTIONS FOR LAUNDERING AND FABRIC CARE Can be used on Nylon, Orlon, Rayon, Dacron 78 cup bleach for each 2 mallons water in wa

LAUNDRY - Add 1/8 cup bleach for each 2 gallons water in washing machine. TOP LOADERS: 1 cup per load; FRONT LOADERS: 1/2 cup per load. For bleaching and sanitizing white or colorfast cottons, linens, nylon, Dacron, Orlon, and rayon. Use bleach in washing machine or first rinse. Wash or soal 10 minutes. Rinse well. If clothes are already in machine, dilute the bleach with one quart of water before using.

REMOVING STAINS - Use 1/6 cup bleach per quart of water. For stubborn stains from fruit, grass, tea, coffee, scorch, ink, and mildew, soak stained area in the solution 5 minutes. Rinse well. Repeat if necessary. Colored fabrics - test small piece before using. Use only in glass, rubber, plastic, porcelain. or enameled containers.

20 420

DIAFER-PAIL PRE-SOAK - Use 1/8 cup bleach per 2 gallons of water. Flush out spiled diagers. Then soak in bleach solution.

DO NOT USE ON SILK, WOOL, ACETATE, SPANDEX OR LEATHER KEEP UPRIGHT IN A COOL PLACE

DIRECTIONS FOR OTHER HOUSEHOLD/FARM USES For cleaning, disinfecting and deodorizing

CLEANING KITCHEN & BATHROOM - Use 1/8 cup per quart of water. To clean sinks, bathtubs, tile, linoleum, porcelain, and enameled metal, spread solution with cloth. Let stand 2 minutes. Rinse well.

TOILET BOWLS - Use 1/2 cup bleach. Pour in bleach - swab with brush. Let stand for 10 minutes. Flush. DO NOT use with bowl cleaners or any other bousehold chemicals.

SARRAGE CANS, TEAPOID & CUPS, STAINED DISHES, WOODEN UTENSILS - 1/8 cup bloads per quark of water. Wash thoroughly with warm suds. Then soak in bleach solution 5 minutes. Rinse well. (Do not use on silverware.)

REFRIGERATORS, STOVES, FLOORS, UNPAINTED WOOD, SICKROOM EQUIPMENT - 1/4 cup bleach per 1 gallon of water. First wash thoroughly with warm suds, then spread the bleach solution with a cloth. Let stand 2 minutes. Rinse well.