

# Supplemental Labeling



DowElanco

9330 Zionsville Road

Indianapolis, Indiana 46268-1054 USA

## Lorsban\*-4E

EPA Reg. No. 62719-220

### Liquid T-Band Treatment for Control of Soil Borne Insect Pests in Corn-Rootworm Larvae

#### ATTENTION

- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- This labeling must be in the possession of the user at the time of application.
- Read the label affixed to the container for Lorsban-4E before applying. Carefully follow precautionary statements and applicable use directions.
- Use of Lorsban-4E according to this supplemental labeling is subject to all use precautions and limitations imposed by the label affixed to the container for Lorsban-4E.

**T-Band At Plant Treatment:** Lorsban\*-4E insecticide may be applied as a liquid T-Band in fields with no more than 30 percent cover of crop residue remaining on the soil surface. Apply Lorsban-4E as a liquid T-Band over an open seed furrow and incorporate into the top one inch of soil using tines, chains or other suitable equipment. Position a flat fan nozzle behind the planter shoe, in front of the press wheel adjusted to provide a 5 to 6 inch band width centered over the row. Apply Lorsban-4E at a rate of 2.4 fluid ounces per 1000 linear feet of row (2 pints per acre with 40 inch row spacing) in a minimum spray volume of 5 gallons per acre. The table below provides equivalent application rates for various row spacings.

Pests	Amount of Lorsban-4E Required	
	Row Spacing (inches)	Pints per acre
corn rootworm larvae	30	2.6
cutworms	36	2.2
grubs	38	2.1
seed corn beetle	40	2.0
seed corn maggot		

**ACCEPTED**

**APR 12 1996**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 62719-220

\*Trademark of DowElanco

A1A/Lorsban-4E/Amend-Supp-122-58-051/02-20-96

(file: 1220-122.doc) EPA-accepted   /  /  

Replaces: 122-55-122R

#### Amendments:

1. Additional pests, other than corn rootworm larvae, controlled by liquid T-Band application.