Supplemental Labeling



Dow AgroSciences LLC

9330 Zionsville Road

Indianapolis, IN 46268-1054 USA

Accord® SP

EPA Reg. No. 62719-322

For Aerial Application in California Only

ATTENTION

- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- This labeling must be in the possession of the user at the time of application.
- Read the label affixed to the container for Accord
 SP herbicide before applying. Carefully follow all precautionary statements and applicable use directions.
- Use of Accord SP according to this supplemental labeling is subject to all use precautions and limitations imposed by the label affixed to the container for Accord SP.

Directions for Use

Extreme care must be exercised to avoid contact of the spray with foliage, green stems, or fruit of desirable crops, plants, trees or other desirable vegetation, since severe damage or destruction may result.

When applied as directed and under the conditions described, this product controls annual and perennial weeds and woody brush and trees listed in the label booklet. See the Weeds Controlled section of the label booklet for rate recommendations.

Aerial applications of this product are allowed in the following situations:

- Forestry site preparation.
- · Aid to burning for establishment and maintenance of fuel breaks
- · Establishment of fire perimeters and back lines.
- Aid to prescribed burning
- Along fire roads
- Wildlife food plots

Aerial Applications

ACCEPTED

MAY 1 5 2002

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No 62719-322

Apply 1 to 5 quarts of this product in 5 to 15 gallons of water per acre using aerial (helicopter only) equipment.

To broaden the spectrum of control, Garlon* 4 may be tank mixed with this product at the rate of 0.5 to 2 quarts per acre. For best results, the rate of Garlon 4 should not exceed 1/2 the rate of this product (e.g., 1 quart of Garlon 4 to 2 quarts of this product).

Do not apply directly to water, to areas where surface water is present or to intertidal areas balow the mean high water mark. Do not contaminate water when disposing of equipment washwaters.

AVOID DRIFT: Do not apply when winds are gusty or under any other condition that will allow drift. Drift may cause damage to any vegetation contacted to which treatment

is not intended. To prevent injury to adjacent desirable vegetation, appropriate buffer zones must be maintained.

Use the following guidelines when aerial applications are made near crops or desirable perennial vegetation after bud break and before total leaf drop, and/or near other desirable vegetation or annual crops:

- 1. Do not apply within 100 feet of all desirable vegetation or crop(s).
- 2. If wind up to 5 miles per hour is blowing toward desirable vegetation or crop(s), do not apply within 500 feet of the desirable vegetation or crop(s).
- 3. Winds blowing from 5 to 10 miles per hour toward desirable vegetation or crop(s) may require buffer zones in excess of 500 feet.
- 4. Do not apply when winds are in excess of 10 miles per hour or when inversion conditions exist.

Coarse sprays are less likely to-drift; therefore, do not use nozzles or nozzle configurations that dispense spray as fine spray droplets. Do not angle nozzles forward into the air-stream and do not increase spray volume by increasing nozzle pressure. Drift control additives may be used. When a drift control additive is used, read and carefully observe the cautionary statements and all other information appearing on the label of the additive.

Ensure uniform application: To avoid streaking, uneven, or overlapped application, use appropriate marking devices.

Prolonged exposure of this product to uncoated steel surfaces may result in corrosion and possible failure of the part. Landing gear is most susceptible. The maintenance of an organic coating (paint) which meets aerospace specification MIL-C-38413 may prevent corrosion. To prevent corrosion of exposed parts, thoroughly wash aircraft, especially landing gear, after each day of spraying to remove residues of this product accumulated during spraying or from spills.

E8A / Accord SP / Prop Sec 3 Suppl - Aerial Applic. CA Only / 03-14-02 D06-XXX-XXX EPA-accepted: __/_/_ Initial Printing.