

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

WASHINGTON, D.C. 20460

September 10, 2025

Anna Crowder
Nisus Corporation

Electronic Transmittal: annac@nisuscorp.com

Subject: Label Amendment – Changes Required by the Naphthenate Salts Amended

Interim Registration Review Decision

Product Name: QNAP5W Copper Naphthenate Concentrate

EPA Registration Number: 64405-15

Received Date: 4/27/2020 Decision Number: 562190

Dear Anna Crowder:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the Registration Review of the above referenced product in connection with the Naphthenate Salts Amended Interim Decision, and has concluded that your submission is acceptable.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling and must be used at your next label printing. Pursuant to 40 CFR 156.10(a)(6) you must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 12 months from the date of this letter. After 12 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Page 2 of 2 EPA Reg. No. 64405-15 Decision No. 562190

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Megan Snyderman by phone at 202-566-0639, or via email at Snyderman.Megan@epa.gov.

Sincerely,

Eric Miederhoff

Chief, Reevaluation Branch

Antimicrobials Division

EPA Office of Pesticide Programs

Enclosure: Stamped Label

ACCEPTED

09/10/2025

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 2440 F. 45

64405-15

QNAP5W COPPER NAPHTHENATE CONCENTRATE

Keep Out of Reach of Children DANGER

See Label for additional Precautionary Statements.

Active ing	realent:				
Coppei	Naphthenate (CAS No. 1	338-02-9) .			45.4%*
Other Ingi	redients				54.6%
Total					100%
C	ontains Petroleum Distilla	tes			
*E	Equivalent to 5% copper	, as metal.			
	Net Weight: 9.0 F	ounds/Gal	lon (3.97 Kilo	s)	
[Net Contents:	1 Quart (.95 Liter)	☐ 1 Gallor	n (3.8 Liters)	55.0 Gallon (208 Liters
	☐ 275 Gallons (10	41 Liters)	■ bulk tank	er]	
	EPA Reg. No. 64405	-15 EP	A Est		
	©I	Made in the	U.S.A.		

First Aid

	Filst Alu			
If in Eyes	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. 			
If on Skin or Clothing	 Take off contaminated clothing. Immediately rinse skin with plenty of water for 15-20 minutes. 			
If Swallowed	 Have person sip a glass of water if able to swallow. Do not give anything by mouth to an unconscious person. Do not induce vomiting unless told to do so by a poison control center or doctor. 			
If Inhaled	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. 			
when calling a po	trol center or doctor for further treatment advice. Have the product container or label with you ison control center or doctor, or going for treatment. [You may also contact {insert appropriate for emergency medical treatment.]			
NOTE TO PHYSI	CIAN: Probable mucosal damage may contraindicate the use of gastral lavage.			

PRECAUTIONARY STATEMENTS

Hazards to Humans & Domestic Animals

DANGER

Corrosive. Causes skin burns and irreversible eye damage. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or mist during brush, roll, and dip applications. Prolonged or repeated skin contact may cause allergic reaction in some individuals.

Wear chemical resistant gloves, protective eyewear, long-sleeved shirt, long pants, socks and shoes when handling or applying this product. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

Personal Protective Equipment (PPE)

- Applicators, mixers and other handlers must wear chemical resistant gloves, protective eyewear, longsleeved shirt, long pants, socks and shoes when handling or applying this product.
- When applying this product to non-pressure treated wood with a brush/roller, applicant must wear an organic vapor respirator.
- Some materials that are chemical-resistant to this product are barrier laminate; butyl, nitrile, neoprene and natural rubbers ≥ 14 mils; polyethylene; polyvinyl chloride; and viton ≥ 14 mils. If you want more options, follow the instructions for category C on an EPA chemical-resistance category selection chart.
- Tank clean-up crews in dip diffusion treatment facilities must wear a minimum of a NIOSH approved (TC-84A) air-purifying half-mask elastomeric respirator with any R or P filter.

User Safety Requirements

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

Users must:

- Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet;
- Remove clothing immediately if pesticide gets inside, then wash thoroughly and put on clean clothing;
- Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

Environmental Hazards

This product is toxic to fish, aquatic invertebrates, and aquatic plants. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your state water board or regional office of the EPA.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Intended For Exterior Use

Notice

Read and understand the entire label before using. Use only according to label directions.

Before buying or using this product, read *Warranty Disclaimer* and *Limitation of Remedies* statements found elsewhere on this label. If terms are unacceptable, return unopened package to seller for full refund of purchase price. Otherwise, use by the buyer or any other user constitutes acceptance of the terms under *Warranty Disclaimer* and *Limitation of Remedies*.

QNAP5W treated wood will prevent infestation of wood destroying organisms including subterranean termites, drywood termites, wood destroying beetles, powderpost beetles, carpenter ants and decay fungi. It may also be used to resist swelling, shrinking, warping, end checking caused by changes in moisture content of wood products, wood rot, mold and mildew, and moss.

Solutions of QNAP5W can be applied to wood and construction products (including lumber, end cuts, timber, rail ties, posts, poles, pilings, foundation sill plates, millwork, freeway fencing, siding, piers, docks, boxes, roofs, shakes, shingles, porches, steps, fences, pickets, rails and beverage cases). QNAP5W treated wood is suitable for ornamental

or planting landscape timbers, greenhouses, nursery flats, wooden seedling trays, outdoor décor, plant boxes, flower boxes and window boxes. QNAP 5W treated wood [Wood treated with this product] can be burned or re-purposed after primary service [as a railroad tie or utility pole] for use in residential landscaping or as a fence posts. [The treated wood can be top-coated with paint or stain.]

Application of this product may produce strong, lingering, unpleasant odor. Wood treated with QNAP5W should not be used where it may come in contact with food, feed or potable water. Do not use QNAP5W treated wood for garden applications where fruit and or vegetables will be grown. Wood treated with this product shall not be used in the construction of beehives. Do not apply with an airless sprayer, by spray or by fine mist. When field treating, do so in a manner that the product does not drip into sensitive environments. Whenever possible, apply field treatments prior to assembling the structure over the body of water or sensitive environment.

APPLICATION INFORMATION:

This product will tint the wood. The color will fade over time. The treated wood can be top-coated with paint or stain. Always test the paint or stain in an inconspicuous area for color satisfaction. Water repellents, colorants (including universal machine colorants) and liquid glycol borate formulations may be mixed with QNAP5W. Wood must be thoroughly seasoned and free of bark. Make certain all areas are fully treated to get the maximum benefits.

QNAP5W must be diluted with water prior to use. Agitate well before using. QNAP5W solutions containing 1% or 2% copper metal are appropriate for wood in non-critical applications. Effective application rates vary according to severity of conditions to which the treated product is exposed.

Coverage is dependent upon application method and the refractory nature of the wood being treated; One gallon of diluted QNAP5W will cover approximately 100 - 300 sq. ft. of surface area. Penetration of QNAP5W through the sapwood may take 24-48 hours, depending upon refractory nature of the wood being treated.

DILUTION CHART Use the following chart to dilute QNAP 5W. When diluting mix thoroughly and agitate or stir well before using.

Copper Metal Amount	Parts of QNAP 5W	Parts of Water Added
0.20%	1	24
0.25%	1	19
0.75%	1	5.6
1.0%	1	4
1.25%	1	3
2.0%	1	1.5

WOOD TREATMENT

DIP. ROLLER. BRUSH

To dip, immerse wood for 3 minutes or longer. For all other applications techniques, apply 2 coats. Allow at least 1 hour between applications. For above ground contact, use a 1.25% copper dilution. For ground contact, use up to a 2% copper dilution.

END CUT TREATMENTS

To comply with AWPA M4-15, apply a 1% or 2% dilution of QNAP5W to cuts, holes or injuries.

PRESSURE TREATMENT

Wood used in critical (structural) above-ground applications or that may be exposed to severe conditions such as extended periods of wetting, should be treated by pressure treatment with a solution containing 0.2% to 1.0% copper metal to a target retention in the wood of not less than 0.04 not more than 0.20 lbs copper metal/ ft³ or in accordance with AWPA Standards U1-18 or T1-18. For ground contact treat with a solution containing 0.25% to 2.0% copper to a

target retention in the wood of not less than 0.03 not more than 0.20 lbs. copper metal/ft³ in accordance with AWPA Standards U1-18 or T1-18.

WOOD TREATMENT: REMEDIAL APPLICATIONS

A QNAP5W solution of 2% copper metal may be used for remedial treatment of standing wood poles, piling and other existing structures. QNAP5W may be re-applied to bare wood at any time.

{For product packaged in rigid, non-refillable containers less than or equal to 5 gallons:}

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal.

Pesticide Storage: Store in a cool, dry (preferably locked) storage area inaccessible to children and pets. Do not freeze. **Pesticide Disposal:** Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. **Container Handling:** Nonrefillable container; do not reuse or refill this container. Triple rinse (or equivalent) container promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with solvent and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times, then offer for recycling, if available; or reconditioning, if appropriate; or puncture and dispose of in a sanitary landfill; or by incineration.

{For product packaged in rigid, non-refillable containers greater than 5 gallons:}

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal.

Pesticide Storage: Store in a cool, dry (preferably locked) storage area inaccessible to children and pets. Do not freeze. Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. Container Handling: Nonrefillable container; do not reuse or refill this container. Triple rinse (or equivalent) container promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with solvent. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling, if available; or reconditioning, if appropriate; or puncture and dispose of in a sanitary landfill; or by incineration.

{For the end-user's bulk tanks}

CONTAINER HANDLING: Refillable container. Refill with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. Use standard industry practices for cleaning bulk containers or contact the registrant for more information.

Spill or Leak Procedures: Refer to the Safety Data Sheet (SDS) associated with this product for information on how to properly clean-up spillage.

{Per PR Notice 2007-4 the batch code/lot number will appear on the label or container.}

WARRANTY DISCLAIMER

To the extent not prohibited by applicable law, Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions, subject to the inherent risks set forth below. To the extent not prohibited by applicable law, MANUFACTURER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Inherent Risks of Use

The directions for use of this product are believed to be adequate and must be carefully followed. It is impossible to eliminate all risks associated with use of this product. Lack of performance or other unintended consequences may result because of such factors as use of the product contrary to label instructions, abnormal conditions, the presence of other materials, climatic conditions or the manner of use/application, all of which are beyond the control of the Manufacturer. To the extent not prohibited by applicable law, the buyer/user assumes all such risks.

Limitation of Remedies

To the extent not prohibited by applicable law the exclusive remedy for losses or damages resulting from this product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's election, one of the following:

- 1. Refund of purchase price paid by buyer or user for product bought, or
- 2. Replacement of amount of product used.

To the extent not prohibited by applicable law: a) Manufacturer shall not be liable for losses or damages resulting from handling or use of this product unless Manufacturer is promptly notified of such loss or damage in writing; and b) TO THE EXTENT NOT PROHIBITED BY APPLICABLE LAW IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES.

The terms of this **Warranty Disclaimer** and **Limitation of Remedies** cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this **Warranty Disclaimer** or **Limitation of Remedies** in any manner.

It is not intended that this product be used to practice any applicable patent, whether mentioned or not, without procurement of a license, if necessary, from the owner, following investigation by the user.]

[{Option 2}

[For a complete and printable Warranty Disclaimer, please visit www.nisuswarranty.com.]

{Note to reviewer: Current Nisus Corporation logo will be used}

100 Nisus Drive Rockford, TN 37853 1-800-264-0870

QNAP5W[®] is a Trademark of Nisus Corporation Made in the U.S.A.

© ______ {Label Code}

{Marketing Claims }

- Non Restricted Use, Ground Contact, Wood Preservative
- General Use Approved For Use On Wood With Ground Contact
- [Use] Above Or Below Ground [& Ground Contact]
- For Wood In Contact With Soil

- For wood in contact with soil and water
- Preserves Wood
- Prolongs The Life Of Non-Pressure Treated Wood
- For Preserving Cedar Shake Roofs
- Cedar Shake Roof Preservative
- Meets AWPA Standards M4-15 [For End Cut Treatments]
- Meets Or Exceeds AWPA Standard [Specifications U1-18 or T1-18]
- For Use on {insert application sites listed on label}
- May Be Used In a Dual Treatment with Borates for Protection of Crossties, Switch Ties and Bridge Timbers [and {insert application sites listed on label}]
- For Preservation of Wood Against {insert pests listed on label}
- Prevents {insert pests listed on label}
- Protects Against Decay (insert pests listed on label)
- Resists mold and mildew
- Anti-wicking controls moisture damage
- Stops {insert pests listed on label}
- Kills {insert pests listed on label} {insert application sites listed on label}
- Highly Effective Against {insert pests listed on label}
- Paintable and Stainable
- Deep Penetrating formula
- Note: application of product on redwood and cedar will darken wood.
- Printed in USA
- Contains Copper Naphthenate
- Contains 3 Naturally Found Components
- This product produced from 100% recycled Copper Metal and by-products from the refining industry
- Non Sludging
- Non Corrosive to Utility Hardware [Railroad Spikes and Tie Plates]
- Can Help Prevent "Spike Kill" when Combined with Borate Treatments
- Non Conductive
- Treated Wood Does Not Become Brittle or Hard
- Reduces Hardening of the Wood Which Allows for Increased [Easy] Gaff Penetration
- · Easy soap and water clean-up
- Water clean up