




3. Submit five (5) copies of final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell  
Acting Product Manager 31  
Antimicrobial Program Branch  
Registration Division 7505C

Enclosure

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS  
AND DOMESTIC ANIMALS  
KEEP OUT OF REACH OF CHILDREN

CAUTION: Causes eye irritation.  
Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing.  
Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled.  
Do not breathe sanding dust, vapor spray mist. Wear NIOSH/MSHA certified mask or respirator. Use adequate ventilation.  
Remove contaminated clothing and wash before reuse.  
Wash thoroughly with soap and water after handling.

#### Statement of Practical Treatment

IF SWALLOWED: Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Call a physician if irritation persists.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

This product is intended for commercial and recreational use



## No Foul-ZDF

### Antifouling Paint for Boat Bottoms Trim Tabs, IO Units Blue

#### Active Ingredients:

Zinc oxide ..... 36.0%

Inert Ingredients..... 64.0%

100.0%

Equivalent to 28.8% metallic zinc

### KEEP OUT OF REACH OF CHILDREN

#### CAUTION

See side panel for additional precautions and the Statement of Practical Treatment.

Net Contents: 1 Gal  
EPA Registration No. 64684-3  
EPA Establishment No.

Manufactured by:

E Paint Co.  
Box 291

Buzzards Bay, Mass. 02532

US Patent #5,008,146

### STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

#### PESTICIDE DISPOSAL

Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state, or local procedures under the Resources Conservation and Recovery Act.

#### CONTAINER DISPOSAL

Dispose of container by triple rinsing and recycling or by other approved State and local procedures

### ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner that is inconsistent with its labeling.

May be used in fresh or salt water, use on outboard motors, trim tabs, lower IO units and the bottom of vessels is recommended.

Directions for mixing: Mix contents of container. Stir until thoroughly mixed before using. Use immediately.

Preparation of Surface: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and/or sanding before any primers or paints are applied. Follow the recommended systems below. Bare metal surfaces should be primed prior to application. When sanding old antifouling paint, use a face mask to prevent inhalation of sanding dust.

Application and Temperature: *No Foul* can be applied by brush or roller. The work should be done under good drying conditions in the temperature range of 40 to 90°F. Two coats are recommended for best antifouling protection.

Thinner: Use odorless mineral spirits sparingly if necessary.

Drying Times: Let the first coat dry for between two and four hours before applying the second coat. After application of the second coat allow at least four hours drying time before launching. Under adverse drying conditions let the boat dry overnight to be sure that all of the solvent has evaporated from the paint film.

ACCEPTED  
with COMMENTS  
In EPA Letter Dated:  
SEP 29 1994  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.  
64684-3

W/C