64684-4

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

12/14/2001

DEC 1 4 2001

1/2

Christine Greene Regulatory Affairs Manager E Paint Company, Inc. 25 Research Road E. Falmouth, MA 02536

Subject: E Paint ZO EPA Registration No. 64684-4 Application Date:10/24/01 Receipt Date: 10/25/01

The following amendment, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, to change the registered product name to "E Paint ZO", is acceptable with comments.

- 1. The "Statement of Practical Treatment" must comply with PR Notice 2001-1. Please refer to the enclosed PR Notice 2001-1 and determine the route of exposure for the appropriate toxicity category.
- 2. Move the "Foul" logo further away from the product name. The logo appears to be part of the name.
- 3. Change "Active Ingredients" to "Active Ingredient."
- 4. Please submit three (3) copies of the corrected label.
- A stamped copy of the label is enclosed for your records.

If you have any question concerning this letter, please contact Solange Garvey 703-308-8911.

Sinderely. Marshall Swindell

Product Manager 33 Regulatory Management Branch I

		CONCURRENCES Division (7510C)						
SYMBOL)								
DATE								
	• • • • • • • • • • • • • • • • • • •						000101	AL EN CODY

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner that is inconsistent with its labeling. May be used in fresh or salt water, use on the bottom of vessels is recommended.

This paint is intended for use on commercial and recreational vessels.

Directions for mixing: Mix contents' of container. Stir until thoroughly mixed before using. Use immediately.

Preparation of Surface: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and/or sanding before any primers or paints are applied. Follow the recommended systems below. Bare metal surfaces should be primed prior to application. When sanding old antifouling paint, use a face mask to prevent inhalation of sanding dust.

Application and Temperature: No Foul can be applied by brush or roller. The work should be done under good drying conditions in the temperature range of 50 to 90° F. Three coats are recommended for best antifouling protection.

Thinner: Thinning not recommended. Clean up with EP-13.

Drying Times: Let the first coat dry for four hours before applying next coat. After application of the third coat allow at least 15 hours drying time before launching. Under adverse drying conditions allow paint to dry overnight to be sure that all of the solvent has evaporated.

E PAINT ZO Antifouling Paint

DANGER! KEEP OUT OF REACH OF CHILDREN See back panel for additional precautions and statement of practical treatment.

NET CONTENTS:

5 U.S. GALLON (18.9 LITERS)

U.S. Patent #5,916,947

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of E Paint Company including surface preparation, proper application, and environmental conditions. Therefore, E Paint Company cannot guarantee this product's suitability for your particular purpose or application. IMPUED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. E PAINT COMPANY SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCI-DENTAL OR CONSECUENTIAL DAMAGES By purchase or use of this product, buyer agrees that the sole and excluser immedy, it any, is limited to refund of the purchase proc. or replacement of the product at E Paint

Active Ingredients

Zinc Pyrithione	4.8%
Inert Ingredients	
10	0.0%

Equivalent to 28.9% metallic zinc Contains Petroleum Distillate EPA Reg. No. 64684-4 EPA Establishment No. 64684-RI-001

Manufactured by:

E Paint Company, Inc. 25 Research Rd. ACCTPTID E. Falmouth, MA 02538/00 COIA: TRATS IA EPA Lotter Day 1

DEC 1 4 2001

Under the Percent first caude, Physicial and f_{charged} in the second s

PRECAUTIONARY ST HAZARDS TO HUMANS AND D KEEP OUT OF REACH O

CORROSIVE: Causes irreversible eye dat absorbed through skin. Do not get in eyes of skin. Wear goggles or face shield. Wash chewing gum, using tobacco or using the clothing and wash clothing before reuse.

STATEMENT OF PRACTICA

If Swallowed: Call a physician or Poison (vomiting. Drink promptly a large quantity of m or if these are not available, drink large qua

If On Skin: Wash with plenty of soap and v

If in Eyes: Hold eyelids open and flush with for 15 minutes. Get medical attention.

Note To Physician: Probable mucosal da use of gastric lavage.

STORAGE & DIS

Do not contaminate water, food, or feed, t dumping is prohibited.

Pesticide Disposal:

Pesticide wastes are toxic. Paint that canninstructions must be disposed of accord procedures under the Resources Conservation

Container Disposal:

Dispose of container by triple rinsing and r state and local procedures.

ENVIRONMENTAL

This pesticide is toxic to aquatic organisms not apply directly to water by cleaning of eq Do not allow chips and dust generated durir Dispose of paint debris in an approved lanc

This Product is Intended for Commen