

64684-4

12/08/2004

1/2

DEC 08 2004

Kimberly Fontaine-Goodwin
E Paint Company
25 Research Road
E. Falmouth, MA 02536

**Subject: Zinc Pyrithione RED Required Label Amendments, Both Dated 11/22/04
E Paint-ZO; EPA Reg. No. 64684-4 ✓
EP 2000; EPA Reg. No. 64684-6**

The two amendments referred to above, submitted in connection with re-registration under the Federal Insecticide, Fungicide, and Rodenticide Act), as amended, which provide revised labels with interim label changes as required by the Zinc Pyrithione Red decision memo dated 9/30/04, and further specified in the EPA letter dated 11/4/04 to each registrant with zinc pyrithione products, are acceptable with the following change.

On the E Paint-ZO label, delete "supplied air" from the last sentence in the "Environmental Hazards" section. The attached stamped label has these words blacked out.

The products listed above must have the accepted label changes on them the earlier of the next product production cycle, or the next boat painting season in 2005. Copies of labels stamped "Accepted With Comments" are enclosed for your records.

As per the registration notices for these product dated 3/17/03, these registration expires 6/30/05.

If you have any questions about the comments in this letter, please feel free to contact Tony Kish at 703-308-9443, or myself at 703-308-6341.

Sincerely,



Marshall Swindell,
Product Manager Team 33,
Regulatory Management Branch I
Antimicrobials Division (7510C)

ACCEPTED
COMMENTS
Letter Dated:

8-4-44

Federal Insecticide,
and Rodenticide Act as
the pesticide,
under EPA Reg. No.

Epaint[®]

E Paint ZO

Antifouling Paint for Boat Bottoms
With Zinc Oxide

DANGER: KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS
AND STATEMENT OF PRACTICAL TREATMENT

Active Ingredients
Zinc Pyrrhione 4.8%
Inert Ingredients 95.2%
100.0%

NET CONTENTS:
ONE U.S. QUART (.946 LITER)

*Contains Petroleum Distillates
EPA Reg. No. 64684-4
EPA Establishment No. 71-223-OH-1

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner that is inconsistent with its labeling. May be used in fresh or salt water, use on the bottom of vessels is recommended. This paint is intended for use on commercial and recreational vessels.

Directions for mixing: Mix contents of container. Stir until thoroughly mixed before using. Use immediately.

Preparation of surfaces: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and/or sanding before any primers or paints are applied. Follow the recommended systems below. Bare metal surfaces should be primed prior to application. When sanding old antifouling paint, use a face mask to prevent inhalation of sanding dust. Clean up with EP-13.

Application and Temperature: E Paint ZO can be applied by spray, brush or roller. The work should be done under good drying conditions in the temperature range of 50 to 90°F. Three coats are recommended for best antifouling protection.

For application by residential (non-commercial) users: Do not apply by splash sprayer. Do not apply more than one coat of this product within 24 hours. Apply only in outdoor, non-enclosed spaces.

Drying Times: Let the first coat dry for four hours at 70 degrees before applying next coat. After application of the third coat allow at least 15 hours drying time at 70 degrees before launching. Under adverse drying conditions allow paint to dry overnight to be sure that all of the solvent has evaporated. See technical data sheets for additional details. Thinning not recommended.

FIRST AID

- If inhaled
 - Move person to fresh air.
 - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.
 - Call a poison control center or doctor for further treatment advice.
- If on skin
 - Take off contaminated clothing.
 - Rinse skin immediately with plenty of water for 15-20 minutes.
 - Call a poison control center or doctor for further treatment advice.
- If in eyes
 - Hold eye open and rinse slowly and gently with water for 15-20 minutes.
 - Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye.
 - Call a poison control center or doctor for further treatment advice.
- If swallowed
 - Call a poison control center or doctor immediately for treatment advice.
 - Do not induce vomiting unless told to by the poison control center or doctor.
 - Do not give anything by mouth to an unconscious person.
 - Do not give any liquid to the person.
 - Do not give anything by mouth to an unconscious person.

IN CASE OF EMERGENCY CALL: 800-424-9300

Note to Physician • Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS AND DOMESTIC ANIMALS KEEP OUT OF REACH OF CHILDREN

CORROSIVE: Causes irreversible eye damage. Harmful if swallowed or absorbed through the skin. May be fatal if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wash thoroughly after handling with soap and water, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse. When mixing and loading, or cleaning equipment, wear a chemical resistant apron.

Residential Use: Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and shoes. While removing existing paint by sanding or blasting, or applying new paint by brush or roller, it is advised to wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

Commercial Use: Users must wear a disposable coverall with hood, chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new paint, user must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

STORAGE & DISPOSAL

Do not store near heat source or open flames. Containers are hazardous when empty. Empty containers retain product residue (vapors and/or liquid). Residual vapors may explode or ignite; do not cut, drill, grind, or weld on or near this container. Do not combine with water, food or feed by storage, disposal, or cleaning of equipment. Pesticide Disposal: Pesticide wastes are hazardous. Improper disposal of excess pesticide or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to the Hazardous Waste representative at the nearest EPA Regional Office for guidance, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. **Collection/Disposal:** If empty, do not reuse this container. Place in trash or other for recycling if available. If partly filled, call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and use appropriate respirator in accordance with the Precautionary Statements above when handling, painting or removing this paint.

2/2