MON 20 2007

#### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



### EPA United States Environmental Protection Office of Pesticide Programs Apercy

**E Paint Company** 25 Research Road East Falmouth, MA 02536

**Attention: Kimberly Fontaine-Goodwin** 

Subject:

E Paint SN-1

**EPA Registration No. 64684-5** 

Amendment Dated October 30, 2007

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, to update the precautionary statements, is acceptable.

A stamped copy of the "accepted" labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha L. Terry at (703) 308-6217.

**Sincerely** 

Marshall Swindell

**Product Manager (33)** 

**Regulatory Management Branch 1** Antimorobials Division (7510P)

Martha L being / Ber

**Enclosure** 

## ACCEPTED with COMMENTS EPA Letter Dated:

NOV 2 0 2007

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 64684-5



Manufactured by: E Paint Company 25 Research Road E. Falmouth, MA 02536

#### U.S. Patenis #5 916 947 #6 063 849

The Company of the Control of the Co



# epaint

## E Paint SN-1

Antifouling Paint for Boat Bottoms With Sea-nine 211®

DANGER
KEEP OUT OF REACH OF CHILDREN
See back plate for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.8 LITERS) VOC <400G/LITER

It is a violation of Federal law to use this product in a manner that is inconsistent with its labeling.

**DIRECTIONS FOR USE** 

This product may be used in fresh or salt water, and is intended for use on the bottom of boats and ships.

Directions for mixing: Mix contents of container. Stir until thoroughly mixed before using. Use immediately.

Preparation of Surface: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and/or sanding before any primers or paints are applied. Follow the recommended systems below. Bare metal surfaces should be primed prior to application. When sanding old antifouling paint, use a face mask to prevent inhalation of sanding dust.

Application and Temperature: Apply by brush, roller, or sprny. The work should be done under good drying conditions in the temperature range of 50 to 90°F. Three coats are recommended for best antifouling protection.

Thinner: Thinning not recommended

**Drying Times:** Let the first coat dry for four hours before applying second coat. After application of the second and third coats allow at least ten hours drying time before launching. Under adverse drying conditions let the boat dry overnight to be sure that all of the solvent has evaporated from the paint film.

#### FIRST AID

#### If Inhaled

Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

#### If on Skin

Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for further treatment advice.

#### If in Eves

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice.

#### If Swallowed

Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

#### IN CASE OF EMERGENCY CALL: 800-424-9300

#### Note to Physician

Probable mucosal damage may contraindicate the use of gastric lavage.

#### Active Ingredient

4, 5-Dichloro-2-n-octyl-3(2H)-

ACCEPTED

with COMMENTS

NOV 2 0 2007

Under the Federal Insecticide.

amended, for the pesticide,

Fungicide, and Rodenticide Act as

registered under EPA Reg. No. 16464-5

**EPA Letter Dated:** 

Use Restrictions: Fortuse in Commercial of Navy shipyards only Not for use by private applicators or marries. Not for use on station

Contains Petroleum Distillates (EPA Reg. No. 64684-5) EPA Establishment No. 71223-OH-1

#### PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS KEEP OUT OF REACH OF CHILDREN

DANGER, CORROSIVE: Causes—irreversible eye damage and may cause severe skin irritation. Product may be fatal if swallowed or absorbed through the skin. Harmful if swallowed, inhaled or absorbed through the skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin or on clothing. Avoid contact with skin. This products a dermal sensitizer. Where skin and eye contact may occur, wear eye protection such as georgles or face shield, rubber gloves, full body coverings such as coveralls—and hat, and other protective clothing such as long sleeved shirt, long pants, and head covering to prevent skin-contact. Avoid breathing vapor, mist, dust or chips from painting and sanding. Use adequate ventilation. While spraying paint or sanding boat surface, wear a supplied-air or powered air purifying respirator (PAPR) approved by NIOSH for use with paints and coatings.

Wear a Tyvek hooded coverall or the exact equivalent, coverall beneath the Tyvek hooded coverall, impervious gloves and impervious footwear that protects the lower leg. Remove contaminated clothing and discard after each use, do not reuse. Wash thoroughly with soap and water after handling and before eating or smoking.

#### STORAGE & DISPOSÁL

Do not store near heat source or open flames. Containers are hazardous when empty. Emptied containers retain product residue (vapors and/or liquid). Residual vapors may explode or ignite; do not cut, drill, grind, or weld on or near this container. Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment.

#### Pesticide Disposal:

Pesticide wastes are hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

#### Container Disposal:

For metal containers, triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

#### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not dicharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Offices of the EPA. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and supplied air respirator in accordance with the Precautionary Statements above when handling, painting or removing this paint.

This Product is Intended for use only on Commercial or
Government Boats or Vessels

2