UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460





United States Environmental Protection Office of Pesticide Programs Agency

E Paint Company 25 Research Road East Falmouth, MA 02536

Attention: Kimberly Fontaine-Goodwin

Subject:

E Paint SN-1

EPA Registration No. 64684-5 Notification Dated October 7, 2008

This will acknowledge receipt of your notification to include an EPA Establishment Number on the product labeling, submitted under the provisions of FIFRA Section 3(c)(9). Based on a review of the submitted material, the following comments apply.

The Notification dated October 7, 2008 is in compliance with PR Notice 98-10 and is acceptable. The information has been added to your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimorobials Division (7510P)

Please read instructions on reverse before	re completing form.	Form A	pproved. OMB No. 2070	Printa-orm	
SEPA Environmental Protection Washington, DC 294		tion Agency	Registration Amendme Other	OPP Identifier Number	
Application for Pesticide - Section I					
1. Company/Product Number E Paint Company		2. EPA Product Manager Marshall Swindell		3. Proposed Classification	
4. Company/Product (Name) E Paint SN-1		PM# 33			
5. Name and Address of Applicant Include ZIP Code) E Paint Company 25 Research Road East Falmouth, MA 02536		(b)(i), my produc to: EPA Reg. No.	EPA Reg. No. 64684-5		
Check if this is a new ac	dress	Product Name E Paint SN-1			
Section - II					
Amendment - Explain below. Resubmission in response to Age Notification - Explain below.	ncy letter dated	Agency I	Final printed labels in response to Agency letter dated "Me Too" Application. Other - Explain below.		
This form is to notify the EPA that ePaint Company would like to use EPA Establishment Number 64684-MA-001 on our product labels. This label is in addition to our current product label which uses EPA Establishment Number 71223-OH-1. The label has no modifications to our current federally registered label other than the use of our alternate EPA Establishment Number.					
Section - III					
1. Meterial This Product Will Be Packaged In:					
Child-Resistant Packaging Yes* X No * Certification must Unit Packa Unit Packa	No. per	Water Soluble Packaging Yes No If "Yes" No. per Package wgt contain	Ple Gli	tainer etic ass per her (Specify)	
be submitted					
3. Location of Net Contents Information 4. Size(s) Retail Container 5. Location of Label Directions On Label On Labeling accompanying product					
6. Manner in Which Label is Affixed to Product Comparison		graph Oth r glued ciled	aph Other		
Section - IV					
1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)					
Nome Kimberly Fontaine-Goodwin		O		phone No. (Include Area Code) 8-540-4412 (c c c ()	
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or (Stamped) both under applicable law.					
2. Signature . Kemberly & S	di .	နှ. Titlပ Operations Manager			
4. Typed Name Kimberly Fontaine-Goodwin		5. Date 10/7/08	· · ·	((((((((((((((((((((



February 22, 2000

PM #33 US EPA, OPP Antimicrobials Division Mr. Marshall Swindell 7510 P One Potomac Yard/2777 South Crystal Drive Arlington, VA 22202

In support of Notification dated 10/7/2008 for EPA# 64684-5.


Notification per PR Notice 98-10 Labeling Notifications

This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the confidential statement of formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 98-10 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

Sincerely,

Rimbelry Fontaine Goodwin

Kimberly Fontaine-Goodwin



-Dichlor

untifouling Paint for Boat Bottoms With Sea-nine 211®

purchase or use of this product, buyer agrees than the sole and exclasive remedy. If any, is limited to returd of the pur-NCIDENTAL OR CTONSEQUENTIAL DAMAGES. BY

these prices or replacement of the product a

E Painn Company's option.

DANGER

U.S. Patents #5,916,947, #6,063,849

18 Petini Company connect guarance this product's suitability for your particular purpose or application MIPLIED. WARRANTIES OF PITMESS FOR A PARTIC LILAR PURPOSE AND OF MERCHANTABILITY ARE ENCLUDED, B PAINT COMPANY SHALL, NOT NIOTE ANY CHICUMSTANCES, BIE LIABLE FOR

environmental conditions.

KEEP OUT OF REACH OF CHILDREN See back panel for additional presautionary statements.

EPA Reg, No

EPA Escabila

Contains Per

applifeators to

Navy sluten Disc Restul

any structum

ONE U.S. GALLON (3.8 LITTERS) NET CONTENTS:

VOC <400GALITIER

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner that is inconsistent with its labeling.

This product may be used in fresh or salt water, and is intended for use on the bot-

Directions for mixing: Mix contents of container. Stir until thoroughly mixed before using. Use immediately o

Preparation of Surface: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and/or sanding before any springers or paints are applied. Follow the recommended systems below. Bare metal osurfaces should be primed prior to application. When sanding old antifouling paint, sue a face mask to provent inhalation of sanding dust.

Application and Temperature: Apply by brush, roller, or spray. The work should be done under good drying conditions in the temperature range of 50 to 90°F. Three coats are recommended for best antifouling protection.

Thinner: Thinning not recommended

Drying Times: Let the first coat dry for four hours before applying second coat. After application of the second and third coats allow at least ten hours drying time before launching. Under adverse drying conditions let the boat dry overnight to be sure that all of the solvent has evaporated from the paint film.

FIRST AID

If Inhaled

Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

If on Skin

Dichloro-2-n-octyl-3(2H)

ains Petroleum Distillates

Establishment No. 64684-MA-001

Reg. No. 64684-5

tructures.

Restrictions: For use in Commercial or

shipyards only. Not for use by private

calors or marinas. Not for use on station-

Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for further treatment advice.

If in Eyes

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice.

If Swallowed

Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

IN CASE OF EMERGENCY CALL: 800-424-9300

Note to Physician

Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS KEEP OUT OF REACH OF CHILDREN

DANGER, CORROSIVE: Causes irreversible eye damage and may cause severe skin irritation. Product may be fatal if swallowed or absorbed through the skin. Harmful if swallowed, inhaled or absorbed through the skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin or on clothing. Avoid contact with skin. This product is a dermal sensitizer. Where skin and eye contact may occur, wear eye protection such as googles or face shield, rubber gloves, full body coverings such as coveralls and hat, and other protective clothing such as long sleeved shirt, long pants, and head covering to prevent skin contact. Avoid breathing vapor, mist, dust or chips from painting and sanding. Use adequate ventilation While spraying paint or sanding boat surface, wear a supplied-air or powered air purifying respirator (PAPR) approved by NIOSH for use with paints and coatings.

Wear a Tyvek hooded coverall or the exact equivalent, coverall beneath the Tyvek hooded coverall, impervious gloves and impervious footwear that protects the lower leg. Remove contaminated clothing and discard after each use, do not reuse. Wash thoroughly with soap and water after handling and before eating or smoking.

STORAGE & DISPOSAL

Do not store near heat source or open flames. Containers are hazardous when empty. Emptied containers retain product residue (vapors and/or liquid). Residual vapors may explode or ignite; do not cut, drill, grind, or weld on or near this container. Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment.

Pesticide Disposal:

Pesticide wastes are hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal:

For metal containers, triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not dicharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Offices of the EPA. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and supplied air respirator in accordance with the Precautionary Statements above when handling, painting or removing this paint.

This Product is Intended for use only on Commercial or
Government Boats or Vessels