

64684-5

12/9/2010

1 of 4



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number: 64684-5

Date of Issuance: DEC 09 2010

Term of Issuance:

Conditional Expires 12/31/2012

Name of Pesticide Product:

No Foul SN-1

NOTICE OF PESTICIDE:

[x] Registration
Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

E. Paint, Inc.
25 Research Road
E. Falmouth, MA 02536

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(a) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
a. Revise the "EPA Registration Number to read, "EPA Reg. No. 64684-5".

Signature of Approving Official:

[Handwritten signature of Marshall Swindell]

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Date:

DEC 09 2010

2014


Page 2
EPA Reg. No. 64684-5

- b. Submit the protocol and study by June 1, 2006:
 - a. Inhalation Monitoring Study:
 - i. Intent: Measure airborne concentrations of Sea-Nine 211 during Ship painting operations with a representative marine antifoulant (MAF) paint. Prior to initiating the monitoring study, submit the study design for Agency review to ensure compliance with Agency methodologies for conducting such studies. Also, note that this Study is intended to support only presence of 3% active ingredient in End-Use paint formulations.

The data being required as a condition of registration must be submitted, reviewed, and found to be acceptable by June 1, 2007.

This conditional registration will expire automatically on 12/31/2012. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice of Registration to Cancel under Section 6(e) of FIFRA. Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records. Submit one (1) copy of your final printed labeling prior to release of this product for shipment. If you have any questions concerning this letter, please contact Abigail Downs at 703-307-5259.

Sincerely,

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Enclosure: (Stamped Label)

ACCEPTED
with COMMENTS
in EPA Letter Dated:

DEC 09 2010

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

64684-5



Manufactured by:
E Paint Company
25 Research Road
E. Falmouth, MA 02536

U.S. Patents #5,916,947 #5,083,849

DISCLAIMER: The performance of any marine
paint or coating depends on many factors
outside the control of E Paint Company, includ-
ing surface preparation, proper application,
and environmental conditions. Therefore,
E Paint Company cannot guarantee the pro-
duct's suitability for your particular purpose
or application. IMPLIED WARRANTIES OF
FITNESS FOR A PARTICULAR PURPOSE AND
OF MERCHANTABILITY ARE EXCLUDED.
E PAINT COMPANY SHALL NOT UNDER ANY
CIRCUMSTANCES BE LIABLE FOR INCIDENTAL
OR CONSEQUENTIAL DAMAGES. By purchase or
use of this product, buyer agrees that the sole and
exclusive remedy, if any, is limited to refund of the
purchase price, or replacement of the product at
E Paint Company's option.

**E
P
A
I
N
T
S
N
-
1**

*E*paint®

E Paint SN-1

**Antifouling Paint for Boat Bottoms
With Sea-nine 211®**

DANGER:
KEEP OUT OF REACH OF CHILDREN
See back panel for additional precautionary statements.

NET CONTENTS:
ONE U.S. GALLON (3.8 Liters)
VOC <400G/LITER

3064

ACCEPTED
with COMMENTS
in EPA Letter Dated:
DEC 09 2010

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

64684-5

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner that is inconsistent with its labeling.

This product may be used in fresh or salt water, and is intended for use on the bottom of boats and ships.

Directions for mixing: Mix contents of container. Stir until thoroughly mixed before using. Use immediately.

Preparation of Surface: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and/or sanding before any primers or paints are added. Follow the recommended systems below. Bare metal surfaces should be primed prior to application. When sanding old antifouling paint, use a face mask to prevent inhalation of sanding dust.

Application and Temperature: Apply by brush, roller, or spray. The work should be done under good drying conditions in the temperature range of 50 to 90°F. Three coats are recommended for best antifouling protection. **Thinner:** Thinning not recommended.

Drying Times: Let the first coat dry for four hours before applying second coat. After application of the second and third coats allow at least ten hours drying time before launching. Under adverse drying conditions let the boat dry overnight to be sure that all of the solvent has evaporated from the paint film.

FIRST AID

If Inhaled

Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

If on Skin

Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for further treatment advice.

If in Eyes

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice.

If Swallowed

Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

IN CASE OF EMERGENCY CALL: 800-424-9300

Note to Physician:

Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS KEEP OUT OF REACH OF CHILDREN

DANGER, CORROSIVE: Causes irreversible eye damage and may cause severe skin irritation. Product may be fatal if swallowed or absorbed through the skin. Harmful if swallowed, inhaled or absorbed through the skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin or on clothing. Avoid contact with skin. This product is a dermal sensitizer. Where skin and eye contact may occur, wear eye protection such as goggles or face shield, rubber gloves, full body coverings such as coveralls and hat, and other protective clothing such as long sleeved shirt, long pants, and head covering to prevent skin contact. Avoid breathing vapor, mist, dust or chips from painting and sanding. Use adequate ventilation. While spraying paint or sanding boat surface, wear a supplied-air or powered air purifying respirator (PAPR) approved by NIOSH for use with paints and coatings.

Wear a Tyvek hooded coverall or the exact equivalent, coverall beneath the Tyvek hooded coverall, impervious gloves and impervious footwear that protects the lower leg. Remove contaminated clothing and discard after each use, do not reuse. Wash thoroughly with soap and water after handling and before eating or smoking.

STORAGE & DISPOSAL

Do not store near heat source or open flames. Containers are hazardous when empty. Empty containers retain product residue (vapors and/or liquid). Residual vapors may explode or ignite; do not cut, drill, grind, or weld on or near this container. Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment.

Pesticide Disposal:

Pesticide wastes are hazardous. Improper disposal of excess pesticide or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal:

For metal containers, triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Offices of the EPA. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and supplied air respirator in accordance with the Precautionary Statements above when handling, painting or removing this paint.

This Product is intended for use only on Commercial or Government Boats or Vessels

Active Ingredient

5-Dichloro-2-n-octyl-3(2H)

imidazolone 2.91%

Inert Ingredients 97.09%

100.0%

Use Restrictions: For use in Commercial
Navy shipyards only. Not for use by
private applicators or marinas. Not for use
on stationary structures.

Contains (Petroleum) Distillates

EPA Reg. No. 64684-5

EPA Establishment No. 64684-MA-001

4084