

64684-6

12-31-2007

1/5



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs  
Antimicrobials Division (7510C)  
1200 Pennsylvania Avenue NW  
Washington, D.C. 20460

NOTICE OF PESTICIDE:  
 Registration  
 Reregistration

(under FIFRA, as amended)

EPA Reg. Number:  
64684-6

Date of Issuance:  
123107

Term of Issuance: Expires on  
December 31<sup>st</sup>, 2008

Name of Pesticide Product: EP-2000

Name and Address of Registrant (include ZIP Code):

E Paint, Inc.  
25 Research Road  
E. Falmouth, MA 02536

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
  - a. Add the phrase "EPA Registration Number 64684-6".

Signature of Approving Official:

Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510P)

Date:

123107

2. The following submitted data must be found acceptable.

**73-1 Whole sediment acute freshwater invertebrate**

**73-2 Whole sediment acute marine invertebrate**

**850.5400 Marine diatom Skeletonema costatum**

**850.4225 Seedling emergence in rice**

**850.5400 Vegetative vigor dose response in rice**

3. Submit by 1/1/05, data to satisfy the following requirements:

**875.1100 Dermal exposure-outdoor**

**875.1330 Inhalation exposure-outdoor**

4. Submit the following "reserved" studies within 12 months of the date of the Agency's written request for these data. The need for these reserved data will be based upon the results of one or more of the above studies as determined by the Agency.

GLN 72-5 Fish Life Cycle

GLN 72-7 Simulated or actual field testing for aquatic organisms

GLN 71-4 Avian Reproduction

GLN 73-3 Acute Pore Water Studies (fish and invertebrates)

GLN 74-1 Whole Sediment Chronic Study(invertebrates)

Special Study: Monitoring of Representative U.S. Waters

~~GLN 162-1 Aerobic Soil Metabolism~~

GLN 162-2 Anaerobic Soil Metabolism

GLN 164-2 Aquatic Field Study

GLN (Not Assigned) Monitoring of Representative US Waters

This conditional registration will expire on December 31<sup>st</sup>, 2008. If you fail to satisfy the conditions imposed on the registration, EPA may issue a Notice of Registration to cancel under section 6(e) of FIFRA.

4. Submit two copies of the revised final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.


A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703)-308-6237.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobial Division(7510P)

# FP 2000

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

123107

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide  
registered under EPA Reg. No.

64684-6

Manufactured by  
E-Paint Company  
275 West 12th Street  
Cincinnati, Ohio 45202

DISCLAIMER: The performance of any  
inert paint or coating depends on  
many factors outside the control of E  
Paint Company including surface prepara-  
tion, proper application, and environ-  
mental conditions. Therefore, E Paint  
Company cannot guarantee the prod-  
uct's suitability for your particular pur-  
pose or application. IMPLIED WAR-  
RANTIES OF FITNESS FOR A PAR-  
TICULAR PURPOSE AND OF MER-  
CHANTABILITY ARE EXCLUDED. E  
PAINT COMPANY SHALL NOT  
UNDER ANY CIRCUMSTANCES, BE  
LIABLE FOR INCIDENTAL OR CONSE-  
QUENTIAL DAMAGES. By purchase or  
use of this product, buyer agrees that  
the sole and exclusive remedy, if any, is  
limited to refund of the purchase price,  
or replacement of the product at E Paint  
Company's option.

# epaint®

Go Fast, Stay Clean

High Performance, Photoactive Water  
Repelling Paint for Boat Bottoms

ZINC OXIDE

DANGER: KEEP OUT OF REACH OF CHILDREN  
SEE BACK PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS.

Active  
Zinc Oxide  
Inert I

NET CONTENTS:  
ONE U.S. GALLON (3.8 LITERS)

EPA R  
EPA E

## DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner that is inconsistent with its labeling. May be used in fresh or salt water, use on the bottom of vessels is recommended.

This paint is intended for use on commercial and recreational vessels.

**Preparation:** REMOVE all existing antifouling paint before applying EP2000. Grind, sandblast, or hydroblast to remove existing antifouling paint.

**Primer:** All surfaces to be coated with EP2000 should be primed with EP-Prime 2000 to provide a fresh, clean substrate for EP2000 to adhere. Follow manufacturer's instructions regarding surface preparation and cure times. After EP-Prime 2000 has fully cured, sand surface with 80-100 grit aluminum oxide sandpaper. Wipe surface with a damp cloth to remove stubborn contaminants and sanding debris. Failure to remove dust and sanding debris will result in adhesion failure.

**Application:** EP2000 may be applied by spraying, rolling or by using a foam brush. Rolling may cause surface imperfections such as pinholing. Only apply EP2000 to clean, dry, well prepared surfaces. **IMPORTANT:** Be sure to follow dry-to-recoat and launch instructions. Apply only at temperatures between 60-90°F.

**For application by residential (non-commercial) users:** Do not apply by airless sprayer. Do not apply more than one coat of this product within 24 hours. Apply only in outdoor, non-enclosed spaces.

**Number of coats:** Apply a minimum of two coats of EP2000. Apply an additional coat along the waterline and other high wear areas.

**Thinning & Mixing:** For spraying thin no more than 5% with water. Thinning is not recommended for brushing or rolling. To mix, stir the product thoroughly until a homogenous blend results. **CLEANING:** Clean up with water.

**Coverage:** 275Sq.Ft/Gal at 2 mil dft. **Film thickness per coat:** 4-6 wet mils to obtain 2-3 dft. **Dry-To-Recoat:** 8 Hours @70°F (21°C) 50%RH **Dry-To-Launch:** 24 Hours @70°F (21°C) 50%RH

### FIRST AID — CLASS 1

- |              |  |
|--------------|--|
| If inhaled   | <ul style="list-style-type: none"><li>• Move person to fresh air.</li><li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>                                    |
| If on skin   | <ul style="list-style-type: none"><li>• Take off contaminated clothing.</li><li>• Rinse skin immediately with plenty of water for 15-20 minutes.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>  |
| If in eyes   | <ul style="list-style-type: none"><li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li><li>• Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>                                    |
| If swallowed | <ul style="list-style-type: none"><li>• Call a poison control center or doctor immediately for treatment advice.</li><li>• Do not induce vomiting unless told to do so by the poison control center or doctor.</li><li>• Do not give any liquid to the person.</li><li>• Do not give anything by mouth to an unconscious person.</li></ul> |

IN CASE OF EMERGENCY CALL: 800-424-9300

**Note to Physician** • Probable mucosal damage may contraindicate the use of gastric lavage.

## PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS KEEP OUT OF REACH OF CHILDREN DANGER

**CORROSIVE:** Causes irreversible eye damage. Harmful if swallowed or absorbed through the skin. May be fatal if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wash thoroughly after handling with soap and water, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse. When mixing and loading, or cleaning equipment, wear a chemical resistant apron.

**Residential PPE:** Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and shoes. While removing existing paint by sanding or blasting, or applying new paint by brush or roller, it is advised to wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

**Commercial PPE:** Users must wear a disposable coverall with hood, chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new paint, user must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

### STORAGE AND DISPOSAL

**Storage:** Do not store near heat source or open flames. Containers are hazardous when empty. Emptied containers retain product residue (vapor and/or liquid). Residual vapors may explode or ignite; do not cut, drill, grind, or weld on or near this container. Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment.

**Pesticide Disposal:** Pesticide wastes are hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** If empty do not reuse this container. Place in trash or offer for recycling if available. If partly filled, call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

### ENVIRONMENTAL HAZARD

This pesticide is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and respirator in accordance with the Precautionary Statement above when handling, painting or removing this paint.