



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

March 17, 2015

M. Alex Walsh
ePaint Company
25 Research Road
East Falmouth, MA 02536

Subject: Label Amendment –Updated Product Description
Product Name: EP2000
EPA Registration Number: 64684-6
Application Date: January 12, 2015
Decision Number: 499202

Dear Mr. Walsh:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance

Page 2 of 2
EPA Reg. No. 64684-6
Decision No. 499202

with FIFRA section 6. If you have any questions, please contact Terria Northern by phone at - 703-347-0265, or via email at northern.terria@epa.gov.

Sincerely,

Elizabeth H. Watkins

Elizabeth Watkins
Acting Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure


EP2000

epaint[®]

Go Fast, Stay Clean
High Performance, Photoactive, Waterborne
Antifouling Paint for Boat Bottoms
and Underwater Equipment
Exposed to Biofouling
With ZINC OMADINE[®]

DANGER: KEEP OUT OF REACH OF CHILDREN
 SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET CONTENTS:
ONE U.S. GALLON (3.8 LITERS)



Manufactured by:
 E Paint Company
 25 Research Road
 E. Falmouth, MA 02536

U.S. Patents #5,916,947 #6,063,849

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of E Paint Company including surface preparation, proper application, and various environmental conditions. Therefore, E Paint Company cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. E PAINT COMPANY SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to refund of the purchase price, or replacement of the product at E Paint Company's option.

Active Ingredients
 Zinc Pyrithione 4.7%
 Inert Ingredients 95.3%
 100.0%

EPA Registration No. 64684-6
 EPA Establishment No. 64684-MA-001

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner that is inconsistent with its labeling. May be used in fresh or salt water, use on the bottom of vessels is recommended. **This paint is intended for use on commercial and recreational vessels.**

Preparation: REMOVE all existing antifouling paint before applying EP2000. Grind, sandblast, or hydroblast to remove existing antifouling paint.

Primer: All surfaces to be coated with EP2000 should be primed with EP-Prime 2000 to provide a fresh, clean substrate for EP2000 to adhere. Follow manufacturer's instructions regarding surface preparation and cure times. After EP-Prime 2000 has fully cured, sand surface with 80-100 grit aluminum oxide sandpaper. Wipe surface with a damp cloth to remove stubborn contaminants and sanding debris. Failure to remove dust and sanding debris will result in adhesion failure.

Application: EP2000 may be applied by spraying, rolling or by using a foam brush. Rolling may cause surface imperfections such as pinholing. Only apply EP2000 to clean, dry, well prepared surfaces. **IMPORTANT:** Be sure to follow dry-to-recoat and launch instructions. Apply only at temperatures between 60-90°F.

For application by residential (non-commercial) users: Do not apply by airless sprayer. Do not apply more than one coat of this product within 24 hours. Apply only in outdoor, non-enclosed spaces.

Number of coats: Apply a minimum of two coats of EP2000. Apply an additional coat along the waterline and other high wear areas.

Thinning & Mixing: For spraying thin no more than 5% with water. Thinning is not recommended for brushing or rolling. To mix, stir the product thoroughly until a homogeneous blend results. **CLEANING:** Clean up with water.

Coverage: 275Sq Ft/Gal at 2 mil dft. **Film thickness per coat:** 4-6 wet mils to obtain 2-3 dft. **Dry-To-Recoat:** 8 Hours @70°F (21°C) 50%RH. **Dry-To-Launch:** 24 Hours @70°F (21°C) 50%RH

FIRST AID — CLASS 1

- If inhaled**
 - Move person to fresh air.
 - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.
 - Call a poison control center or doctor for further treatment advice.
 - If on skin**
 - Take off contaminated clothing.
 - Rinse skin immediately with plenty of water for 15-20 minutes.
 - Call a poison control center or doctor for further treatment advice.
 - If in eyes**
 - Hold eye open and rinse slowly and gently with water for 15-20 minutes.
 - Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye.
 - Call a poison control center or doctor for further treatment advice.
 - If swallowed**
 - Call a poison control center or doctor immediately for treatment advice.
 - Do not induce vomiting unless told to do so by the poison control center or doctor.
 - Do not give any liquid to the person.
 - Do not give anything by mouth to an unconscious person.
- IN CASE OF EMERGENCY CALL: 800-424-9300**
- Note to Physician**
 - Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS
HAZARD TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN

DANGER

CORROSIVE: Causes irreversible eye damage. Harmful if swallowed or absorbed through the skin. May be fatal if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wash thoroughly after handling with soap and water, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse. When mixing and loading, or cleaning equipment, wear a chemical resistant apron.

Residential PPE: Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and shoes. While removing existing paint by sanding or blasting, or applying new paint by brush or roller, it is advised to wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHANIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHANIOSH approval number TC-14C), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

Commercial PPE: Users must wear a disposable coverall with hood, chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new paint, user must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHANIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHANIOSH approval number TC-14C), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

STORAGE AND DISPOSAL

Storage: Do not store near heat source or open flames. Containers are hazardous when empty. Empty containers retain product residue (vapor and/or liquid). Residual vapors may explode or ignite; do not cut, drill, grind, or weld on or near this container. Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment.

Pesticide Disposal: Pesticide wastes are hazardous. Improper disposal of excess pesticide or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: If empty do not reuse this container. Place in trash or offer for recycling if available. If partly filled, call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

ENVIRONMENTAL HAZARD

This pesticide is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and respirator in accordance with the Precautionary Statement above when handling, painting or removing this paint.