

PM 31 65105-1 1276  
US ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF PESTICIDES PROGRAMS  
REGISTRATION DIVISION (TS-767)  
WASHINGTON, DC 20460

EPA REGISTRATION NO.

65105-1

DATE OF ISSUANCE

DEC 04 1992

TERM OF ISSUANCE

NOTICE OF PESTICIDE:

☒ REGISTRATION  
☐ REREGISTRATION

(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT

Copper Poxy

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

System Three Resins  
P.O. Box 70436  
1155 NW 46th Street  
Seattle, WA 98107

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

a. Add the phrase "EPA Registration No. 65105-1"

b. Include a net contents statement on the label or container of Part B (Hardner).

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.



ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL


DATE

2046

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



John H. Lee  
Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (H7505C)

Enclosures

)

PM31 65105-1

3046

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

FRONT PANEL

DEC 04 1992

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

CopperPoxy

Part A

Antifouling Epoxy Barrier Coat For  
Fiberglass and Wood/Epoxy Boat Hulls  
Only For Use With CopperPoxy Part B Hardener

KEEP OUT OF REACH OF CHILDREN

WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

Active Ingredient

)	Copper Metal.....	66.0%
	Inert Ingredient.....	<u>44.0%</u>
	Total	100.0%

Total copper as metallic, 66.0%

EPA Reg. No. 65105-  
EPA Est. No. 65105-WA-001

Net Contents:

STATEMENT OF PRACTICAL TREATMENT

- ) IF IN EYES: Flush with plenty of water. Call a physician.  
IF ON SKIN: Wash with plenty of soap and water. If irritation persists, call a physician.  
IF SWALLOWED: Call a physician or poison control center and induce vomiting by touching back of throat with finger, or, if available, by administering syrup of ipecac. Do not induce vomiting or give anything by mouth to an unconscious person.  
IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth... Get medical attention.

4046  
October 20, 1992

ACCEPTED  
with COMMENTS  
to EPA Letter Dated:

DEC 04 1992

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

65105-1

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING:** May be fatal if inhaled. Do not breathe dust or vapor. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling.

**ENVIRONMENTAL HAZARDS:** This material is toxic to fish and other marine organisms. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint\CopperPoxy removal to enter water. Dispose of debris in an approved landfill.

**PHYSICAL OR CHEMICAL HAZARDS: EXOTHERMIC!** When mixed, parts A & B will generate heat if left in a pot to cure. Spread any unused mixed material in a thin film and allow to cure before disposal.

**DIRECTIONS FOR USE:** It is a violation of federal law to use this product in a manner inconsistent with its labeling.

CopperPoxy is a two part antifouling epoxy barrier coat containing copper metal for use on fiberglass and wood/epoxy hulls. CopperPoxy coated boats may be hauled and relaunched without recoating. Sanding old surfaces exposes new antifouling material.

**HULL PREPARATION**

**NEW HULLS:** Degrease with a solvent designed to remove traces of mold, wax, and other release agents. Remove gelcoat gloss with 60 grit sandpaper. Wash hull with water to remove dust. Dry and apply CopperPoxy.

**OLD HULLS:** Remove all traces of existing bottom paint. Prepare as with new hulls.

**BLISTERED HULLS:** Remove gelcoat and dry hull. Fill hull blisters and sand fair. Remove dust and apply CopperPoxy.

**MEASURING AND MIXING**

**SAFETY PRECAUTIONS FOR USE OF PART B (HARDENER) READ AND FOLLOW ALL DIRECTIONS ON PART B (HARDENER) BOTTLE WHEN MIXING WITH CopperPoxy PART A (RESIN). AVOID CONTACT WITH SKIN AND EYES AND INHALATION OF MIXED SOLUTION. WEAR SAFETY GLASSES, PROTECTIVE CLOTHING AND GLOVES**

October 20, 1992

5076

DEC 04 1992

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the purpose of  
registration under EPA Reg. 16

65105-1

CopperPoxy Part A (resin) and CopperPoxy Part B (hardener) must be combined at a ratio of 100 parts of Part A to 14 Parts of Part B by weight (one full can of Part A + one full bottle of Part B) before applying to the hull. Never change this ratio. Stir contents of Part A can to mix any liquid floating on top of copper paste before using. Measure Parts A & B carefully and mix thoroughly to a smooth uniform texture free of lumps or clots. Do not mix more that can be applied in 20 minutes. For roller application, never thin or add other materials to CopperPoxy.

#### APPLICATION

- ) Do not apply CopperPoxy when the temperature is below 50° F (10° C). CopperPoxy may be applied by roller or by spraying with suitable equipment. When rolling, several thin coats with sufficient curing between coats will result in a smoother finish. Allow final coat to cure for several days and sand smooth, if desired, anytime prior to launching. Do not launch boat if CopperPoxy is still soft as straps may bite into coating.

#### STORAGE AND DISPOSAL

**STORAGE:** Store in original unopened container at normal temperatures (50° - 80° F). Do not contaminate water food or feed by storage or disposal. Open dumping is prohibited.

) **PESTICIDE DISPOSAL:** Do not contaminate water, food, or feed by storage or disposal. Excess CopperPoxy should be mixed according to label directions with Part B Hardener and allowed to cure. Fully cured CopperPoxy may be disposed of on site or at an approved waste disposal facility, according to federal, state or local procedures under the Resource Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill, or by other approved state and local procedures.

SYSTEM THREE RESINS  
1155 NW 46th STREET  
SEATTLE, WA 98107

CopperPoxy

Part B

HARDENER

Antifouling Epoxy Barrier Coat For  
Fiberglass and Wood/Epoxy Boat Hulls -  
Only for use with CopperPoxy Part A Resin

KEEP OUT OF REACH OF CHILDREN

WARNING!

SAFETY PRECAUTIONS FOR USE OF PART B (HARDENER) READ AND FOLLOW ALL DIRECTIONS ON CAN WHEN MIXING WITH CopperPoxy PART A (RESIN). DO NOT USE AROUND AN OPEN FLAME. AVOID CONTACT WITH SKIN AND EYES AND INHALATION OF MIXED SOLUTION. WEAR SAFETY GLASSES, PROTECTIVE CLOTHING AND GLOVES. MAY CAUSE SKIN SENSITIZATION. IF CONTACT WITH SKIN CAUSES IRRITATION, REDNESS, BLISTERS, SORENESS, SWELLING OR NAUSEA STOP USE AND CONTACT A PHYSICIAN IMMEDIATELY.

Statement of Practical Treatment - If contact with eyes occurs, flush with plenty of water and call a physician. Wash with plenty of soap and water if CopperPoxy Part B gets on skin. If accidentally ingested, immediately contact a physician or poison control center. DO NOT INDUCE VOMITING. Drink a large quantity of water. *Physicians should note that due to the alkaline nature of this product, probable mucosal damage may contraindicate the use of gastric lavage.*

FOLLOW ALL DIRECTIONS FOR USE ON PART A WHEN APPLYING.

EPA Est. No. 65105-WA-001

EPA Reg. No. 65105-

Manufactured by

SYSTEM THREE RESINS  
1155 NW 46th STREET  
SEATTLE, WA 98107

60916  
ACCEPTED  
with COMMENTS  
to EPA Letter Dated:

DEC 04 1992

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

65105-1