CHLORINE

For use by trained personnel from large stationary containers such as tank cars, tank trucks, 1-ton and 150 pound cylinders as a disinfectant, algicide, and/or slimicide in municipal water treatment plants, sewage plants, industrial/commercial cooling systems, pulp and paper mills, and/or commercial swimming pools. This product cannot be transferred to portable cylinders. Pool service operators with portable cylinders must obtain their own registrations with the EPA.

Active Ingredient Chlorine Inert Ingredients Total

99.7% <u>0.3%</u> 100.0%

KEEP OUT OF REACH OF CHILDREN

DANGER - POISON

FATAL IF INHALED

LIQUID CAUSES SEVERE BURNS

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS & DOMESTIC ANIMALS: Fatal if inhaled. Do not breathe vapor. Corrosive to eyes, skin and mucous membranes in the presence of moisture. Do not get in eyes, on skin or on clothing. Wear goggles, protective clothing and rubber gloves when handling. Do not heat containers.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to seer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA

CHEMICAL-PHYSICAL HAZARDS: Chlorine is a non-flammable gas, liquefied under pressure. Do not drop container. Keep away from intense heat or direct sunlight. Corrosive to most metals in the presence of moisture.

FIRST AID

In case of skin or eye contact, immediately flush all affected areas with large amounts of running victor for at least 15 minutes while removing contaminated clothing and shoes. For eyes, hold eyelids apart during flushing to ensure rinsing of the entire surface of the eye and lids with water. 'Call a physician immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth if breathing is difficult, give oxygen, preferably with a physician's advise. Keep warm by covering with a blanket and keep quiet.

A C C P P E D

NET CONTENTS:

OCT 2 | 1997
Under 131 Act, as amended, for the particide registered under 12A Reg. No. 6 5 5 60 -/

20/2

CHLORINE

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Only specifically designed dispensing equipment should be used in accordance with manufacturer's instructions and according to state regulatory agency recommendations for dosages or residual chlorine levels which should be maintained for each specific site of application.

Have available gas masks approved for chlorine service by the U.S. Bureau of Mines or the National Institute for Occupational Safety and Health. Handle and use only in accordance with practice recommended in the CHLORINE MANUAL published by the Chlorine Institute, Inc., Washington, D.C. Use only in well ventilated areas.

STORAGE AND DISPOSAL

STORAGE: Cylinders and ton containers of chlorine should be stowed in a dry area away from sources of heat and protected from direct sunlight and precipitation. They should be segregated from other compressed gases and never stored near hydrocarbons, finely divided metals, turpentine, ether, anhydrous ammonia or other flammable materials. All storage containers must have a weather resistant label attached near the outlet valve and must not be accessible to the general public.

DISPOSAL OF CONTAINERS: All chlorine containers are returnable and should be properly identified with return tags and returned as promptly as possible to the supplier according to prescribed instructions and practices recommended by the Chlorine Institute. All valves must be closed tightly and closure of caps secured. It is illegal to ship a leaking chlorine container.

Worth Chemical Corporation Greensboro, NC

EPA Reg. No. 65560-

•

EPA Est. No. 65560-NC-1

ACCEPTED

CCT 2 | 1997