PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

"CAUTION": "Harmful if swallowed. Causes moderate eye irritation. Avoid contact with eyes or clothing. Personal protective clothing, normal work clothes (i.e., long pants, shoes plus socks, a long sleeved shirt) plus waterproof gloves for all handlers, and a NIOSH/MSHA certified respirator during mixing and loading. Wash thoroughly with soap and water after handling. Avoid contamination of food and feed. Do not leave container where children or animals may gain access.

"FIRST AID": "IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison Control Center or doctor for treatment advise. "IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water 15-20 minutes. Call a Poison Control Center or doctor for treatment advise. "IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advise. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a Poison Control Center or doctor. "IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison Control Center for further treatment advise." Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment". "In case of emergency, for additional information call. (208) 265-5911

ENVIRONMENTAL HAZARDS: "This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Polluant Discharge System (NPDES) permit and permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA."

NOTICE: Because of many varying conditions affecting use and application, manufacturer warns buyer that these may impair or vary the results or effects of the use of this product. In any event, complete prevention of decay by fungi or other organisms is not guaranteed. Neither manufacturer or seller shall be liable in respect to any injury or damage suffered by reason of the use of this product for a purpose not indicated by the label or when used contrary to the directions or instructions hereon nor with respect to breach of any warranty not expressly specified herein. Buyer accepts this material subject to these terms, assumes all risk of usage and handling except when used or handled in accordance with this label. Neither manufacturer nor seller, makes, and their employees and agents are not permitted to make, any representations or warranties, express or implied by law, not specifically set forth herein. DIRECTIONS FOR USE: IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELLING.

ENVIROTECH INSECTICIDE is a water soluble inorganic borate salt for the protection and treatment of lumber and wood-foam composite structural components against decay fungi and wood boring beetles including Powder Post Beetles (Lyctidae), Furniture Beetles and Old House Borers (Anodiidae), and Longhorn Beetles (Cerambycidae). This treatment is not effective against wood staining fungi and may require mixing with compatible products. ENVIROTECH INSECTICIDE also controls Subterranean Termites (Reticulitermes, Coptotermes, Hetertermes), Dampwood Termites (Zootermopsis), Drywood Termites (Kalotermes, Incisitermes), and Carpenter Ants, (Camponotus).

ENVIROTECH INSECTICIDE is recommended for all interior and exterior wood and wood-foam composite structural components which will be protected from rain and not in direct contact with soil. The treatment of lumber is permanent even after cutting and finishing providing the wood is not exposed to moisture or in contact with the soil.

This product is toxic to wood destroying insects but surface etching of treated wood and wood-foam composite structural components may occur.

ENVIROTECH ™ INSECTICIDE

A Preservative for Protection and Treatment of Wood and Wood-Foam Composite Structural Components Against Decay Fungi and Wood-Destroying Insects

Only for sale to, use and storage by Professional pest control operators

ACTIVE INGREDIENTS

Disodium Octaborate Tetrahydrate . 98% (Na₂B₈O₁₃.4H₂O).

INERT INGREDIENTS

2%

KEEP OUT OF REACH OF CHILDREN

CAUTION
See Side Panel for Additional
Precautionary Statements
and Practical Treatment

Manufactured by:

ENVIROTECH VENTURES
INTERNATIONAL, INC.
P.O. BOX 712
Sandpoint Idaho 83864
EMERGENCY PHONE: (208) 265-5911

EPA REG.NO.: 65705-1 Est. No. 65705-ARG-001 Net Contents 50 lbs.

DEC 1 2 2000

The free of increme as Fungicide and the representation for the code rep

DIP-DIFFUSION TREATMENT: PREPARATION OF SOLUTIONS: To prepare solutions, described below, water should be added to the tank to about 80% of the solution required. The temperature is then raised to the desired level and the calculated amount of ENVIROTECH INSECTICIDE is gradually added with good agitation. The remaining water is then added and the solution agitated for an additional 10 minutes to ensure that all of the product has dissolved. The temperature of the solution should be maintained during treatment. Upon cooling some borate may crystallize out of the solution, but will redisolve when the solution is heated for the next treatment session. In very cold weather, some heating or insulation should be provided to prevent solidification in the bottom of the tank. The tank should be covered when not in use to prevent contamination and evaporation of water.

SUGGESTED CONDITIONS AND SOLUTION STRENGTHS FOR THE DIFFUSION METHOD

Lumber Diffusion Thickness	Pounds of ENVIROTECH INSECTICIDE Solution			
	Fo	r 100 Gallous Solution	Тетр	
Complete in				
Up to 1 inch	(2.5cm)	140	105°F(40°C)	2 to 4 weeks
1 to 1.75 inches	(2.5cm to 4.0	cm) 180	120°F(50°C)	4 to 6 weeks
1.75 to 2.5 inches			130°F(55°C)	4 to 6 weeks
2.5 to 3 inches*			135°F(57°C)	6 to 8 weeks

* Lumber over 3 inches (7.5cm) in thickness or over 5 inches (12.5cm) in width should be dipped twice 24 to 72 hours apart.

DIP-DIFFUSION METHOD OF APPLICATION: Dip freshly-cut tumber in a tank containing a hot aqueous solution of ENVIROTECH INSECTICIDE for 2 to 5 minutes. After dipping, the newly treated wood should be stacked and stored under a tarpaulin or shed roof to show the drying process and prevent wash off by rainfall, thus improving penetration. Diffusion of the wood preservative into the interior of the wood will start immediately and will require several weeks to thoroughly penetrate the lumber, depending on species and thickness of wood. The dip-diffusion method of treatment can result in complete penetration throughout the whole cross-sectional area of treated lumber.

PRESSURE TREATMENT: Pressure treatment must rigidly adhere to the current specifications of ENVIROTECH INSECTICIDE and/or those of the American Wood Preserver's Association (AWPA).

PRE-TREATMENT: Wood-foam composite structural components may be treated to prevent infestation of attacking organisms. Apply a 10% aqueous solution of ENVIROTECH INSECTICIDE (1 lb/gallon solution). Solution may be applied by spray or brush until surface thoroughly wetted (approximately 7-10 gallons per 1000 sq.ft.) Current ENVIROTECH INSECTICIDE and/or American Wood Preservers' Association specifications and test methods should be followed to ensure adequate chemical loadings in wood.

Note: a quart or 32 oz container loose packed equals one pound

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store in a dry place. Do not store where children or animals may gain access.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Completely empty bag into application equipment. Then dispose of empty bag in a sanitary landfill or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

12/12/

page 1

ONI