



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

February 16, 2017

Cheryl Woodard
Sr. Regulatory Specialist
U.S. Agent: Thor Specialties, Inc.
50 Waterview Drive
Shelton CT 06484

Subject: Notification per PRN 98-10 – To revise container handling and make administrative changes
Product Name: ACTICIDE 14F
EPA Registration Number: 67071-5
Application Date: November 4, 2016
Decision Number: 523575

Dear Ms. Woodard:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If you have any questions, you may contact Zebora Johnson at (703) 308-7080 or via email at johnson.zebora@epa.gov.

Sincerely,

A handwritten signature in blue ink, appearing to read "John Hebert", is positioned above the printed name.

John Hebert, Chief
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs



ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARD

This product is corrosive to mild steel.

STORAGE AND DISPOSAL

PROHIBITIONS: This product (pH 3.0) is corrosive to mild steel.

PESTICIDE STORAGE: Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Plastic non-refillable container: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incinerator or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. Do not reuse this container to hold materials other than pesticides or dilute pesticides (rinsate). After emptying and cleaning, it may be allowable to temporarily hold rinsate or other pesticide-related materials in the container. Contact your state regulatory agency to determine allowable practices in your state.

[OR:

CONTAINER DISPOSAL: Non-refillable containers (> 5 gallons in size). Do not reuse this container to hold materials other than pesticides or dilute pesticides (rinsate). After emptying and cleaning, it may be allowable to temporarily hold rinsate or other pesticide-related materials in the container. Contact your state regulatory agency to determine allowable practices in your state. Empty tote container may be returned to a tote collection agent. Residue removal – Cleaning container before final disposal is the responsibility of the person disposing of the container. To clean container before final disposal, fill container about 10 percent full with water; agitate container vigorously; discard rinsate according to pesticide disposal instructions; repeat this rinsing procedure two more times. Then offer recycling if available or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. For additional container disposal information, contact product supplier.]

GENERAL: CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

CONDITIONS OF SALE AND WARRANTY

Thor GmbH warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. THOR GMBH MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES EITHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. Handling, storage and use of the product by Buyer or User are beyond the control of Thor GmbH and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow label directions will be assumed by the Buyer or User. IN NO CASE WILL THOR GMBH OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.

ACTICIDE® 14F

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one.....10.60%
2-Methyl-4-isothiazolin-3-one.....3.50%

OTHER INGREDIENTS:.....85.90%
TOTAL:.....100.00%

ACTICIDE® 14F microbiocide weighs 10.4 lb. per gallon

KEEP OUT OF REACH OF CHILDREN

DANGER - PELIGRO

See Side panel for additional precautionary statements

FIRST AID

- If in Eyes:** ➤ Hold eye open and rinse slowly and gently with water for 15-20 minutes.
➤ Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
➤ Call a poison control center or doctor for treatment advice.
- If Swallowed:** ➤ Call a poison control center or doctor immediately for treatment advice.
➤ Have person sip a glass of water if able to swallow.
➤ Do not induce vomiting unless told to do so by the poison control center or doctor.
- If on Skin:** ➤ Take off contaminated clothing.
➤ Rinse skin immediately with plenty of water for 15-20 minutes.
➤ Call a poison control center or doctor for treatment.
- If Inhaled:** ➤ Move person to fresh air.
➤ If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
➤ Call a poison control center or doctor for further treatment advice

Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage.

EPA Reg. No. 67071-5

EPA Est. No. 67071-DEU-001

Manufactured By/For: Thor GmbH

D-67346 Speyer, Germany
Tel. (06232) 6360

U.S. Office:

Thor Specialties, Inc.
50 Waterview Drive; Shelton, CT 06484 USA
Tel. (203) 516-6980

[OR:

EPA Est. No. 67071-MEX-001

Manufactured By:

Thor Químicos de México SA de CV;
Autopista Mex-Oro Km 182; Pedro Escobedo,
Querétaro; México. **Tel. (448) 2752200**

Manufactured For:

Thor GmbH
U.S. Office: Thor Specialties, Inc.
50 Waterview Drive, Shelton, CT 06484 USA
Tel. (203) 516-6980]

Precautionary Statements:

Hazards to Humans and Domestic Animals

DANGER

Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed or absorbed through skin. Harmful if swallowed. Do not get in eyes, on skin or on clothing. Do not breathe vapor or spray mist. Avoid contact with skin prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Remove contaminated clothing and wash before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE): Mixers, loaders, and others exposed to methylisothiazolinone must wear:

- Coveralls over long-sleeved shirt and long pants
- Socks and chemical resistant footwear
- Goggles or face shield
- Chemical-resistant gloves (such as rubber or made out of any waterproof material)
- A respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or NIOSH approved Respirator with an organic (OV) cartridge or canister with any R, P, or HE prefilter.
- In addition, mixers and loaders and persons cleaning equipment must wear a chemical-resistant apron.

Follow manufacturer's instructions for cleaning / maintaining PPE. If there are no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations: users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Industrial microbiocide for use in metal working fluids, metal cleaning fluids, hydraulic fluids, dispersed pigments, adhesives and tackifiers, wood and wood products, paints and coatings, building materials, polymer latices, *aqueous compositions, liquid household, consumer, industrial, janitorial products; semi-solid/solid household, consumer, industrial, janitorial products; oil field injection waters, *paper slime control, recirculating water cooling towers, *air washer systems, recirculating closed loop water cooling systems, *brewery pasteurizer and can warmer systems, *Ultra filtration units, *industrial wastewater treatment systems and sewage systems and fuels. **READ AND FOLLOW THE DIRECTIONS FOR USE ON THE ACCOMPANYING INFORMATION SHEET.**

*Not approved for these uses in the State of California

NOTIFICATION

67071-5

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

02/16/2017

UN 2922

, CORROSIVE LIQUID,

TOXIC, N.O.S. (mixture containing 5-Chloro-2-methyl-4-isothiazolin-3-one and 2-Methyl-4-isothiazolin-3-one (3:1)), 8 + 6.1, PG-II

Batch:

Mfg Date:

Net Contents (pounds):
(gallons):

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

METAL WORKING FLUIDS:

ACTICIDE® 14F microbiocide is recommended for the control of bacteria and fungi in soluble and emulsifiable type aqueous metal working fluid solutions and emulsions.

The preservative should be dispensed into the use dilution of the metal working fluid using a metering pump and uniformly dispersed throughout the system.

A higher dosage rate and/or increased frequency of treatment may be required depending upon the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

For a noticeably fouled system:

7 to 16 FL OZ (0.6 to 1.3 LB) per 1000 GAL of emulsion.
(55 to 125 ppm ACTICIDE® 14F)
Repeat until control is achieved.

When control is evident:

3.5 FL OZ (0.3 LB) per 1000 GAL of emulsion every 4 weeks.
(27 ppm ACTICIDE® 14F)

METAL CLEANING FLUIDS:

ACTICIDE® 14F microbiocide is recommended as a preservative for use in the manufacture and use of alkaline, acid and emulsion based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations.

The preservative should be dispensed into the use dilution of the metal cleaning fluid using a metering pump and uniformly dispersed throughout the system.

A higher dosage range and/or increased frequency of treatment may be required depending on the rate of dilution of the preservative with the make up fluid, the nature and severity of the contamination, level of control required, filtration effectiveness, system design, etc.

CONCENTRATES:

For addition to a metal cleaning concentrate, add ACTICIDE® 14F microbiocide at a level to ensure that the final use-dilution fluid will contain 56 to 225 ppm product.

For direct addition to a fouled system:

7.2 to 29 FL OZ (0.6 to 2.3 LB) per 1000 GAL of use-dilution metal cleaning fluid every 3-4 weeks to provide 56 to 225 ppm product

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

WATER-BASED HYDRAULIC FLUIDS:

ACTICIDE® 14F microbiocide is recommended as a preservative for use in the manufacture and use of high water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume of mineral oil using an oil soluble emulsifying agent.

A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with make-up fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

For a noticeably fouled system:

15 to 25 FL OZ (1.2 to 2.0 LB) per 1000 GAL of fluid
(117 to 195 ppm ACTICIDE® 14F) every 8 weeks to be followed by subsequent maintenance dosage

For non-fouled system maintenance:

12 to 15 FL OZ (1.0 to 1.2 LB) per 1000 GAL of fluid every 8 weeks
(94 to 117 ppm ACTICIDE® 14F)

DISPERSED PIGMENTS AND *COLORANTS:

ACTICIDE® 14F microbiocide is recommended for the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin clay, montmorillonite clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate and kieselguhr used in paint and paper productions coatings.

**Not approved for this use in the State of California.*

0.006 – 0.0225%

0.06 – 0.225 LB per 1000 LB fluid
25 – 102 grams per 454 kg fluid
(60 to 225 ppm ACTICIDE® 14F)

ADHESIVES AND TACKIFIERS:

ACTICIDE® 14F microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in water soluble and water dispersed adhesive such as animal glues, vegetable glues, natural rubber latices, polyvinyl acetate, styrene-butadiene and acrylic latices. ACTICIDE® 14F microbiocide is recommended as a preservative for tackifiers derived from rosin and hydrocarbon resins.

A higher dosage rate providing up to 45 ppm active ingredients may be required for storage during extremely high temperatures and humidity.

0.006 – 0.022%

0.06 – 0.22 LB per 1000 LB fluid
25 – 102 grams per 454 kg fluid
(60 to 220 ppm ACTICIDE® 14F)

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

WOOD AND WOOD PRODUCTS:

ACTICIDE® 14F is recommended for the protection of wood and wood products such as landscape timbers, fences, posts, pilings, cross ties, decks and similar exterior structures, from mold and mildew. Treat pressure-treatment solution in the pressure treating process for mold and mildew control.

0.027 – 0.086 GAL (3.4 to 11 FL OZ) per 1000 GAL of solution

Under extreme mildew conditions, ACTICIDE® 14F may be used up to a maximum concentration of 343 ppm product (33 fluid ounces ACTICIDE® 14F per 1000 gallons of treatment solution).

This application will afford protection up to 12 weeks and during repeated use of solution.

ACTICIDE® 14F may be used at higher concentrations so long as the end-use product/article contains a maximum concentration of 343 ppm ACTICIDE® 14F.

*For the control of blue stain, mold and decay of freshly cut lumber and logs:

1 GAL per 3500 GAL of water
(286 ppm ACTICIDE® 14F)

Treat lumber immediately after it is sawn. Freshly dipped or sprayed lumber must be protected from rain. Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of stain solution. Antistain treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use antistain solution must be adjusted to accommodate seasonal changes in the exposure and species being treated. Dip tanks and spray equipment and metering equipment must be properly maintained.

Lumber and logs must be totally immersed or sprayed to ensure all surfaces are treated. Ensure good mixing prior to and during the treatment process.

**Not approved for this use in the State of California.*

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PAINTS AND COATINGS:

ACTICIDE® 14F microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in water based coatings such as paper and wood coatings and paints used for architectural product finishes and special purpose coatings.

A higher dosage rate providing up to 45 ppm active ingredients may be required for storage during extremely high temperatures and humidity.

0.006 – 0.022%

0.06 – 0.22 LB per 1000 LB fluid

25 – 102 grams per 454 kg fluid (60 to 220 ppm ACTICIDE® 14F)

Specifically as a wood coating, ACTICIDE® 14F is recommended for the protection of wood and wood products such as landscape timbers, fences, posts, pilings, cross ties, decks and similar exterior structures, from mold and mildew. As a pressure treatment for mold and mildew control for southern yellow pine, hemlock, ponderosa pine and other soft woods. Thoroughly wet and allow to dry.

0.2 – 0.7 LB (3.4 – 11 FL OZ) per 1000 GAL preservative (27 – 86 ppm of ACTICIDE® 14F)

A single application will afford protection for 12 weeks.

Under extreme mildew conditions:

ACTICIDE® 14F may be used at higher concentrations so long as the end-use product/article contains a maximum concentration of 330 ppm ACTICIDE® 14F.

1.4 – 2.7 LB (17 – 33 FL OZ) per 1000 GAL preservative (160 – 330 ppm of ACTICIDE® 14F)

*Special purpose coating uses

Use as a preservative for:

- Electrodeposition paints or solutions
- Photo/photoplasting solutions or coatings
- Fount (or fountain) solutions used in the printing process as a maintenance fluid/coating and as a special coating for printing plates.

The application/addition directions for these special purpose coating uses are:

*ELECTRODEPOSITION

ACTICIDE® 14F microbiocide is recommended as a tankside additive for the control of bacteria, fungi, and algae in re-circulating electrodeposition systems and associated rinse systems. Alternately, ACTICIDE® 14F microbiocide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*Tankside Addition to Electrodeposition Systems:

ACTICIDE® 14F microbiocide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to insure uniform mixing.

A change of frequency of treatment may be required depending on the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

**Not approved for this use in the State of California*

For a noticeably fouled system:

7.1 to 24.5 ppm (0.7 to 2.5 GAL per 10,000 GAL of fluid). Repeat until control is achieved.

When control is evident:

3.5 to 10.5 ppm (0.35 to 1.1 GAL per 10,000 GAL of fluid) weekly or as needed.

*TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS

Initial Dose of Paint Components:

ACTICIDE® 14F microbiocide should be added to the resin, pigment, or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 35 to 245 ppm product.

**Not approved for this use in the State of California*

For a noticeably fouled system:

7.1 to 24.5 ppm (0.7 to 2.5 GAL per 10,000 GAL of fluid). Repeat until control is achieved.

When control is evident:

3.5 to 10.5 ppm (0.35 to 1.1 GAL per 10,000 GAL of fluid) weekly or as needed.

*Supplemental Tanked Dosing of Electrodeposition System:

If additional microbial control is necessary, ACTICIDE® 14F microbiocide may be added to the electrodeposition system tankside to supplement the microbiocide incorporated through paint components.

**Not approved for this use in the State of California*

NOTE: To ensure uniform mixing, add ACTICIDE® 14F microbiocide to latex or solution slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*PHOTOPLATE PROCESSING, FOUNTAIN SOLUTIONS, AND INK/INK COMPONENTS

ACTICIDE® 14F microbiocide is recommended for the control of bacteria and fungi in photoplate processing such as stabilizer solutions and in fountain solutions. ACTICIDE® 14F is recommended for water-based printing inks such as flexographic, gravure, screen and ink jet types.

ACTICIDE® 14F is recommended for the control of bacteria and fungi in printing ink components such as resins, plasticizers, water soluble dyes, pigments, gelling agents, waves, surfactants, and thickeners.

A level adjustment may be necessary to accommodate slight changes in solution formulations.

CONCENTRATES:

ACTICIDE® 14F should be added to concentrates at a level to ensure that the final use dilution of the product will contain 0.035% ACTICIDE® 14F.

To ensure uniform mixing add ACTICIDE® 14F microbiocide to the product slowly with agitation.

**Not approved for this use in the State of California*

BUILDING MATERIALS:

ACTICIDE® 14F microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in building materials such as mastics, caulks, joint cements, concrete admixtures, spackling and grouting.

0.01 – 0.035%
0.1 to 0.35 LB per 1000 LB
formulation
(100 to 350 ppm ACTICIDE®
14F)

0.005 – 0.0225%
0.05 – 0.225 LB per 1000 LB
fluid
(50 to 225 ppm ACTICIDE®
14F)

THOR

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

LATTICES, POLYMER EMULSIONS OR SOLUTIONS:

ACTICIDE® 14F microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer latices including: acrylics, styrene-butadiene, carboxylated styrene-butadiene, ethylene-vinyl acetate and biopolymers intended for industrial use such as xanthan gum, gum arabic, guar gum, protein derived polymers, starches and casein derived polymers.

0.006 – 0.045%
0.06 – 0.45 LB per 1000 LB
fluid
25 – 205 grams per 454 kg
fluid
(60 to 450 ppm ACTICLIDE®
14F)

CONCENTRATES:

ACTICIDE® 14F microbicide may be added to the above products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will not exceed the concentration indicated.

***AQUEOUS COMPOSITIONS:**

ACTICIDE® 14F microbicide is recommended as an in-container preservative for the control of bacteria and fungi in aqueous products such as:

0.005 – 0.035%
0.05 – 0.35 LB per 1000 LB
aqueous product
(50 to 350 ppm ACTICIDE®
14F)

*fiberglass sizing solutions

*aqueous emulsions and dispersions including

*stabilized oil/water emulsions

*surface preparation compounds

*foam control products

*nutrient solutions

*pesticide formulations.

**Not approved for this use in the State of California*

ACTICIDE® 14F INFORMATION SHEET



THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

LIQUID HOUSEHOLD, CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS

0.004 – 0.016%

0.04 – 0.16 LB per 1000 LB
product

For the control of bacteria and fungi in liquid soaps, liquid cleaners, liquid detergents, liquid laundry products, liquid dishwashing detergents, waxes, polishes, liquid fabric treatment/fresher products, liquid air fresheners/deodorizers, car care products, and other similar cleaners. ACTICIDE® 14F may also be used for the control of bacteria and fungi in package utility products such as pre-moistened sponges and mops. ACTICIDE® 14F may also be used from the control of bacteria and fungi in solutions that are then put into/onto wet wipes for use in industrial, commercial, residential and household uses cited above. Wet wipes containing a solution preserved with this product may not be used for personal care, as baby wipes, or for food contact.

CONCENTRATES:

ACTICIDE® 14F microbiocide may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 40 to 160 ppm ACTICIDE® 14F microbiocide.

ACTICIDE® 14F INFORMATION SHEET



THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

SEMI-SOLID/SOLID HOUSEHOLD, CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS	
For the control of bacteria and fungi in semi-solid/solid soaps, semi-solid/solid cleaners, semi-solid/solid detergents, semi-solid/solid laundry products, semi-solid/solid dishwashing detergents, waxes, polishes, semi-solid/solid fabric treatment/fresher products, semi-solid/solid air fresheners/deodorizers, car care products, and other similar cleaners. ACTICIDE® 14F may also be used for the control of bacteria and fungi in package utility products such as pre-moistened sponges and mops. ACTICIDE® 14F may also be used from the control of bacteria and fungi in solutions that are then put into/onto wet wipes for use in industrial, commercial, residential and household uses cited above. Wet wipes containing a solution preserved with this product may not be used for personal care, as baby wipes, or for food contact.	0.004 – 0.016% 0.04 – 0.16 LB per 1000 LB product
CONCENTRATES:	
ACTICIDE® 14F microbicide may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 40 to 160 ppm ACTICIDE® 14F microbicide.	
*INDUSTRIAL PROCESS WATER:	0.005 – 0.035%
Process wash waters: recommended for the control of bacteria and fungi in the storage of process wash water during the manufacture of adhesives and tackifiers; paints and coatings; photoplate processing, fountain solutions, and ink / ink components; building materials; latices, polymer emulsions or solutions; aqueous compositions; liquid household, consumer, industrial, janitorial products; semi-solid / solid household, consumer, industrial, janitorial products.	0.05 – 0.35 LB per 1000 LB wash water (50 to 350 ppm ACTICIDE® 14F)
<i>*Not approved for this use in the State of California</i>	
OIL FIELD INJECTION WATERS:	2.5 – 6.1 LB (0.29 to 0.7 GAL) per 1000 barrels of water
To maintain control of slime-forming and sulfate reducing bacteria in oil and gas field water systems including enhanced recovery injection fluids and drilling fluids. An initial dose of 6.1 to 12.4 lb ACTICIDE® 14F per 1000 barrels of water (17.4 to 34.8 ppm ACTICIDE® 14F) may be used until control is achieved. This product may be used for terrestrial and offshore oil drilling muds and packer fluids.	(7.1 to 17.5 ppm ACTICIDE® 14F)

ACTICIDE® 14F

INFORMATION SHEET



THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*PAPERMILLS:

For the control of bacterial and fungal slime in the production of paper. ACTICIDE® 14F should be added to a point such as the Beater or Hydropulper to ensure uniform mixing.

**Not approved for this use in the State of California*

INDUSTRIAL RECIRCULATING WATER COOLING TOWER:

ACTICIDE® 14F is recommended for the control of bacteria, algae and fungi. It should be added to the tower basin or some other point to ensure uniform mixing. For noticeably fouled systems use an initial dose of 0.13 to 0.79 lb ACTICIDE® 14F per 1000 gallons of water. Repeat if necessary to achieve control.

*AIR WASHER SYSTEMS / *PAINT SPRAY BOOTHS:

For use only in industrial air washing systems that maintain effective mist eliminating components. Add to water in the air washer sump, or chill water sump to ensure uniform mixing for the control of bacteria, fungi and algae. A repeat treatment may be needed depending on the severity of contamination.

**Not approved for this use in the State of California*

INDUSTRIAL RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS AND PROCESS WATER SYSTEMS:

To maintain control of bacteria, fungi and algae. Add to water in the reservoir, recirculating line or some other point to ensure uniform mixing. For noticeably fouled systems an initial treatment with 0.13 to 0.79 lb ACTICIDE® 14F per 1000 gallons of water may be needed depending on the severity of the fouling.

*BREWERY PASTEURIZERS AND CAN WARMER SYSTEMS:

To maintain control of bacteria, algae and fungi.

For noticeably fouled systems an initial treatment with 0.13 to 0.79 lb ACTICIDE® 14F per 1000 gallons of water may be needed depending on the severity of the fouling.

NOTE: Regardless of the manner of incorporation, the total level should never exceed 248 ppm ACTICIDE® 14F or 2.5 gallons per 10,000 gallons of system fluid.

**Not approved for this use in the State of California*

ACTICIDE® 14F

THOR

INFORMATION SHEET

THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT

OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*ULTRA FILTRATION UNITS, such as REVERSE OSMOSIS SYSTEMS

ACTICIDE® 14F microbiocide is recommended for the control of bacteria and fungi in ultra filtration units, such as reverse osmosis systems.

1 – 35 ppm ACTICIDE® 14F

Add into industrial ultra filtration or reverse osmosis systems by either continuous feed or periodic injection. Compatibility of ACTICIDE® 14F microbiocide with reverse osmosis membranes should be confirmed with membrane manufacturers.

For the control of bacteria and fungi in carbon beds.

1 – 35 ppm ACTICIDE® 14F

For periodic membrane cleaning.

0.04 – 0.10 LB per 120 GAL of cleaning solution

Badly fouled systems should be cleaned before treatment is begun.

**Not approved for this use in the State of California*

*INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS:

ACTICIDE® 14F microbiocide is recommended for the control of microbial biofilms, bacteria, fungi, and algae in industrial waste water treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE:

When the system is noticeably fouled, apply ACTICIDE® 14F as indicated. Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

0.13 – 0.78 LB or 2 – 12 FL OZ per 1000 GAL of water in the system
(15.5 to 93 ppm ACTICIDE® 14F)

SUBSEQUENT DOSE:

When microbial control is evident, add ACTICIDE® 14F weekly or as needed to maintain control.

0.03 – 0.2 LB or 0.45 – 3 FL OZ per 1000 GAL of water in the system
(3.5 to 23 ppm ACTICIDE® 14F)

**Not approved for this use in the State of California*

ACTICIDE® 14F INFORMATION SHEET



THIS ACTICIDE® 14F INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® 14F

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*FUELS AND OILS:

ACTICIDE® 14F is recommended for the control of bacteria and fungi in the following liquid hydrocarbon fuels and oils: crude oils, aviation fuels, kerosene, heating oils, diesel fuels, residual fuel oils, coal slurries, liquefied petroleum gases and petrochemical feedstocks. ACTICIDE® 14F is recommended for REFINERY AND TERMINAL USE ONLY. ACTICIDE® 14F should be directly dispensed into a fuel tank, storage tank or a flowing stream of fuel in a manner to ensure uniform distribution of the preservative in the fuel system. Slug dose or continuous feed methods are recommended.

A shock dose of up to 42 gallons of ACTICIDE® 14F per 1 million gallons of fluid is recommended in the case of extreme contamination. Grossly contaminated systems should be physically cleaned to remove debris.

**FOR USE IN AVIATION FUEL, THE FEDERAL AVIATION
ADMINISTRATION MUST BE CONSULTED AS TO THE ACCEPTABILITY
OF THE ADDITIVE FOR USE IN SPECIFIC ENGINES AND/OR AIRCRAFT.**

**Not approved for this use in the State of California*

For a noticeably fouled system:

11 to 21 GAL per 1 million
GAL of fluid.

(11 to 21 ppm ACTICIDE®
14F)

Repeat until control is
achieved.

Maintenance dose:

5 – 16 GAL per 1 million
GAL of fluid

(5 to 16 ppm ACTICIDE®
14F)

Repeat every 4 – 6 weeks or
when microbial
contamination is detected.