UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

4/14/2011

SEPA United States Environmental Protection Office of Pesticide Programs

Thor GmbH Landwehrstrasse 1 D-67346. Speyer, Germany

APR 1 4 2011

AGENT: Acti-Chem Specialties, Inc. 56 Quarry Road Trumbull, CT 06611

Attention: Lynn P. Tordo, MS. **Regulatory Manager**

Subject: ACTICIDE 45 EPA Registration No. 67071-6 Amendment Dated December 29, 2010

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

Proposed Amendment

- To include the preservation of fuels and for clarification of an existing use

General Comments

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6341.

Sincerely,

Marshall Swindell

Product Manager (33) **Regulatory Management Branch 1** Antimicrobials Division (7510P)

Enclosure

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

Do not contaminate food or feed by storage, disposal or cleaning of equipment. STORAGE DISPOSAL: Do not store or transport in unlined metal containers.

Pesticide Disposal: Pesticide wastes are acutely hazardous, Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Non-refillable container. Do not reuse or refill this container. Triple rinse container promptly after emptying. Triple rinse as follows: [For containers < 5 gallons in size] - Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. [For containers > 5 gallons in size] - Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

CONSULT FEDERAL, STATE OR LOCAL DISPOSAL GENERAL: AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

CONDITIONS OF SALE AND WARRANTY

Thor GmbH warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. THOR GMBH MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES EITHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. Handling, storage and use of the product by Buyer or User are beyond the control of Thor GmbH and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow label directions will be assumed by the Buyer or User. IN NO CASE WILL THOR GMBH OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.

Batch:					0 000		
Buton.	^	<i>c</i>	r r	r	$\hat{}$	с с	
	c	<u>م</u>	c r	r	Ċ	¢ 0	
	<i>c</i>			с <u>с</u>	с		
	<u>^</u>		с. с			<u>^</u> 0	
	-	^	<u>_</u>	c c	C	<u>_</u>	

ACTICIDE[®] 45

ACTIVE INGREDIENT: 2-n-Octvl-4-isothiazolin-3-one **INERT INGREDIENTS:** TOTAL:

KEEP OUT OF REACH OF CHILDREN DANGER - PELIGRO

46.5%

53.5%

100.0%

See Side panel for additional precautionary statements

FIRST AID					
If Swallowed:	*Call a poison control center or doctor immediately for treatment advice.				
	*Have person sip a glass of water if able to swallow.				
	*Do not induce vomiting unless told to do so by the poison control center or doctor.				
	*Do not give anything by mouth to an unconscious person				
If on Skin:	*Take off contaminated clothing.				
Or Clothing	*Rinse skin immediately with plenty of water for 15-20 minutes.				
	*Call a poison control center or doctor for treatment.				
If Inhaled:	*Move person to fresh air.				
	*If person is not breathing, call 911 or an				
	ambulance, then give artificial respiration,				
	preferably by mouth-to- mouth, if possible.				
	*Call a poison control center or doctor for further treatment				
If in Eyes:	*Hold eye open and rinse slowly and gently with water for 15-20 minutes.				
	*Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.				
	*Call a poison control center or doctor for treatment advice.				
when calling a p	IBER: Have the product container or label with you poison control center or doctor, or going for treatment. ontact 1-800-424-9300 for emergency medical nation.				
Note to physicia use of gastric la	an: Probable mucesel damage may contraindicate the wage. ACCEPTED				
	with COMMENTS				
Mfg Date:					

Precautionary Statements: Hazards to Humans and Domestic Animals

DANGER

CORROSIVE. CAUSES PERMANENT, IRREVOCABLE EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION, MAY BE FATAL IF SWALLOWED. HARMFUL IF ABSORBED THROUGH SKIN OR INHALED. PROLONGED OR REPEATED OVEREXPOSURE CAN CAUSE CENTRAL NERVOUS SYSTEM EFFECTS AND KIDNEY AND LIVER DAMAGE. DO NOT GET IN EYES, ON SKIN, ON CLOTHING. WEAR GOGGLES OR FACE SHIELD. WEAR PROTECTIVE CLOTHING AND RUBBER GLOVES. AVOID BREATHING VAPOR OR MIST. KEEP CONTAINER CLOSED, USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY, WASH THOROUGHLY WITH SOAP AND WAT! AFTER HANDLING AND BEFORE EATING, DRINKING, OR USI TOBACCO.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

ACTICIDE® 45 is an industrial microbiocide to be used for the protection of paint films: coatings: including wood coatings and *wood coating solutions including sapstain control: adhesives: Building Materials including *sealants: *mastics: *caulks: *joint cements: *spackling: *stucco; * grouts: *applied film/wet state of adhesives, tackifiers, paints, coatings and other building materials; *hides; *leather; *textiles; *fibers; *fabrics; *plastic/PVC/vinyl products: *Metalworking Fluids; *Hydraulic Fluids against attack by mildew, and fungus. READ AND FOLLOW THE DIRECTIONS FOR USE ON THE ACCOMPANYING INFORMATION SHEET.

* Not approved for these uses in the State of California

EPA Reg. No. 67071-6

Manufactured For/By: Thor GmbH D-67346 Speyer, Germany Tel. (06232) 6360

EPA Est. No. 67071-DEU-001

U.S. Office: Thor Specialties, Inc. 56 Quarry Road Trumbull, CT 06611 USA Tel. (203) 365-6530

UN 2922, CORROSIVE LIQUID, TOXIC, N.O.S. (2-n-Octvl-4-isothiazolin-3-one), 8 (6.1), PG-III

For Transportation / Spills Emergency: Call Chemtrec at 1-800-424-9300

Net Contents (pounds):

APR 1 4 2011

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 62071-6



ACTICIDE[®] 45 INFORMATION SHEET



THIS ACTICIDE® 45 INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE[®] 45

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

DRY FILM PRESERVATIVE FOR PAINTS, COATINGS, WOOD COATINGS, WOOD COATING SOLUTIONS (INCLUDING *SAPSTAIN CONTROL): ACTICIDE® 45 mildewcide is recommended for the control of fungi in latex and oil-based paints, coatings-(non-food contact).

The amount of ACTICIDE[®] 45 needed to protect dry and the applied/wet-states of paint films and wood coatings varies with the type of formulation and exposure conditions of the film (e.g., indoor vs. tropical climates). Add 0.02 - 0.29% (wt) [0.02 - 0.29 lbs of ACTICIDE[®] 45 per 100 pounds of formulation The Thor Specialties Technical Department will assist in the determination of the optimum quantity required by your product. This facility is especially helpful where a formulation has a greater than usual susceptibility to microbiological spoilage and/or is to be used in an area where the environmental conditions are particularly conducive to fungal growth.

ACTICIDE[®] 45 may be used at higher concentrations so long as the end-use product/article contains a maximum concentration of not greater than 1320 ppm OIT

*To control sapstain on debarked logs and lumber, prepare a working solution by mixing with water at a rate of 1 to 5 quarts of ACTICIDE[®] 45 per 250 gallons of water. The working solution must be mixed thoroughly before and during use. Apply the working solution with a spray or dip system that coats all surfaces of the wood evenly and thoroughly. Treated wood must not be used or placed where it may contact food or animal feed

*Not approved for this use in the State of California

DRY FILM PRESERVATIVE FOR ADHESIVES: ACTICIDE® 45 mildewcide is recommended for the control of fungi in adhesives (non-food contact).

The amount of ACTICIDE® 45 needed to protect dry and the applied/wet-states of industrial adhesives varies with the type formulation. Add 0.02 - 0.29% (wt) [0.02 - 0.29 lbs of ACTICIDE[®] 45 per 100 pounds of formulation. The Thor Specialties Technical Department will assist in the determination of the optimum quantity required by your product. This facility is especially helpful where formulation has a greater than usual susceptibility to microbiological spoilage and/or is to be used in an area where the environmental conditions are particularly conducive to fungal growth.

DRY FILM PRESERVATIVE FOR BUILDING MATERIALS (INCLUDING *SEALANTS, *MASTICS, *CAULKS, *JOINT CEMENTS; *SPACKLING; *STUCCO; * GROUTS: ACTICIDE[®] 45 mildewcide is recommended for the control of fungi in Building Materials (non-food contact). *Not approved for these uses in the State of California

The amount of ACTICIDE[®] 45 needed to protect dry and the applied/wet-states of Building Materials varies with the type formulation and exposure conditions of the film (e.g., indoor vs. tropical climates). Add 0.02 - 0.29% (wt) [0.02 - 0.29 lbs of ACTICIDE[®] 45 per 100 pounds of formulation. The Thor Specialties Technical Department will assist in the determination of the optimum quantity required by your product. This facility is contained by your product. especially helpful where a formulation has a greater than usual susceptibility to microbiological spoilage and/or is to be used in an area where the environmental conditions are particularly conducive to fundation growth. ιιίι

ACCEPTED with COMMENTS Information Sheet # 060(h) - 12)29 For Letter Dated: Page 1 of 3 APR 1 4 2011

EPA Reg. No. 67071-6 Manufactured By/For: Thor GmbH

U.S. Office:

D-67346 Speyer, Germany Tel. (06232) 6360 Thor Specialties, Inc. 56 Quarry Road, Trumbull, CT 06611 USA Tel. (203) 365-6530

ίιι

Under the Federal Insecticide, Fungicide, and Rodenticide Act as emenaed for the pesticide, registered under EPA Reg. No. 67071-6

ACTICIDE[®] 45 INFORMATION SHEET



THIS ACTICIDE[®] 45 INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE[®] 45

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*APPLIED FILM/WET STATE PRESERVATIVE: ACTICIDE[®] 45 microbiocide is recommended for the control of bacteria and fungi in the applied film/wet state of adhesives, tackifiers, paints, coatings and building materials (such as fire-proofing and sound-proofing coatings) for the purpose of protecting the applied film/wet state prior to a full cure. *Not approved for these uses in the State of California

*LEATHER PRESERVATION: ACTICIDE[®] 45 is recommended for the prevention of bacterial and fungal growth on wet leather stock such as pickled, chrome-tanned and vegetable-tanned hides and leather, including wet-blues. Normal addition levels are in the range of 0.014% - 0.06% by weight of ACTICIDE[®] 45 calculated on the pelt weight. The optimum use concentrations will depend on the manufacturing process, the required properties of the product and the environment to which it will be exposed. Levels will be particularly affected by natural fat content, skin thickness, storage time and tannery conditions. *Not approved for these uses in the State of California

*TEXTILE, *FIBER AND *FABRIC PRESERVATION: ACTICIDE[®] 45 is recommended for the prevention of bacterial and fungal growth, in the presence of moisture, in/on fibers, textiles and fabrics, including carpets and backing materials, natural and man-made. Normal addition levels are in the range of 0.1%-0.25% by weight of ACTICIDE[®] 45 calculated on the materials weight. The optimum use concentrations will depend on the manufacturing process, the properties of the product and the environment to which it will be exposed. Levels will be particularly affected by the fabric thickness, proximity to the air circulation, storage time and ambient humidity. *Not approved for these uses in the State of California

***PRESERVATION OF PLASTIC/PVC/VINYL PRODUCTS**: ACTICIDE[®] 45 mildewcide is recommended for the control of mildew and fungi in PVC flooring and wall coverings, coated fabrics for upholstery, interior automotive parts, refrigerator gaskets, shower curtains, mattress covers, artificial leather, rain wear, protective wear, shoes, boots, PVC slippers and gloves. For these uses, generally not subject to continuous external environmental conditions, use 0.1%-0.5% of ACTICIDE[®] 45 based on the total weight of the formulation/composition (or 0.05% to 0.5% based on plastisol).

ACTICIDE[®] 45 is also recommended in situations generally subject to external environmental variations such as use in automotive landau tops, external automotive trim, tarpaulins, tents, awnings, indoor/outdoor carpeting, garden hoses, pool and pond liners, marine upholstery, swimming pool liners, roof liners, lining foils, cable casings, PVC tiles and fibers. For these external-type uses apply 0.15%-0.75% of ACTICIDE[®] 45 based on the total weight of the formulation/composition (4.35 lbs/1000 lbs. of compound).

Mode of application for plastic/PVC/Vinyl Products. ACTICIDE[®] 45 can, in most of the standard methods of plastics production, be introduced in different phases of the process cycle. An absolutely homogeneous incorporation into the material is essential for a good antimicrobial (anti-fungal) activity. The mixture of the product with fluid additives should be ensured by the use of a good mechanical stirring device. The product ^CCCC may never be introduced directly into fillers and pigments. ACTICIDE[®] 45 is first dissolved in the product can ^CCCC subsequently, the rest of the additives are mixed in and homogeneously worked together. The product can ^CCCC subsequently distributed in finished plastisols by intensive mixing. *Not approved for the second state of California

ACCEPTED with COMMENTS Information Sheet # 060(h) - 12/292924 Letter Dated: Page 2 of 3

APR 1 4 2011

Under the Federal Insecticide, Fundicide and Rogenheide Act as amended to the Destructor registered under EPA reg. No. 67071-6

EPA Reg. No. 67071-6 Manufactured By/For: Thor GmbH

U.S. Office:

Thor GmbH ^C D-67346 Speyer, Germany Tel. (06232) 6360 Thor Specialties, Inc. 56 Quarry Road, Trumbull, CT 06611 USA Tel. (203) 365-6530

ι : ιιιιίι

ACTICIDE[®] 45 INFORMATION SHEET



LCCCC

THIS ACTICIDE[®] 45 INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE[®] 45

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*METALWORKING FLUID PRESERVATION: ACTICIDE[®] 45 is recommended for the control of fungi in the manufacture and use of soluble, synthetic, and semi-synthetic metalworking fluids. ACTICIDE[®] 45 is not recommended for use in systems or fluids which are subject to foaming or systems with high levels of tramp oil. ACTICIDE[®] 45 should be directly dispensed into the metalworking concentrate or use-dilution metalworking fluid using a metered pump or other point-of-use device and uniformly dispersed throughout the liquid. Greatly contaminated systems must be cleaned before treatment is begun. *Not approved for these uses in the State of California

FLUID CONCENTRATES:

ACTICIDE[®] 45 should be added to the metalworking concentrate at a level to ensure that the final usedilution fluid will contain 55-167 ppm of product (25-75 ppm active ingredient).

USE-DILUTION FLUID:

For a noticeably fouled system, add 0.47 – 1.44 pounds of ACTICIDE[®] 45 per 1,000 gallons of emulsion. This will provide 25-75 ppm active ingredient. Repeat until control is achieved. For maintenance of a nonfouled system, add 0.09 – 0.58 pounds of ACTICIDE[®] 45 per 1,000 gallons of emulsion every 4 weeks. This will provide 5-30 ppm active ingredient. A higher dose range and/or increased frequency of treatment may be required, depending upon rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

*HYDRAULIC FLUID PRESERVATION: ACTICIDE[®] 45 is recommended as a preservative in the manufacture and use of soluble oils, high water-based and emulsion hydraulic fluids. ACTICIDE[®] 45 should be directly dispensed into the hydraulic concentrate or use-dilution hydraulic fluid using a metered pump or other point-of-use device and uniformly dispersed throughout the fluid. Greatly contaminated systems must be cleaned before treatment is begun. *Not approved for these uses in the State of California

FLUID CONCENTRATES:

ACTICIDE[®] 45 should be added to the hydraulic fluid concentrate at a level to ensure that the final usedilution fluid will contain 55-167 ppm of product (25-75 ppm active ingredient).

USE-DILUTION FLUID:

For a noticeably fouled system, add 0.47 – 1.44 pounds of ACTICIDE[®] 45 per 1,000 gallons of emulsion. This will provide 25-75 ppm active ingredient. Repeat until control is achieved. For maintenance of a nonfouled system, add 0.09 – 0.58 pounds of ACTICIDE[®] 45 per 1,000 gallons of emulsion every 4 weeks. This will provide 5-30 ppm active ingredient. A higher dose range and/or increased frequency of treatmant may be required, depending upon rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

	ACCEPTED with COMMENTS EPA Letter Dated:				
	APR 1 4 2011			, ((((((ιιιι
Information Sheet # 060(h) Page 3 of 3	-Uzdezthe Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.	EPA Reg. No. 67071-6 Manufactured By/For:			
	67071-6	U.S. Office:	Thor Specialties, Inc. 56 Quarry Road, Trumbull, CT 06611 USA Tel. (203) 365-6530		