

67071-18

1/14/2002

Page 175

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JAN 14 2002

Thor GmbH
D-67346 Speyer,
Germany

Attention: Geraldine W. Werdig, Manager
Regulatory Affairs

Subject: **Anticide SR 2060**
EPA Registration No. 67071-18
Amendment Dated September 6, 2001


The amendment referred to above, submitted in connection with registration under the FIFRA sec. 3(c)(7)(A), to add uses to the "Directions for Use" section of the label, is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Submit two (2) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the labeling constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

Enclosure		CONCURRENCES					
SYMBOL							
SURNAME							
DATE							

275

Acticide SR 2060
Page 1 of 4
09/01



ACTICIDE® SR 2060

Industrial microbiocide for use in adhesives, tackifiers, paints, coatings, building materials, polymer latices, printing inks, metal working, metal cleaning fluids and other cleaners such as liquid soaps, cleaners, detergents, carpet shampoos for industrial and household uses and in polishes and waxes.

ACTIVE INGREDIENTS:

2-Bromo-2-nitropropane-1, 3-diol	5.2%
5-Chloro-2-methyl-4-isothiazolin-3-one	0.8%
2-Methyl-4-isothiazolin-3-one	0.3%

INERT INGREDIENTS: 93.7%

TOTAL: 100.0%

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JAN 14 2002

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide.
registered under EPA Reg. No.

6767-18

**KEEP OUT OF REACH OF CHILDREN
DANGER**

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

FIRST AID

- IF SWALLOWED:** *Call poison control center or doctor immediately for treatment advice.
*Have person sip a glass of water if able to swallow.
*Do not induce vomiting unless told to do so by the poison control center or doctor.
*Do not give anything by mouth to an unconscious person.
-
- IF ON SKIN** *Take off contaminated clothing.
OR CLOTHING: *Rinse skin immediately with plenty of water for 15-20 minutes.
*Call a poison control center or doctor for treatment advice.
-
- IF IN EYES:** *Hold eye open and rinse slowly and gently with water for 15-20 minutes.
*Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
*Call a poison control center or doctor for treatment advice.
-
- IF INHALED:** *Move person to fresh air.
*If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.
*Call a poison control center or doctor for further treatment advice.

HOT LINE NUMBER: Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-424-9300 for emergency medical treatment information.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

Manufactured By:
Thor GmbH
D-67346 Speyer, Germany
Tel. (06232) 6360

U.S. Office:
Acti-Chem Specialties, Inc.
56 Quarry Road
Trumbull, CT 06611 U.S.A.
Tel. (203) 365-6530

EPA Reg. No. 67071-18

EPA Est. No. 67071-DEU-1

NOT FOR SALE OR USE AFTER 12 MONTHS FROM DATE OF MANUFACTURING.

Net Contents: _____ Pounds

Date of Manufacture: _____

9/01

Lot # _____

3 7 5

Acticide
SR 2060
Page 2 of 4
09/01

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE CAUSES EYE DAMAGE AND SKIN BURNS MAY CAUSE ALLERGIC SKIN REACTION MAY BE HARMFUL IF INHALED OR ABSORBED THROUGH THE SKIN Do not get in eyes, on skin, on clothing. Wear goggles or face shield when handling. Harmful if swallowed. Avoid breathing vapor or spray mist. Avoid contamination of food. Wash thoroughly with soap and water after handling. Remove contaminated clothing, and wash clothing before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

PROHIBITIONS: This product (pH 3.5) is corrosive to mild steel. Do not store in unlined containers. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or incinerator or, if allowed by state and local authorities, by burning. If burned, stay out of the smoke.

GENERAL: CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JAN 14 2002

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
amended, for the pesticide,
registered under EPA Reg. No.

67071-18

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PRESERVATIVE FOR ADHESIVES AND TACKIFIERS: Acticide SR 2060 microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in water soluble and water dispersed adhesives such as animal glues, vegetable glues, natural rubber latices, polyvinyl acetate, styrene-butadiene and acrylic latices. Acticide SR 2060 microbiocide is recommended as a preservative for tackifiers derived from rosin and hydrocarbon resins.

Add 0.5 to 1.65 lb Acticide SR 2060 microbiocide to each 1000 lb of fluid to provide 5.5 ppm to 18.3 ppm isothiazolones and 26 to 86 ppm bronopol. A higher dosage rate providing up to 33 ppm isothiazolones and 248 ppm bronopol may be required for storage during extremely high temperatures and humidity.

PRESERVATIVE FOR BUILDING MATERIALS: Acticide SR 2060 microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in building materials such as mastics, caulks, joint cements, spackling and grouting. Add 0.5 to 1.65 lb of Acticide SR 2060 microbiocide to each 1000 lb of fluid to provide 5.5 ppm to 18.3 ppm isothiazolones and 26 to 86 ppm bronopol.

PRESERVATIVE FOR LATICES: Acticide SR 2060 microbiocide is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer latices including acrylics, styrene-butadiene, carboxylated styrene-butadiene, ethylene-vinyl acetate and biopolymers intended for industrial use such as xanthan gum, gum arabic, guar gum, protein derived polymers, starches and casein derived polymers.

Add 0.5 to 3.3 lb (227 g to 1.5 kg) of Acticide SR 2060 microbiocide to each 1000 lb (454 kg) of emulsion to provide 5.5 ppm to 36.6 ppm active isothiazolones and 26 to 172 ppm bronopol.

NOTE: To insure uniform mixing, add Acticide SR 2060 microbiocide to latex or solutions slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

CONDITIONS OF SALE AND WARRANTY

Thor GmbH warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. THOR GMBH MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES EITHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. Handling, storage and use of the product by Buyer or User are beyond the control of Thor GmbH and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow label directions will be assumed by the Buyer or User. IN NO CASE WILL THOR GMBH OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.

PRESERVATIVE FOR PAINTS AND COATINGS: Acticide SR 2060 microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in water based coatings such as paper, wood coatings and paints used for architectural, product finishes and special purpose coatings. Add 0.5 to 1.65 lb (227 to 750 grams) Acticide SR 2060 microbiocide to each 1000 lb (454 kg) of fluid to provide 5.5 ppm to 18.3 ppm isothiazolones and 26 to 86 ppm bronopol. A higher dosage rate providing up to 33 ppm isothiazolones and 248 ppm bronopol may be required for storage during extremely high temperatures and humidity.

Special purpose coating uses: Include use as a: <> preservative for electrodeposition paints or solutions, <> preservative for photoplatin solutions or coatings, <> preservative in fount (or fountain) solutions used in the printing process as a maintenance fluid/coating and as a special coating for printing plates, and <> preservative in spin finish coatings for fibers. The application/addition directions for these special purpose coating uses are:

ELECTRODEPOSITION: Acticide SR 2060 microbiocide is recommended as a tankside additive for the control of bacteria, fungi, and algae in re-circulating electrodeposition systems and associated rinse systems. Alternately, Acticide SR 2060 microbiocide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

Tankside Addition To Electrodeposition Systems: Acticide SR 2060 microbiocide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to insure uniform mixing. When the system is noticeably fouled, add 670 to 2400 ppm Acticide SR 2060 microbiocide (6.4 to 22.9 gallons per 10,000 gallons of fluid in the system). This will provide 7.4 to 26 ppm of isothiazolones and 35 to 125 ppm bronopol. Repeat until control is achieved.

When microbial control is evident, add 334 to 1055 ppm Acticide SR 2060 (3.2 to 10.1 gallons per 10,000 gallons of fluid in the system) weekly or as needed to maintain the system. This will provide 4 - 12 ppm of isothiazolones and 17-55 ppm bronopol. A change of frequency of treatment may be required depending on the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS: Initial Dose of Paint Components: Acticide SR 2060 microbiocide should be added to the resin, pigment, or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 334 to 2400 ppm product (4 - 26 ppm isothiazolones and 17-125 bronopol).

Supplemental Tanked Dosing of Electrodeposition System: If additional microbial control is necessary, Acticide SR 2060 microbiocide may be added to the electrodeposition system tankside to supplement the microbiocide incorporated through paint components. If the system becomes noticeably fouled, add 670 to 2400 ppm Acticide SR 2060 microbiocide (6.4 to 22.9 gallons per 10,000 gallons of fluid in the system). This will provide 7.4 - 26 ppm of isothiazolones and 35-125 ppm of bronopol. Repeat until control is achieved.

When microbial control is evident, the system can be maintained by addition of 334 to 1055 ppm. Acticide SR 2060 microbiocide (3.2 to 10.1 gallons per 10,000 gallons of fluid in the system) weekly or as needed. This will provide 4 - 12 ppm of isothiazolones and 17-55 ppm of bronopol.

NOTE: Regardless of the manner of incorporation, the total active ingredient level in the system should never exceed 26 ppm isothiazolones and 125 ppm bronopol (equivalent to 2400 ppm Acticide SR 2060 or 22.9 gallons per 10,000 gallons of system fluid).

PHOTOPATE PROCESSING, FOUNTAIN SOLUTIONS, AND INK/INK COMPONENTS:

Acticide SR 2060 microbiocide is recommended for the control of bacteria and fungi in photoplate processing such as stabilizer solutions and in fountain solutions. Acticide SR 2060 microbiocide is recommended for water-based printing inks such as flexographic, gravure, screen and ink jet types. Acticide SR 2060 microbiocide is recommended for the control of bacteria and fungi in printing ink components such as resins, plasticizers, water soluble dyes, pigments, gelling agents, waxes, surfactants, and thickeners. Acticide SR 2060 microbiocide should be added to achieve the recommended dosage range for ink, ink components, fountain solutions and photoplate processing chemicals of 0.1% to 1.0% on a total weight basis. The optimum level range for acidic fountain solutions is 0.2% to 0.5%; the optimum level range for neutral fountain solutions is 0.5% to 0.8%. A level adjustment may be necessary to accommodate the slight change in solution formulations.

NOTE: To insure uniform mixing, add Acticide SR 2060 microbiocide to latex or solution slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

GENERAL ADVISORY STATEMENT

ACTICIDE SR 2060 SHOULD BE ADDED TO THOSE PRODUCTS FORMULATED AS CONCENTRATES WHICH ARE IN TURN DILUTED FOR USE AT A LEVEL TO ENSURE THAT THE FINAL USE-DILUTION PRODUCT WILL CONTAIN BETWEEN 4-36.6 PPM ACTIVE ISOTHIAZOLONES AND 26-172 PPM BRONOPOL, AS DESCRIBED ABOVE, EXCEPT FOR PAINTS AND COATINGS WHICH SHOULD BE AT 4 - 33 PPM ISOTHIAZOLONES AND 26 - 248 PPM BRONOPOL, AS DESCRIBED ABOVE.

ACCEPTED with COMMENTS EPA Letter Dated:

JAN 14 2002

Under the Federal Insecticide, Fungicide, and Rodenticide Act, amended, for the pesticide, registered under EPA Reg. No.

67071-18

METAL WORKING AND METAL CLEANING FLUID PRESERVATION

Acticide
SR 2060
Page 4 of 4
09/01

Metal Working Fluid Preservation: Acticide SR 2060 microbiocide is recommended for the control of bacteria and fungi in aqueous metal working fluid solutions and emulsions.

Add 32 fluid ounces (2.2 lb.) per 1000 gallons of emulsion every 4 weeks for maintenance of a non-fouled system. For a noticeably fouled system use an initial dose of 64 to 160 fluid ounces (4.5 to 11 lb.) per 1000 gallons emulsion followed by subsequent maintenance dosage above. A higher dosage rate and/or increased frequency of treatment may be required depending upon the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the use dilution of the metal working fluid using a metering pump and uniformly dispersed throughout the system.

Metal Cleaning Fluid Preservation: Acticide SR 2060 microbiocide is recommended as a preservative for use in the manufacture and use of alkaline, acid and emulsion based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations.

For addition to a metal cleaning concentration, add Acticide SR 2060 microbiocide at a level to ensure that the final use-dilution fluid will contain 334 to 2400 ppm product (about 4 to 26 ppm active isothiazolones and 17 to 125 ppm bronopol).

For direct addition to a fouled system, add 83 to 293 fluid ounces (5.6 to 20 lb) of Acticide SR 2060 microbiocide to each 1000 gallons of use-dilution metal cleaning fluid every 3 to 4 weeks to provide 668 to 2110 ppm product (about 7.4 to 26 ppm active isothiazolones and 35 to 125ppm bronopol). A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with the make-up fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed into the use-dilution metal cleaning fluid using a metering pump and uniformly dispersed throughout the system.

LIQUID SOAPS, CLEANERS, DETERGENTS, CARPET SHAMPOOS FOR INDUSTRIAL AND HOUSEHOLD USES AND IN POLISHES AND WAXES

Acticide SR 2060 is added at a level of 0.4 to 1.5 lb. (180 - 680 grams) to each 1000lb. (453.6 kilograms) of product to be protected to provide 6 to 22.5 ppm of active isothiazolinones.

For control of bacteria and fungi in liquid detergents, in liquid laundry products and also in dishwashing detergents, waxes, polishes, and other similar cleaners, use 0.4 to 1.0 lb. of Acticide SR 2060 per each 1000lb. (453.6 kilograms) of treated product to provide a level of 6 to 15 ppm of active ingredient (isothiazolinones).

Acticide SR 2060 may also be used for control of bacteria and fungi in package utility products such as pre-moistened sponges and mops. Use 0.4 to 1.5 lb. in each 1000 lb. of water to pre-moistened sponges and mops.

Acticide SR 2060 microbiocide weighs 8.7 lb. per gallon.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JAN 14 2002

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

67071-18