AUG 1 9 2008

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



United States Environmental Protection Office of Pesticide Programs

Thor GmbH Landwehrstrasse 1 D-67346. Speyer, Germany

AGENT: Thor Specialties, Inc.

56 Quarry Road Trumbull, CT 06611

Attention: Lynn P. Toro

Subject: ACTICIDE WB 200

EPA Registration No. 67071-30 Amendment Dated May 13, 2008

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, to include the "in-can" preservation of various aqueous products, is acceptable, provided that you:

- 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3©(5) and sec. 4 when the Agency requires all registrants of similar products to submit such data.
- 2. Submit two (2) copies of final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

Page 2 EPA Registration No. 67071-30

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell Product Manager 33

Regulatory Management Branch 1 Antimicrobials Division (7510P)

Enclosure

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

Do not contaminate food or feed by storage, disposal or cleaning of equipment.

STORAGE DISPOSAL: This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. Plastic container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incinerator or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL: CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

CONDITIONS OF SALE AND WARRANTY

Thor GmbH warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. THOR GMBH MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES EITHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. Handling, storage and use of the product by Buyer or User are beyond the control of Thor GmbH and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow label directions will be assumed by the Buyer or User. IN NO CASE WILL THOR GMBH OR SELLER BE HELD LIABLÉ FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS

CORROSIVE LIQUID, N.O.S. (2-n-Octyl-4-isothiazolin-3one), 8, UN 1760, PG-III

ACTICIDE® WB 200

ACTIVE INGREDIENT:

2-n-Octyl-4-isothiazolin-3-one **INERT INGREDIENTS:** TOTAL:

20.9% 79.1% 100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

See Side panel for additional precautionary statements FIRST AID

If Swallowed:*Call a poison control center or doctor immediately for treatment advice.

> *Have person sip a glass of water if able to swallow. *Do not induce vomiting unless told to do so by the poison control center or doctor.

*Do not give anything by mouth to an unconscious person

*Take off contaminated clothing. If on Skin:

Or Clothing *Rinse skin immediately with plenty of water for 15-20 minutes.

*Call a poison control center or doctor for treatment advice.

If Inhaled: *Move person to fresh air.

> *If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-tomouth, if possible.

*Call a poison control center or doctor for further treatment advice.

*Hold eye open and rinse slowly and gently with water for If in Eyes: 15-20 minutes.

> *Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.

*Call a poison control center or doctor for treatment

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-424-9300 for emergency medical treatment information. NOTE TO PHYSICIAN: Probable mucos damage may contraindicate the use of gastric lavage.

with COMMENTS EPA Letter Dated:

Precautionary Statements: Hazards to Humans and Domestic

Animals DANGER

CORROSIVE. CAUSES PERMANENT, IRREVOCABLE EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION, MAY BE FATAL IF SWALLOWED, HARMFUL IF ABSORBED THROUGH SKIN OR INHALED. PROLONGED OR REPEATED OVEREXPOSURE CAN CAUSE CENTRAL NERVOUS SYSTEM EFFECTS AND KIDNEY AND LIVER DAMAGE. DO NOT GET IN EYES, ON SKIN, ON CLOTHING. WEAR GOGGLES OR FACE SHIELD. WEAR PROTECTIVE CLOTHING AND RUBBER GLOVES. AVOID BREATHING VAPOR OR MIST. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

ACTICIDE® WB 200 is an industrial microbiocide to be used for the protection of *hides and *leather, *Plastic/PVC/Vinyl Products. *textiles, *fibers, *fabrics, *paint films, *coatings including *wood coatings, *polymer latices, *adhesives, *fillers, *caulks, *sealants, *building *pigments/filler *grouts, materials, *dyės, slurries/suspensions, to control mildew and fungi. READ AND FOLLOW THE DIRECTIONS FOR USE ON THE **ACCOMPANYING INFORMATION SHEET**

* Not approved for use in the State Of California

EPA Reg. No. 67071-30

Manufactured For/By:

Thor GmbH

D-67346 Speyer, Germany

Tel. (06232) 6360

EPA Est. No. 67071-DEU-001

U.S. Office:

Thor Specialties, Inc. 56 Quarry Road Trumbull, CT 06611 USA

Tel. (203) 365-6530

Batch:

Mfg Date:

Net Contents (pounds):

Under the Federal Assecticide, Puncicide, and Redenticide Act as emended, for the perilcide, registered under EPA Reg. No. 67071-30

4 8 85



ACTICIDE® WB 200 INFORMATION SHEET

THIS ACTICIDE® WB 200 INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® WB 200

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*LEATHER PRESERVATION:

ACTICIDE® WB 200 is recommended for the prevention of bacterial and fungal growth on wet leather stock such as pickled, chrome-tanned and vegetable-tanned hides and leather, including wet-blues. Normal addition levels are in the range of 0.02% - 0.10% by weight of ACTICIDE® WB 200 calculated on the pelt weight. The optimum use concentrations will depend on the manufacturing process, the required properties of the product and the environment to which it will be exposed. Levels will be particularly affected by natural fat content, skin thickness, storage time and tannery conditions

Emulsion Preparation: The emulsion of ACTICIDE® WB 200 has only short term stability and therefore it should be prepared immediately before addition to the drum. For optimum stability the biocide must be added to the water rather than vice versa and should be diluted to give a concentration of at least 1:40. In order to obtain a homogeneous distribution on skins, the emulsion must be added slowly and immediately after the first application of chrome during the tanning process.

* Not approved for this use in the State Of California

*PRESERVATION OF PLASTIC/PVC/VINYL PRODUCTS:

ACTICIDE WB 200 mildewcide is recommended for the control of mildew and fungi in PVC flooring and wall coverings, coated fabrics for upholstery, interior automotive parts, refrigerator gaskets, shower curtains, mattress covers, artificial leather, rain wear, protective wear, shoes, boots, PVC slippers and gloves. For these uses, generally not subject to continuous external environmental conditions, use 0.05% - 0.5% of ACTICIDE WB 200 based on the total weight of the formulation/composition.

ACTICIDE WB 200 is also recommended in situations generally subject to external environmental variations such as use in automotive landau tops, external automotive trim, tarpaulins, tents, awnings, indoor/outdoor carpeting, garden hoses, pool and pond liners, marine upholstery, swimming pool liners, roof liners, lining foils, cable castings, PVC tiles and fibers. For these external-type uses apply 0.07% - 0.5% of ACTICIDE WB 200 based on the total weight of the formulation/composition.

Mode of application for Plastic/PVC/Vinyl products: ACTICIDE WB 200 can, in most of the standard methods of plastics production, be introduced in different phases of the process cycle. An absolutely homogeneous incorporation into the material is essential for a good antimicrobial activity. The mixture of the product with fluid additives should be ensured by the use of a good mechanical stirring device. The product may never be introduced directly into fillers and pigments. ACTICIDE WB 200 is first incorporated in the plasticizer. Subsequently, the rest of the additives are mixed in and homogeneously worked together. The product can also be homogeneously distributed in finished plastisols by intensive mixing.

* Not approved for this use in the State Of California

ACCEPTED
with COMMENTS
WEPA Letter Dated

AUG 19 2008

Information Sheet # 300(b1-plas) (c)- 11/02/05 (15/(19/08

Page 1 of 2

Under the Federal Insecticide, Fungicide, and Rodenticide Act as: amended, for the pesticide, registered under EPA Reg. No.

67071-30

EPA Reg. No. 67071-30

Manufactured By/For: Thor GmbH

D-67346 Speyer, Germany Tel. (06232) 6360

U.S. Office:

Thor Specialties, Inc. 56 Quarry Road, Trumbull, CT 06611 USA

Tel. (203) 365-6530



ACTICIDE® WB 200 INFORMATION SHEET

THIS ACTICIDE® WB 200 INFORMATION SHEET MUST ACCOMPANY EACH SHIPMENT OF ACTICIDE® WB 200

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*DRY FILM AND APPLIED FILM/WET-STATE PRESERVATIVE FOR PAINTS, COATINGS, WOOD COATINGS, POLYMER LATICES, ADHESIVES, FILLERS, CAULKS, SEALANTS, GROUTS AND **BUILDING MATERIALS:**

ACTICIDE® WB 200 mildewcide is recommended for the control of fungi in paint films, coatings, wood coatings, including stains, polymer latices, adhesives, fillers, caulks, sealants, grouts (non-food contact) and building materials.

Add 0.1% to 0.65% ACTICIDE® WB 200 based on the weight of the formulation of paint, wood coating polymer, latices, adhesive, or building materials.

ACTICIDE® WB 200 can be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain 0.1% to 0.65% ACTICIDE® WB 200.

ACTICIDE® WB 200 can be incorporated with most products at any stage in the manufacturing process. It is preferably added in the let-down stage during the manufacture of paints or wood coatings. Add slowly with good agitation just before addition of thickener.

* Not approved for this use in the State Of California

*DYES, PIGMENTS/ FILLER SLURRIES/SUSPENSIONS:

Recommended for the control of bacteria & fungi in the manufacture and storage of Dyes, Pigments and Filler Slurries/Suspensions, including Dyes, Pigments and Filler Slurries/Suspensions used in paper Dated: production.

Add 0.1% to 0.25% ACTICIDE® WB 200 based on weight of formulation

Pulp and paper Systems: recommended for the preservation of paper/paperboatdiproducts/components Flungicide, and Rodenticide not as including pulp, pigment slurries, emulsions, adhesives. amended, for the pesticide, Add 0.1% to 0.25% ACTICIDE® WB 200 based on weight of formulation

* Not approved for this use in the State Of California

*TEXTILE, *FIBER AND *FABRIC PRESERVATION:

ACTICIDE® WB 200 is recommended for the prevention of bacterial and fungal growth, in the presence of moisture, in/on fibers, textiles and fabrics, including carpets and backing materials, natural and man-made. Normal addition levels are in the range of 0.2%-0.65% by weight of ACTICIDE® WB 200 calculated on the materials weight. The optimum use concentrations will depend on the manufacturing process, the properties of the product and the environment to which it will be exposed. Levels will be particularly affected by the fabric thickness, proximity to the air circulation, storage time and ambient humidity.

* Not approved for this ASIA Citie State Of California

with COMMENTS EPA Letter Dated:

Information Sheet #.300(c) .05/09/08
Page 2 of 2 The Factoral Insecticide, Page 2 of Pungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

EPA Reg. No. 67071-30

Manufactured By/For: Thor GmbH

D-67346 Speyer, Germany Tel. (06232) 6360

registered under EPA Reg. No.

U.S. Office:

Thor Specialties, Inc. 56 Quarry Road, Trumbull, CT 06611 USA

Tel. (203) 365-6530



CONFIDENTIAL EXPLANATION Amendment to clarify uses on the ACTICIDE® WB 200 label

Clarification of this "in-container" materials preservative to include various aqueous products. This use clarification is in accordance with language on other Thor products containing the same active:

Proposed
ACTICIDE® WB 200 Label
(67071-30)
(product contains 20.9 % OIT)

Corresponding Uses on ACTICIDE® OTW Label (67071-31) (product contains 16.84% OIT)

DRY FILM AND APPLIED FILM/WET-STATE
PRESERVATIVE FOR PAINTS, COATINGS, WOOD
COATINGS, POLYMER LATICES, ADHESIVES, FILLERS,
CAULKS, SEALANTS, GROUTS AND BUILDING
MATERIALS:

ACTICIDE® WB 200 mildewcide is recommended for the control of fungi in paint films, coatings, wood coatings, including stains, polymer latices, adhesives, fillers, caulks, sealants, grouts (non-food contact) and building materials.

Add 0.1% to 0.65% ACTICIDE® WB 200 based on the weight of the formulation of paint, wood coating polymer, latices, adhesive, or building materials.

ACTICIDE® WB 200 can be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain 0.1% to 0.65% ACTICIDE® WB 200.

ACTICIDE® WB 200 can be incorporated with most products at any stage in the manufacturing process. It is preferably added in the let-down stage during the manufacture of paints or wood coatings. Add slowly with good agitation just before addition of thickener.

* Not approved for this use in the State Of California

[Page 2 of Information Sheet]

DRY FILM AND APPLIED FILM/WET-STATE PRESERVATIVE FOR PAINTS, COATINGS, WOOD COATINGS, POLYMER LATICES, ADHESIVES, FILLERS, CAULKS, SEALANTS, GROUTS AND BUILDING MATERIALS:

ACTICIDE® OTW mildewcide is recommended for the control of fungi in paint films, coatings, wood coatings, including stains, polymer latices, adhesives, fillers, caulks, sealants, grouts (nonfood contact) and building materials.

Add 0.1% to 2.0% ACTICIDE® OTW based on the weight of the formulation of paint, wood coating polymer, latices, adhesive, or building materials.

ACTICIDE® OTW can be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain 0.1% to 2.0% ACTICIDE® OTW.

ACTICIDE® OTW can be incorporated with most products at any stage in the manufacturing process. It is preferably added in the let-down stage during the manufacture of paints or wood coatings. Add slowly with good agitation just before addition of thickener.

* Not approved for use in the State Of California

[Page 1 of Information Sheet]

CONFIDENTIAL EXPLANATION

Amendment to clarify uses on the ACTICIDE® WB 200 label May 13, 2008

Page 2 of 3

Proposed ACTICIDE® WB 200 Label (67071-30) (product contains 20.9 % OIT)

Since

> Dyes are a type of "coating"

> Pigments/filler slurries/suspension are types of "fillers" then,

Corresponding Uses on ACTICIDE® OTW Label

(67071-31)

(product contains 16.84% OIT)

the following use listed on the ACTICIDE® OTW label applies:

DRY FILM AND APPLIED FILM/WET-STATE PRESERVATIVE FOR PAINTS, COATINGS, WOOD COATINGS, POLYMER LATICES, ADHESIVES, FILLERS, CAULKS, SEALANTS, GROUTS AND BUILDING MATERIALS:

ACTICIDE® OTW mildewcide is recommended for the control of fungi in paint films, coatings, wood coatings, including stains, polymer latices, adhesives, fillers, caulks, sealants, grouts (nonfood contact) and building materials.

Add 0.1% to 2.0% ACTICIDE® OTW based on the weight of the formulation of paint, wood coating polymer, latices, adhesive, or building materials.

ACTICIDE® OTW can be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain 0.1% to 2.0% ACTICIDE® OTW.

ACTICIDE® OTW can be incorporated with most products at any stage in the manufacturing process. It is preferably added in the let-down stage during the manufacture of paints or wood coatings. Add slowly with good agitation just before addition of thickener. *Not approved for use in the State Of California

[Page 1 of Information Sheet]

*DYES, PIGMENTS/ FILLER SLURRIES/SUSPENSIONS:

Recommended for the control of bacteria & fungi in the manufacture and storage of Dyes, Pigments and Filler Slurries/Suspensions, including Dyes, Pigments and Filler Slurries/Suspensions used in paper production.

Add 0.1% to 0.25% ACTICIDE® WB 200 based on weight of formulation

Pulp and paper Systems: recommended for the preservation of paper/paperboard products/components including pulp, pigment slurries, emulsions, adhesives. Add 0.1% to 0.25% ACTICIDE® WB 200 based on weight of formulation

* Not approved for this use in the State Of California

[Page 2 of Information Sheet]

CONFIDENTIAL EXPLANATION

Amendment to clarify uses on the ACTICIDE® WB 200 label May 13, 2008

Page 3 of 3

Proposed
ACTICIDE® WB 200 Label
(67071-30)
(product contains 20.9 % OIT)

Corresponding Uses on ACTICIDE® 45 Label (67071-6) (product contains 46.50% OIT)

*TEXTILE, *FIBER AND *FABRIC PRESERVATION:

ACTICIDE® WB 200 is recommended for the prevention of bacterial and fungal growth, in the presence of moisture, in/on fibers, textiles and fabrics, including carpets and backing materials, natural and man-made. Normal addition levels are in the range of 0.2%-0.65% by weight of ACTICIDE® WB 200 calculated on the materials weight. The optimum use concentrations will depend on the manufacturing process, the properties of the product and the environment to which it will be exposed. Levels will be particularly affected by the fabric thickness, proximity to the air circulation, storage time and ambient humidity.

* Not approved for this use in the State Of California

[Page 2 of Information Sheet]

*TEXTILE, *FIBER AND *FABRIC PRESERVATION:

ACTICIDE® 45 is recommended for the prevention of bacterial and fungal growth, in the presence of moisture, in/on fibers, textiles and fabrics, including carpets and backing materials, natural and man-made. Normal addition levels are in the range of 0.1%-0.25% by weight of ACTICIDE® 45 calculated on the materials weight. The optimum use concentrations will depend on the manufacturing process, the properties of the product and the environment to which it will be exposed. Levels will be particularly affected by the fabric thickness, proximity to the air circulation, storage time and ambient humidity. *Not approved for these uses in the State of California

[Page 1 of Information Sheet]