

PM 32 67262-16

10/3



United States  
Environmental Protection Agency  
Washington, DC 20460

Registration  
 Amendment  
 Other

OPP Identifier Number  
248820

Application for Pesticide - Section I

1. Company/Product Number 67262-16	2. EPA Product Manager W. Francis	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) RWP Master Dichloro	PM# 32	
5. Name and Address of Applicant (Include ZIP Code) Recreational Water Products, Inc. PO Box 887 Scottdale, GA 30079 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

See attached.

*Advisory statement*

NOTIFICATION  
SEP 23 1996

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	If "Yes" Unit Packaging wgt. No. per container		<input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted		If "Yes" Package wgt. No. per container			
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container	5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product.		
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Mark Jernigan	Title Federal Registration Manager	Telephone No. (Include Area Code) (404) 378-1761, x359
<b>Certification</b> I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)  
2. Signature <i>Mark Jernigan</i>	3. Title Federal Registration Manager	
4. Typed Name Mark Jernigan	5. Date 8/29/96	

2013

"MASTER LABEL"

# Recreational Water Products

## MASTER DICHLORO

**ACTIVE INGREDIENT:**  
Sodium dichloro-s-triazinetriene ..... 97.0%  
Inert Ingredients: ..... 3.0%  
**TOTAL INGREDIENTS** ..... 100.0%

**KEEP OUT OF REACH OF CHILDREN  
DANGER**

(See back panel for additional precautionary statements.)

**STATEMENTS OF PRACTICAL TREATMENT: IF IN EYES:** Hold eyelids open and flush with a steady, gentle stream of water for at 15 minutes. Get medical attention. **IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration preferably mouth-to-mouth. Get medical attention. **IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation persists. **IF SWALLOWED:** Drink promptly large quantities of water. Avoid alcohol. **NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Get medical attention. **IN CASE OF MEDICAL EMERGENCY, CALL 1-303-623-5716.**

59505

MANUFACTURED FOR:  
Recreational Water Products  
Scottsdale, Georgia 30079

EPA REG. #67262-16  
EPA EST. # 5185-GA-1

**NET CONTENTS:**

67262-16

### FOR POOL SANITIZATION:

**WHY TO USE THIS PRODUCT:** This product is a quick dissolving stabilized granular swimming pool sanitizer, which when applied according to label directions, will release sufficient chlorine to retard the growth of harmful algae and micro-organisms. This product's quick dissolve characteristics not only make it appropriate for all pool types, but won't leave behind the grit and haze other granular products can. Unlike calcium hypochlorite or liquid chlorine (bleach), this product's stabilized formula protects against sun light burn off, making it an efficient type of granular sanitizer for pools.

### IMPORTANT NOTES:

1. When using other products, as outlined in directions for this product, always follow label directions for those products.
2. Damage may be caused by direct contact of this product with pool surface or materials such as colored plaster, vinyl, wood or fiberglass.
3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a Stain & Scale Inhibitor prior to the addition of this product.
4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

### DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

### BEFORE YOU BEGIN:

1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
2. Adjust stabilizer levels to 40-50 ppm by adding Chlorine Stabilizer.
3. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 - 7.6 by adding pH Down to lower pH, or by adding pH Up to raise pH. Adjust alkalinity to 80 - 125 ppm for plaster pools, 125 - 150 for vinyl or fiberglass pools by adding Alkalinity Increaser. Adjust calcium hardness to 200 - 275 ppm for plaster pools, 175 - 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.

### NOW USE THIS PRODUCT:

#### START-UP/INITIAL TREATMENT:

1. If water is cloudy or green, superchlorinate pool with appropriate shock product until pool is clear.
2. With pump running and pool not in use, use a clean, dry, empty plastic scoop to broadcast 4 ounces of this product per 10,000 gallons of water directly into the deep end of the pool.
3. Repeat treatments until test kit indicates a chlorine level of 1-3 ppm.
4. When chlorine level is between 1-3 ppm, add an algae preventative to keep your pool algae free.

#### ROUTINE MAINTENANCE:

1. Check your pool weekly with a test kit. Add this product as needed to maintain a chlorine level of 1-3 ppm.
2. With pump running and pool not in use, use a clean, dry, empty plastic scoop to broadcast 2-3 ounces of this product per 10,000 gallons of water directly into the deep end of the pool.

### FOR VINYL POOL ALGAE KILLER:

**WHY TO USE THIS PRODUCT:** This product is an easy and potent way to destroy black algae and green tree floating algae in vinyl, colored plaster or fiberglass pools. This product's quick-dissolving granular form makes it ideal for treating most algae types and is appropriate for most pool surfaces under normal conditions. For treatment of mustard or yellow colored algae, use Mustard Algae Killer.

### IMPORTANT NOTES:

1. When using other products, as outlined in directions for this product, always follow label directions for those products.
2. Damage may be caused by direct contact of this product with pool surface or materials such as colored plaster, vinyl, wood or fiberglass.
3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a Stain & Scale Inhibitor prior to the addition of this product.
4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and

chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

**DIRECTIONS FOR USE:** It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

### BEFORE YOU BEGIN:

1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 - 7.6 by adding pH Down to lower pH, or by adding pH Up to raise pH. Adjust alkalinity to 80 - 125 ppm for plaster pools, 125 - 150 for vinyl or fiberglass pools by adding Alkalinity Increaser. Adjust calcium hardness to 200 - 275 ppm for plaster pools, 175 - 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.
3. Shut pump off, vigorously brush any visible algae spots and wait 4 hours before proceeding to the next step.

### NOW USE THIS PRODUCT:

1. For heavy to medium algae growth use 2 pounds per 10,000 gallons of water. For light algae growth use one pound per 10,000 gallons of water. At night or when pool is not in use, broadcast this product directly into the water in the deep end of the pool. To prevent damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool.
2. After treatment, wait 12 - 24 hours, then turn pump on and remove dead algae from pool surfaces with a brush, and vacuum dead algae through filter. Brush any remaining algae and backwash filter.
3. If living algae is still visible, repeat procedure.

### FOR VINYL POOL SHOCK

**WHY TO USE THIS PRODUCT:** This product contains a completely soluble active ingredient to destroy non-filterable swimmer wastes in vinyl-lined, colored plaster or fiberglass pools. When used as directed, this product restores water clarity, kills germs, helps kill algae, and destroys unpleasant odors. For white plaster pools, use All-Purpose Shock, and to shock your pool and swim in 15 minutes, use Non-Chlorine Quick-Swim Shock.

### IMPORTANT NOTES:

1. When using other products, as outlined in directions for this product, always follow label directions for those products.
2. Damage may be caused by direct contact of this product with pool surface or materials such as colored plaster, vinyl, wood or fiberglass.
3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a Stain & Scale Inhibitor prior to the addition of this product.
4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

### DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

### BEFORE YOU BEGIN:

1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 - 7.6 by adding pH Down to lower pH, or by adding pH Up to raise pH. Adjust alkalinity to 80 - 125 ppm for plaster pools, 125 - 150 for vinyl or fiberglass pools by adding Alkalinity Increaser. Adjust calcium hardness to 200 - 275 ppm for plaster pools, 175 - 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.

### NOW USE THIS PRODUCT:

#### For Start-Up Initial Shocking:

1. With pump running and pool not in use, broadcast 1 pound of this product per 10,000 gallons of water directly into the pool in the deep end of the pool. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool.

SEP 23 1996  
NOTIFICATION

3043



2. Repeat procedure after 24 hours, if needed, to establish a chlorine residual of 1-3 ppm as determined by a test kit.

**For Routine Shocking:**

1. Every 2 weeks with pump running and pool not in use, broadcast 1 pound of this product per 10,000 gallons of water directly into the pool in the deep end of the pool. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool.

**FOR WINTER POOL SHOCK:**

**WHY TO USE THIS PRODUCT:** To avoid costly spring problems (algae, stains, cloudy water, high chlorine demand) properly prepare your pool for the winter using this product. This product oxidizes organic wastes, provides long lasting chlorine protection, helps keep pool surfaces clean, and helps protect water during the off season months.

**IMPORTANT NOTES:**

1. When using other products, as outlined in directions for this product, always follow label directions for those products.
2. This product may cause damage to pool finish or materials such as colored plaster, vinyl, wood or fiberglass pool surfaces. Avoid spilling granules on pool surface.
3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a Stain & Scale Inhibitor prior to the addition of this product.
4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

**BEFORE YOU BEGIN:**

1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
2. Adjust stabilizer levels to 40-50 ppm by adding Chlorine Stabilizer.
3. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 - 7.6 by adding pH Down to lower pH, or by adding pH Up to raise pH. Adjust alkalinity to 80 - 125 ppm for plaster pools, 125 - 150 for vinyl or fiberglass pools by adding Alkalinity Increaser. Adjust calcium hardness to 200 - 275 ppm for plaster pools, 175 - 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.

**DIRECTIONS FOR USE:**

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

**NOW USE THIS PRODUCT:**

**START-UP/INITIAL TREATMENT:**

1. Use one pound of this product per 10,000 gallons of water. Broadcast this product directly into water in the deep end of the pool.
2. Circulate water for several hours, then add algicide.
3. Cut off pump. Drain equipment or add antifreeze to equipment to prevent freeze damage.
4. Install pool cover. A second treatment of this product in mesh covered or non-covered pools may be required prior to water freezing.

**FOR SPA SANITIZING USE**

**WHY TO USE THIS PRODUCT:** This product is a quick dissolving stabilized granular spa sanitizer, which when applied according to label directions, will release sufficient chlorine to retard the growth of harmful algae and micro-organisms.

**IMPORTANT NOTES:**

1. When using other products, as outlined in directions for this product, always follow label directions for those products.
2. This product may cause damage to spa or hot tub finish or materials such as colored plaster, vinyl, wood or fiberglass surfaces. Avoid spilling granules on spa surface.
3. This product may promote metal stains on spa or hot tub surfaces. Always check water for metal content and if present, remove metals with a Stain & Scale Inhibitor prior to the addition of this product.
4. Sunlight, rainfall, temperature, number of swimmers and frequency of spa and hot tub use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly.

**BEFORE YOU BEGIN:**

1. Ensure all spa equipment is working properly. Backwash filter following manufacturer's directions.
2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 - 7.6 by adding pH Down to lower pH, or by adding pH Up to raise pH. Adjust alkalinity to 80 - 125 ppm for plaster spas, 125 - 150 for vinyl or fiberglass spas by adding Alkalinity Increaser. Adjust calcium hardness to 200 - 275 ppm for plaster spas, 175 - 225 for vinyl or fiberglass spas by adding Calcium Hardness Increaser.

**DIRECTIONS FOR USE:**

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

**NOW USE THIS PRODUCT:**

**FOR ROUTINE MAINTENANCE DOSES:**

1. With pump on, add 1/2 teaspoon of this product per 100 gallons of water (or 5 teaspoons per 1,000 gallons) as an initial treatment.
2. Repeat at 15 to 20 minute intervals until a residual of 3-5 ppm of available chlorine is established as determined by test kit.
3. A test kit must be used regularly to determine the frequency of additional doses of this product needed to maintain 3-5 ppm of available chlorine in the water.

**FOR POOLS:**

Reentry into treated swimming pools is prohibited above levels of 3 ppm chlorine due to risk of body injury.

**STORAGE AND DISPOSAL:** Keep this product dry in original tightly closed container when not in use. Store in a cool, dry, well ventilated area away from heat or open flame. Moisture may decompose this product and cause a violent reaction leading to fire and explosion. In case of decomposition, isolate container if possible and flood area with large amounts of water to dissolve all material before discarding this container. Do not contaminate food or feed by storage or disposal. **CONTAINER DISPOSAL:** Do not reuse container, but place in trash collection. Rinse thoroughly before discarding in trash.

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS: DANGER: Corrosive:** Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or on clothing. Do not breathe dust, vapor or spray mist. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

**PHYSICAL OR CHEMICAL HAZARDS STRONG OXIDIZING AGENT:** Do not mix with other chemicals. Mix only with water. Never add water to product. Always add product to large quantities of water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals will start a chemical reaction and generate heat, hazardous gas, possible fire and explosion. In case of contamination or decomposition, do not reuse container. If possible, isolate container in open air or well ventilated area. Flood area with large volumes of water.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**NOTE:** Buyer assumes all responsibility for safety and use not in accordance with directions.

**OPTIONAL INFORMATION TO BE ADDED IF SPACE ALLOWS:**

<b>HOW TO CALCULATE POOL CAPACITY</b>	
Shape of Pool	Gallons of water
Rectangular	Average depth x average length x average width x 7.5
Circular	Diameter x diameter x average depth x 5.9
Oval	Full width x full length x average depth x 6.7
Irregular	Consult pool builder