NOV 2 0 2000

Mark Jernigan Recreational Water Products, Inc. P.O. Box 887 Scottdale, GA 30079

Subject:

RWP Master Dichloro

EPA Registration No. 67262-16 Submission Dated August 23, 2000

Dear Mr. Jernigan:

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided you make the labeling changes listed below before you release the product for shipment bearing the amended label.

- 1. Under the "Directions For Use" for Pools and Spas identify the micro-organisms that are to be eliminated.
- 2. On page 7, item #2 the statement "...remove deal algae from pool surfaces with a brush..." must be revised to read, "...remove dead algae from pool surfaces with a brush..."

A stamped copy of your labeling is enclosed for your records. Submit one (1) copy of the final printed label prior to release of the product for shipment.

If you have any questions concerning this letter, please contact at (703) 308-6345.

Sincerely,

Robert S. Brennis Product Manager 32

Regulatory Management Branch II Antimicrobials Division (7510C)

CONCURRENCES							
SYMBOL 75/DC							
SURNAME) Mitchell				Ì	[·
DATE 11-20-00							
AFFICIAL FUE CODY							

EPA Form 1320-1A (1/90)

Printed on Recycled Paper

☆ GPO : 2000 - 187-381

. . .

{All text in brackets [xxx] is optional and may or may not be included on a final label.} {All text in braces {xxx} is administrative and will not appear on a final label.}

RWP MASTER DICHLORO

{Marketing statements to be used with swimming pool sanitization}

[Ideal for pool start-ups]

[Stabilized Chlorinator]

[Routine Chlorinator]

[For everyday use]

[Granular Chlorinating Concentrate]

{Marketing statements to be used with killing algae in vinyl pools}

[Kills algae in vinyl-lined and colored pools]

[Algaecide]

[For Vinyl, Colored Plaster and Fiberglass Pools]

{Marketing statements to be used with vinyl pool shock}

[Destroys swimmer wastes]

[Restores water clarity]

[Best for vinyl-lined and colored pools]

[Do not mix with other products]

[Fast dissolving shock treatment]

[Destroys swimmer contaminants]

[Kills Bacteria & Algae]

[For Vinyl, Colored Plaster and Fiberglass Pools]

[No pre-dissolving]

{Marketing statements to be used with winter pool shock}

[Winter shock treatment]

[Fast dissolving shock treatment]

[Makes spring start up easier]

{Marketing statements to be used with spa sanitizer}

[For Spas & Hot Tubs]

[Stabilized Chlorinator]

[Routine Chlorinator]

[For everyday use]

[Granular Chlorinating Concentrate]

[Destroys Contaminants]

[Kills Bacteria]

with COLL in EPA Letter 2.1 NOV 2 0 2000

.to. 67262-16

{Optional marketing statements that may be used with spa and hot tub shock treatment.}

[Shock Treatment for Spas]

[For Spas & Hot Tubs]

[Spa Treatment]

[Destroys Algae]

[Destroys Bacteria]

[Destroys Algae and Bacteria]

[Fast Dissolving]

[For Crystal Clear Spa Water]

[For Crystal Clear Water]

[For Sparkling Water]

[For Sparkling, Clear Water]

[Oxidizes Chloramines]

[Oxidizes Undesirable Compounds]

[Destroys undesirable compounds]

[Destroys contaminants]

ACCEPTED with COMMENTS NOV 20 2000

Un per die Federal Insecticide. Rungicide, and Rocenticide Act as

_erea una.

rended, for the posteride to 67262-76

ACTIVE INGREDIENT:

Sodium dichloro-s-triazinetrione 97.0%
OTHER INGREDIENTS 3.0%
TOTAL INGREDIENTS 100.0%

(Available Chlorine: 62%)

KEEP OUT OF REACH OF CHILDREN DANGER

See [back] [side] panel for additional precautionary statements.

FIRST AID: IF IN EYES: Hold eye open and rinse slowly and gently with water for 15 – 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 minutes. Call a poison control center or doctor for treatment advice. IF INHALED: Remove person to fresh air. If not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for treatment advice. IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. IN CASE OF MEDICAL EMERGENCY, CALL 1-877-800-5553. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

MANUFACTURED FOR: RECREATIONAL WATER PRODUCTS SCOTTDALE, GEORGIA

EPA REG. #67262-16 EPA EST. #5185-GA-1

NET CONTENTS:

ACCEPTED with COMMENTS in EPA Letter Dated:

Under the Federal Insecticide,
Fingicide, and Rodenticide Act as
emended, for the pesticide,
and the federal Insecticide,
and federal Insectici

POOL SANITIZATION

WHY TO USE THIS PRODUCT: This product is a quick dissolving stabilized granular swimming pool sanitizer, which when applied according to label directions, will release sufficient chlorine to retard the growth of harmful algae and micro-organisms. This product's quick dissolve characteristics not only make it appropriate for all pool types, but won't leave behind the grit and haze other granular products can. Unlike calcium hypochlorite or liquid chlorine (bleach), this products stabilized formula protects against sun light burn off, making it an efficient type of granular sanitizer for pools.

IMPORTANT NOTES

- 1. When using other products, as outlined in directions for this product, always follow label directions for those products.
- 2. Damage may be caused by direct contact of this product with pool surface or materials such as colored plaster, vinyl, wood or fiberglass.
- 3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a stain & scale inhibitor prior to the addition of this product.
- 4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

BEFORE YOU BEGIN

- 1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
- 2. Adjust stabilizer levels to 40-50 ppm by adding [Chlorine Stabilizer] [Stabilizer].
- 3. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 7.6 by adding [pH Down] [pH Decreaser] to lower pH, or by adding [pH Up] [pH Add] to raise pH. Adjust alkalinity to 80 125 ppm for plaster pools, 125 150 for vinyl or fiberglass pools by adding [Alkalinity Increaser] [Alkalinity Plus]. Adjust calcium hardness to 200 275 ppm for plaster pools, 175 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000

NOW USE THIS PRODUCT:

START-UP/INITIAL TREATMENT:

- 1. With pump running and pool not in use, use a clean, dry, empty plastic scoop to broadcast 4 ounces of this product per 10,000 gallons of water directly into the deep end of the pool.
- 2. After two hours, test chorine level (residual). Repeat treatments until you obtain a chlorine level of 1-3 ppm.
- 3. Add an algae preventative to keep your pool free of algae growth.

ROUTINE MAINTENANCE:

- 1. Check the chlorine level of your pool frequently with a test kit or test strips. Add this product as needed to maintain a chlorine level of 1-3 ppm. You may need to test and add product as often as each day.
- 2. With pump running and pool not in use, use a clean, dry, empty plastic scoop to broadcast 2-3 ounces of this product per 10,000 gallons of water directly into the deep end of the pool.

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000

Under the Federal Insecticide,
Puncicide, and Rodenticide Act as
amended, for the pesticide,
registered under PPR Rog. No. 67262-16

FOR KILLING ALGAE IN VINYL POOLS

WHY TO USE THIS PRODUCT: This product is an easy and potent way to destroy black algae and green free floating algae in vinyl, colored plaster or fiberglass pools. This products quick-dissolving granular form makes it ideal for treating most algae types and is appropriate for most pool surfaces under normal conditions. For treatment of mustard or yellow colored algae, use [Mustard Algae Killer] [a mustard algae killer] [or] [Algaecide Plus] [Algicide Plus].

IMPORTANT NOTES:

- 1. When using other products, as outlined in directions for this product, always follow label directions for those products.
- 2. Damage may be caused by direct contact of this product with pool surface or materials such as colored plaster, vinyl, wood or fiberglass.
- 3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a stain & scale inhibitor prior to the addition of this product.
- 4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

BEFORE YOU BEGIN

- 1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
- 2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 7.6 by adding [pH Down] [pH Decreaser] to lower pH, or by adding [pH Up] [pH Add] to raise pH. Adjust alkalinity to 80 125 ppm for plaster pools, 125 150 for vinyl or fiberglass pools by adding [Alkalinity Increaser] [Alkalinity Plus]. Adjust calcium hardness to 200 275 ppm for plaster pools, 175 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.
- 3. Shut pump off, vigorously brush any visible algae spots and wait 4 hours before proceeding to the next step.

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000

Under the Federal Insecticide, Pungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 67262-16

NOW USE THIS PRODUCT:

- 1. For heavy to medium algae growth use 2 pounds per 10,000 gallons of water. For light algae growth use one pound per 10,000 gallons of water. At night or when pool is not in use, broadcast this product directly into the water in the deep end of the pool. To prevent damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool.
- 2. After treatment, wait 12 24 hours, then turn pump on and remove deal algae from pool surfaces with a brush, and vacuum dead algae through filter. Brush any remaining algae and backwash filter.
- 3. If living algae is still visible, repeat procedure.

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000

Under the Federal Insecticide, Functicide, and Rodenticide Act as amended, for the pesticide, act are referred under EPA Reg. No. 67262-16

VINYL POOL SHOCK

WHY TO USE THIS PRODUCT: This product contains a completely soluble active ingredient to destroy non-filterable swimmer wastes in vinyl-lined, colored plaster or fiberglass pools. When used as directed, this product restores water clarity, kills germs, helps kill algae, and destroys unpleasant odors. For white plaster pools, use [All-Purpose Shock] [Shock Treatment] [or] [Shock] [or] [Chlorinating Granules Plus], and to shock your pool and swim in 15 minutes, use [Non-Chlorine Quick-Swim Shock] [Shock & Swim] [or] [Shock Plus].

IMPORTANT NOTES:

- 1. When using other products, as outlined in directions for this product, always follow label directions for those products.
- 2. Damage may be caused by direct contact of this product with pool surfaces or materials such as colored plaster, vinyl, wood or fiberglass.
- 3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a stain & scale inhibitor prior to the addition of this product.
- 4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

BEFORE YOU BEGIN:

- 1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
- 2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 7.6 by adding [pH Down] [pH Decreaser] to lower pH, or by adding [pH Up] [pH Add] to raise pH. Adjust alkalinity to 80 125 ppm for plaster pools, 125 150 for vinyl or fiberglass pools by adding [Alkalinity Increaser] [Alkalinity Plus]. Adjust calcium hardness to 200 275 ppm for plaster pools, 175 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.

ACCEPTED with COMMENTS in EPA Letter Dated

Under the Federal Insecticide,
Plingicide, and Rodenticide Act as
amended, for the perticide,
registered under EPA Reg. No. 67262-16

NOW USE THIS PRODUCT:

For Start-Up Initial Shocking:

- 1. With pump running and pool not in use, broadcast [1 pound of this product per 10,000 gallons] {or with a 10 ounce bag of product} [one bag of this product per 6,000 gallons] {or with a 12 ounce bag of product} [one bag of this product per 7,500 gallons] of water directly into the pool in the deep end of the pool. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool.
- 2. Repeat procedure after 24 hours, if needed, to establish a chlorine residual of 1-3 ppm as determined by a test kit.

For Routine Shocking:

1. Every week with pump running and pool not in use, broadcast [1 pound of this product per 10,000 gallons] for with a 10 ounce bag of product] [one bag of this product per 6,000 gallons] for with a 12 ounce bag of product] [one bag of this product per 7,500 gallons] of water directly into the pool in the deep end of the pool. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
NOV 2 0 2000

Under the Federal Insecticide.

Pungicide, and Rodenticide Fot as amended, for the postcio:
registered under EPA Reg. No. 67262-16

WINTER POOL SHOCK

WHY TO USE THIS PRODUCT: To avoid costly spring problems (algae, stains, cloudy water, high chlorine demand) properly prepare your pool for the winter using this product. This product oxidizes organic wastes, provides long lasting chlorine protection, helps keep pool surfaces clean, and helps protect water during the off season months.

IMPORTANT NOTES

- 1. When using other products, as outlined in directions for this product, always follow label directions for those products.
- 2. This product may cause damage to pool finish or materials such as colored plaster, vinyl, wood or fiberglass pool surfaces. Avoid spilling granules on pool surface.
- 3. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a stain & scale inhibitor prior to the addition of this product.
- 4. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and micro-organisms, superchlorinate pool every 2-4 weeks.

BEFORE YOU BEGIN

- 1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions.
- 2. Adjust stabilizer levels to 40-50 ppm by adding [Chlorine Stabilizer] [Stabilizer].
- 3. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 7.6 by adding [pH Down] [pH Decreaser] to lower pH, or by adding [pH Up] [pH Add] to raise pH. Adjust alkalinity to 80 125 ppm for plaster pools, 125 150 for vinyl or fiberglass pools by adding [Alkalinity Increaser] [Alkalinity Plus]. Adjust calcium hardness to 200 275 ppm for plaster pools, 175 225 for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

NOW USE THIS PRODUCT:

- 1. Use one pound of this product per 10,000 gallons of water. Broadcast this product directly into water in the deep end of the pool.
- 2. Circulate water for several hours, then add algicide.
- 3. Cut off pump. Drain equipment or add antifreeze to equipment to prevent freeze damage.
- 4. Install pool cover. A second treatment of this product in mesh covered or non-covered pools may be required prior to water freezing.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
NOV 2 0 2000

SPA SANITIZATION

WHY TO USE THIS PRODUCT: This product is a quick dissolving stabilized granular spa sanitizer, which when applied according to label directions, will release sufficient chlorine to retard the growth of harmful algae and micro-organisms.

IMPORTANT NOTES

- 1. When using other products, as outlined in directions for this product, always follow label directions for those products.
- 2. This product may cause damage to spa or hot tub finish or materials such as colored plaster, vinyl, wood or fiberglass surfaces. Avoid spilling granules on spa surface.
- 3. This product may promote metal stains on spa or hot tub surfaces. Always check water for metal content and if present, remove metals with a stain & scale inhibitor prior to the addition of this product.
- 4. Sunlight, rainfall, temperature, number of swimmers and frequency of spa and hot tub use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly.

BEFORE YOU BEGIN

- 1. Ensure all spa equipment is working properly. Backwash filter following manufacturer's directions.
- 2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 7.6 by adding [pH Down] [pH Decreaser] to lower pH, or by adding [pH Up] [pH Add] to raise pH. Adjust alkalinity to 80 125 ppm for plaster spas, 125 150 for vinyl or fiberglass spas by adding [Alkalinity Increaser] [Alkalinity Plus]. Adjust calcium hardness to 200 275 ppm for plaster spas, 175 225 for vinyl or fiberglass spas by adding Calcium Hardness Increaser.

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

.....

NOW USE THIS PRODUCT:

FOR ROUTINE MAINTENANCE DOSES:

- 1. With pump on, add 1/2 teaspoon of this product per 100 gallons of water (or 5 teaspoons per 1,000 gallons) as an initial treatment.
- 2. Repeat at 15 to 20 minute intervals until a residual of 3-5 ppm of available chlorine is established as determined by test kit.
- 3. A test kit must be used regularly to determine the frequency of additional doses of this product needed to maintain 3-5 ppm of available chlorine in the water.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
NOV 2 0 2000

[SUPERCHLORINATION OR SHOCK TREATMENT] [SUPERCHLORINATION] [SHOCK TREATMENT]

[Superchlorinate] [or] [shock] weekly as part of your routine maintenance program, or more frequently following heavy spa use. Make sure recirculating pump is operating. Use one teaspoon of this product per 100 gallons of water (or $\frac{1}{2}$ cup per 1,000 gallons) by broadcasting across water surface. Allow circulating pump to operate for 15-20 minutes. Do not enter spa until chlorine level is between 3-5 ppm.

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000

 $= \pi_{k,\,k}$

{Directions to be used for spa and hot tub shock treatment.}

SHOCK TREATMENT FOR SPAS AND HOT TUBS

WHY TO USE THIS PRODUCT: This product is a fast-dissolving, granular product used for periodic shocking to eliminate the organic compounds in a spa or hot tub which cause odors and cloudy water. This product will raise residual chlorine levels but is not intended for use as a routine sanitizer.

IMPORTANT NOTES:

- 1. When using other products, as outlined in directions for this product, always follow label directions for those products.
- 2. Damage may be caused by direct contact of this product with spa surface or materials such as colored plaster, vinyl, wood or fiberglass.
- 3. This product may promote metal stains on spa surfaces. Always check water for metal content and if present, treat with a stain & scale inhibitor prior to the addition of this product.
- 4. Sunlight, rainfall, temperature, number of bathers and frequency of spa use affect the rate of sanitizer loss. Adjust cleaning and chemical maintenance accordingly. Use this product to shock weekly or more often as needed.

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

BEFORE YOU BEGIN:

- 1. Ensure all spa equipment is working properly. Backwash filter following manufacturer's directions.
- 2. Adjust stabilizer levels to a minimum of 40-50 ppm in outdoor spas by adding stabilizer.
- Check water alkalinity, pH and calcium hardness with a test kit. Adjust alkalinity to 80-125 ppm for plaster spas, 125-150 for other types of spas by adding an alkalinity increaser. Adjust pH to 7.2 7.6 by adding a pH decreaser to lower pH, or by adding a pH increaser to raise pH. Adjust calcium hardness to 200-275 ppm for plaster spas, 175-225 for other types of spas by adding a calcium hardness increaser.
- 4. Ensure chlorine level is between 3-5 ppm before using this product.

NOW USE THIS PRODUCT:

- 1. Make sure recirculating pump is operating. Use one teaspoon of this product per 100 gallons of water (or ¼ cup per 1,000 gallons) by broadcasting across water surface.
- 2. Allow circulating pump to operate for 15-20 minutes.
- 3. Use this product weekly as part of your routine maintenance program, or more frequently following heavy spa use.
- 4. Do not enter spa until chlorine level is between 3-5 ppm.

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000

{The following statement is for use on products with swimming pool use directions. }
[Reentry into treated swimming pools is prohibited above levels of 3 ppm chlorine due to risk of body injury.]

{The following statement is for use on products with spa use directions. }
[Reentry into treated spas is prohibited above levels of 5 ppm chlorine due to risk of body injury.]

STORAGE AND DISPOSAL Keep this product dry in original tightly closed container when not in use. Store in a cool, dry, well ventilated area away from heat or open flame. Moisture may decompose this product and cause a violent reaction leading to fire and explosion. In case of decomposition, isolate container if possible and flood area with large amounts of water to dissolve all material before discarding this container. Do not contaminate food or feed by storage or disposal. CONTAINER DISPOSAL: Do not reuse container, but place in trash collection. Rinse thoroughly before discarding in trash.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER: Corrosive: Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or on clothing. Do not breathe dust or fumes. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

PHYSICAL OR CHEMICAL HAZARDS STRONG OXIDIZING AGENT: Do not mix with other chemicals. Mix only with water. Never add water to product. Always add product to large quantities of water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals will start a chemical reaction and generate heat, hazardous gas, possible fire and explosion. In case of contamination or decomposition, do not reseal container. If possible, isolate container in open air or well ventilated area. Flood area with large volumes of water.

ACCEPTED with COMMENTS in EPA Letter Deted:
NOV 2 0 2000

{Environmental hazards statement for end-use products in containers of less than 50 pounds (solid, dry weight).}

[ENVIRONMENTAL HAZARDS This pesticide is toxic to fish and aquatic organisms.]

{Environmental hazards statement for end-use products in containers of equal to or greater than 50 pounds (solid, dry weight).}

[ENVIRONMENTAL HAZARDS This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.]

NOTE: Buyer assumes all responsibility for safety and use not in accordance with directions.

{The following is optional text to be used at Recreational Water Products' discretion with swimming pool use directions. This information is non-essential and will be provided only as a courtesy. Will not appear on all swimming pool products.}

HOW TO CALCULATE POOL CAPACITY

Shape of Pool

Gallons of water

Rectangular

Average depth x average length x average width x 7.5

Circular

Diameter x diameter x average depth x 5.9

Oval

Full width x full length x average depth x 6.7

Irregular

Consult pool builder

{The following is optional text to be used at Recreational Water Products' discretion. This information is non-essential and will be provided only as a courtesy. Will not appear on all labels.}

[NOTE: Any questions or comments about Aqua Chem Products? In the continental U.S. call 1-800-252-POOL (7665). Ask for your free pool care booklet.]

[Questions or comments, Call 1-800-252-POOL (7665).]

ACCEPTED with COMMENTS in EPA Letter Dated: NOV 2 0 2000