

REVISED LABEL

(Panel #1)

Ethylene Fluid® PATENT PENDING

ONLY FOR USE WITH PRECISION GENERATORS TO PRODUCE ETHYLENE GAS TO ACCELERATE RIPENING OF:

- | | | |
|----------|---------|----------|
| Avocados | | Pears |
| Bananas | Melons | Tomatoes |
| Citrus | Papayas | Tobacco |

ACTIVE INGREDIENT

Ethanol.....95%
 Inert Ingredients.....5%

TOTAL.....100%

KEEP OUT OF THE REACH OF CHILDREN

"DANGER - POISON"



NOT TO BE TAKEN INTERNALLY

(SEE SIDE PANEL FOR PRECAUTIONARY STATEMENTS AND STATEMENT OF PRACTICAL TREATMENT.)

MFG. BY: PRECISION GENERATORS CO., INC.

907 Washington Ferry Road - Prattville, Al. 36067

(205)365-3844

Est. No. 67346-AL001

E.P.A. Reg. No. 67346-1

Net Contents - 64 Ounces

One - Half (1/2) US Gallon

(Panel #3)

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE - Store in dry, locked storage area, at temperatures below 125F. Keep container closed. Use adequate ventilation.

PESTICIDE DISPOSAL - Mix with compatible chemical which is less flammable and incinerate. Comply with all federal, state, and local codes pertaining to the disposal of flammable liquids.

CONTAINER DISPOSAL - (Triple rinse or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

AVOCADOS, BANANAS, CITRUS, MELONS, PAPAYAS, PEARS, TOMATOES. Use in a Precision Generator the first 24 hours of ripening period. One Quart used as directed in a 4000 to 8,000 cu. ft. ripening room produces ethylene concentrations varying from 20 to 1200 P.P.M. over a period of 16 hours. One pint used as directed in 1,000 to 4,000 cu.ft. ripening room produces ethylene concentrations varying from 20 to 600 P.P.M. over a period of 8 hours. Do not use concentrations of ethylene above 5 ppm on citrus or burning may result.

TOBACCO (FLUE-CURED) Use Two (2) quarts in a Precision Generator immediately after filling a 1,500 to 2,500 Cubic Foot curing barn over a period of 12 hours. Use additional 2 quarts of ETHYLENE FLUID® as required.

(Panel #4)

USE PRECAUTIONS

Use of this product in enclosures less than 1,000 cubic feet is prohibited. The treated room should be reasonably airtight, all vents and doors closed, cracks or holes in walls and doors should be repaired or covered over. No workers are permitted in the treatment room during treatment.

WARRANTY

Seller's liability for breach of warranty, expressed or implied, in connection with the sale or lease of this product shall be limited to repairs or replacement at seller's expense of the defective product, and in no case shall seller be liable for incidental or consequential damages.

NOTICE

Use of any other product than ETHYLENE FLUID® may damage the PRECISION GENERATOR. Also use of other products in the generator may produce harmful by-products.

(Panel #2)

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER - Not to be taken internally. Do not get in eyes or on skin. Harmful if inhaled. Avoid breathing vapors.

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush with plenty of water for at least 15 minutes. Get medical attention immediately.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if symptoms occur.

IF INHALED: Move victim to fresh air. Treat symptomatically. Get medical attention if symptoms persist.

IF SWALLOWED: Induce vomiting by touching the back of the throat with finger or blunt object. Seek medical advice.

PHYSICAL OR CHEMICAL HAZARDS.

Extremely flammable. Keep away from fire, sparks, and heated surfaces. Exposure to temperatures above 130 degrees Fahrenheit may cause bursting.

PRINTED IN RED

