

PM 33

67471-5
U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (TS-767)
WASHINGTON, DC 20460

EPA REGISTRATION NO. 67471-5	DATE OF ISSUANCE OCT 16 1987
TERM OF ISSUANCE	
NAME OF PESTICIDE PRODUCT Pacific Sailor Vinco 65 Antifouling Paint	

10/16/87
1/4

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION
(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Walker Brothers
Division of Consolidated Coatings
1101 West 10th Street
P.O. Box 66036
Vancouver, WA 98666

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Add the phrase, "EPA Registration No.67471-5" to your label before you release the product for shipment.
3. Submit five (5) copies of labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.


If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL M. Swindell PM 33/RMB/AD	DATE
---	------

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshali Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobial Division (7510W)

Enclosures

Pacific Sailor

Quality Marine Finishes

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes eye irritation. Avoid contact with skin, eye, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor, or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator (only approved by the Mining Safety and Health Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

If swallowed do not induce vomiting, keep warm, apply artificial respiration if necessary. Never give anything by mouth to unconscious person. Get medical attention.
 IF IN EYES: Flush with water for 15 minutes. Get medical attention.
 IF ON SKIN: Wash with soap and water. Get medical attention.
 IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration. Get medical attention.

ENVIRONMENTAL HAZARDS

The pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of waste. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, and other waters unless in accordance with requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewer treatment plant authority. For guidance contact your "State Water Board or Regional Office of the EPA".

STORAGE AND DISPOSAL

Do not contaminate water, food, feed, by storage or disposal. Open dumping is prohibited.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved state and local procedure. If burned stay out of smoke.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

Vinco 65 Antifouling Black

ACTIVE INGREDIENT

Cuprous oxide 65.0 %

INERT INGREDIENTS 35.0 %

ELEMENTAL COPPER 57.7 %

E.P.A. Reg. 67471-

E.P.A. Est. 67471-

WARNING
KEEP OUT OF REACH OF CHILDREN

See Side Panel for additional precautionary statements.

ONE GALLON

3.78 LITRES

CONSOLIDATED



COATINGS

b/e

ACCEPTED
with COMMENTS
in EPA Letter Dated:

OCT 16 1997

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
amended, for the pesticide,
registered under EPA Reg. No.

67471-5

Pacific Sailor

Quality Marine Finishes



DISCLAIMER

The performance of any marine paint or coating depends on many factors outside the control of Consolidated Coatings Corporation including surface preparation, proper application, and environmental conditions. Therefore Consolidated Coatings Corporation cannot guarantee this product's suitability for your particular purpose or application.

IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. CONSOLIDATED COATINGS CORPORATION SHALL NOT, UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Consolidated Coatings Corporation option.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Vinco 65 ANTI FOULING is used as a protective coating resistant to the growth of algae, barnacles and other marine fouling on hulls. For surface preparation and application see back panel.

GENERAL DESCRIPTION

Vinco 65 Antifouling is a supreme quality copper based antifouling paint using an advanced vinyl copolymer resin system. It is designed to be used directly or over primer on wood, steel, or fiberglass hulls to reduce marine growth.

SURFACE PREPARATION AND APPLICATION

WOOD HULLS: NEW WORK - Sand smooth, make sure all seams are properly caulked. All exposed metal should be coated with 64-0001 Swiftsure Silver Anticorrosive and allow 4 hrs. to dry. Apply a coat of Antifouling thinned 10%-15% with 85-0313 Antifouling Reducer allowing 4 hrs. to dry. Apply 2 more coats of full strength allowing 4 hrs. drying between coats.

WOOD HULLS: REPAINT - Remove by sanding or scraping all loose or powdery material. All exposed metal should be coated with 64-0001 Swiftsure Silver Anticorrosive. Apply 2 coats of Antifouling allowing 4 hrs. drying between coats.

STEEL HULLS: NEW WORK - Scrape or blast to remove rust scale, apply 1 thin coat of 50-1619/20 Wash Primer, allow 1 hr. to dry. Apply 1 coat of

64-0001 Swiftsure Silver Anticorrosive and allow 4 hrs. to dry. Apply 2 coats of Antifouling allowing 4 hrs. drying between coats.

FIBERGLASS: NEW WORK - Wash hull with 85-0313 Antifouling Reducer then sand to remove gloss and any traces of paring wax. Apply the Antifouling directly to the sanded hull. If a smoother finish is desired first apply a coat of 60-1013/14 High Build Epoxy Primer prior to the Antifouling.

FIBERGLASS: RECOAT - Remove loose material by scraping and sanding. If using it's point over a different or unknown antifouling apply some coating to a small area and let dry. Check this area to determine that the adhesion is adequate and no incompatibility is apparent prior to proceeding.

CLEAN - UP - Use 85-0313 Antifouling Reducer for cleaning of brushes and rollers.

LAUNCHING - Prolonged exposure to air affects the performance of Copper based Antifouling. Launch as soon as possible for best results.

WARNING - DO NOT USE ON ALUMINIUM HULLS, OUTBOARDS, OR ANY OTHER ALUMINIUM AS DAMAGE FROM ELECTROLYSIS MAY RESULT

CONSOLIDATED COATINGS

7881 Versage Way, Tibbury Industrial Park, Delta, B.C. V4G 1A8 (504) 945-7828

CONSOLIDATED



COATINGS

4/4