

67543-7

8-1-2000

1/7



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

AUG 01 2000

OFFICE OF  
PREVENTION, PESTICIDES  
AND TOXIC SUBSTANCES

International Paint, Inc.  
2270 Morris Avenue  
Union, NJ 07083

Attention: John P. Pazdera

Subject: Super KL  
EPA Registration Number 67543-7  
Your Submission Dated July 12<sup>th</sup>, 2000  
EPA Received Date July 17<sup>th</sup>, 2000


The notification referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to revise the product labeling as per the Label Improvement Program for Antifouling Paints to add the following phrases, is acceptable:

- The phrase "while spraying and/or sanding boat surfaces" to the Pre-cautionary Statements section which states "Wear a mask or respirator..."
- The phrase "Copper as Metallic: 61.6% just below the ingredients statement on the front panel.
- The phrase "against barnacles, algae, and hydroids..." and "salt or fresh water areas ..." to the product description section above the "Directions for Use" section.

Your notification has been made a part of the permanent records for this file.

If you have any questions concerning this letter, please contact Karen M. Leavy- Munk at (703)-308-6237.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobial Division(7505C)



United States  
**Environmental Protection Agency**  
 Washington, DC 20460

Registration  
 Amendment  
 Other

OPP Identifier Number  
 256075

**Application for Pesticide - Section I**

1. Company/Product Number 67543-7	2. EPA Product Manager M. Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Super KL	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) International Paint Inc. 2270 Morris Avenue Union, NJ 07083  <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

**Section - II**

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

**Explanation:** Use additional page(s) if necessary. (For section I and Section II.)

**Notification:** Minor Labeling Changes: Add Product Descriptors, update per Label Improvement Program for Antifouling Paints

**Section - III**

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
<i>Certification must be submitted</i>	If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt.	<input type="checkbox"/> Glass	<input type="checkbox"/> Paper
				<input type="checkbox"/> Other (Specify) _____	
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

**Section - IV**

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Reg. Manager	Telephone No. (Include Area Code) 908-964-2288
<b>Certification</b> I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>John P. Pazdera</i>	3. Title Pesticide Registration Manager	
4. Typed Name John P. Pazdera	5. Date 7/12/2000	

Super KL

KL-990 Anti-Fouling Coating

Red K90

Use on wood, fiberglass and steel hulls

"Premium Protection without the premium price!"

**KEEP OUT OF REACH OF CHILDREN**

**WARNING**

See back panel for additional Precautionary Statements

ONE U.S. GALLON 3.79 LITERS

ACTIVE INGREDIENT

Cuprous Oxide 70.2%

INERT INGREDIENTS 29.8%

Total 100.0%

Copper as Metallic: 61.6%

CONTAINS PETROLEUM DISTILLATES

EPA Registration No.: 67543-7

EPA Establishment No.: 23566-NJ-1

**Super KL**

Super KL is a premium anti-fouling coating that provides effective protection against barnacles, algae and hydroids for boats that are used in high fouling salt or fresh water areas, or which remain in the water for prolonged periods between haul outs. It forms a smooth surface and can be applied over most hard and soft bottom paints.

**Directions for Use**

**It is a violation of federal law to use or dispose of this product in a manner inconsistent with its labeling.**

**New Fiberglass – No Sanding:** Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants off the surface with clean rags.

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

Apply one thin coat of 179 No Sanding Primer, allowing to dry a minimum of one hour and a maximum of four hours, then apply two coats of Super KL by brush, roller or spray.

**New Fiberglass – Epoxy Barrier Coat:** Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants off the surface with clean rags.

Abrade with 80 grit sandpaper, then seal with two coats of B370 Two-part Epoxy Primer. Sand between coats and before applying the anti-fouling coating to improve adhesion. Apply two coats of Super KL by brush, roller or spray.

**New Wood:** Sand with 80 grit sandpaper, clean thoroughly and apply two coats of Super KL by brush, roller or spray.

**Metal:** Super KL contains cuprous oxide and is not recommended for aluminum surfaces.

Iron and steel should be cleaned to bright metal and then sealed with two coats of an anticorrosive primer such as B274 Red Lead Epoxy. Apply two coats of Super KL by brush, roller or spray.

**Previously Coated Surfaces:** Super KL can be applied over most other hard and soft bottom paints so long as they are clean and in good condition. Coatings that are cracked, damaged or peeling should be completely removed before painting.

**Application Information**

Mix thoroughly. Allow to dry at least overnight between coats and before launching. For best results apply at least two coats. Apply by spray, short-nap roller or brush. Use mineral spirits for thinning and cleaning equipment. Recommended application temperature range is 65°F - 80°F. Expected coverage is 350-400 square feet per gallon.

**Maintenance**

Physical damage, fuel spills and pollution can reduce the effectiveness of anti-fouling coatings. Therefore, it is recommended that the bottom be inspected periodically. If necessary, clean with a soft towel. Never use a stiff brush, scrub pad or abrasives.

**Storage and Disposal**

Do not contaminate water, food or feed by storage and disposal. Store anti-fouling coatings in their original tightly-sealed containers.

