PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Corrosive. Causes irreversible eye damage. Harmful if swallowed or absorbed through skin or Inhaled. Do not get in eyes or on clothing. Avoid contact with skin. Avoid breathing spray mist. Wear googles or face shield. Wash thoroughly with scap and water after handling. Remove contaminated clothing and wash clothing before reuse.

ENVIRONMENTAL HAZARDS
Do not discharge effluent containing this product into lakes, streems, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination Systems (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional

STORAGE AND DISPOSAL Do not contaminate water, 100d or feed by storage or disposal.

STORAGE: Store unused product in original container only in a cool, dry area out of the reach of children or animals.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed

of at an approved waste disposed facility.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and then dispose of in a santary landfill or by other approved Federal, State and local procedures.

EPA REG NO. 67673-1

EPA EST. NO. 067673-WG-001

AlliedSignal

Product-Code:

-,1

MERGAL® S 89R Paste

Industrial Microbioode for Use in Paints, Coatings, Plasters, Stuccos, Sealants, Caulks, and Fillers

ACTIVE INGREDIENT 3-(3.4-dichlorophenyl)-1.1-dimethyl urea 19.00% methyl (1H-benzimidazol-2-yl) carbamate 9.90% INERT INGREDIENTS 71.10%

[MERGAL* S 89R Pasta weighs 9 3 lbs /gallon]

KEEP OUT OF REACH OF CHILDREN DANGER - PELIGRO

PRECAUCION AL USUARIO: Si Vd. no lee inglés no use este producto hasta que la etiqueta haya sido explicado completemente.

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES. Keep eyelids open and flush with a gentle steady stream of water for 15 minutes. Get medical attention.

Get medical attention.

If SWALLOWED: Call a physician or poison control center. Drink promptly a targe quantity of milk, egg white or getatin mixture, or if these are not available, a large quantity of water Avoid alcohol. Do not induce vomiting. Do not give anything by mouth to an unconscious person. If ON SKIN, Wash thoroughly with soap and water. Get medical attention, if INHALED. Bemove victim to fresh air 11 not breathing, give artificial respiration, preferably

mouth-to-mouth. Get medical attention

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. See Side Panel for Additional Precautionary Statements.

AffiedSignal Inc., 101 Columbia Tpk., Morristown, NJ 07962 Emergency phone. 1-800-424-9300 and 201-455-2000 Manufactured by Riedel-de Haen AG, D-30926 Seelze, Germany

DIRECTIONS FOR USE It is a violation of Federal Law to use this product in a manner inconsistent with its

labeling.
MCRCAL* S SSR Paste is an entimicrobial preservative for control of fungl and algae

MERCAL* S SSR Paete is an entimicrobial preservative for control of fungl and algae growing on paints, coatings, plasters, sealants, and filters used for architectural products, finishes, and special purpose coatings which are exposed to warm, motst, and humid conditions favoring microbial growth.

Typically MERCAL* S SSR Paets should be added at the beginning of the formulation process while mixing of the final product (paint, plaster, etc.) to assure uniform distribution of the MERCAL* S SSR Paets.

PAINTS AND COATING MATERIALS (0.2 – 2.0%): Add 2 – 20 lbs. (0.9 – 9.0 kg) of MERCAL* S SSR Paete to each 1000 lbs. (453 kg) of peint. Use higher addition rate within the above tisted and registered range in warm, moist, and humid conditions where microbial growth is favored.

PLASTERS AND STUCCOS (0.1 – 1.0%): Add 1 – 10 lbs. (0.45 – 4.5 kg) of MERCAL* S SSR Paete to each 1000 lbs. (453 kg) of plasters. Use higher addition rate within the above listed and registered range in warm, moist, and humid conditions where microbial growth is favored.

microbial growth is fevored.

SEALANTS, CAULKS AND FILLERS (0.1 - 1.5%); Add 1 - 15 lbs. (0.45 - 6.8 kg) of MERGAL* S 89R Parts to each 1000 lbs. (453 kg) of sealant or filler. Use higher addition rate within the above listed and registered range in warm, moist, and humid conditions where microbial growth is favored.

WARRANTY STATEMENT
This label provides information which Seller believes to be reliable based on Seller's present state of knowledge relating to this product and its application. This information is not intended to be a quarantee of specific properties of this product or its suitability for a particular application, Seller warrants that this product conforms to the chemical description on this label. SELLER MAKES NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR ANY OTHER WARRANTY EXCEPT AS EXPRESSLY STATED ABOVE. In no event shall seller be liable for any consequential, special, indirect, or incidental damages relating to the use of this product.

Net weight:

Lot:

Storage temperature: 32 – 104° F (0 – 40° C)

