

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER: Keep out of reach of children. Flammable liquid and vapor. Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get into eyes, on skin or on clothing. May be fatal if inhaled. Do not breathe vapor or spray mist. Wear a mask or pesticide respirator (not approved by the Mine Safety and Health Administration and the National Institute of Occupational Safety and Health). Wear protective eyewear (goggles, face shield, or safety glasses), protective clothing and rubber gloves. Wash thoroughly after handling with soap and water, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse.

FIRST AID
IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor.
IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage. Measure against circulatory shock respiratory depression, and convulsion may be needed. Have the product container or label with you when calling a poison control center or doctor.

HOTLINE: FOR EMERGENCY INFORMATION ON N-2001 ANTIMICROBIAL, CALL 1-800-778-5462, MONDAY THROUGH FRIDAY, 9 AM TO 5 PM. AFTER 5 PM CALL YOUR POISON CONTROL CENTER. FOR TRANSPORTATION EMERGENCIES CALL CHEMTREC AT 1-800-424-9300.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL
PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Do not use or store near heat or open flame.
PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If waste cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
CONTAINER DISPOSAL: Metal Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by other approved state or local guidance. Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by incineration or if allowed by state and local authorities, if burned stay out of smoke.

N-2001 ANTIMICROBIAL

**FOR THE CONTROL OF ALGAE,
BACTERIA, FUNGI, AND MOLLUSKS
IN A WIDE RANGE OF COMMERCIAL
AND INDUSTRIAL PROCESSES AND
MATERIAL PRESERVATIONS**

Active Ingredient:	
Dodecylguanidine hydrochloride	35.0%
Inert Ingredients	65.0%
TOTAL	100.0%

DANGER

• KEEP OUT OF REACH OF CHILDREN

EPA Reg. No. 67869-43
EPA Est. No. 10445-PA-01

LOT NO. _____

_____ LB. NET WT. _____ kg

SOLD BY:



VERICHEM

VERICHEM INC.

3499 Grand Avenue
Pittsburgh, PA 15225
412-331-7296



(COMBO)

DIRECTIONS FOR USE
 It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL PROCESSES AND WATER SYSTEMS

AIR WASHING SYSTEMS: For use only in industrial Air Washer Systems that maintain effective mist eliminating components. Badly fouled systems must be cleaned before treatment is begun.

SLUG OR INTERMITTENT METHOD: Initial dose: When system is noticeably fouled, apply 6.6 to 13.2 oz/1000 gal (50 to 100 ppm). Repeat until control is achieved. Subsequent dose: When control is evident, apply 3.3 to 6.6 oz/1000 gal. (25-50 ppm) every three days or as needed.

CONTINUOUS METHOD: Initial dose: When system is noticeably fouled, apply 6.6 oz/1000 gal (25-50) per day. Subsequent dose: Maintain initial rate by continuously feeding 3.3 to 6.6 oz/1000 gal. (25-50 ppm) per day.

AUXILIARY AND STANDBY COMMERCIAL AND INDUSTRIAL SYSTEMS: For use only in Auxiliary and Standby Commercial and Industrial Systems that maintain effective mist eliminating components. Badly fouled systems must be cleaned before treatment is begun.

SLUG OR INTERMITTENT METHOD: Initial dose: When system is noticeably fouled, apply 6.6 to 13.2 oz/1000 gal (50 to 100 ppm). Repeat until control is achieved. Subsequent dose: When control is evident, apply 3.3 to 6.6 oz/1000 gal. (25-50 ppm) every three days or as needed.

CONTINUOUS METHOD: Initial dose: When system is noticeably fouled, apply 6.6 oz/1000 gal (25-50) per day. Subsequent dose: Maintain initial rate by continuously feeding 3.3 to 6.6 oz/1000 gal. (25-50 ppm) per day.

BREWERY PASTEURIZER WATER: For use only in Brewery Pasteurizer Water that maintain effective mist eliminating components. Badly fouled systems must be cleaned before treatment is begun.

SLUG OR INTERMITTENT METHOD: Initial dose: When system is noticeably fouled, apply 6.6 to 13.2 oz/1000 gal (50 to 100 ppm). Repeat until control is achieved. Subsequent dose: When control is evident, apply 3.3 to 6.6 oz/1000 gal. (25-50 ppm) every three days or as needed.

CONTINUOUS METHOD: Initial dose: When system is noticeably fouled, apply 6.6 oz/1000 gal (25-50) per day. Subsequent dose: Maintain initial rate by continuously feeding 3.3 to 6.6 oz/1000 gal. (25-50 ppm) per day.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS: For use only in industrial Recirculating Water Cooling Towers that maintain effective mist eliminating components. Badly fouled systems must be cleaned before treatment is begun.

SLUG OR INTERMITTENT METHOD: Initial dose: When system is noticeably fouled, apply 6.6 to 13.2 oz/1000 gal (50 to 100 ppm). Repeat until control is achieved. Subsequent dose: When control is evident, apply 3.3 to 6.6 oz/1000 gal. (25-50 ppm) every three days or as needed.

CONTINUOUS METHOD: Initial dose: When system is noticeably fouled, apply 6.6 oz/1000 gal (25-50) per day. Subsequent dose: Maintain initial rate by continuously feeding 3.3 to 6.6 oz/1000 gal. (25-50 ppm) per day.

PULP AND PAPER MILL SYSTEMS: N2001 Antimicrobial should be added to a paper making system at a point of uniform mixing such as the beaters, broke chest pump, seal-off tank, or white tank. Initial Dose: When the system is noticeably contaminated, add 0.007-0.57 lbs of N2001 Antimicrobial per ton of pulp or paper (dry basis) (1.2 - 100 ppm active) as a slug dose. Repeat until control is achieved. Heavily fouled systems should be bled out prior to initial treatment. Subsequent Dose: When microbial control is evident, add 0.007 - 0.57 lbs of N2001 Antimicrobial per ton of pulp or paper (dry basis) (1.2 - 100 ppm active) as a slug dose as necessary to maintain control.

MATERIAL PRESERVATION

PULP AND PAPER MILL PROCESSING CHEMICALS, ADHESIVES, AND COATINGS: Add N2001 Antimicrobial directly to the material to be preserved prior to manufacturing into the finished product. (i.e., pulp, broke, polymers, adhesives, slurries, emulsions, adhesives, papermill coatings, pigment slurries, and paper products). The dosage rate will depend upon the material to be preserved and the storage time. The usual addition should be 1.3 to 4.0 oz/1000 gal. (10-30 ppm). Under extreme conditions of spoilage, the dosage rate should be increased to 1.7 to 10.8 oz/1000 gal (12.5 to 80 ppm). The dosage rates are based on a maximum storage time of 2 weeks. For storage time greater than 2 weeks the maximum concentration should be increased to 6.6 to 13.2 oz/1000 gal (50 to 100 ppm). Do not use for adhesives or coatings that involve direct or indirect food, or human drinking water contact application.

Dosage Rate Per 1000 Gallons of Material:

Adhesives:	1.3 to 4.0 oz. (10-30 ppm)
Alkalis:	1.3 to 4.0 oz. (10-30 ppm)
Broke:	1.3 to 4.0 oz. (10-30 ppm)
Delaminers:	1.3 to 4.0 oz. (10-30 ppm)

Emulsions:	1.3 to 4.0 oz. (10-30 ppm)
Paper products:	1.3 to 4.0 oz. (10-30 ppm)
Pigment slurries:	1.3 to 4.0 oz. (10-30 ppm)
Pigment slurries:	1.3 to 4.0 oz. (10-30 ppm)
Polymers:	1.3 to 4.0 oz. (10-30 ppm)
Pulp:	1.3 to 4.0 oz. (10-30 ppm)

ADHESIVE SYSTEMS (NON-PAPER): N2001 Antimicrobial is used in the preservation of non paper related aqueous systems. Laboratory testing shows N2001 Antimicrobial to be effective in the range of 0.025 to 0.1% (250 to 1000 ppm). The exact amount for the preservative of any given formulation will depend on the components, storage time, temperature, etc., and can be determined by the actual testing based on formula weight.

Dosage Rate Per 1000 Gallons of Material:

Glues:	2.1 - 8.3 lbs (250-1000 ppm)
Automobile adhesive tapes:	2.1 - 8.3 lbs (250-1000 ppm)

PASTES: N2001 Antimicrobial is used in the preservation of non paper related aqueous systems. Laboratory testing shows N2001 Antimicrobial to be effective in the range of 0.025 to 0.1% (250 to 1000 ppm). The exact amount for the preservative of any given formulation will depend on the components, storage time, temperature, etc., and can be determined by the actual testing based on formula weight.

Dosage Rate Per 1000 Gallons of Material:

Wallpaper:	2.1 - 8.3 lbs (250-1000 ppm)
------------	------------------------------

Wood glue: 2.1 - 8.3 lbs (250-1000 ppm)
 Nonfood packaging adhesives: 2.1 - 8.3 lbs (250-1000 ppm)

PAINTS, COATINGS, AND STAINS: N2001 Antimicrobial is used in the preservation of non paper related aqueous systems. Laboratory testing shows N2001 Antimicrobial to be effective in the range of 0.025 to 0.1% (250 to 1000 ppm). The exact amount for the preservative of any given formulation will depend on the components, storage time, temperature, etc., and can be determined by the actual testing based on formula weight.

Dosage Rate Per 1000 Gallons of Material:

Paints and coatings (between manufacture and use):	2.1 - 8.3 lbs (250-1000 ppm)
Coatings systems (paints and coatings as finished products):	2.1 - 8.3 lbs (250-1000 ppm)

Thermoset coatings and calcium carbonate (precursors to paint and coating products): 2.1 - 8.3 lbs (250-1000 ppm)

PIGMENTS, DYES, AND FILLER SUSPENSIONS: N2001 Antimicrobial is used in the preservation of non paper related aqueous systems. Laboratory testing shows N2001 Antimicrobial to be effective in the range of 0.025 to 0.1% (250 to 1000 ppm). The exact amount for the preservative of any given formulation will depend on the components, storage time, temperature, etc., and can be determined by the actual testing based on formula weight.

FOOD PACKAGING: For paper and paperboard intended for use in contact with food, the rate of application of this product must be adjusted so that the amount of active ingredient (dodecylguanidine hydrochloride) applied does not exceed 0.4 percent by weight of the paper or paperboard. This product is effective in controlling microorganisms, such as bacteria, fungi, and yeasts, which cause deterioration of paper and paperboard products or articles made from paper pulp. It may be added to the pulp stock in the beater or applied to the formed sheet by size press or roll coater, or as a uniform spray. If the product is used as a beater additive, the degree of retention of the active ingredients will depend upon the nature of the other additives in the system. Technical service is available from the manufacturer of the product to assist customers in making the proper and most efficient use of the product.

NOTICE: Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FOR FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.

NOTICE TO BUYER: Buyer assumes all risk of use and handling which are at variance in any way with the directions hereon. There are no questions which extend beyond the description on this label.

ACCEPTED

JAN 19 2006

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under Reg. No. 67869-43

CORROSIVE

8

**8, UN 2924, III
FLAMMABLE LIQUID,
CORROSIVE N.O.S.**

(CONTAINS: ISOPROPANOL AND
DODECYLGUANIDINE
HYDROCHLORIDE)

67869-43

11/19/2006

Page 181