



# Barnacle Ban

# Antifouling Paint

## An Antifouling Boat Bottom Paint

Active Ingredient:	
Cuprous Oxide . . . . .	33.34%
Inert Ingredients: . . . . .	66.66%
TOTAL: . . . . .	100.00%

**ACCEPTED**  
 SEP 8 1995  
 Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 68316-1

KEEP OUT OF REACH OF CHILDREN

**DANGER**

**STATEMENT OF PRACTICAL TREATMENT**

- IF IN EYES:** Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.
- IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.
- IF SWALLOWED:** Call a doctor or get medical attention. Do not induce vomiting. Drink promptly a large quantity of water. Do not give anything by mouth to an unconscious person. Avoid Alcohol.
- IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Registration No. 68316-  
 EPA Establishment No. 68316-PA-001

Net Contents: 1 gallon



# Barnacle Ban Antifouling Paint An Antifouling Boat Bottom Paint

## Directions for Use

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**Where to Use** - Salt and fresh water environments where submerged boat surfaces are subject to fouling by zebra mussels, barnacles, tube worms, and other marine organisms.

**Coverage** - For one coat, apply at 250-300 square feet per gallon. Application of one appropriate primer coat and two top coats are recommended.

**What Tools to Use** - Application with a good quality brush such as china bristle or short nap roller. If sprayer is used, heed the warnings on this label. The operator and other persons in the painting area should be fully suited and have a mask with a clean air supply.

**When to Apply** - Air temperature should be between 50° F and 90° F. Allow a minimum of six hours to dry thoroughly between coats.

**How to Apply** - Read "DANGER" section on this label before opening the can. Mix thoroughly or shake well, and stir occasionally while in use. Thin only if required with lacquer thinner or xylol. Slower drying solvents may be used if required. Test with a small amount first for compatibility and drying performance. Select from among aromatics, ketones or esters.

**Clean Up** - If accidentally spilled, absorb with inert, nonflammable material and place in properly labeled containers for disposal. Brushes, rollers, and equipment can be cleaned with lacquer thinner or xylol.

**Launching Time** - Preferred launch time is 3-7 days with a minimum of one day and a maximum of 50 days.

## Surface Preparation and Use

**Unpainted wood** - Sand to a smooth finish, and wipe clean. For the first coat, thin Barnacle Ban Antifouling Paint with xylol or lacquer thinner about 10% by volume to penetrate the grain of the wood. Finish with two coats of Barnacle Ban Antifouling Paint.

**Unpainted fiberglass** - Clean the entire surface with a cloth soaked with xylol or lacquer thinner to remove the mold wax. Wipe dry with a clean cloth. Apply an appropriate primer and dry thoroughly. Finish with two coats of Barnacle Ban Antifouling Paint.

**Unpainted steel** - Sand blast to a near white metal finish. Remove residue and wipe clean. Immediately apply a thin coat of vinyl butyral prime wash and allow to dry a minimum of 24 hours. Apply four coats of an appropriate primer. Finish with three coats of Barnacle Ban Antifouling Paint.

**Previously Painted Surfaces** - Remove contaminants and clean thoroughly. Sand to remove loose paint and any residue that would interfere with obtaining good adhesion. Wipe clean with cloths wetted with lacquer thinner and wipe dry with a clean cloth. Note: Barnacle Ban Antifouling Paint contains strong solvents that might lift a paint that is not well cured. If there is any doubt, paint a small test strip to verify performance.

**Previously Painted Fiberglass and Wood** - Patch and prime as with unpainted surfaces where required. Finish with two coats of Barnacle Ban Antifouling Paint.

**Previously Painted Steel Surfaces** - On bare spots, follow the procedure for unpainted steel. Where the paint is good, prime with an appropriate marine primer. Finish with two coats of Barnacle Ban Antifouling Paint.

## Hazards to Humans and Domestic Animals DANGER

### Precautionary Statements

Corrosive. Causes irreversible eye damage. Do not get in eyes or on clothing. Wear goggles, face shield, or safety glasses. Remove contaminated clothing and wash before reuse. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or pesticide respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Harmful if absorbed through skin. Avoid contact with skin.

### Environmental Hazards

This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

### Physical Hazards

FLAMMABLE: Keep away from heat and open flame.

READ THE MATERIAL SAFETY DATA SHEET BEFORE USING

## Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal. **Pesticide Storage:** Store in a well ventilated, cool, dry space in sealed containers away from sunlight, flames or other surfaces of heat or ignition or corroding environments. **Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. **Container Disposal:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DOT PAINT

FLAMMABLE LIQUID

UN 1263

## Barnacle Ban Corporation

### Sales

1407 Parkway View Drive  
Pittsburgh, PA 15205  
(412) 787-0329/0414  
FAX: (412) 787-0291

### Administration

1103 Parkway View Drive  
Pittsburgh, PA 15205  
(412) 787-0329/0414

Barnacle Ban Corporation is  
BIOCONTROL TECHNOLOGY

