 <p>U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460</p> <p>NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> Registration <input type="checkbox"/> Reregistration</p> <p>(under FIFRA, as amended)</p>	<p>EPA Reg. Number: 68687-5</p>	<p>Date of Issuance: MAR 16 1999</p>
	<p>Term of Issuance: Conditional</p>	
	<p>Name of Pesticide Product: 3807 HS Red Oxide Vinyl Anti-Fouling Paint</p>	
<p>Name and Address of Registrant (include ZIP Code): Sea-Master Marine Coatings, Inc. P.O. Box 339 Channelview, Texas 77530</p>		
<p>Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.</p>		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4. 2. Make the labeling change listed below before you release the product for shipment: <ol style="list-style-type: none"> a. Revise the EPA Registration Number to read, "EPA Reg. No. 68687-5". 		
<p>Signature of Approving Official: Marshall Swindell Product Manager 33 Regulatory Management Branch 1 Antimicrobials Division (7510C)</p>		<p>Date: MAR 16 1999</p>

SYMBOL	7510C						
EPA Form	8570-6						
SURNAME	P. Swindell						
DATE	3/2/99						

page 2
EPA Reg. No. 68687-5

3. Submit two copies of the revised final printed label for the record.


The Confidential Statement of Formula dated July 31, 1998 is acceptable.

A stamped copy of the label is enclosed for your records.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

If you have any questions concerning this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,



Marhsall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7504C)

Enclosure

SEA-MASTER

3807 HS

RED OXIDE VINYL ANTI-FOULING PAINT

ACTIVE INGREDIENT:

Cuprous Oxide	48.6 %
Inert Ingredients	51.4 %
Total	100.0 %

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

68687-5

KEEP OUT OF REACH OF CHILDREN

WARNING

THIS PRODUCT CONTAINS PETROLEUM DISTILLATES. SEE
BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

BATCH # K-00001 DATE OF MANUFACTURE OCTOBER 1998

5 U.S. GALLONS / 18.93 LITERS

EPA Establishment No. 068687

EPA Registration No. 68687-?

TEXAS D.O.A. REGISTRANT # 0000000 PRODUCT LICENSE #0000000

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Close container after each use.

PESTICIDE DISPOSAL:

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL:

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved state and local procedures. If burned, stay out of smoke.

**DIRECTIONS FOR USE: "IT IS A VIOLATION OF FEDERAL
LAW TO USE THIS PRODUCT IN A MANNER INCONSISTANT
WITH ITS LABELING".**

ENVIRONMENTAL HAZARDS

"This pesticide is toxic to aquatic organisms, including fish and shellfish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated by paint removal to enter water. Dispose of paint debris in an approved landfill."

FOR COMPLETE APPLICATION INSTRUCTIONS: Refer to product data sheet.

SURFACE PREPARATION: Remove surface contaminants, loose dirt, paint and oil. Surface should be dry before applying primer and anti-fouling topcoat.

DRY FILM THICKNESS: 2.0 mils dft per coat.

MIXING: Mix well with mechanical agitation to a smooth and uniform consistency.

THINNING: Normally not required. If necessary, 10% maximum (by volume) of T-10X may be used, or contact Sea-Master Marine Coatings for technical assistance.

APPLICATION: Airless or conventional spray preferred. Apply in a smooth even pattern. Avoid excessive film build and overspray. Minimum temperatures, 50°F for paint, 40°F for surfaces. Maximum 110°F for paint, 150°F for surfaces.

CLEANUP: Use T-10X or gun cleaner for equipment. Do not contaminate water, food or feed by storage, cleaning of equipment, disposal, or solvents. Open dumping prohibited.

SHELF LIFE: 12-24 months

FLASHPOINT:: 25°F(T.C.C.)

PRECAUTIONARY STATEMENTS:

HAZARDOUS TO HUMANS AND ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breath dust or vapor. Wear a mask or respirator approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRATICAL TREATMENT

If Inhaled: If you experience difficulty in breathing, leave the area or remove victim to fresh air. If difficulty continues, get medical attention immediately.

If In Eyes: Flush eyes with plenty of water for at least 15 minutes and get medical attention

If swallowed: Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

If On Skin: Wash thoroughly with soap and water. Get medical attention immediately.

This is an Industrial Product and NOT intended for Household use. The contents of this can are intended for use only by industrial or commercial applicators.

MANUFACTURED BY : SEA-MASTER MARINE COATINGS, INC.

P. O. BOX 339

CHANNELVIEW, TEXAS 77530

**FOR INDUSTRIAL AND COMMERCIAL
BOAT PAINT APPLICATORS**

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

68687-5

5 7 6

SEA-MASTER MARINE COATINGS, INC.

281 452-6200 * FAX 281 452-5112 * P.O. BOX 339 * CHANNELVIEW, TEXAS 77530

3807 HS RED OXIDE VINYL ANTI-FOULING

DESCRIPTION: Sea-Master 3807 HS is a VOC compliant one package anti-fouling coating for boat bottoms which may be applied over properly primed surfaces.

PRODUCT DATA:

Weight/gallon	15.7 lbs
Sp.Gr.	1.885
Flashpoint	25° F.
Solids Content	79.0 % wt. 51.7 % vol
Temperature limit	150°F dry 100°F wet

PRODUCT FEATURES:

Flexibility	Good
Abrasion Resistance	Good
Weatherability	Fair
Dry Time	20 min to touch 1 hr to handle 1 to 2 hrs to recoat
Coverage	820 sq ft/gal (@ 1 dry mil
Thickness	2.0 mils dry/ 4.0 mils wet

RECOMMENDATIONS:

This coating has good anti-fouling properties, flexibility, and has excellent recoatability.

APPLICATIONS:

Apply by spray, roll or brush to primed steel. Applied coverage is 185 sq ft/gal at 4 mils wet (10% loss). You may use Sea-Master T-10 X thinner for cleanup.

PRECAUTIONS: This product contains solvent and anti-fouling toxicants, that are hazardous to humans and animals. Please read M.S.D.S. and dispose of waste according to federal, state and local regulations under the Resources Conservation and Recovery Act..

For best results, apply one coat by brush roll, or spray at 2.0 mils dft (4.0 wet) to a clean and dry surface.

PACKAGING: This product is available in one gallon and five gallon steel pails.

ACCEPTED...
with COMMENTS
in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

6,8687-5

The technical data presented here, to the best of our knowledge, is accurate and conforms to our Quality Control guidelines. The manufacturer does not assume any responsibility of the user in connection with application, performance or coverage. Product liability, if any, is limited to the replacement of the product. User must refer to the M.S.D.S. and is responsible for following their precautions and recommendations allowed by the guidelines.

APPLICATION INFORMATION

IMMERSION SERVICE

Recommended for constant immersion

Blast clean to a Commercial metal surface (SSPC SP-6 or NACE # 3) or to a SSPC

SP-3 surface with power tools. Then apply to a properly primed surface.

MIXING

Mix well with mechanical agitation before applying. You can use T-10 X to clean your equipment, brushes and rollers.

NON-IMMERSION SERVICE:

Not Recommended.

APPLICATION:

Airless or conventional spray is preferred.

Apply in a smooth even pattern. Avoid high film thickness which may result in running or sagging of the coating. May be applied by brush or roller.

SPRAY INFORMATION:

AIRLESS;

Pump Ratio	30:1
Air Supply	100 psi
Hose Dia (ID)	1/4 inch
Hose Length (Max)	75 ft
Tip Size	.017-.019
Atomization	2000 psi

CONVENTIONAL;

Spray Pot	10-20 psi
Air Supply	100 psi
Hose Dia (ID)	1/4 inch
Hose Length	50 ft
Tip Size	.042-.048
Atomization	50-60 psi

SHIPPING DATA:

Name	Paint, Liquid
Hazard Class	3, Flammable Liquid
UN Number	UN-1263
Flashpoint	25 F (T.C.C.)
Packaging Group	II
5 gallons (18.92 liters)	82.5 lbs
	[DEC 1998]

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

68687-5