

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

October 13, 2016

Ms. Connie Ivey Regulatory Affair Associate Clearon Corporation 95 MacCorkle Avenue S.W. South Charleston, WV 25303

Subject: Notification per PRN 98-10 – Add Optional Metric Units to Directions Product Name: CDB Clearon Granular EPA Registration Number: 69470-20 Application Date: September 12, 2016 Decision Number: 521485

Dear Ms. Ivey:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Page 2 of 2 EPA Reg. No. 69470-20 Decision No. 521485

If you have any questions, you may contact Killian Swift at 703-308-6346 or via email at <u>Swift.Killian@epa.gov</u>.

Sincerely,

b

Demson Fuller Product Manager – Team 32 Regulatory Management Branch II Antimicrobials Division (7510P)

{CDB[®] CLEARON GRANULAR Master Label Ver.1213} **{69470-20}**

{All text in brackets [xxx] is optional and may or may not be intended on a final label and/or kit label.} {All text in braces {xxx} is administrative and will not appear on a final label and kit label.} {For text that may or may not appear on a kit label, refer to MASTER KIT LABEL.}

DB[®] CLEARON GRANULAR

NOTIFICATION

69470-20

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

10/13/2016

{DOA: 0414201609142016}

{Alternate product names:} [ChloRun] [CDB[®] Clearon Granular Industrial Water Biocide] [Pool Brand Maintenance Kit for Above Ground Pools] {Referenced as the MARKETING STATEMENTS for the master kit label.} (Optional marketing statements that may be used with Swimming pool sanitization. One or more statements may be combined.} [24-hr chlorine residual for round the clock activity] [3-in-1 Sanitizer, Algaecide and Stabilizer] [3-in-1 Sanitizer, Algaecide and Shock] [1 lb Treats 10.000 Gallons] [99% Active Ingredient] [3 times (x) a week] [[Three] [3] times [x] [a] [per] week] [Chlorinating] [Completely Soluble] [Concentrate] [Concentrated] [Controls [Bacteria] [and] [Algae]] [Controls Bacteria and Algae in Spa Water] [Convenient Complete Pool Care] [Designed For Backyard Pools] [Destroys organic pollutants, bacteria, and algae] [Dichlor] [Disinfects] [Eliminates Chlorine Odor] [Essential Products to Treat Your [Pool] [And] [Hot Tub] [Spa]] [[Fast], [Effective], [Stabilized] [Shock] [For] [Swimming Pools] [and] [Spas]] [For all types of pools] [For Hot Tubs] [For lasting protection against organic contaminants] [For Pools & Spas] [For all Pools & Spas] [For Routine Use] [For Sparkling and Crystal Clear Water] [For Spas] [[For] [Spa[s]] [and] [Hot Tubs]] [For use in all pool types]{This statement alerts consumers to the fact that they may use this product in above ground, in-ground, indoor, outdoor, plaster, vinyl, fiberglass pools} [Helps prevent staining and line wrinkling] [In Spa Water] [Keeps Water Clear] [Kills Bacteria] [Kills Bacteria & Algae] [Kills Bacteria and Controls Algae] [Kills Bacteria, Controls Algae, and Clarifies] [Leaves No Residue] [Maintains pool for up to 3 weeks] [No mineral scale build-up] [Non-Blended] [Not Blended (no fillers)] [[QUALITY] [AND] [PERFORMANCE] GUARANTEED] [pH Neutral] [Pool Algaecide] [Powdered Chlorine Sanitizer] [Protects Against Organic Contaminants] [Protects Pool Equipment From Corrosion]

[Sanitizer] [Sanitizer, Shock and Algaecide] [Sanitizer for sparkling and crystal clear water] [Sanitizes, Clarifies, and Protects against Algae] [See How Quality Makes A Difference] [Shock] [Shocks water clear] [Sodium Dichlor] [Stabilize[s]] [Stabilized] [Stabilized Shock for [Swimming Pools] [and] [Spas]] [Suppresses algae] [Swimming Pool Algaecide] [Above Ground Pool Maintenance Kit] [Treats up to 5,000 Gallons] [Treats up to 7,500 Gallons] [Why To Use:] [[Step] [1]:] [Balance] [This Is] [[Step] [2]:] [Sanitize] [Chlorinate] [This Is] [[Step] [3]:] [Shock] [[Step] [4]:] [Algaecide] [Prevent Algae] [[Step] [5]:] [1 X [a] [per] Week] [One Time [A] [Per] Week] [12 x 1 lbs. Individual Pouches] [12 1-pound Individual Pouches] [24 x 1 lbs. Individual Pouches] [24 1-pound Individual Pouches] [Made in the U.S.A.] [American Flag] [Ready] [,] [Set] [,] [Swim] {Optional marketing statements/logos/icons that may be used with Water Disinfection.} [American flag icon] [Made in the U.S.A.] [NSF/ANSI Standard 60 logo. Refer to master for options.] [Member's Mark optional logo. Refer to master.] {Referenced as the KOOROC AND SIGNAL WORD for the master kit label.} **KEEP OUT OF REACH OF CHILDREN** DANGER {Referenced as the INGREDIENT STATEMENT for the master kit label.} Active Ingredient: {Referenced as the FIRST AID for the master kit label.} **FIRST AID** If in eyes Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice. • If inhaled Move person to fresh air. • If person is not breathing, call 911 or an ambulance then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice. If on skin or Take off contaminated clothing. • clothing Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice. . If • Call a poison control center or doctor immediately for treatment advice. swallowed • Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. •

Do not give anything by mouth to an unconscious person.

Have the product container or label with you when calling a

poison control center, doctor or when going for treatment. YOU MAY ALSO CONTACT [1-800-420-9236]

FOR EMERGENCY MEDICAL TREATMENT INFORMATION.

NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate the use of gastric lavage.

[See [back] [side] panel[s] for additional precautionary statements [and first aid].] [See [side] panel[s] and individual container[s] for complete product label[s]. Read entire label of each product before using.]

{Referenced as the OTHER LABEL TEXT for the master kit label.}
PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER
CORROSIVE
CAUSES IRREVERSIBLE EYE DAMAGE
MAY BE FATAL IF INHALED
HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN

Do not get in eyes, on skin, or on clothing. Do not breathe dust, vapor, or spray mist. Wear protective eyewear (goggles, face shield, or safety glasses). Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

{for end-use products packaged in containers with sizes of less than 50 pounds}

[ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms.]

{for end-use products packaged in container sizes of 50 or more pounds}

[ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, ponds, streams, estuaries, oceans, or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.]

PHYSICAL OR CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Use only clean dry utensils. Mix only into water. Contamination with moisture, dirt, organic matter or other chemicals (including other pool chemicals) or any other foreign matter may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible generation of fire and explosion. Avoid any contact with flaming or burning material such as a lighted cigarette. Do not use this product in any chlorinating device which has been used with any inorganic or unstabilized chlorinating compounds (e.g., calcium hypochlorite). Such use may cause fire or explosion.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

[See [side] [back] panel[s] for additional use directions.] [See [final] [kit] labeling for directions for use.]

{For products intended for swimming pool uses}

[FOR SWIMMING POOL DISINFECTANT

When used as directed, this product is effective as a swimming pool water disinfecting agent. The dosage necessary for your pool will change considerably depending upon those factors that burden the disinfection system. Some of the factors that will vary the required dosages are water temperature, bather load, exposure to windblown debris, thunder or rain storms and length of filtration cycle.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturer's directions. Adjust pH to between 7.2-7.6. Add stabilizer to establish a minimum level of 30-40 ppm to reduce degradative effects of sunlight upon the chlorine residual. Check for metals. Before using this product, add stain and scale inhibitor to prevent staining of pool surface due to metals. When using other products as outlined in the directions for this product, always follow directions on those products.

With pump running, broadcast 4 ounces of this product per 10,000 gallons [(113 g per 38 m³)] directly into the water in the deep end of the pool as an initial treatment. Repeat additions until a residual of 1-3 ppm chlorine is established as determined by the use of a test kit. To prevent damage to pool surface, use a pool brush to disperse granules that may have settled to the bottom of the pool. NEVER ALLOW UNDISSOLVED PRODUCT TO REST IN CONTACT WITH BLEACHABLE POOL SURFACES. Regular use of a test kit is necessary to determine when it is necessary to add another dose of this product to maintain a residual of 1-3 ppm available chlorine in the pool water. An average daily dose requirement is 2-3 ounces of this product per 10,000 gallons [(57-85 g per 38 m³)] of water. After use of this product it is recommended that a preventative algae treatment be added on a weekly basis.]

[FOR] [SWIMMING POOL] [SUPERCHLORINATION]]: Broadcast one pound of this product per 10,000 gallons [(500 g per 42 m³)] directly into the water in the deep end of the pool. To prevent damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of your pool. NEVER ALLOW UNDISSOLVED PRODUCT TO REST IN CONTACT WITH BLEACHABLE POOL SURFACES. In water temperatures less than 70°F, or as an alternate application procedure, pre-dissolve this product prior to applying evenly to the deep end of the pool. Dissolve this product outdoors, in a clean plastic bucket stirring with a clean plastic or wooden spoon. Add this product to water; NEVER add water to product. NEVER add more than 1 pound of this product to 3 gallons [(500 g per 12.5 L)] of cool water. Do not mix with other products when pre-dissolving.] **[REENTRY:** Reentry into treated swimming pools is prohibited above levels of 3 ppm of chlorine due to risk of bodily harm.]

[FOR SWIMMING POOL ALGAE:

When used as directed, this product kills algae and will rid your pool of unsightly algae spots. This product is ideal for use in vinyl lined, fiberglass or colored plaster surface pools.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturer's directions. Adjust pH to between 7.2-7.6. Check for metals and if present, add stain and scale inhibitor to prevent staining of pool surface. When using other products as outlined in the directions for this product, follow directions on those products.

Before using this product, brush all surface-clinging algae paying special attention to pool steps, ladder steps and around skimmer and lights. At night, or when pool is not in use, broadcast this product directly into the deep end of the pool with pump running. Use two pounds per 10,000 gallons [(1 kg per 42 m³)] for medium to heavy algae growth and one pound per 10,000 gallons [(500 g per 42 m³)] for light algae growth. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled to the bottom of the pool. Brush any remaining algae and clean backwash filter. If algae is still visible, repeat treatment.]

[FOR WINTERIZING POOL:

To avoid costly spring problems (algae, stains, cloudy water, high chlorine demand) properly prepare your pool for the winter using this product. This product oxidizes organic wastes, provides long lasting chlorine protection, helps keep pool surfaces clean, and helps protect water during the off season months.

NOTE: For WHITE PLASTER POOLS, broadcast this product directly into the pool water. FOR VINYL, FIBERGLASS, PAINTED AND COLORED PLASTER POOLS, PRE-DISSOLVE THE RECOMMENDED DOSE.

Dissolve this product outdoors, in a clean plastic bucket stirring with a clean plastic or wooden spoon. Add this product to water; NEVER add water to product. NEVER add more than 1 pound of this product to 3 gallons [(500 g per 12.5 L)] of cool water. Do not mix with other products when pre-dissolving.

Before treating the pool, chemically balance the water and adjust pH to 7.4-7.6. Brush and vacuum the pool. Backwash the filter and clean skimmer, pump baskets, and filter.

Sprinkle the powder or pour the pre-dissolved treatment dose (see NOTE above) into the water around the edges of the pool. Use one pound of this product per 10,000 gallons [(500 g per 42 m³)] of water.

Circulate water for several hours, and then apply a winterizing algae treatment following appropriate directions. Cut off pump. Drain equipment or add a swimming pool antifreeze to equipment to prevent freeze damage. Install pool cover. A second treatment of the product in mesh covered or non-covered pools may be required prior to water freezing (mid-winter). If second treatment is required, re-dissolve treatment (see NOTE above) and pour along edges of the pool.]

{For products intended for spa and/or hot tub uses}

[FOR SPA AND HOT TUB DISINFECTANT: When used as directed, this product is effective as a spa and hot tub water disinfecting agent.

Ensure all spa and hot tub equipment is working properly. Backwash/clean the filter system following manufacturer's directions. Adjust pH to between 7.2-7.6. When using other products as outlined in the directions for this product, always follow directions on those products.

MAINTENANCE DOSES: With pump on, add ½ teaspoon of this product per 100 gallons of water (or 5 teaspoons per 1,000 gallons [(247 g per 38 m³)]) as an initial treatment. Repeat at 15 to 20 minute intervals until a residual of 3-5 ppm of available chlorine is established as determined by test kit. A test kit must be used regularly to determine the frequency of additional doses of this product needed to maintain the chlorine residual of 3-5 ppm.

SUPERCHLORINATION: Use one teaspoon of this product per 100 gallons of water (or ¼ cup per 1,000 gallons [(494 g per 38 m³)]). Superchlorination may be needed on a nightly basis in a heavily used spa or as infrequently as once a week in a moderately used spa.]

[REENTRY: Reentry into treated spas and hot tubs is prohibited above levels of 3 ppm of chlorine due to risk of bodily harm.]

[HOW TO CALCULATE [POOL] [&] [SPA] CAPACITY

{69470-20} {CDB[®] CLEARON GRANULAR Master Label Ver.<u>1213</u>} {DOA: 0414201609142016}

Shape of [Pool] [or] [Spa]:	Gal. of Water (Dimensions in feet)
Rectangular:	Average depth x average length x average width x 7.5
Circular:	Diameter x diameter x average depth x 5.9
Oval with straight sides:	Full width x full length x average depth x 6.7
Irregular:	Consult pool builder]

{The following uses are intended for products marketed for industrial water treatment} [FOR USE IN INDUSTRIAL RECIRCULATING WATER COOLING TOWERS, AIR WASHERS & EVAPORATIVE CONDENSERS:]

[Treatment with this product is an effective way to control the growth of bacteria and algae in industrial recirculating water cooling towers, air washers and evaporative condensers.

[1.] Badly fouled systems should be cleaned prior to initiating treatment.

[2.] Initial Dosage - When the system is just noticeably fouled, add 10-13 oz. of this product per 10,000 gallons of water contained in the system. Repeat this dosage, if necessary, until free available chlorine level (FAC) of 0.5-1.0 ppm is obtained (as determined by use of a reliable test kit).

[3.] Maintenance Dosage - To obtain a FAC of 0.5 - 1.0 ppm, add 1-3 oz. of this product per 10,000 gallons of water daily or as needed.

[4.] This product should be added to the system at a point where adequate flow is maintained. Variations in water temperature, chlorine demand and flow rate will affect the dissolution rate. Warmer seasons may require an upward adjustment of the FAC.

Air Washers: For use only in industrial air washer systems that maintain effective mist eliminating components. Hypochlorite controls slime-forming bacteria and fungi in air washer systems. This product may be added to the system either continuously or intermittently or as needed. The frequency of feeding and duration of the treatment will depend on the severity of the problem.

BADLY FOULED SYSTEMS should be cleaned prior to initiating treatment.

[1.] Initial Dosage - When the system is just noticeably fouled, add 10-13 oz. of this product per 10,000 gallons of water contained in the system. Repeat this dosage, if necessary, until a free available chlorine level (FAC) of 0.5-1.0 ppm is obtained (as determined by use of a reliable test kit).

[2.] Maintenance Dosage - To maintain a FAC of 0.5-1.0 ppm, add 1-3 oz. of this product per 10,000 gallons of water, daily or as needed.

[3.] This product should be added to the system at a point where adequate flow is maintained. Variations in water temperature, chlorine demand and flow rate will affect the dissolution rate. Warmer seasons may require an upward adjustment of the FAC.]

{The following uses are intended for products marketed as drinking water disinfectants.}

[DISINFECTION OF DRINKING WATER] [EMERGENCY] [PUBLIC] [INDIVIDUAL] [SYSTEMS]

[PUBLIC SYSTEM: Feed 1 ounce of this product per 6000 gallons of water until a free available chlorine residual of at least 0.2 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details.]

[INDIVIDUAL SYSTEMS: DUG WELLS - Upon completion of the casing (lining) wash the interior of the casing (lining) with a 100 ppm available chlorine solution using a stiff brush. This solution can be made by dissolving 1 ounce of this product into 40 gallons of water. After covering the well, pour the disinfectant solution into the well through both the pipe sleeve opening and the pipeline. Wash the exterior of the pump cylinder also with the disinfectant solution. Start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours, flush well until all traces of chlorine have been removed from the water. Contact your local Health Department for further details.]

[INDIVIDUAL WATER SYSTEMS: DRILLED, DRIVEN & BORED WELLS - Run pump until water is as free from turbidity as possible. Pour a 100 ppm available chlorine disinfecting solution into the well. This solution can be made by dissolving 1 ounce of this product into 40 gallons of water. Add 5 to 10 gallons of clean, chlorinated water to the well in order to force the disinfectant into the rock formation. Wash the exterior of pump cylinder with the disinfectant. Drop pipeline into well, start pump, and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours, flush well until traces of chlorine have been removed from the water. Deep wells with high water levels may necessitate the use of special methods for introduction of the disinfectant into the well. Consult your local Health Department for further details.]

[INDIVIDUAL WATER SYSTEMS: FLOWING ARTESIAN WELLS - Artesian wells generally do not require disinfection. If analyses indicate persistent contamination the well should be disinfected. Consult your local Health Department for further details.]

[EMERGENCY DISINFECTION:

This product is recommended for disinfecting raw or pre-treated (settled, coagulated and/or filtered) water supplies intended for use as drinking water for humans and domestic animals.

The source of the water to be treated may be a river, lake, well, cistern or similar system. To obtain the desired disinfectant results, the water to be treated should be clear and free of dirt and organic debris. If the source of the water is cloudy and contains dirt and organic debris, the water should be held in holding tanks or ponds, treated with coagulating agents and filtered to remove the dirt and organic debris.

Dissolve 0.1 ounce of this product into 40 gallons of water (120 milligrams per 10 liters) to obtain a concentration of 10-ppm (mg/L) of available chlorine. Let the water stand for one hour before using. A residual of 1ppm (mg/L) of available chlorine, as measured by a reliable test kit, should be maintained in the water to insure disinfection.

Preparation of Stock Solution - Dissolve one heaping teaspoon of this product (approximately 10 grams or 1/3 ounce into 1 liter of water). The mixture will produce a 0.6% stock chlorine solution (6,000 mg/L). Add 20 drops of this stock solution to each liter of water to be treated. The stock solution should be prepared fresh weekly.]

[PUBLIC WATER SYSTEMS:]

[RESERVOIRS: ALGAE CONTROL - Continuous chlorination is the most effective method for destroying algae, however, slug treatment can also be effective. Suitable chlorine feeding points should be selected on each stream at least 50 yards upstream from the points of entry into the reservoir. Add this product at the following rates: Initial Dose: When the system is noticeably fouled, add this product at the rate of 1.5 to 7.5 ounces per 10,000 gallons to achieve 0.5-1.5 ppm (mg/L) available chlorine, as measured by a suitable test kit. Repeat dosage until residual is achieved.]

[Subsequent Dose: When control is evident, add this product at the rate of 0.5 to 2.3 ounces per 10,000 gallons to maintain 0.2-0.5 ppm (mg/L) available chlorine, as measured by a suitable test kit.]

[MAINS - Thoroughly flush section to be disinfected by discharging from hydrants. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of chlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.]

[NEW TANKS, BASIN, ETC.: Remove all physical soil from surfaces. Place 9 ounces of this product for each 10 cubic feet of moving capacity (500 ppm available chlorine). Fill to working capacity and allow to stand for at least 4 hours. Drain and flush with potable water and return to service.]

[NEW FILTER SAND - Apply 16 ounces of this product for each 150 to 200 cubic feet of sand. The action of the product dissolving as the water passes through the bed will aid in sanitizing the new sand.]

[NEW WELLS - Flush the casing with a 50 ppm available chlorine solution of water containing 1.2 ounces of this product for each 100 gallons of water. The solution should be pumped or fed by gravity into the well after thorough mixing with agitation. After 24 hours, flush well until all traces of chlorine have been removed from the water. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary. Contact your local Health Department for further details.]

[EXISTING EQUIPMENT: Remove equipment from service; thoroughly clean surfaces of all physical soil. Sanitize by placing 9 ounces of this product for each 10 cubic feet capacity (approximately 500 ppm available chlorine) Fill to working capacity and let stand at least 4 hours. Drain and place in service. If the previous treatment is not practical, surfaces may be sprayed with a solution containing 1.2 ounces of this product for each 5 gallons of water (approximately 1000 ppm available chlorine). After drying, flush with water and return to service.]

[EMERGENCY DISINFECTION AFTER FLOODS:]

[WELLS - Thoroughly flush contaminated casing with 500-ppm available chlorine solution. Prepare this solution by mixing 1.2 ounces of this product with 10 gallons of water. Backwash the well to increase yield and reduce turbidity, adding sufficient chlorinating solution to the backwash to produce a 10 ppm available chlorine residual, as determined by a chlorine test kit. After the turbidity has been reduced and the casing has been treated, add sufficient chlorinating solution to produce a 50-ppm available chlorine residual. After 24 hours, flush well until all traces of chlorine have been removed from the water. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary. Repeat treatment if water samples are biologically unacceptable. Contact your local Health Department for further details.]

IEMERGENCY DISINFECTION AFTER MAIN BREAKS:1

[MAINS - Before assembly of the repair section, flush out mud and soil. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of chlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.]

[RESERVOIRS - In case of contamination by overflowing streams, establish chlorinating stations upstream of the reservoir. Chlorinate the inlet water until the entire reservoir obtains a 0.2 ppm available chlorine residual, as determined by a suitable chlorine test kit. In case of contamination from surface drainage, apply sufficient product directly to the reservoir to obtain a 0.2 ppm available chlorine residual in all parts of the reservoir.]

[BASIN, TANKS, FLUMES, ETC.: Thoroughly clean all equipment; then apply 9 ounces of product per 10 cu. ft. of water to obtain 500 ppm available chlorine, as determined by a suitable test kit. After 24 hours, drain flush and return service. If the previous method is not suitable, spray or flush the equipment with a solution containing 1.2 ounces of this product for each 5 gallon of water (1000 ppm available chlorine.) Allow to stand for 2 to 4 hours, flush and return to service.]

[FILTERS - When the sand filter needs replacement, apply 16 ounces of this product for each 150 to 200 cubic feet of sand. When the filter is severely contaminated, additional product should be distributed over the surface at the rate of 16 ounces per 20 sq. ft. Water should stand at a depth of 1 foot above the filter bed for 4 to 24 hours. When filter beds can be back-washed of mud and silt, apply 16 ounces of this product per each 50 sg. ft., allowing the water to stand at a depth of 1 foot above the filter sand. After 30 minutes, drain water to the level of the filter. After 4 to 6 hours drain, and proceed with normal back- washing.]

[DISTRIBUTION SYSTEM - Flush repaired or replaced section with water. Establish a chlorinating station and apply sufficient product until a consistent available chlorine residual of a least 10 ppm (as measured by a chlorine test kit) remains after a 24 hour retention time.]

[EMERGENCY DISINFECTION AFTER FIRES:]

[CROSS CONNECTIONS OR EMERGENCY CONNECTIONS - Set up a chlorine feed system near in the intake of the untreated water supply. Add 1.3 ounces of this product per 1,000 gallons of water until a chlorine residual of at least 0.2 ppm (as measured by a chlorine test kit) at the point where the untreated supply enters the regular distribution system.]

[EMERGENCY DISINFECTION AFTER DROUGHT:]

[SUPPLEMENTARY WATER SUPPLIES - A chlorine feed system should be set up on the supplementary water line. This product should be added at 0.7 ounces per 1,000 gallons until a minimum chlorine residual of 0.2 ppm (as measured by a chlorine test kit) is achieved. The water should be held for 20 minutes before use.]

[WATER SHIPPED IN BY TANKS, TANK CARS, ETC. - Thoroughly clean all containers and equipment. Spray a 500 ppm available chlorine solution and rinse with potable water after 5 minutes. This solution is made by mixing 1.2 ounces of this product for each 5 gallons of water. During the filling of the containers, dose with sufficient amounts of this product to provide at least a 0.2 ppm chlorine residual, as measured by a chlorine test kit.]

[SEWAGE WASTE WATER SYSTEMS

This product is intended for use in sewage waste water systems. This product provides rapid disinfection of primary, secondary and tertiary waste water treatment systems.

Dose Rate: Add this product at the rate of 0.03 to 0.75 pounds per 1,000 gallons (3.6 to 90 grams per 1,000 liters) in the system to achieve 0.2-3 ppm (mg/L) available chlorine, as measured by a suitable test kit, at the injection point in the disinfection contact chamber. Adjust the dose to achieve disinfection and minimize the halogen concentration at the exit of the contact chamber.]

{The following uses are intended for products marketed as food contact sanitizers}

(FOR USE ON FOOD CONTACT SURFACES

This product may be used on food contact surfaces in accordance with 21 CFR 178.1010 of the Federal Food Drug and Cosmetic Act.]

[SOLUTION PREPARATION: Prepare a 100 ppm (mg/L) sanitizing solution by thoroughly mixing 17 grams (0.6 oz) of this product with 25 gallons of water (0.18 gram per liter). Solutions containing an initial concentration of 100 ppm (mg/L) available chlorine must be tested with a suitable chlorine test kit and adjusted periodically to insure the available chlorine level does not drop below 50 ppm (mg/L). If the available chlorine level drops below 50 ppm

{CDB[®] CLEARON GRANULAR Master Label Ver.<u>1213</u>} {DOA: 0414201609142016}

(mg/L), either discard the solution and prepare a new one or add 17 grams (0.6 oz) of this product per 50 gallons of water to increase the available chlorine level 50 ppm (mg/L) and maintain the 100 ppm (mg/L) solution strength.]

[SANITIZATION OF NON-POROUS FOOD CONTACT SURFACES:

This product is recommended for use in poultry houses, egg handling equipment, dairy farm milk handling facilities/equipment, dairy farm milking equipment, household/domestic dwelling indoor food handling areas, food processing plant premises and equipment (food and non food contact, dairies/cheese processing plant premises and equipment (food and non-food contact), meat processing plant premises and equipment (food and non-food contact), poultry processing plant premises and equipment (food and non-food contact), eating establishments, eating establishment equipment/utensils (food contact), milk shake machines, soft serve ice cream machines.]

[RINSE OR SPRAY METHOD: Prepare solution in accordance with Solution Preparation in above paragraph. Clean equipment surfaces in the normal manner and rinse with potable water. It may be necessary to remove gross filth and heavy soil from surfaces by a pre-scrape, pre-flush, and where necessary, a pre-soak treatment. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for 2 to 5 minutes. Do not rinse equipment with water after treatment. The same solution may used in feed tanks of spray type machines providing at least one minute contact time to sanitize equipment.]

[IMMERSION METHOD: Prepare solution in accordance with Solution Preparation in above paragraph. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for 2 to 5 minutes and allow the sanitizer to drain. Do no rinse equipment with water after treatment.]

{The following uses are intended for products for use in commercial egg washing treatments.}

[EGG WASHING:

This product is recommended for use in commercial egg washing treatments and hatching egg washing treatments.]

[Prepare solution in accordance with Solution Preparation in above paragraph. The eggs should be washed in a continuous operation and shall be completed as rapidly as possible. The eggs shall not be allowed to stand or soak in water. Immersion-type washer shall not be used. After washing, the eggs shall be spray rinsed with the sanitizing solution. At intervals during use, this product should be added to the circulating spray rinse solution to maintain 100 ppm (mg/L) available chlorine.]

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage and disposal.

PESTICIDE STORAGE: Store in a dry, cool and well-ventilated area. Avoid moisture getting into container. Keep off wet floors. In case of spillage, wash with large amounts of water. After each use, keep container tightly closed. Oxidizing material. Keep away from flames, sparks and all sources of heat. Avoid contact with organic material.

{For non-residential use products, the following will be depicted on the market label.}

[PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.]

{Nonrefillable container – household/residential use; equal to or less than 50 pounds} [CONTAINER HANDLING: [Nonrefillable container. Do not reuse or refill this container. Rinse empty container thoroughly with water to dissolve all material prior to disposal. Offer for recycling, if available.]

{Nonrefillable container – single-use, non-reseatable package; equal to or less than 50 pounds} [CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Rinse empty container thoroughly with water to dissolve all material prior to disposal. Offer for recycling, if available.]

{Nonrefillable container – Fiber Drums with Liners; greater than 50 pounds}

[CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then offer for recycling if available or dispose of liner in a sanitary landfill or by incineration. If drum is contaminated and cannot be reused, dispose of it in the same manner required for its liner.]

{Nonrefillable container- non-household/non-residential use; greater than 50 pounds}

{CDB[®] CLEARON GRANULAR Master Label Ver.<u>1213</u>} {DOA: 0414201609142016}

[CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Rinse empty container thoroughly with water to dissolve all material prior to disposal. Offer for recycling, if available.]

{Refillable container- non-household/non-residential use}

[CONTAINER HANDLING: Refillable container. Refill this container with Sodium Dichloro-s-Triazinetrione Hydrated only. Do not use this container for any other purpose. Cleaning of this container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. Rinse empty container thoroughly with water to dissolve all material prior to disposal.]

EMERGENCY HANDLING: In case of contamination or decomposition do not reseal container. If possible, isolate container in open, well-ventilated area. Flood with large volumes of water. Dispose of contaminated material in an approved landfill area.

WARRANTY

Seller warrants that this product conforms to the chemical description and is reasonably fit for the purposes stated on the label when used in accordance with label directions under normal conditions of use. But to the extent consistent with applicable law neither this warranty nor any other warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, expressed or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller, and Buyer assumes the risk of any such use.

Manufactured by:

CLEARON CORP. 95 MacCorkle Avenue S.W. South Charleston, WV 25303 {for DOMESTIC labels only:}[Tel: 1-(800) 811-2327] {for INTERNATIONAL labels only:}[Tel: 1-(304) 746-3000]

[Made] [and Printed] [in U.S.A.] [CDB Clearon® is a registered trademark of Clearon Corp.]

[Master Logos for Final and/or Kit Labels] [NSF/ANSI Standard 60 Logos]



[Member's Mark Logo]




100% MONEY BACK GUARANTEE

We would like to hear from you with any comments or suggestions. In the continental U.S. or Canada, you can call us toll-free at 1.888.301.0332 from 8 a.m. to 5 p.m. CST Monday - Friday. You can also send us an email using the feedback icon at SamsClub.com.

[Kosher certification Logos]

<u>{Note to reviewer. The following may be used only if the supplemental registrant has obtained a Kosher</u> <u>certificate. Any Kosher Symbol such as:}</u>



{MASTER KIT LABEL}

{Front Panel: Content below may or may not appear on the Front Panel of a kit label.}

[CDB[®] CLEARON GRANULAR] [EPA Approved Kit Name] [MARKETING STATEMENTS] {See master label for approved MARKETING STATEMENTS text.} [INGREDIENT STATEMENT] {See master label for approved INGREDIENT STATEMENT text.} [KOOROC AND SIGNAL WORD] {See master label for approved KOOROC AND SIGNAL WORD text.} [FIRST AID] {See master label for approved FIRST AID text.} [KIT CONTENTS] [KIT CONTAINS] [INCLUDED IN THIS KIT] {List of additional, separate items, including this product, in a kit.}

[See [side][back] panel[s] and individual containers for complete [product] [final] labels.] [Read [the] entire label of each product [inside] [kit] [EPA Approved Kit Name] before using.] [See [final] [product] label[s] for additional precautionary statements [and first aid].]

[[This kit] [EPA Approved Kit Name] contains [a pesticide pro	oduct] [CDB® CLEARON GRANULAR].]
[EPA Reg. No. 69470-20-XXXX]	
[EPA Est. No]	
[[Material][Label] No]	
[[TOTAL] [CONTENTS] [NET WEIGHT]:	[lbs.][kg.][oz.][g.]]
[[Batch][Lot] No.]	

{Back Panel: Content below may or may not appear on the Back Panel of a kit label.}

[MARKETING STATEMENTS] {See master label for approved MARKETING STATEMENTS text.} [KIT CONTENTS] [KIT CONTAINS] [INCLUDED IN THIS KIT] {List of additional, separate items. including this product, in a kit.}

[This Kit] [EPA Approved Kit Name] [is] [Distributed by:] [Produced for:] [Manufactured for:] [Company Name] [Company Address] [City][State][Zip Code]

{Side Panels: Content below may or may not appear on the Side Panels of a kit label.}

[The information below references [the EPA registered pesticide] [CDB[®] CLEARON GRANULAR] packaged inside [this kit] [EPA Approved Kit Name].] [[This] [box] [kit] [EPA Approved Kit Name] contains the following EPA registered product.]

[OTHER LABEL TEXT] {See master label for approved OTHER LABEL TEXT which includes Precautionary Statements and additional labeling text to follow. All OTHER LABEL TEXT may or may not appear on a kit label as directed on the master label.}

{Full approved label of California (CA) registered adjuvant(s) in a kit. This references adjuvant labeling approved by the State of California only. This labeling will ONLY appear if a kit, containing State of CA registered adjuvant(s), is sold or distributed in CA.}

[See [side][back] panel[s] and individual containers for complete [product] [final] labels.] [Read the entire label of each product [inside] [kit] [EPA Approved Kit Name] before using.] [See [final] [product] label[s] for additional precautionary statements [and first aid].]