



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Ave., N.W.
Washington, D.C. 20460

NOTICE OF PESTICIDE:

☒ Registration
☐ Reregistration
(under FIFRA, as amended)

EPA Reg. Number:

69470-40

Date of Issuance:

9/18/19

Term of Issuance:

Conditional

Name of Pesticide Product:

ClearControl 1.5%

Name and Address of Registrant (include ZIP Code):

Clearon Corp
95 MacCorkle Ave., SW
South Charleston WV 25303

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Zeno Bain, Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Date:

9/18/19

2. You are required to comply with the data requirements described in the DCI Order identified below:
 - a. GDCI 107103-1709 EPA-HQ-OPP-2013-0605
 - b. GDCI 107104-149 EPA-HQ-OPP-2013-0605

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>

3. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, “EPA Reg. No. 69470-40.”
4. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated April 25, 2019

If you have any questions, please contact Zebora Johnson by phone at (703) 308-7080, or via email at johnson.zebora@epa.gov.

{All text in brackets [xxx] is optional and may or may not be intended on a final label.} {All text in braces {xxx} is administrative and will not appear on a final label.}

ClearControl 1.5%

Industrial microbicide for use in Adhesives and Tackifier Preservation, Air Conditioner and Air Refrigeration Condensate Water Systems, Air Washer Systems, Aqueous Compositions[*], Brewery Pasteurizer and Can Warmer Systems, Building Material Preservation, Coal Slurry Systems, Commercial Photoprocessing Systems[*], Dispersed Pigments[*], Electrodeposition Paint Components, Evaporative Condenser Water Systems, Fountain Solutions and Ink / Ink Components[*], Hydrostatic Sterilizer Water Systems, Immersion Ultrasonic Tank Water[*], In-container Preservation, Industrial Process Water Systems, Industrial Scrubbing Systems, Industrial Wastewater Treatment Systems[*], Influent Water Filtration Systems, Laboratory Equipment Water Baths[*], Metal Working and Metal Cleaning Fluid Preservation, Oil Field Injection Waters, Paint and Coating Preservation, Paint Spray Booth Systems, Photoplate Processing[*], Polymer Latexes[*], Pulp and Papermills[*], Recirculating Closed Loop Water Cooling Systems, Recirculating Electrodeposition Systems, Recirculating Water Cooling Towers, Retort Water Systems, Reverse Osmosis and Ultra Filtration Systems, Sewage Systems[*], Textile Chemicals Preservation[*], Water Based Hydraulic Fluid Preservation, and Wood and Wood Products[*].

ACCEPTED

Sep 18, 2019

Under the Federal Insecticide, Fungicide,
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 69470-40

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one 1.2%

2-Methyl-4-isothiazolin-3-one 0.4%

OTHER INGREDIENTS: 98.4%**TOTAL:** 100.0%**KEEP OUT OF REACH OF CHILDREN**

DANGER

FIRST AID

IF ON SKIN:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 min. • Call a poison control center or doctor for treatment advice.
IF IN EYES:	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 min. • Remove contact lenses, if present, after the first 5 min. then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none"> • Call poison control center or doctor immediately for treatment advice. • Do not induce vomiting unless told to do so by the poison control center or doctor. • Have person sip a glass of water if able to swallow. Do not give anything by mouth to an unconscious person.
IF INHALED:	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferable by mouth-to-mouth if possible. • Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a poison control center or doctor or going for treatment. In case of emergency, call poison control center at 1-800-222-1222 for treatment advice.	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measure against circulatory shock, respiratory depression and convulsions may be necessary.	

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET CONTENTS:

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS. MAY BE FATAL IF ABSORBED THROUGH THE SKIN OR SWALLOWED. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF INHALED. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or spray mist. Wear goggles or face shield and rubber gloves when handling. Wear a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or NIOSH approved Respirator with an organic (OV) cartridge or canister with any R, P, or HE prefilter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE):

Mixers, loaders and others exposed to this product must wear:

- Long-sleeve shirt and long pants
- Chemical-resistant apron
- Chemical-resistant gloves
- Shoes plus socks

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer system without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

DIRECTIONS FOR USE

[READ AND FOLLOW THE DIRECTIONS FOR USE ON THIS ACCOMPANYING INFORMATION SHEET.]

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ADHESIVE AND TACKIFIER PRESERVATION

ClearControl 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in water soluble and water dispersed adhesives such as animal glues, vegetable glues, natural rubber lattices, polyvinyl acetate, styrene-butadiene and acrylic lattices.

ClearControl 1.5% microbicide is recommended as a preservative for tackifiers derived from rosin and hydrocarbon resins. Add 0.43 – 1.65 pounds (195-750 grams) of ClearControl 1.5% to each 1000 pounds (454 kilograms) of fluid to provide 425 – 1675 ppm product.

AIR WASHER SYSTEMS/PAINT SPRAY BOOTHS

For use only in industrial air washing systems that maintain effective mist eliminating components. Add to the air washer sump, chill water sump or paint spray booth to ensure uniform mixing, 35 – 883 ppm ClearControl 1.5% microbicide (0.3 – 7.46 pounds or 4.5 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system) depending upon the severity of contamination to control microbial slime, bacteria, fungi, and algae, which cause fouling in industrial air washer systems and paint spray booths.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 – 883 ppm ClearControl 1.5% microbicide (1.26 – 7.46 pounds or 19 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm ClearControl 1.5% microbicide (0.3 – 1.86 pounds or 4.5 – 28 fluid ounces of ClearControl 1.5% per 1000 gallons of water) in the system weekly or as needed to maintain control. Clean badly fouled systems before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOES: When the system is noticeably fouled, apply 148 – 883 ppm ClearControl 1.5% microbicide (1.26 – 7.46 pounds or 19 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system).

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 – 219 ppm ClearControl 1.5% (0.3 – 1.86 pounds or 4.5 – 28 fluid ounces of ClearControl 1.5% per 1000 gallons of makeup water). Clean badly fouled systems before treatment is begun.

AQUEOUS COMPOSITIONS [*]

ClearControl 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in aqueous products such as: fiberglass sizing solutions and aqueous emulsions and dispersions including surfactants, stabilized oil/water emulsions, surface preparation compounds, foam control products, nutrient solutions and pesticide formulations. Add 0.5 – 3.3 pounds (227 – 1.5 kilograms) of ClearControl 1.5% per 1000 pounds (454 kilograms) of aqueous product to provide 500 – 3300 ppm product.

CONCENTRATES: ClearControl 1.5% microbicide should be added to concentrates at a level to ensure that the final use dilution of the product will contain 500 – 3300 ppm product.

BUILDING MATERIAL PRESERVATION

ClearControl 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in building materials such as mastics, caulks, joint cements, concrete admixtures, spackling and grouting. Add 0.43 – 1.65 pounds (195 – 750 grams) of ClearControl 1.5% to each 1000 pounds (454 kilograms) of fluid to provide 425 – 1675 ppm product.

COMMERCIAL PHOTOPROCESSING SYSTEM PRESERVATION [*]

ClearControl 1.5% microbicide is recommended to prevent microbial slime formation or accumulation in filters and ion exchange resin tanks of commercial photoprocessing systems. For the maintenance of a non-fouled system, use at 32 – 64 fluid ounces (2 – 4 pounds) per 1000 gallons fluid in the system once weekly, or as needed to maintain control. This corresponds to 250 – 500 ppm of ClearControl 1.5%. For a noticeably fouled system, use an initial dose of 64 – 148 fluid ounces (4 – 10 pounds) per 1000 gallons fluid to be followed by subsequent maintenance dosage. This corresponds to 500 – 1167 ppm ClearControl 1.5%. Increased frequency of treatment may be required depending on rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required,

filtration effectiveness, system design, etc. The preservative should be dispensed into the final rinse or used water collection tank.

DISPERSED PIGMENT PRESERVATION [*]

ClearControl 1.5% microbicide is recommended for the control of microbial slimes, bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin and montmorillonite clays, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselguhr used in paint and paper productions. Add 0.43 – 1.65 pounds of ClearControl 1.5% (195 – 750 grams) to each 1000 pounds (454 kilograms) of fluid to provide 425 – 1675 ppm product.

IN-CONTAINER PRESERVATION

ClearControl 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in liquid and semi-solid or solid household consumer, janitorial and industrial products, such as air fresheners, automotive products, fabric softeners, hand cleaners, polishers for floors and furniture, shoe polishes, moist sponges, mops and towelettes, spray starch, waxes and automotive polishes, hand and automatic dish detergents, stain pretreatment products, liquid laundry detergents and car washes, household cleaners, industrial cleaners, liquid hand soaps, oil and grease removers, carpet cleaners, carpet shampoos and spot removers, waterless hand cleaners, raw materials for cleaning products, surfactants and silicone emulsions.

Add 0.4 – 1.5 pounds of ClearControl 1.5% (180 – 680 grams) to each 1000 pounds (454 kilograms) of product to be treated to provide 400 – 1500 ppm ClearControl 1.5%. To ensure uniform mixing, slowly disperse ClearControl 1.5% into product with agitation.

ClearControl 1.5% microbicide may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 400 – 1500 ppm ClearControl 1.5%. Add 0.4 – 1.5 pounds of ClearControl 1.5% (180 – 680 grams) per 1000 pounds (454 kilograms) of product to be treated. To ensure uniform distribution, slowly disperse ClearControl 1.5% into product with agitation. Mix thoroughly until evenly dispersed throughout product.

Wet wipes containing a solution preserved with this product may not be used for personal care, as baby wipes, or for food contact.

INDUSTRIAL RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS

To maintain control of microbial slimes, bacteria, fungi and algae, add ClearControl 1.5% microbicide to the reservoir, recirculating line or some other point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 – 883 ppm ClearControl 1.5% microbicide (1.26 – 7.46 pounds or 19 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm ClearControl 1.5% microbicide (0.3 – 1.86 pounds or 4.5 – 28 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system) weekly or as needed to maintain control.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of microbial slimes, bacteria, algae, and fungi add ClearControl 1.5% microbicide to the tower basin, distribution box, or some other point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 – 883 ppm ClearControl 1.5% microbicide (1.26 – 7.46 pounds or 19 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm ClearControl 1.5% microbicide (0.3 – 1.86 pounds or 4.5 – 28 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system) weekly or as needed to maintain control.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS [*]

ClearControl 1.5% microbicide is recommended for the control of microbial slimes, bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE: When the system is noticeably fouled, apply 148 – 883 ppm ClearControl 1.5% microbicide (1.26 – 7.46 pounds or 19 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm ClearControl 1.5% microbicide (0.3 – 1.86 pounds or 4.5 – 28 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system) weekly or as needed to maintain control.

METAL CLEANING FLUID PRESERVATION

ClearControl 1.5% microbicide is recommended as a preservative for use in the manufacture and use of alkaline, acid, and emulsion-based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations. For addition to a metal cleaning concentrate, add ClearControl 1.5% at a level to ensure that the final use-dilution fluid will contain 425 – 1675 ppm product. For direct addition to a fouled system, add 54 – 214 fluid ounces (3.6 – 14.1 pounds) of ClearControl 1.5% to each 1000 gallons of use-dilution metal cleaning fluid every 3 to 4 weeks to provide 425 – 1675 ppm product. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed as an additive into the circulating use-dilution metal cleaning fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

METAL WORKING FLUID PRESERVATION

ClearControl 1.5% microbicide is recommended for the control of microbial slimes, bacteria and fungi in soluble and emulsifiable-type aqueous metalworking fluids. For the maintenance of a non-fouled system, use ClearControl 1.5% at 32 fluid ounces (2 pounds) per 1000 gallons of emulsion every 4 weeks or 32 – 148 fluid ounces per 1000 gallons emulsion (2 – 10 pounds) every 8-12 weeks to provide 250 – 1167 ppm product.

For a noticeably fouled system, use an initial dose of 64 – 148 fluid ounces (4 – 10 pounds) per 1000 gallons of emulsion to provide 500 – 1167 ppm product to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. Increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed as an additive into the circulating use dilution of the metalworking fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

OIL FIELD INJECTION WATERS

For the control of microbial slime-forming and sulfate-reducing bacteria in oil and gas field water systems, including enhanced recovery injection fluids, drilling, fracturing and completion fluids, slug treat with 67 – 332 ppm ClearControl 1.5% microbicide depending on the severity of contamination.

INITIAL DOSE: Add 166 – 332 ppm ClearControl 1.5% (6.9 – 13.9 gallons or 58.0 – 116.8 pounds ClearControl 1.5% per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

SUBSEQUENT DOSE: Add 67 – 166 ppm ClearControl 1.5% (2.8 – 6.9 gallons or 23.5 – 58.0 pounds ClearControl 1.5% per 1000 barrels of water) every seven days or as needed to maintain control.

PAINT AND COATING PRESERVATION

ClearControl 1.5% microbicide is recommended as an in container preservative for the control of bacteria and fungi in water-based coatings such as paper and wood coatings and paints used for architectural product finishes and special purpose coatings. Add 0.43 – 1.65 pounds (195 – 750 grams) of ClearControl 1.5% to each 1000 pounds (454 kilograms) of fluid to provide 425 – 1675 ppm product.

PHOTOPLATE PROCESSING, FOUNTAIN SOLUTIONS AND INK/INK COMPONENTS [*]

ClearControl 1.5% microbicide is recommended for the control of bacteria and fungi in photoplate processing chemicals, fountain solutions, and printing inks and ink components. ClearControl 1.5% should be added to achieve 0.1% to 0.3% on a total weight basis. ClearControl 1.5% should be added to fountain solution concentrates at a level to ensure that the final use-dilution of the product will contain 0.1% to 0.3% ClearControl 1.5% on a total weight basis. To ensure uniform mixing, add ClearControl 1.5% to the product slowly with agitation. The actual concentration required will depend upon the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

POLYMER LATEX PRESERVATION [*]

ClearControl 1.5% microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer latices including: acrylics, styrene/butadiene, carboxylated styrene/butadiene, ethylene/vinyl acetate; and biopolymers intended for industrial use, such as a xanthan gum, gum arabic, guar gum, protein-derived polymers, starches, casein-derived polymer latices, and solution polymers. Add 0.43 – 3.3 pounds of ClearControl 1.5% (195 grams – 1.5 kilograms) to each 1000 pounds (454 kilograms) of emulsion to provide 425 – 3350 ppm product.

NOTE: To ensure uniform mixing, add ClearControl 1.5% to latex or solutions slowly with agitation. The actual required concentrations will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected, and level of production required.

PULP AND PAPER MILLS [*]

For the control of microbial slimes, bacteria, algae and fungi, add ClearControl 1.5% microbicide to the Beater, Hydropulper, or Fan or Broke Storage Pumps or some other point in the system to ensure uniform mixing. Apply 0.44 to 1.5 pounds (7 – 23 fluid ounces) of ClearControl 1.5% microbicide per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Clean badly fouled systems before initial treatment.

RECIRCULATING ELECTRODEPOSITION SYSTEMS

METHOD OF ADDITION

ClearControl 1.5% microbicide is recommended as a tankside additive for the control of bacteria, fungi, and algae in recirculating electrodeposition systems and associated rinse systems. Alternatively, ClearControl 1.5% microbicide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

TANKSIDE ADDITION TO ELECTRODEPOSITION SYSTEMS

ClearControl 1.5% microbicide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, add 667 – 2333 ppm ClearControl 1.5% microbicide (6.7 – 23.3 gallons per 10,000 gallons of fluid in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 333 – 1000 ppm ClearControl 1.5% microbicide (3.3 – 10 gallons per 10,000 gallons of fluid in the system) weekly or as needed. A change of frequency of treatment may be required depending upon the rate of dilution of the preservative with

the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, and system design.

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS

INITIAL DOSE OF PAINT COMPONENTS

ClearControl 1.5% microbicide should be added to the resin, pigment or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 333 – 2333 ppm product.

SUPPLEMENTAL TANKSIDE DOSING OF ELECTRODEPOSITION SYSTEMS

If additional microbial control is necessary, ClearControl 1.5% microbicide may be added to the electrodeposition system tankside to supplement the microbicide incorporated through paint components.

INITIAL DOSE: If the system becomes noticeably fouled, add 667 – 2333 ppm ClearControl 1.5% (6.7 – 23.3 gallons per 10,000 gallons of fluid in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 333 – 1000 ppm ClearControl 1.5% (3.3 – 10 gallons per 10,000 gallons of fluid in the system) weekly or as needed.

NOTE: Regardless of the manner of incorporation, the total product concentration in the system should at no time exceed 2333 ppm ClearControl 1.5% or 23.3 gallons per 10,000 gallons of fluid in the system.

TEXTILE CHEMICALS PRESERVATION [*]

Use ClearControl 1.5% microbicide for the control of bacteria and fungi in the manufacture and storage of textile processing chemicals such as fiber lubricants, spin finishes, sizes, dyestuffs, textile printing inks, dispersants, thickeners, dye fixatives, hand builders and weighters. These textile processing chemicals are commonly used in the production of natural and synthetic fibers and fabrics.

Add 0.4 – 1.67 pounds (181 – 757 grams) of ClearControl 1.5% to each 1000 pounds (454 kilograms) of fluid to provide 400 – 1667 ppm product.

ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS

ClearControl 1.5% microbicide is recommended for the control of microbial slimes, bacteria and fungi in ultra filtration units and nonmedical/non-potable reverse osmosis systems. Use of ClearControl 1.5% microbicide in potable water or dialysis is prohibited. Add 10 – 333 ppm of ClearControl 1.5% microbicide into industrial ultra filtration or reverse osmosis systems by either continuous feed or periodic injection. Compatibility of ClearControl 1.5% microbicide with reverse osmosis membranes should be confirmed with membrane manufacturers.

For the control of bacteria and fungi in carbon beds, add 10 – 333 ppm of ClearControl 1.5% microbicide by either continuous or batch feed.

For periodic membrane cleaning, add 0.4 – 1.0 pounds (181 – 454 grams) of ClearControl 1.5% microbicide to every 120 gallons of cleaning solution to provide 400 – 1000 ppm product. Badly fouled systems should be cleaned before treatment is begun.

WATER BASED HYDRAULIC FLUID PRESERVATION

ClearControl 1.5% microbicide is recommended as a preservative for use in the manufacture and use of high water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume of mineral oil using an oil soluble emulsifying agent. For the maintenance of a non-fouled system, use ClearControl 1.5% at 110 – 135 fluid ounces (7.2 – 8.8 pounds) per 1000 gallons fluid every 8 weeks. This corresponds to 980 – 1200 ppm product.

For a noticeable fouled system, use an initial dose of 135 – 235 fluid ounces (8.8 – 15.4 pounds) per 1000 gallons fluid to be followed by subsequent maintenance dosage. This corresponds to 1200 – 2100 ppm product. Increased frequency of treatment may be required depending upon rate of dilution of the

preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed as an additive into the circulating use-dilution of the hydraulic fluid using a metering pump or by manual pouring any uniformly dispersed throughout the system.

WATER SYSTEMS

For the control of microbial slimes, bacteria, fungi and algae, add ClearControl 1.5% microbicide to air conditioner/refrigeration condensate water systems, can warmers, coal slurry systems, evaporative condenser water systems, hydrostatic sterilizer water systems, immersion ultrasonic tank water [*], industrial scrubbing systems, influent water filtration systems, laboratory equipment water baths[*], brewery pasteurizers, retort water systems, and industrial process water systems. Add ClearControl 1.5% microbicide at some point in the system to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm ClearControl 1.5% microbicide (1.26 – 7.46 pounds or 19 – 113 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm ClearControl 1.5% microbicide (0.3 – 1.86 pounds or 4.5 – 28 fluid ounces of ClearControl 1.5% per 1000 gallons of water in the system) weekly or as needed to maintain control.

WOOD AND WOOD PRODUCTS[*]

ClearControl 1.5% microbicide is recommended for the protection of wood and wood products, such as landscape timbers, fences, posts, pilings, cross ties, decks and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine, and other soft woods with 148 – 1000 ppm ClearControl 1.5% (1.26 – 8.4 pounds or 13 – 128 fluid ounces of ClearControl 1.5% per 1000 gallons) as an aqueous dip or pressure treatment for mold and mildew control. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

PESTICIDE STORAGE

Keep this product in the original container when not in use. Container must be stored and transported in an upright position to prevent spilling the contents.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING

{Use the following for product sold in nonrefillable containers:}

Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple Rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container $\frac{1}{4}$ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available, or reconditioning if appropriate, or puncture and dispose of in a sanitary landfill or by incineration.

{Use the following for product sold in refillable containers:}

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times. Then offer container for recycling if available, or reconditioning if appropriate, or puncture and dispose of in sanitary landfill, or by incineration, or by other procedures approved by state and local authorities.

CONDITIONS OF SALE AND WARRANTY

Clearon Corp warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions as defined under the Directions for Use on this label. Clearon Corp makes no other express or implied warranties, either of merchantability or fitness, for a particular use. Handling, storage, and use of the product by Buyer or User are beyond the control of Clearon Corp and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. To the extent permitted by law, neither Clearon Corp nor Seller shall be liable for consequential, special, or indirect damages resulting from the use, handling, application, storage, or disposal of this product.

[*] Not For Use in the State of California

Manufactured [by][for]:

Clearon Corp.

95 MacCorkle Avenue, SW

South Charleston, WV 25303

{for DOMESTIC labels only:}[Tel: 1-(800) 811-2327]

{for INTERNATIONAL labels only:}[Tel: 1-(304) 746-3000]

EPA Reg. No. 69470-40

EPA Est. No. _____

[Batch][Lot] No. _____