



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

June 7, 2019

Abigail T. D. Wacek
c/o Rust-Oleum Corporation
Technology Sciences Group, Inc.
1150 18th Street NW
Suite 1000
Washington, D.C. 20036

Subject: Label Amendment – *Adding optional graphics and alternate brand name:*
“Mold Blocking Primer”
Product Name: Mold Preventing Primer
EPA Registration Number: 69587-6
Application Date: 03/08/19
Decision Number: 550126

Dear Ms. Wacek:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. “To distribute or sell” is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

Page 2 of 2
EPA Reg. No. 69587-6
Decision No. 550126

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Stacey Grigsby by phone at 703.305.6440, or via email at grigsby.stacey@epa.gov.

Sincerely,

A handwritten signature in cursive script that reads "Stacey Grigsby".

Stacey Grigsby
Regulatory Risk Manager, 34
Regulatory Management Branch II
Antimicrobials Division (7510P)

Enclosure: 6/7/19 Accepted stamped label

{Note to Reviewer: Language in {braces} is informative. Language in [brackets] is optional.}


{MASTER LABEL}

MOLD PREVENTING PRIMER [PAINT, SPRAY, AEROSOL]

[Alternate Brand Name(s): Mold Blocking Primer]

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

See First Aid statement on back/side panel.



ACTIVE INGREDIENT:

3-Iodo-2-Propynyl Butyl Carbamate:	0.15%
Other Ingredients*:	99.85%
TOTAL:	100.00%

*Contains petroleum distillates, xylene or xylene range aromatic solvents

EPA Reg. No. 69587-6 EPA Est. No. xxxxx-xx-xxx

Manufactured by Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

Net Contents: Fluid Ounce/Fluid Millimeter/Grams: [6 oz, 178 ml, 170 g, 8 oz, 237 ml, 227 g, 10 oz, 297 ml, 283 g, 11 oz, 326 ml, 312 g, 12 oz, 355 ml, 340 g, 13 oz, 385 ml, 368 g, 14 oz, 415 ml, 397 g, 15 oz, 445 ml, 425 g, 16 oz, 473 ml, 453 g, 18 oz, 534 ml, 510 g, 20 oz, 592 ml, 567 g]

{Label to include any of the following optional statements/graphics}

- [30 Minute Fast Dry]
- [After]
- [Any Angle Spray with Comfort Tip]
- [Before]
- [Binds chalky siding, masonry, and metal]
- [Blocks crayon, lipstick, grease, handprints, and cedar tannins]
- [Blocks Odors]
- [Blocks Stains]
- [Color: White]
- [Dries in 30 minutes]
- [Dries Fast]
- [Excellent Hide]
- [Features an any angle spray feature that allows you to spray in any direction, even upside down.]
- [Great for small projects and touch-ups]
- [Great for: Priming inside, using as a complement to Mold Killing Primer brush product, use under wallcovering, priming outdoors, galvanized metal]
- [High Hide]
- [Interior/Exterior]
- [LeakSeal]
- [Made in [the] USA]

{Note to Reviewer: Language in {braces} is informative. Language in [brackets] is optional.}

- **[Mold Preventing Primer [paint, spray, aerosol]** is an EPA registered protective coating that can be used to paint over*] all existing mold, mildew, fungi, and odor causing bacteria and any other fungal organisms.]
- [Mold Preventing Primer contains an EPA registered antimicrobial to prevent the growth of mold and mildew on the paint film for up to 7 days.]
- [Mold Preventing Primer also aides in covering residual microbiological stains.]
- [Mold Preventing Primer is formulated for use on non-porous interior and exterior applications and may be applied in factories, warehouses, storage facilities, refrigerated storage facilities, office buildings, residential living, schools, hospitals, veterinary care facilities, elderly care facilities, prisons and correction facilities, wash houses, restaurants, fitness centers and locker rooms, attics, basements, window frames, bathrooms, wall cavities, baseboards, sub-floors and table tops.]
- [Mold Preventing Primer can be used with any topcoat including] [Zinsser PERMA WHITE®, Rust-Oleum Professional, Rust-Oleum Professional High Performance Protective Enamels, Rust-Oleum Stops Rust.]
- [Paint directly over existing mold, mildew, odor causing bacteria and other fungal organisms]
- [paint, spray, aerosol]
- [Professional]
- [Rust-Oleum High Performance]
- [Rust-Oleum Professional Enamels]
- [Rust-Oleum Professional High Performance Protective Enamels]
- [Rust-Oleum Professional High Performance]
- [Rust-Oleum Professional Primer]
- [Rust-Oleum Professional]
- [Rust-Oleum Stops Rust]
- [Sheen: Flat]
- [Solvent based]
- [Topcoat in 30 minutes]
- [Tough enough for industrial application.]
- [Trusted quality since 1921.]
- [Zinsser®]



{Note to Reviewer: Language in {braces} is informative. Language in [brackets] is optional.}



[Before]



[After]



[Do not use on new or unpainted aluminum, metal or vinyl siding.]

{Note to Reviewer: Language in {braces} is informative. Language in [brackets] is optional.}

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Check with all local, state and federal regulations prior to using or working with this product. Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.

Surface Preparation: *For applications that have existing wet, slimy, heavy soiled, gross filth, overgrowth or loose material on the substrate a pre-cleaning step is required. Physically or mechanically remove gross filth, heavy soil, overgrowth or loose material including dirt, grease and oily films before application and ensure the substrate is free of slime or excessive moisture to ensure long-term adhesion and product performance particularly on exterior surfaces. If mold or mildew needs to be removed prior to application, remove with a mildew remover that is EPA registered and let dry. Wear eye, skin, and NIOSH approved respiratory protection. Patch surface irregularities with appropriate patching compounds.

Application: Mold Preventing Primer is a ready to use product. Use at room temperature (70°F) in a well ventilated area –do not use in high humidity conditions. Shake can vigorously until ball inside can rattles. Turn upside down and continue shaking for one minute – shake occasionally during use. If ball does not rattle, do not strike the can. [Contact Rust-Oleum.] Spray 10-12” from object with short dusting strokes. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

Mold, Mildew, Fungi, and Odor Causing Bacteria Control: Mold Preventing Primer will reduce the growth of all mold, mildew and fungal organisms for up to 7 days. Apply Mold Preventing Primer generously and uniformly, ensuring that the surface is completely coated. Allow to dry.

Coverage: Approximately [8, 12, 14, 15, 16, 18, 20] sq. ft. per can.

Drytime: Dries in minutes; topcoat in 30 minutes with latex or oil-based paints. [For optimal protection, apply a topcoat that prevents mold & mildew on the paint film within 72 hours of application.] Full adhesion and hardness develops in 7 days. [For best results allow primer to cure overnight when applying strong solvent-base topcoats.]

Clean Up: Wipe off tip before storing. Clean up wet paint with xylol or mineral spirits.

ATTENTION! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and others by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

{Note to Reviewer: Language in {braces} is informative. Language in [brackets] is optional.}

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Storage: Store between 32-86F (0-30C) in a secure area inaccessible to children and away from food or feed.

Pesticide Disposal and Container Handling: Nonrefillable container. Do not reuse or refill this container. Do Not Puncture or Incinerate! If empty: Place in trash or offer for recycling, if available. If partly filled: Call your local solid waste agency for disposal instructions.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Wear gloves.

FIRST AID

IF ON SKIN:	<ul style="list-style-type: none">• Take off contaminated clothing• Rinse skin immediately with plenty of water for 15-20 minutes• Call a poison control center or doctor for treatment advice
IF SWALLOWED:	<ul style="list-style-type: none">• Immediately call a poison control center or doctor• Do not induce vomiting unless told to do so by a poison control center or doctor• Do not give any liquid to the person• Do not give anything by mouth to an unconscious person
Note to Physician: Contains petroleum distillate. Vomiting may cause aspiration pneumonia.	
For 24 hour emergency information on this product, call the National Pesticides Information Center: 1-800-858-7378 [(6:30 AM to 4:30 PM Pacific Time (PT))], seven days a week. During other times call the Poison Control Center: 1-800-222-1222. In case of emergency call 847-367-7700. Have the product container/label with you when calling Poison Control Center, doctor or going for treatment.	

[Proposition 65 Statement: This product contains a chemical(s) known to the State of California to cause cancer [and birth defects or other reproductive harm.]

ENVIRONMENTAL HAZARDS

This product is toxic to fish. To protect the environment, do not allow pesticide to enter or run off into storm drains, drainage ditches, gutters or surface waters. Applying this product in calm weather when rain is not predicted for the next 24 hours will help to ensure that wind or rain does not blow or wash pesticide off the treatment area.

PHYSICAL OR CHEMICAL HAZARDS

Extremely flammable. Contents under pressure. Keep away from fire, sparks, and heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum product support at 1-888-855-1774 for product replacement or a full refund of the purchase price. Refer to product number and batch code on bottom of can.

{Note to Reviewer: Language in {braces} is informative. Language in [brackets] is optional.}

[Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061 www.rustoleum.com]

Primer – MIR less than 0.70g O3/g of product; VOC less than 60% by weight.

(RUST-OLEUM LOGO)

RUST-OLEUM address

RUST-OLEUM PHONE NUMBER

{company website address}

(BATCH CODE XXXXXXXX ON CONTAINER)