



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Antimicrobials Division (H7510C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

69681-11

Date of Issuance:

JAN 19 1999

Term of Issuance:

Conditional

Name of Pesticide Product:

Clor Mor Trichlor
Cartridge

NOTICE OF PESTICIDE:

- Registration
- Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Allchem Industries, Inc.
6010 NW First Place
Gainesville, FL 32607

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/ reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
2. Change the label by revising the EPA Registration Number to read, "EPA Reg. No. 69681-11".
3. Submit two copies of the revised final printed label for the record.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Signature of Approving Official:

Robert S. Brennis, Acting PM 32

Date:

1/19/99

Center Panel

CLOR MOR TRICHLOR CARTRIDGE

ACTIVE INGREDIENT:
Trichloro-s-triazinetrione 99%
INERT INGREDIENTS: 1%

Provides 90% Available Chlorine

KEEP OUT OF REACH OF CHILDREN

DANGER

See First Aid Statement and Other
Precautions on Back Panel Before Opening Container

Net Contents:

ACCEPTED
JAN 19 1999
For The Federal Insecticide, Fungicide and
Rodenticide Act, as amended, for the
purpose of registration
LAB-11

Left Panel

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE. Causes irreversible eye damage and skin burns. May be fatal if absorbed through the skin. May be fatal if inhaled. Do not breathe dust or spray mists. Irritating to nose and throat. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, protective clothing and rubber gloves when handling this product. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible generation of fire and explosion.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

INSTRUCTIONS FOR USE IN EZ CHLOR TYPE FEEDER

Chlorination feed rate is regulated by the height of the water flowing within the cartridge and the amount of water flowing through the feeder.

1. Using a knife, slice off all #1 tabs at the bottom of the cartridge.
2. Use the tool supplied with feeder to punch out one hole on the canister corresponding to your pool size as outlined below.

GALLONS

- 5,000 A
- 10,000 B
- 15,000 C
- 20,000 D
- 25,000 E
- 30,000 F

3. Place the cartridge into the feeder and turn until it drops into place. Test water frequently using a reliable test kit to maintain a chlorine residual of between 1.0 - 1.5 ppm. If chlorine level is too high, reduce flow through the flow meter. If chlorine level is too low, increase flow through meter or slice off one of the #2 tabs. The next highest holes should be punched or additional tabs sliced off as needed to maintain the required chlorine residual. Flow valve should be adjusted to limit the flow of chlorine entering the water.

INSTRUCTIONS FOR USE IN GUARDEX TYPE FEEDER

Chlorination feed rate is regulated by the height of the cartridge in the feeder and the amount of water flowing through the feeder.

- 1. Using a knife, slice off all #1 tabs at the bottom of the cartridge.
- 2. Using the tool provided with the feeder, punch out the hole marked "VENT."
- 3. Using the following chart, choose the number that best approximates the size in gallons of your pool.

GALLONS

| | |
|--------------|---|
| 10,000 | 1 |
| 15,000 | 2 |
| 20,000 | 3 |
| 25,000 | 4 |
| 30,000 | 5 |
| 35,000 | 6 |
| 40,000 | 7 |

- 4. Insert the cartridge into the feeder to the number chosen above, and twist 1/6 of a turn to engage the raised steps.
- 5. Test water frequently using a reliable test kit to maintain a chlorine residual of between 1.0 and 1.5 ppm. If chlorine level is too high, reduce flow through the flow meter or twist cartridge out and reinsert one step higher at the next lowest number. If highest settings will not supply enough chemical, additional tabs should be sliced off in successive order and the cartridge repositioned so as to maintain the prescribed chlorine residual as determined by a reliable test kit.

**INSTRUCTIONS FOR USE IN
CHLOR-TROL TYPE FEEDER**

Chlorination feed rate is regulated by the height of the cartridge in the feeder and the amount of water flowing through the feeder.

- 1. Using a knife, slice off all #1 tabs at the bottom of the cartridge.
- 2. Using the tool provided with the feeder, punch out the hole marked "VENT."
- 3. Position the cartridge in the feeder with step marked "I" over the left adjustment guide and "II" facing you. Test water frequently using a reliable test kit to maintain a chlorine residual of between 1.0 - 1.5 ppm. If chlorine level is too high, reposition chlorinator one step toward "LESS." If chlorine level is too low, reposition chlorinator one step toward "MORE." If necessary, additional tabs may be sliced off and the cartridge raised or lowered on the steps so as to maintain the prescribed chlorine residual as determined by a reliable test kit.

INSTRUCTIONS FOR USE WITH FLOAT RINGS

Use of this cartridge in vinyl lined pools is not recommended, as particles of chlorine which may fall out can cause discoloration of vinyl. Before setting cartridge into float, use a sharp tool to slice off the three "1" tabs on the small end of the cartridge and punch one set of holes for each 5,000 gallons of pool capacity above 10,000 gallons. Additional holes may be punched to allow increased circulation so as to maintain a chlorine residual at all times of between 1.0 - 1.5 ppm as determined through the use of a reliable test kit. In addition, greater chlorination will occur if the floating cartridge is located in an area of high agitation, such as when it is tied with a piece of fishing line near the inlet of the pool's filtration system. Conversely, lesser chlorination may be accomplished by moving the assembly further from the area of high agitation.

PLEASE NOTE: The pH of these tablets is on the acid side and will tend to reduce the pH and alkalinity of the pool water. Proper pH should be maintained by periodic additions of sodium carbonate or sodium hydrogen carbonate.

To determine pool capacity, see Pool Calculator below.

POOL GALLON CALCULATOR
(all dimensions in feet)

Square or Rectangular

Length x Width x Average Depth x 7.5 = Gallons

Round or Oval

Length x Width x Average Depth x 5.9 = Gallons

Right Panel

STATEMENT OF PRACTICAL TREATMENT (FIRST AID)

IF SWALLOWED: Drink promptly large quantities of water. Do not induce vomiting. Avoid alcohol. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Keep product dry in tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat or open flame. In case of decomposition, isolate container if possible, and flood with large amounts of water to dissolve all material before discarding. Place in trash collection or dispose in approved landfill area.

LOT NO.

UN 2468

EPA REG. NO. 69681-RR

EPA EST. NO. 69681-TX-1

ALLCHEM INDUSTRIES, INC.

**6010 NW First Place
Gainesville, FL 32607**