

ILS. ENVIRONMENTAL PROTECTION AGENCY Office of Pestoide Programs Registration Division (H7505C)

401 TMT St., S.W. Washington, D.C. 20160 HPA Reg. Number

Date of Issuance NOV 17/997

70214-1

Lenn of Issuance

Conditional

NOTICE OF PESTICIDE:

<u>x</u> Registration ____ Reregistration

Name of Pesticide Product.

Sealife 1000 Antifouling Marine Paint

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Sealife Marine Coatings 51 Beaver Creek Place Suite 19120D Avon, CO 81620

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label at commerce. In any correspondence on this product always refer to the above EPA registration mamber.

On the basis of information furnished by the registrant, the above named posticide is hereby registered ferregistered under the Federal Inscrience. Form ode and Rodenticide Act

Registration is in no way to be constituted as an endotsement or recommendation of this product by the Agency - in order to protect health and the even month. the Administrator, on his motion, may at any time suspend or cancel the registration of a posticide in accordance with the Act. The acceptance of acts ware in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name of to as so at at has been revered by others

This product is conditionally registered in accordance with FIFRA sec. ?(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration/ reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
 - Make the following label changes:
 - Revise the EPA Registration Number to read, "EPA Reg. No. "70214-1".
 - Submit two copies of the revised final printed label for the record.

Signature of Approving Official

Marshall Swindell //

Acting Product Manager (33)

Regulatory Management Branch 1 Antimicrobial Division (7510W) Date:

MOV 17 997

LPA Form 8570.5

page 2 EPA Reg. No. 70214-1

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha L. Terry at (703) 308-6217.

Sincerely,

Marshall Swindell

Acting Product Manager (33) Regulatory Management Branch 1 Antimicrobial Division (7510W)

Enclosure

SeaLife 1000 ™

Antifouling Marine Paint

Active ingredient (cuprous oxide) Inert ingredients

39.95% 60.05%

TOTAL

100.00%

KEEP OUT OF REACH OF CHILDREN WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED

Drink promptly a large quantity of water. Avoid alcohol. Get medical

attention.

IF INHALED

Remove victim to fresh air. If not breathing give artificial respiration,

preferably mouth-to-mouth. Get medical attention.

IF ON SKIN

Wash with soap and water. Get medical attention.

IF IN EYES

Flush eyes with plenty of water for at least 15 minutes. Get medical

attention.

SEE BACK LABEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MI-G BY
SEALIFE MARINE COATINGS
51 BEAVER CREEK PLACE
SUITE 19122
AVON, COLORADO 81620
(970) 926-0437

ACCEPTED with COMMENTS in EPA Letter Dated:

NOV 17 1997

Under the Federal Insecticide, Plangicide, and Rodenticide Act as amended, for the pesucide, registered under EFA Reg. No.

ESTABLISHMENT NO XXXXXX EPA REGISTRATION NO XXXXXXXX

10214-1

ONE U.S. GALLON (3.79 LITERS)

4046

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, and other waters unless in accordance with requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewer treatment plant authority. For guidance, contact your State Water Board of Regional Office of the EPA.

PRECAUTIONS FOR SAFE HANDLING AND USE

Avoid contact with eyes. Use hand & eye protection (rubber gloves & goggles). May cause eye irritation. Do not ingest. Avoid contact with skin and open wounds. Wash hands at breaks and at end of work. Observe usual precautions when handling chemicals.

ACCEPTED

RESPIRATORY PROTECTION:

NO

VENTILATION:

YES

PROTECTIVE GLOVES:

YES

EYE PROTECTION:

YES, GOGGLES

OTHER PROTECTIVE EQUIPMENT:

NONE

with COMMENTS in EPA Letter Dated: NOV | 7 | 1997

Under the Federal Insecticide, Finigicide, and Rodendcide Act as amended, for the pesticide, registered under EPA Reg. No.

PHYSICAL OR CHEMICAL HAZARDS:

Flammable. Keep away from heat and open flame. Store at temperatures not exceeding $110^{\mbox{O}}$ F.

IF MATERIAL IS RELEASED OR SPILLED:

Let paint dry or take up with absorbent material (eg: sawdust, sand).

Suffe

STORAGE AND DISPOSAL

STORAGE:

Store at room temperature. Avoid temperatures above 110° F. Do not allow to freeze.

DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Pesticide Disposal: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

Under the Federal Insecticide,
Fungicide, and Rodentacide Acr as
amended for the posticide,
registered judger EPA Reg. No.

GENERAL DESCRIPTION

SERLIFE 1000 is an anti-fouling marine paint which provides protection to hulls in both salt and fresh water.

This paint has a unique, environmentally compatible formulation. It contains no silicones, arsenic, tributyl tin, lead, mercury, or toxic metals. It does not allow algaes, fungi, marine plant life or shellfish (barnacles, mussels, etc.) to attach to it due to its formulation and silky-smooth surface.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PREPARATION

A clean, dry surface is recommended. For maximum anti-fouling protection, surface should be clean, dry and solid. However, **SERLIFE 1808** can be applied on old paint provided the surface is sound. Undercoating is not needed.

HANDLING

Stir thoroughly. Use with adequate ventilation.

60f6

APPLICATION

SERLIFE 1000 may be applied by brushing, rolling or spraying. **SERLIFE 1000** offers superior adhesion on wet or oily surfaces without the necessity of pre-coating. It provides long life protection under water on steel, fiberglass, aluminum and wooden hulls. It adheres to tar, bitumen and other paints. It is highly elastic and ultra violet resistant

DRY TIME (HOURS)

	TO RECOAT	TO LAUNCH
90 ⁰ F	1	6
70 ^O F	2	8
50^{O_F}	4	24

CLEANUP

)

Mineral spirits or paint thinner.

STORAGE

Store at temperatures not exceeding 110°f. Do not allow to freeze.

COVERAGE

One gallon will coat approximately 300-400 square feet. A thin double coating provides optimal results.

THICKNESS PER COAT

PAINT	APPLIED	BY:
4 4 1 4 4	<u> </u>	

roller	1.2-1.6 mils
brush	1.2-1.6 mils
airspray	1.2-2.8 mils
airless spray	2-7.8 mils

VOC 130 grams per liter

ACCEPTED
with COMMENTS
in EPA Letter Dated:

NOV 17 1997

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

702.14-1