

70214-1

09/18/2000

1/4

SeaLife 1000™
Antifouling Marine Paint

Active ingredient (cuprous oxide)	39.95%
Inert ingredients	60.05%
TOTAL	100.00%

Contains Petroleum Distillates

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED	Call a doctor or get medical attention. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Avoid alcohol.
IF INHALED	Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.
IF ON SKIN	Wash with soap and water. Get medical attention.
IF IN EYES	Flush eyes with plenty of water for at least 15 minutes. Get medical attention.

SEE BACK LABEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MFG by
 SeaLife Marine Coatings
 La Quinta, CA 92253

EPA Reg. No. 70214-1

ONE U.S. Gallon
 (3.79 Liters)

RED

ACCEPTED

SEP 18 2000

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 70214-1

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS & DOMESTIC ANIMALS

DANGER: Harmful or fatal if swallowed, inhaled or absorbed through skin. Do not breathe dust, vapor or spray mist. Do not get in eyes, on skin, or on clothing. Causes eye and skin damage or skin irritation. While spraying paint, sanding or sand blasting boat surfaces, wear protective clothing such as rubber gloves, long-sleeved cotton shirt, long pants, hat, safety goggles and a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health.

ENVIRONMENTAL HAZARDS

Concentrate is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, and other waters unless in accordance with requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewer treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PRECAUTIONS FOR SAFE HANDLING AND USE

Avoid contact with eyes. Use hand & eye protection (rubber gloves & safety goggles). May cause eye irritation. Do not ingest. Avoid contact with skin and open wounds. Wash hands thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse. Observe usual precautions when handling chemicals.

RESPIRATORY PROTECTION:	NO
VENTILATION:	YES
PROTECTIVE GLOVES:	YES
EYE PROTECTION:	YES, SAFETY GOGGLES
OTHER PROTECTIVE EQUIPMENT:	NONE

PHYSICAL OR CHEMICAL HAZARDS: NONE

IF MATERIAL IS RELEASED OR SPILLED:

Let paint dry or take up with absorbent material (eg: sawdust, sand).

ACCEPTED

SEP 18 2000

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 70214-1

STORAGE AND DISPOSAL

STORAGE:

Store at room temperature. Avoid temperatures above 110° F. Do not allow to freeze.

DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Pesticide Disposal: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

GENERAL DESCRIPTION

SEALIFE 1000 is an anti-fouling marine paint which provides protection to hulls in both salt and fresh water.

This paint has a unique, environmentally compatible formulation. It contains no silicones, arsenic, tributyl tin, lead, mercury, or toxic metals. It does not support algae, fungi, marine plant life or shellfish (barnacles, mussels, etc.) growth due to its formulation and silky-smooth surface.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PREPARATION

A clean, dry surface is recommended. For maximum anti-fouling protection, surface should be clean, dry and solid. However, SEALIFE 1000 can be applied on old paint provided the surface is sound. Undercoating is not needed except on bare steel and aluminum hulls.

HANDLING

Stir thoroughly. Use with adequate ventilation.

APPLICATION

SEALIFE 1000 may be applied by brushing, rolling or spraying. SEALIFE 1000 offers superior adhesion on wet or oily surfaces without the necessity of pre-coating. It can be applied to dry, wet or humid surfaces. It provides long life protection under water on steel, fiberglass, aluminum and wooden hulls. It adheres to tar, bitumen and other paints. It is highly elastic and ultra violet resistant

ACCEPTED
SEP 18 2000
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 70214-1

4/4

DRY TIME (HOURS)

	<u>TO RECOAT</u>	<u>TO LAUNCH</u>
90° F	1	6
70° F	2	8
50° F	4	24

CLEANUP

THIN with Xylene if necessary

Mineral spirits or paint thinner.

COVERAGE

One gallon will coat approximately 300-400 square feet. A thin double coating provides optimal results.

THICKNESS PER COAT

PAINT APPLIED BY:

roller	2.0 mils
brush	2.0 mils
airspray	2.0 mils
airless spray	2.0-7.8 mils

VOC 130 grams per liter

ACCEPTED

SEP 18 2000

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 70214-1