



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

April 21, 2020

Keivan Mehrtabar
Regulatory Affairs Manager
Diacon Technologies Ltd.
c/o Lonza wood Protection
3941 Bonsal Road
Conley, GA 30288

Subject: Label Notification per PRN 98-10 – To add the qualifier statement “Not for use in California” to uses not approved in the State of California.
Product Name: Mycostat P51
EPA Registration Number: 70227-10
Application Date: February 12, 2020
Decision Number: 560809

Dear Mr. Mehrtabar:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Srinivas Gowda at 703-308-6354 or via email at gowda.srinivas@epa.gov.

Sincerely,

A handwritten signature in black ink that reads "Srinivas Gowda for".

Jacqueline Hardy
Product Manager – Team 34
Regulatory Management Branch II
Antimicrobials Division (7510P)

Enclosure: “Notification” Stamped EPA Label

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
CAUTION

Harmful if swallowed or absorbed through skin. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Some materials that are chemical-resistant to this product are [barrier laminate gloves.] Follow the instructions for category [G,] on the chemical-resistance category selection chart in the EPA Label Review Manual, 3rd Edition (EPA-735-B-03-001, August 2003).

Applicators, and other handlers must wear:

- long-sleeved shirt and long pants
- shoes and socks
- chemical-resistant gloves
- protective eyewear

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

USER SAFETY INSTRUCTIONS

Users must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users must remove clothing/ PPE immediately if pesticide gets inside, then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and shrimp. Do not apply directly to water. Do not contaminate water when disposing of equipment wastewater. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permit authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your local State Water Board or Regional Office of the Environmental Protection Agency.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Store in original container in a cool, dry place.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA regional office for guidance.

CONTAINER DISPOSAL:

Nonrefillable Container (equal to or less than 5 gallons): Nonrefillable container. Do not reuse or refill this container. Triple rinse container promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling (if available), or dispose of in a sanitary landfill, or by other state and local approved procedures.

Nonrefillable Container (greater than 5 gallons): Nonrefillable container. Do not reuse or refill this container. Triple rinse container promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling (if available) or reconditioning, or dispose of in a sanitary landfill, or by other state and local approved procedures.

Batch (lot) Code: _____

MYCOSTAT® P51
PRESERVATIVE FOR INDUSTRIAL
AND COMMERCIAL USE

ACTIVE INGREDIENT:

Propiconazole:

1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl] methyl] -1H-1,2,4-triazole 50.0%
OTHER INGREDIENTS: 50.0%
TOTAL 100.0%

Contains 4.17 lbs. active ingredient per gallon

KEEP OUT OF REACH OF CHILDREN
CAUTION

FIRST AID	
If swallowed	• Call a poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by the poison control center or doctor. • Do not give anything by mouth to an unconscious person.
If on skin or clothing	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a Poison Control Center or doctor for treatment advice.
If in eyes	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. • Call a Poison Control Center or doctor for treatment advice.
If inhaled	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
NOTE TO PHYSICIAN There is no specific antidote for Mycostat® P51. Give a saline laxative and supportive therapy.	
HOT LINE NUMBER: In case of chemical emergency, call CHEMTREC at 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.	

NET CONTENTS:

EPA REG. NO. 70227-10

70227-10

EPA Est. No. 70227-CAN-001 ☐

EPA Est. No. 82634-WA-001 ☐

EPA Est. No. 44637-FL-001 ☐

EPA Est. No. 62190-GA-001 ☐

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

DIACON Technologies Ltd.

135-11960 Hammersmith Way

Richmond BC Canada V7A 5C9

04/21/2020

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

SAPSTAIN AND MOLD CONTROL

Mycostat® P51 is used to control sap stain and mold in freshly cut hardwood and softwood lumber, poles, posts, timbers and other wood products. Examples of wood products include:

Logs: Fungal staining can be inhibited in freshly debarked logs used for log home construction, export, yarding prior to sawing and other purposes.

Wood Furnish: Engineered wood composites, such as particle board, wafer board, oriented strand board, and similar products can be protected from fungal discoloration during storage by treatment with Mycostat® P51.

Wood Chips/Saw Dust (Not for use in California): Treatment of wood chips, saw dust or other similar by products intended for papermaking (Not for food grade/food contact paper or paper board) reduces fungal discoloration and lowers bleaching requirements for finished paper products.

Plywood Veneer: Treatment with Mycostat® P51 is effective for freshly peeled green veneer and other similar plywood furnish that can be especially subject to sap stain and mold development that can interfere with appearance or laminating adhesive performance.

Mycostat® P51 is used to control sap stain and mold in freshly cut hardwood and softwood lumber, logs, poles, posts, and timbers. Mycostat® P51 is applied by dipping or spraying the wood until complete surface wetting is achieved.

For *bulk dip tanks*, Mycostat® P51 is diluted by using 0.06 gallons (0.5 gallon Mycostat® P51 in 800 gallons of water) to 0.5 gallon Mycostat® P51 in 100 gallons of water. Agitate vigorously until completely dispersed.

For *conventional spray systems*, a 0.12% to 0.9% Mycostat® P51 spray solution is used. For example, in a 100 gallon day tank, 0.12 to 0.9 gallons of Mycostat® P51 are added to the day tank and then enough water is added to bring the total volume up to 100 gallons of solution.

In *electrostatic spray applications*, Mycostat® P51 dilution is not required, treatment strength is varied by number of application nozzles used and line speed. Rates, for all applications used will vary according to temperature, humidity, wood moisture, storage conditions, etc.

Remove sawdust and other debris from treating solution on a regular basis to maintain correct concentration of Mycostat® P51 in application solution. To prevent fungal attack below the surface of the wood, freshly sawn lumber must be treated within 24 hours. Treated lumber must be protected from rain and removed from direct soil/ground contact.

DECAY AND STAIN PROTECTION (Not for use in California)

DESCRIPTION: Mycostat® P51 is a wood preservative concentrate that requires dilution with water prior to use on wood products to protect against decay (brown and white rot) and staining fungi (blue stain).

Product Uses: For application to millwork, shingles, shakes, siding, plywood, and structural lumber & composites that are used in above ground applications only. Do not use on wood which will come in contact with food.

Wood Preparation: Machine, cut, glue, and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Wood must be clean and dry before treatment. Wood for pressure treatment must be kiln dried or air seasoned to moisture content of about 25% or less, that will permit adequate penetration of preservative during treatment.

Treatment: Apply by immersion, roller coater, flood, spray, brush or pressure treatment processes (double vacuum, full-cell or modified full-cell). For non-pressure application methods, mix 1-2 gallons of Mycostat® P51 with water to achieve 100 gallons of treating solution at the concentration of 0.5% -1% a.i., respectively. Wood products to be treated by the bundle-dipping process must be completely immersed for three (3) minutes. Individual wood pieces treated by immersion, roller-coated or flood must be treated for at least fifteen (15) seconds. Coverage for brush and spray application is approximately 150 square feet per gallon of treating solution, but varies by the species and condition of the wood. Pressure treatment must be performed according to the methods described in the American Wood Preservers Association (AWPA) Standards. A minimum propiconazole retention level of 0.025 pounds per cubic foot (pcf) is recommended. All treated wood must be held on the drip pan until drippage has stopped. Any surface, cut after first treatment must be retreated using 1% a.i. concentration solution.

Finishing: Before glazing, staining, painting, varnishing, or application of water repellents, treated wood must be completely dry and odor-free. For non-pressure applications, allow 4-8 hours drying time under average temperature and humidity conditions; treated wood can be heat dried for plant protection. Pressure treated wood requires drying after treatment to a moisture content suitable for the type of coating to be applied.

Clean-up: Use water to remove wet Mycostat® P51 wood preservative from all surfaces, brushes and rollers.

COATINGS, CAULKS, SEALANTS, ADHESIVES, AND INKS (Not for use in California)

This product may not be used in food grade coatings, adhesives, paper and paperboard, which will come into contact with food.

Sufficient mixing to ensure adequate dispersion of the biocide is required. Mycostat® P51 must be used at levels between 0.1 and 2.4% based on the total weight of the formulation to inhibit fungal disfigurement and deterioration. For solvent-based formulations, Mycostat® P51 can be dissolved in aromatic solvents or combination of aromatic and aliphatic solvents and added in the ledown or added directly to the finished product. For water-thinned latex emulsion formulation, Mycostat® P51 can be premixed with the wetting agent and added to the pigment slurry or simply added to the let down or finished product.

METALWORKING FLUIDS (Not for use in California)

Use Mycostat® P51 to inhibit fungal degradation of water based and water emulsifiable cutting fluids and coolants used in metalworking operations. Prior to using metalworking fluids, add Mycostat® P51 to the fluid concentrate or to the diluted metalworking fluid in an amount which will provide 50 to 700 ppm active ingredient in the diluted fluid.

TEXTILES, FABRICS, CANVAS AND CORDAGE (Not for use in California)

For the control of odor and stain causing microorganisms in textiles, fabrics and fibers of the following products: APPAREL: aprons, bibs, dresses, footwear (including socks and innersoles), gloves (non-medical), gowns (medical & consumer), hosiery, intimate apparel, linings, shirts, sports apparel, uniforms (service, medical, dental, sports). FURNISHINGS: blankets, cloths, curtains, draperies, furniture coverings, linens (towels, sheets, pillowcases), mattress & pillow ticking, mattress pads, napkins, shower curtains. BUILDING MATERIALS: awnings, boat covers, carpet (fibers and backing), cordage, tents, tarpaulins, wall coverings, yarn.

Addition of up to 2000 ppm of this active ingredient (0.4% of product), based on weight of goods, can inhibit the growth of mold and mildew that cause stains, odors and product degradation in textiles, fabrics and fibers composed of acetate, acrylic, acrylonitrile butadiene styrene, natural fibers (cotton, paper, wool, etc.), nitrile copolymers, nylon, polyester, polyethylene, polypropylene, rayon, rubber (natural & synthetic), coatings/finishes composed of silicone, urethane or vinyl applied to such materials. The material must be added at an appropriate manufacturing step to ensure adequate mixing and complete, uniform coverage of the treated material. Product can be applied by dye incorporation, pad, exhaust, or spray application.

NOTICE OF WARRANTY AND DISCLAIMER

Diacon Technologies Ltd. warrants that this product conforms to the chemical description on the label thereof and is reasonably fit for purposes stated on such label only when used in accordance with the directions under normal use conditions. It is impossible to eliminate all risks inherently associated with the use of this product. Ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond the control of Diacon Technologies Ltd. In no case shall Diacon Technologies Ltd. be liable for consequential, special or indirect damages resulting from the use or handling of this product. All such risks shall be assumed by the Buyer. DIACON TECHNOLOGIES LTD. MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE NOR ANY OTHER EXPRESS OR IMPLIED WARRANTY EXCEPT AS STATED ABOVE.