70506-15

7/17/2002

Page 1321

JUL 17 2002

Ms. Elizabeth Anne Brown Agent for UNITED PHOSPHORUS, INC. ChemReg International, LLC 1990 Old Bridge Road Suite 201 Lake Ridge, VA 22192-2383

Dear Ms. Brown:

This is in response to your request dated June 18, 2002 to change the primary brand name for EPA Registration 70506-15 from <u>Ouik-Fume Bags</u> to:

WEEVIL-CIDE GAS BAGS

Your request for the name change is accepted and the change will be made to the Agency's records. All future correspondence on this product should reference the new name.

Sincerely yours,

/s/

Sherada D. Hobgood Notifications Review Coordinator Registration Division (7505C)

						937
Please read instructions on reverse		ed States	<u>F</u>	Registrat	ion	60, Approval expires 5-31-98 OPP Identifier Number
SEPA	Environmental	Protection ton, DC 20460		Amendm X Other	ent	
•			Pesticide - Secti	on l		•
. Company/Product Number	<u> </u>		2. EPA Product	·····	3. Propo	sed Classification
70506-15			S. Oonnithan PM #			ne Restricted
 Company/Product (Name) Quik-Fume Bags / WEEVIL-CID 	E GAS BAGS		Insecticide Branc	h		
5. Name and Address of Applic Jnited Phosphorus, Inc. 123 Riverview Plaza Trenton, NJ 08611	ant (Include ZIP Code)					FRA Section 3(c)(3) position and labeling
Check if this is a new addi	ress		Product Name			
				· · · · · · · · · · · · · · · · · · ·		
Amendment – Explain bek		Se	ction - II	ed labels in respor	nse to	······································
Resubmission in response			Agency let	-		
X Notification - Explain belo	w		Other – Ex	kplain below		
This notification is consistent will to the labeling or the confidentia alse statement to EPA. I furthe product may be in violation of Fl	I statement of formula c r understand that if this	of this product. notification is n	I understand that it is a ot consistent with the te	violation of 18 U.S erms of PR Notice	S.C. Sec. 1 [,] 98-10 and	001 to willfully make any 40 CFR 152.46, this
		Se	ection III			·
Material This Product Will be Child-Resistant Packaging	Packaged in: Unit Packaging		Water Soluble Packag	ing	2 Тиро	of Container
Yes No	Yes		Yes No		X Mi	etal astic
	If "Yes"	No por	If "Yes"	No por		ass
	Unit Packaging wgt.	No. per container	Package wgt	No. per container		per her (Specify)
Location of Net Contents Info	ormation Container	4. Size(s) Re	etail Container		On Label	bel directions
. Manner in Which Label is Aff	ixed to Product	Lithogra Paper g	glued	Other		
				·		
		Se	ection IV			
	ems directly below for ic	lentification of i				
lame	ems directly below for ic	<i>lentification of i</i> Title Chem F		Telep		<i>is application.</i> , nclude Area Code)
lame lizabeth Anne Brown certify that the statements I hav acknowledge that any knowing! oth under applicable law	Ce e made on this form and	tentification of i Title Chem F Authoriz rtification all attachments rement may be p	ndividual to be contacte Reg International, LLC red agent 5 thereto are true, accura	Telep 703-4 ate and complete.	hune No. (1 92-7905	nclude Area Code) Date Application Received
. Contact Person (Complete it lame Elizabeth Anne Brown certify that the statements I hav acknowledge that any knowing oth under applicable law . Signature	Cer re made on this form and y false or misleading star	tentification of i Title Chem F Authoriz rtification all attachments tement may be p 3. Title ChemRi	ndividual to be contacte Reg International, LLC red agent 5 thereto are true, accura	Telep 703-4 ate and complete.	hune No. (1 92-7905	nclude Area Code) Date Application
lame lizabeth Anne Brown certify that the statements I hav acknowledge that any knowingl oth under applicable law . Signature	Cer re made on this form and y false or misleading star	tentification of i Title Chem F Authoriz rtification all attachments tement may be p 3. Title ChemRi	ndividual to be contacte Reg International, LLC red agent s thereto are true, accura punishable by fine or imp reg International, LLC. red Agent	Telep 703-4 ate and complete.	hune No. (1 92-7905	nclude Area Code) Date Application Received

•

•

EPA Form 8570-1 (Rev. 8-94) Previous editions are obsolete.

-

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS KEEP OUT OF REACH OF CHILDREN DANGER/POISON

Aluminum phosphide powder, may be latal if swallowed. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke while handling aluminum phosphide lumigants. If a sealed contakter is opened, or if the material comes into contact with moisture, water or acids, extremely toxic phosphine gas will be released. If a garlic odor is detected, refer to the Applicator and Worker Exposure section of the applicator's manual for appropriate monitoring procedures. Pure phosphine gas is odorless; the odor is due to a contaminant. Since an odor may not be detected under certain circumstances, the absence of a garlic odor does not mean that phosphine gas is absent. Observe proper application, aeration, reentry and disposal procedures specified elsewhere in the labeling to prevent overexposure.

NOTE TO PHYSICIAN

Aluminum phosphide bags react with motsture in the air, acids and many other liquids to release phosphine gas. Mild exposure by inhalation causes malaise, ringing of ears, fatigue, nausea and pressure in the chest which are relieved by removal to fresh air.

Moderate poisoning causes weakness, vomiting, epigastric pain, chest pain, diarrhea and duspnea.

Severe poisoning may occur in a few hours to several days, resulting in pulmonary edema and may lead to dizziness, cyanosis, unconsciousness and death.

in sufficient quantity, phosphine affects the liver, kidneys, kings, nervous system and circulatory system. Inhibition can cause lung edema and hyperemia, small perivascular brain hemorrhages and brain edema. Ingestion can cause king and brain symptoms, but damage to the viscera is more common. Phosphine polsoning may result in (1) pulmonary edema; (2) liver elevated serum GOT, LDH and alkaline phosphatase, reduced prothrombin, hemorrhage and jaundice; and (3) liddney hematuria and anuria. Pathology is characteristic of hypoxia. Frequent exposure over a period of days or weeks may cause polsoning. Treatment is symptomatic. For further information, contact the nearest National Polson Control Center.

ENVIRONMENTAL HAZARDS

This product is very highly toxic to wildlife. Non-target organisms exposed to phosphine gas in burrows will be killed. Do not apply directly to water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water by cleaning of equipment or disposal of waste.

ENDANGERED SPECIES RESTRICTIONS - Refer to the applicator's manual. PHYSICAL AND CHEMICAL HAZARDS

Aluminum phosphide will release phosphine gas if exposed to moisture from the air or if it comes into contact with water, acids and many other liquids. Piling of the bags may cause a temperature increase and confine the release of gas so that ignition could occur,

Always open containers of aluminum phosphide products outdoors or indoors, in the presence of appropriate mechanical ventilation as under certain conditions they may flash upon opening. When opening, point the container away from the face and body, and slowly open. Although the chances for flash are very remote, never open these containers in a flammable atmosphere. These precautions will also reduce the applicator's exposure to phosphine gas.

Pure phosphine gas is practically insoluble in water and oils and is stable at normal fumigation temperatures. However, it may react with certain metals and cause corrosion, especially at higher temperatures and relative humidities. Metals such as copper, brass and other copper alloys and precious metals, such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors, smoke detectors, brass sprinkler heads, batteries, battery chargers, fork lifts, temperature monitoring devices, computers, calculators and other electrical equipment should be protected or removed before fumigation.

RESTRICTED USE PESTICIDE DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC PHOSPHINE GAS

For retail sale to and use only by certified applicators for those uses covered by the applicator's certification or persons trained in accordance with the applicator's manual working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on site or on the premises. Read and follow the label and the applicator's manual which contains complete instructions for safe use of this pesticide.



Aluminum Phosphide Fumigant

A fumigant for use against listed insects which infest listed raw agricultural commodilies, specified processed foods and animal feeds.

PRECAUCION AL USUARIO: Si usted no lee ingles no use este productn hasta que la eliqueta se le haya sido explicado ampliamente.



STATEMENT OF PRACTICAL TREATMENT

SYMPTONS of overexposure to phosphine are headache, dizziness, nausea, difficult breathing, vomiting and diarrhea. In all cases of overexposure, get immediate medical attention. Take the victim to a doctor or emergency treatment facility. If the gas from aluminum phosphide is INHALED: Move exposed person to fresh air. Keep person warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person. If aluminum phosphide powder is SWALLOWED: Drink or administer one or two glasses of water and induce vomiting by fouching back of throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert. If aluminum phosphide powder gets on SKIN: Brush materiat off clothes and shoes in a well ventilated area. Allow clothes to availate in a ventilated area prior to laundering. Wash contaminated bare skin thoroughly with soap and water. If in EYES: Flosh with plenty of water. Get medical attention immediately.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS CONTENTS: 10 BAGS (34 grams each) NET WEIGHT: 340 Grams (12 oz.)

Manufactured for: United Phosphorus Inc.

423 Riverview Plaza, Trenton, NJ 08611 E.P.A. Registration No. 70506-15, E.P.A. Establishment No. 41876-1Y-1 @ Registered trademark of United Phosphorus Inc.

NOTIFICATION

JUL 17 2002

DIRECTIONS FOR USE

"It is a violation of federal law to use this product in a manner inconsistent with its labeling."

The Applicator's Manual for Weevil-Cide[®] Tablets, Pellets and Gas Bags is a part of labeling. Refer to it for application procedures and other information necessary to properly use Weevil-Cide[®] Gas Bags.

STORAGE AND DISPOSAL

STORAGE

Store in a dry, well ventilated area away from heat, under lock and key. Post as a pesticide storage area. Do not contaminate water, food or feed by storing pesticides in the same areas used to store these commodities. Do not store in buildings where humans or domestic animals reside.

DISPOSAL

Do not contaminate water, food or feed by storage and disposal.

Unreacted or partially reacted aluminum phosphide is acutely hazardous. Improper disposal of excess pesticides or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your state pesticide or environmental control agency or the hazardous waste representative at the nearest E.P.A. regional office for guidance. For specific instructions, refer to the Spill and Lgak Procedures in the applicator's manual.

Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your state pesticide or environmental control agency or the hazardous waste representative at the nearest E.P.A. regional office for guidance.

Dispose of empty cans in a sanitary landfill or by other approved state and local procedures.

If properly exposed, the spent residual dust remaining after a furnigation with aluminum phosphide will be grayish-white and contain only a small amount of unreacted material. However, residual dust from incompletely exposed aluminum phosphide will require specialcare.

Bags containing spent aluminum phosphide may be collected and disposed in a sanitary landfill, inclinerator or other approved sites or by other procedures approved by federal, state or local authorities.

For complete disposal, spill and leak procedures refer to the Applicator's Manual for Weevil-Cide[®] Tablets, Pellets and Gas Bags.

SG/RP/03/04/97

For retail sale to and use only by certilied applicators for those uses covered by the applicator's certification or persons trained in accordance with the applicator's manual working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on site or on premises. Read and follow the label and the Applicator's Manual which contain complete instructions for safe use of this pesticide.



Tablets, Pellets and Gas Bags Aluminum Phosphide Fumigant

A fumigant for use against listed insects which infest listed raw agriculture	iral \
commodities, specified processed foods and animal feeds	
Active ingredient: Aluminum Phosphide	. 60.0%
Inert Ingredients	. 40.0%

PRECAUTION AL USUARIO: Si usted no lee ingles no use este producto hasta que la etiqueta se le haya sido explicado ampliamente.

KEEP OUT OF REACH OF CHILDREN DANGER/PELIGRO-POISON

PRACTICAL TREATMENT STATEMENT

SYMPTOMS of overexposure to phosphine are headache, dizziness, nausea, difficult breathing, vomiting and diarrhee. In all cases of overexposure, get immediate medical attention. Take the victim to a doctor or emergency treatment facility.

If the gas from aluminum phosphide is INHALED: Move exposed person to fresh air. Keep the person warm and make sure the person can breathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

If aluminum phosphide tablets, pellets, granules or powder are SWALLOWED: Drink or administer one or two glasses of water and induce vorniting by touching back of throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If tablets, petiets, granules or powder of aluminum phosphide get on SKIN: Brush material off clothes and shoes in a well ventilated area. Allow clothes to aerate th a ventilated area prior to laundering. Wash contaminated bare skin thoroughly with soap and water.

If in EYES: Flush with plenty of water. Get medical attention immediately.

Manufactured for: UNITED PHOSPHORUS INC.

423 Riverview Plaza, Trenton, NJ 08611 EPA Registration Nos. 70506-13, 70506-14, and 70506-15

10. SPILL AND LEAK PROCEDURES

2. 2

Cide[®] Gas Bag's container cannot be researed for future use: Storage and managing instructions will be given in detail later in the Applicator's Manual.

1

S

SAFETY RECOMMENDATION SUMMARY

1. Carefully read the labeling and follow instructions.

2. Never fumigate alone from inside the storage structure.

- Person supervising must be a certified fumigator, and the personnel assisting must be trained in the use of aluminum phosphide. Never allow uninstructed personnel to handle aluminum phosphide.
- Approved respiratory protection must be available for the fumigation of structures from within.
- Wear dry gloves of cotton or other materials if contact with Weevil-Cide® Tablets, Pellets or the powder from Gas Bags is likely. Aerate used gloves and other contaminated clothing in a well ventilated area prior to laundering. Wash hands thoroughly after using Weevil-Cide®.
- 6. Open fumigant container in open air only. Never open in a flammable atmosphere.
- 7. Do not allow Weevil-Cide® to contact water or pile up.
- 8. Dispose of empty containers and spent residual dust in a manner consistent with the label instructions.
- 9. Post warning placards on fumigated areas.
- Prior to fumigation, notify appropriate company employees. Provide to local officials (fire department, rescue squad, police, etc.) on an annual basis, relevant safety information for use in the event of an emergency.
- 11. Phosphine fumigants are not to be used for vacuum fumigations.
- 12. Exposure to phosphine must not exceed the eight hour TWA of 0.3 ppm during application or a ceiling concentration of 0.3 ppm after application is completed.
- 13. Furnigated areas must be aerated to 0.3 ppm phosphine or less prior to reentry by unprotected workers.
- 14. Finished foods and feeds that have been fumigated with Weevil-Cide® must be aerated for 48 hours prior to offering to the end use consumer.
- 15. Transfer of a treated commodity to another site without complete aeration is permissible provided that the new storage site is placarded if the phosphine concentration is above 0.3 ppm.
- Keep containers of Weevil-Cide[®] tightly closed except while removing product for application.
- 17. Protect materials containing metals such as copper, nilver, gold and their alloys and salts from corrosive exposure to phosphir.e.
- 18. Tablets, Pellets and Gas Bags must not come in contact with any processed food, except that tablets and pellets may be added directly to processed brewers rice, malt and com grits used in the manufacture of beer.

- 19. Do not use aluminum phosphide containers for any purpose other than recycling or reconditioning.
- OSHA recommends pre-exposure screening of employees to detect impaired pulmonary function. They recommend that any employee developing this condition be referred for medical examination.

SECTION 2

PRECAUTIONARY STATEMENTS

A. HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Aluminum phosphide powder, granules, tablets or pellets may be fatal if swallowed. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke while handling aluminum phosphide fumigants. If a sealed container is opened or if the material comes into contact with moisture, water or acids, extremely toxic phosphine gas will be released. If a garlic odor is detected, refer to APPLICATOR AND WORKER EXPOSURE section of the applicator's manual for appropriate monitoring procedures. Pure phosphine gas is odorless; the odor is due to a contaminant. Since an odor may not be detected under certain circumstances, the absence of a garlic odor does not mean that phosphine gas is absent. Observe proper application, aeration, reentry and disposal procedures specified elsewhere in the labeling and in this manual to prevent overexposure.

B. PRACTICAL TREATMENT STATEMENT

SYMPTOMS of overexposure to phosphine are headache, dizziness, nausea, difficult breathing, vomiting and diarrhea. In all cases of overexposure, get immediate medical attention. Take the victim to a doctor or emergency treatment facility.

If the gas from aluminum phosphide is INHALED: Move exposed person to fresh air. Keep person warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth to mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

If aluminum phosphide tablets, pellets, granules or powder are **SWALLOWED**: Drink or administer one or two glasses of water and induce vomiting by touching back of throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If tablets, pellets, granules or powder of aluminum phosphide get on SKIN: Brush material off clothes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to laundering. Wash contaminated bare skin thoroughly with soap and water.

- If in EYES: Flush with plenty of water, Get medical attention immediately.
- C. NOTE TO PHYSICIAN (We recommend that this section be given to the attending physician):

Aluminum phosphide lablets, pellets, granules or powder react with moisture in the air, acids, and many other liquids to release phosphine gas. Mild exposure by inhalation causes malaise, ringing of ears, fatigue, nausea and pressure in the chest which is relieved by removal to fresh air.

3

 σ

Moderate poisoning causes weakness, vomiting, epigastric pain, chest pain, diarrhea and dyspriea.

Severe poisoning may occur in a few hours to several days, resulting in pulmonary edema and may lead to dizziness, cyanosis, unconsciousness and death.

In sufficient quantity, phosphine affects the liver, kidneys, lungs, nervous system and circulatory system. Inhalation can cause lung edema and hyperemia, small perivascular brain hemorrhages, and brain edema. Ingestion can cause lung and brain symptoms, but damage to the viscera is more common. Phosphine poisoning may result in (1) pulmonary edema; (2) liver elevated serum GOT. LDH and alkaline phosphatase; reduced prothrombin; hemorrhage and jaundice; and (3) kidney hematuria and anuria. Pathology is characteristic of hypoxia. Frequent exposure over a period of days or weeks may cause poisoning. Treatment is symptomatic. For further information, contact the national poison control center.

D. PHYSICAL AND CHEMICAL HAZARDS

Aluminum phosphide in tablets, pellets, bags and partially spent dust will release phosphine gas if exposed to moisture from the air or if it comes into contact with water, acids and many other liquids. Piling of tablets, pellets or dust from their fragmentation may cause a temperature increase and confine the release of gas so that ignition could occur.

Hydrogen phosphide (phosphine) air mixtures at concentrations above the lower flammable limit may ignite spontaneously. Ignition of high concentrations of hydrogen phosphide can produce a very energetic reaction. Explosions can occur under these conditions and may cause severe personal injury. <u>Never allow the buildup of hydrogen phosphide to exceed</u> <u>explosive concentrations</u>. Do not confine spent or partially spent dust from metal phosphide fumigants as the slow release of hydrogen phosphide from this material may result in formation of an explosive atmosphere.

Always open containers of aluminum phosphide products outdoors or indoors in the presence of mechanical ventilation that vents immediately outside, as under certain conditions, they may flash upon opening. When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for flash are very remote, never open the container in a flammable atmosphere. These precautions will also reduce the applicator's exposure to phosphine gas.

Pure phosphine gas is practically insoluble in water and oils and is stable at normal fumigation temperatures. However, it may react with certain metals and cause corrosion, especially at higher temperatures and relative humidities. Metals such as copper, brass and other copper alloys, and precious metals such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors, smoke detectors, brass sprinkler heads, batteries and battery chargers, fork lifts, temperature monitoring systems, electrical switchgear, communication devices, computers, calculators and other electrical equipment should be protected or removed before fumigation.

Phosphine gas will also react with certain metallic salts and therefore, sensitive items such as photographic film, some inorganic organets, etc. should not be exposed.

SECTION 3

DIRECTIONS FOR USE

A. GENERAL

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

- 1. Weevil-Cide® Tablets, Pellets and Gas Bags are RESTRICTED USE PESTICIDES due to the acute inhalation toxicity of phosphine gas. These products are for retail sale to and use only by certified applicators for uses covered by the applicator's certification or persons trained in accordance with the manual, working under the direct supervision and in the physical presence of the applicator. Physical presence means on site or on the premises. Read and follow the label and the manual which contains complete instructions for the safe use of this pesticide.
- Weevil-Cide[®] is a highly hazardous material and should be used only by individuals trained in its proper use. Before using, read and follow the precautions and directions contained in the Weevil-Cide[®] label and in the applicator's manual.

Persons working with Weevil-Cide[®] should be knowledgeable of the hazards of this chemical and trained in the use of required respiratory equipment and detector device, emergency procedures and use of the fumigant.

Additional copies of the applicator's manual are available from:

United Phosphorus Inc. P.O. Box 570. Exton, Pa. 19341

- 3. At least two persons trained in the use of aluminum phosphide must be present during furnigation of a structure if entry into the structure is required for application of the furnigant. Two trained persons must also be present during reentry into furnigated or partially aerated structures. Only one trained person is required to be present when Weevil-Cide[®] is applied from outside the area to be treated.
- 4. Ship holds, barges, containers on ships, railroad cars and containers shipped piggyback by railway may be fumigated in transit. However, trucks, vans, trailers and similar transport vehicles cannot be moved over public roads and highways until they are aerated and the warning placards removed.
- Do not furnigate commodities with Weevil-Clde^e when commodity temperature or the temperature to which aluminum phosphide is exposed is below 41°F (5°C).
- 6. The site to be fumigated must first be inspected to determine if it can be made sufficiently gastight. Then a plan should be developed to provide for safe and efficient application of the fumigant to include emergency procedures etc., where required, and to decide how monitoring should be conducted to prevent excessive exposures.
- Wear dry gloves of cotton or other material while handling Weevil-Cide[®] Tablets or Pellets. Wash hands thoroughly after use.
- Phosphine gas may flash at concentrations above its flammable limit. Therefore, always open Weevil-Cide[®] containers in open air and never in a flammable atmosphere. This

5

precaution will not only prevent harm in the unlikely event of a flash but will reduce the applicator's exposure to phosphine gas.

- Piling of tablets, pellets or gas bags or addition of water to Weevil-Cide® may speed up the reaction, cause a temperature increase and/or confine the gas so that ignition could occur.
- 10. As much as is possible, protect unused Weevil-Cide[®] from excessive exposure to atmospheric moisture during application and tightly reseal the aluminum flask prior to returning tablets or pellets to storage. Weevil-Cide[®] Gas Bag containers, once opened, cannot be resealed for future use.
- 11. Phosphine gas may react with certain metals and their salts to produce corrosion. Copper, copper alloys and precious metals such as silver and gold are susceptible to corrosion and items containing these elements should be removed or protected prior to furnigation with Weevil-Cide^e.
- 12. Do not allow Weevil-Cide[®] or its residual dust to come in contact with processed foods or commodity packages intended for retailers except that Weevil-Cide[®] Tablets, Pellets or Gas Bags may be added directly to processed brewers rice, malt and com grits used in the manufacture of beer.
- 13. Respiratory protection approved for the concentration to which the furnigator will be exposed must be available if Weevil-Cide[®] is to be applied from within the structure to be furnigated. Respiratory protection need not be available for uses such as outdoor application or addition of tablets or pellets to automatic dispensing devices etc., if exposure above the TLV's will not be encountered. A NIOSH/MSHA approved, tull-face gas mask, phosphine canister combination may be used at levels up to 15 ppm. Above this level or in situations where the phosphine concentration is unknown a NIOSH/ MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used.
- Notify appropriate company employees prior to furnigation. Provide to local officials (fire department, rescue squad, police, etc.) on annual basis relevant safety information for use in the event of an emergency.

B. EFFICACY

Weevil-Cide[®] has been found effective against the following insects and their preadult stages (eggs, larvae and pupae):

٠	almond moth	٠	European grain moth	٠	Mediterranean flour moth
٠	angoumois grain moth	٠	flat grain beetle	•	pink bollworm
٠	bean weevil	•	truit flies	٠	raisin moth
٠	bees	٠	granary weevel	٠	red flour beetle
•	cadelle	•	greater wax moth	*	rice weevil
٠	cereal leaf beetle	•	nairy fungus heetle	٠	rusty grain beetle
٠	cigarette beetle	•	Hessian fly	•	saw-toothed grain beetle
٠	confused flour beetle	•	Indian meal moth	*	spider beetle
٠	dermestid beetle	•	khaµra beetle	,	tobacco moth
*	dried fruit beetle	•	auser grain borei	· •	yellow meal worm
٠	dried fruit moth	•	naize wievil		

Although it is possible to achieve total control of the listed insect pests, this is frequently not realized in actual practice. Factors contributing to less than 100% control are leaks, peor gas distribution, unfavorable exposure conditions, etc. In addition, some insects are less susceptible to phosphine than others. If maximum control is to be attained, extreme care must be taken in sealing, the higher dosages must be used, exposure periods must be lengthened, proper application procedures followed and temperature and humidity must be favorable.

C. EXPOSURE CONDITIONS

The following conditions may be used as a guide in determining the <u>minimum</u> length of the exposure period at the indicated temperatures:

Minimum Exposure Periods for Weevil-Cide*

Temperature to which Fumigant or insects are Exposed	Tablets	Pellets	Gas Bags
below 41°F (5°C)	Do not furnigate	Do not fumigate	Do not fumigate
41°-53°F (5-12°Ć)	10 days (240 hours)	8 days (192 hours)	14 days (336 hours)
54°-59°F (12-15°C)	5 days (120 hours)	4 days (96 hours)	9 days (216 hours)
60°-68°F (16-20°C)	4 days (96 hours)	3 days (72 hours)	6 days (144 hours)
above 68°F (20°C)	3 days (72 hours)	2 days (48 hours)	4 days (96 hours)
above 77°F (25°C)		<u> </u>	3 days (72 hours)

The length of the fumigation must be great enough to provide for adequate control of the insect pests which infest the commodity being treated. Additionally, the fumigation period should be long enough to allow for more or tess complete reaction of Weevil-Cide[®] with moisture so that little or no unreacted aluminum phosphide remains. This will minimize phosphine exposure during further storage and/or processing of the treated bulk commodity as well as reduce hazards in the disposal of partially spent aluminum phosphide products remaining after space fumigations. The proper length of the fumigation period will vary with exposure conditions, since in general, insects are more difficult to control at lower temperatures and the rate of phosphine gas production by Weevil-Cide[®] is less at lower temperatures.

It should be noted that there is little to be gained by extending the exposure period if the structure to be fumigated has not been carefully sealed or if the distribution of gas is poor and insects are not subjected to lethal concentrations of phosphine. Careful sealing is required to ensure that adequate gas levels are retained and proper application procedures must be followed to provide satisfactory distribution of phosphine gas. Some structures can only be treated when completely tarped; while others cannot be properly sealed by any means and should not be fumigated. Exposure times must be lengthened to allow for penetration of gas throughout the commodity when furnigant is not uniformly added to the mass, for example by surface application or shallow probing. This is particularly important in the fumigation of a bulk commodity contained in large storages. Exposure times need not be lengthened if phosphine is being re-circulated in bulk storage.

Remember, exposure periods in the table are minimum periods and may not be adequate to control all stored product pests under all conditions nor will they always provide for total reaction of WeevII-Cide⁶, particularly if temperature and commodity moisture levels or humidity are low during the fumigation. A temperature of 70°F and 11.5% grain molsture (60% relative humidity) provides excellent conditions for fumigation. At lower humidities the listed exposure period must be increased.

7

D. COMMODITIES WHICH MAY BE FUMIGATED WITH WEEVIL-CIDE*

Weevil-Cide® may be used for the fumigation of the listed raw agricultural commodities, animal leed and feed ingredients, processed foods, tobacco and certain other nonfood items.

1. Baw Agricultural Commodities, Animal Feed and Feed Ingredients

The listed commodities may be fumigated with Weevil-Cide[®], Weevil-Cide[®] Tablets, Pellets and Gas Bags may be added directly to animal feed, feed ingredients and raw agricultural commodities. For space fumigations Weevil-Cide[®] Tablets & Pellets may also be applied in moisture permeable envelopes or on trays or similar devices.

* almonds	 barley 	 coffee beans 	* peanuts
* animal feed and	* wheat	* corn	' pecans
feed ingredients	* filberts	* cottonseed	 pistachio nuts
* millet	 flower seed 	* dates	 popcorn
* soybeans	* grass seed	 safflower seed 	* rice
* sunflower seeds	* sorghum	sesame seed	* rye
 triticale 	 Brazil nuts 	seed & pod vegetables	cocoa beans
 vegetable seeds 	* cashews	* walnuts	
—		* oats	

2. Processed Foods

The listed processed foods may be fumigated with Weevil-Cide[®]. Under no conditions shall any processed food come in contact with Weevil-Cide[®] Tablets, Pellets, Gas Bags or residual dust except that Weevil-Cide[®] may be added directly to processed brewer's rice, malt and corn grits for use in the manufacture of beer.

- Processed candy and sugar
- Cereal flours and bakery mixes
- Cereal foods (including cookies, crackers, macaroni, noodles, pasta, pretzels, snack foods and spaghetti)
- Processed cereals (including milled fractions and packaged cereals)
- Cheese and cheese by-products
- Chocolate and chocolate products (assorted chocolate, chocolate liquor, cocoa, cocoa powder, dark chocolate coating and milk chocolate)
- Processed coffee
- Corn grils
- Cured, dried and processed meat products and dried fish
- Dates and ligs
- Dried eggs and egg yolk solids
- Dried milk, dried milk powder, nondairy creamers, and nonfat dried milk
- Dried or dehydrated fruits (apples, dates, figs, peaches, pears, prunes, raisins and sultanas)
- Processed herbs, spices, senschinus and condiments
- Malt
- Processed nuts (almonds, apricot kernels, Brazil nuts, cashews, filberts, peanuts, pecans, pistachio nuts and walnuts)
- Processed oats (including oatmeal)
- Rice (brewers rice, grils, enriched and polished rice and wild rice).
- Sovbean flour and milled fractions.
- Processed lea
- Yeast (including primary yeast)

3. Nonfood Commodities, including Tobacco

The listed nonfood items may be fumigated with Weevil-Cide[®]. Tobacco and certain other of the nonfood commodities should not be contacted by tablets, pellets or residual dust.

- * Processed or unprocessed cotton, wool and other natural fibers or cloth
- * Clothing
- Straw and hay
- * Feathers
- * Human hair, rubberized hair, vulcanized hair, and mohair
- Leather products, animal hides and furs
- * Tobacco
 - * Wood, cut trees, wood chips, and wood and bamboo products
 - Paper and paper products
 - Dried plants and flowers
 - * Seeds (including but not limited to grass seed, ornamental herbaceous plant seeds and vegetable seed)

E. RECOMMENDED DOSAGES

Phosphine is a mobile gas and will penetrate to all parts of the storage structure. Therefore, dosage must be based upon the total volume of the space being treated and not on the arnount of commodity it contains. The same amount of Weevil-Cide[®] is required to treat a 30,000 bushel silo whether it is empty or full of grain, unless the surface of the commodity is sealed off by a tarpaulin. The following dosage ranges are recommended for bulk and space funigations:

Dosage Guidelines For Fumigation With Weevil-Cide*

Product	per 1000 cu. ft.* 2 - 13	per 1000 bu.* 2 - 16
Gas Bags Pellets	100 - 725	120 - 900
Tablets	20 - 145	25 - 180

*Dosage range for dates, nuts and dried fruits is 20 - 40 tablets, 100 - 200 pellets, 2 - 4 gas bags/1000 cu. It; 25 - 50 tablets, 125 - 250 pellets, 2-6 gas bags/1000 bu.

These dosages are not to be exceeded. It is important to be aware that a shortened exposure period cannot be fully compensated for with an increased dosage of phosphine. The wide range of dosages listed above is required to handle the variety of furnigation situations encountered in practice. Somewhat higher dosages are usually recommended under cooler, drier conditions or where exposure periods are relatively short. However, the major factor in selection of dosage is the ability of the structure to hold phosphine gas during the furnigation. A good illustration of this point is a comparison of the low dosages required to treat modern, well-sealed warehouses with the higher dosage used for poorly constructed buildings that cannot be sealed adequately. In certain other furnigations, proper distribution of lethal concentrations of gas becomes a very important factor in dose selection. An example where this may occur is in the treatment of grain stored in flat storage. Poor gas distribution frequently results when the furnigant cannot be uniformly added to the grain, and it must be treated by surface application.

Although it is permissible to choose from the full range of dosages listed above, the following dosages are recommended for the various types of furnigations:

Recommended Weevil-Cide® Dosages for Various Types of Fumigations

Тур	e of Fumigation	Tablets	Peilets	Gas Bags
1.	Space			
	Mills, warehouses etc.	20-60/1000 cu.ft.	100-300/1000 cu.ft.	2-6/1000 cu.ft
	Bagged commodities	30-60/1000 cu.ft.	150-300/1000 cu.ft.	3-6/1000 cu.ft.
	Processed fruits & nuts	20-40/1000 cu.ft.	100-200/1000 cu.ft.	2-4/1000 cu.lt.
	Stored Tobacco	20-40/1000 cu.ft.	100-200/1000 cu.ft.	2-4/1000 cu.ft.
2.	Bulk Stored Commodities	5		
	Vertical storage	30-60/1000 cu.ft.	150-300/1000 cu.ft.	3-6/1000 cu.ft.
	_	40-75/1000 bu.	200-375/1000 bu.	4-7/1000 bu.
	Tanks	30-70/1000 cu.ft.	150-350/1000 cu.ft.	4-7/1000 cu.lt.
		40-90/1000 bu.	200-450/1000 bu.	5-8/1000 bu
	Flat storages	50-145/1000 cu.ft.	250-725/1000 cu.ft.	5-13/1000 cu.ft.
	m	60-180/1000 bu.	300-900/1000 bu.	6-16/1000 bu.
	Farm bins	70-145/1000 cu.ft.	350-725/1000 cu.ft.	6-13/1000 cu.ft.
		90-180/1000 bu.	450-900/1000 bu.	8-16/1000 bu.
	Bunker & tarped	30-80/1000 cu.ft,	150-400/1000 cu.lt.	3-6/1000 cu.ft.
	ground storages	40-100/1000 bu.	200-500/1000 bu.	4-8/1000 bu.
	Railcars	30-65/1000 cu.it.	150-325/1000 cu.ft.	3-6/1000 cu.ft.
	_	40-80/1000 bu.	200-400/1000 bu.	4-7/1000 bu.
	Barges	30-80/1000 cu.ft.	150-400/1000 cu.ft.	3-7/1000 cu.ft.
	-	40-100/1000 bu	200-500/1000 bu.	4-9/1000 bu.
	Ship holds	30-66/1000 cu.ft.	150-330/1000 cu.ft.	3-6/1000 cu.ft.
		40-75/1000 bu.	200-375/1000 bu.	4-7/1000 bu.

Higher dosages are recommended in structures that are loose construction and in the fumigation of bulk stored commodities in which diffusion will be slowed and result in poor distribution of phosphine gas.

F. APPLICATION PROCEDURES

1. General Statement

Regardless of the type of storage to be treated, there are several important factors common to all application procedures. A number of these points have been covered in other sections of the applicator's manuaj but are tisted again in the following for completeness.

- a. A plan should be devised tor application, aeration and disposal of the fumigant to keep at a minimum. Envision of hosphine. See the requirements in the APPLICATOR AND WORKER EXPOSURE section of the applicator's manual.
- b. Weevil-Cide[®] Tablets, Pellets or Gas Bags should be applied to provide effective gac concentrations throughout the storage. When Weevil-Cide[®] is not applied poliformaly to a bulk commodity (surface application in a flat storage or ship hold for example), exposure times should be lengthened to allow for penetration of gas throughout the storage.
- c. The storage structure should be sealed to maintain a suitable gas concentration over the time period required for control of insect pests.

- d. Ideally, exposure periods should be long enough to provide for adequate control of insect pests and also more or less completely react the fumigant.
- e. Piling of tablets, pellets or gas bags, whether applied to a bulk commodity or for space furnigation, may prevent complete breakdown of the product by limiting its access to moist air. This can result in decreased efficacy as a result of poor gas release and may leave an active residue for disposal which contains considerable amounts of unreacted aluminum phosphide. Piling of product may also result in increased hazard of fire particularly if contacted by water.
- f. Contact with water should be carefully avoided when applying Weevil-Cide[®] for treatment of bulk commodities or space.
- g. Aluminum phosphide lumigants should not be applied to confined spaces where the concentration of phosphine may build up to exceed its lower llammable limit.
- Observe the precautionary and safety statements mentioned in the applicator's manual.

NOTE: The following instructions are intended to provide general guidelines for typical furnigations. These instructions are not intended to cover every type of situation nor are they meant to be restrictive. Other procedures may be used if they are safe, effective and consistent with the properties of aluminum phosphide products.

2. Fumigations of Farm Bins

Leakage is the single most important cause of failure in the treatment of farm storages. Since these storages are often small, they usually have a higher leakage area in proportion to their capacity. Most wooden storage structures are so porous that they cannot be successfully furnigated unless they are completely tarped. Do not furnigate storages which will be entered by humans or animals prior to aeration. Do not furnigate areas which house sensitive equipment containing copper or other metals likely to be corroded by phosphine gas. (See Physical and Chemical Hazards section in this manual.)

All vents and aeration ducts must be tightly sealed using 4 mil polyethylene sheeting or its equivalent. The plastic must be sealed diractly to the metal with tape or other adhesive. It is not sufficient to "cinch up" the plastic as with a belt. The surface of the grain may be covered with plastic sheeting after Weevil-Cide[®] has been applied. Tarping of the grain surface will greatly reduce leakage. Other sealing techniques are recommended, i.e. closure of all large cracks with caulking, foam insulation or other sealant. Sealing these cracks will greatly reduce the required dosage. Two mil or thicker plastic can be used for tarping the grain surface; however, the plastic used on the outside of the bin should be at least 4 mils. When an entire structure is tarped, the plastic must be at least 6 mils thick to prevent excessive tearing during furnigation.

Probing tablets or pellets into the grain mass is a recommended method of application. Probe insertions should be scattered evenly over the surface. A rigid pipe, about 5 to 7 feel long and 17 inch diameter can be used. In this event, use about 20-50 tablets or 100-250 pellets per probe. The lumigant is gradually released into the probe as it is withdrawn from the grain. Releasing all the furnigant into the probe at once may retard the production of hydrogen phosphide and might cause an ignition of gas trapped in the clump of tablets or pellets. The uniform spreading of a large portion of the furnigant in floor level aeration ducts in combination with tarping the grain surface is a preferred method of treatment. Be sure the inside of the aeration duct is dry before adding the furnigant. This method should not be used if it is likely or suspected that the grain immediately surrounding the aeration duct is "caked" or otherwise in Cide[®] to water in an aeration duct can cause a fire. Seal the aeration fan as described above.

Post fumigation warning signs on entrances to the bin and near the ladder.

If monitoring equipment is not available, an approved canister respirator must be worn for indoor application. If an approved respirator is not available, application must be done from outside of the site to be lumigated. Also refer to all other precautions given in this manual.

Following aeration of the bin, the surface of the grain may be sprayed with an approved protectant to discourage reinfestation.

3. Fumigation of Flat Storages

- a. Establish a plan for application of furnigant to the structure. Treatment of these types of storages may require considerable effort; therefore, sufficient manpower should be available to complete the work rapidly enough to prevent excessive exposure to phosphine gas. Vent flasks outside the storage, conduct furnigations during the cooler periods of the day, and employ other work practices to minimize exposures. It is advisable to wear respiratory protection during application of furnigant to flat storages. Refer to the sections on APPLICATOR AND WORKER EXPOSURE AND RESPIRATORY PROTECTION in the applicator's manual.
- b. Seal any vents, cracks and other sources of leaks.
- c. Apply tablets or pellets by surface application, shallow probing, deep probing or uniform addition as the bin is filled. Gas Bags are usually surface applied unless equipped for shallow probing.
 - Storages requiring more than 24 hours to fill should not be treated by addition of fumigant to the commodity stream as large quantities of phosphine may escape before the bin is completely sealed. Probes should be inserted vertically at intervals along the length and width of the flat storage. Tablets or pellets may be dropped into the probe at intervals as it is withdrawn.
 - Surface application may be used if the bin can be made sufficiently gastight to contain the fumigant long enough for II to penetrate the commodity. In this instance, it is advisable to place about 25 per cent or more of the dosage in the floor level aeration ducts. Check the ducts prior to addition of Weevil-Cide® to make sure that they contain no water. For bins that are difficult to adequately seal, it may be desirable to uniformly spread a larger percentage of the dosage in the aeration ducts. Refer to instructions given in the farm bin section above.
- d. Tarping the surface of the commodity is often advisable, particularly if the overhead section of the storage cannot be well sealed.
- e. Lock all entrances to the storage and post furnigation warning placards.
- 4. Furnigation of Vertical Storage (Concrete Upright Bins And Other Silos In Which Commodities Can Be Rapidly Transferred)
 - a. Close all openings and seal all cracks to make the structure as airlight as possible. Prior to the fumigation, seal the vents near the bin top which connects to adjacent outs.
 - b. Tablets or pellets may be applied continuously by hard or by an automatic dispenser on the hettdhouse/gullery tell or the fill opening as the commodity is loaded into the bin.

- c. Seal the bin deck openings after the furnigation has been completed.
- d. Bins requiring more than 24 hours to fill should not be furnigated by continuous addition into the commodity stream. These bins must be furnigated by probing, surface application, re-circulation or a combination of these methods. Exposure periods should be lengthened to allow for diffusion of gas to all parts of the bins if Weevil-Cide[®] has not been applied uniformly throughout the commodity mass. Shallow probing and surface application should only be used as a last resort and only in bins that can be sealed virtually gas tight. Long exposure periods are required to assure complete penetration of the gas.
- e. Place warning placards on the discharge gate and on all entrances.

5. Recirculation of Phosphine in Bulk Storage

It is permissible and sometimes desirable to recirculate phosphine gas in certain bulk storages. This method may be used in ship's holds, various types of flat storage and vertical storage bins.

Recirculation usually involves the application of fumigant to the surface of the commodity. The phosphine gas is then continuously or intermittently drawn out of the over space and blown into the bottom of the storage using specially designed low volume fans and duct work. This method facilitates the quick and uniform penetration of phosphine throughout the commodity. In some instances a reduced dosage may be used.

6. Fumigation of Mills, Food Processing Plants and Warehouses

- a. Using the label, calculate the length of the fumigation and dosage of tablets, pellets or gas bags to be applied based upon volume of the building, air and/ or commodity temperature and the general tightness of the structure.
- b. Carefully seal and placard the space to be fumigated.
- c. Place trays or sheets of paper or foil on the floor throughout the structure to hold Weevil-Cide[®] Pellets or Tablets. Gas Bags can be placed directly on the floor.
- d. Spread Weevil-Cide[®] on the sheets at a density no greater than 30 tablets or 150 pellets per sq.ft. This corresponds to appx. ³/₄h's flask of tablets or ³/₄h's flask of 2500 pellets or slightly more than one flask of 1660 pellets per 3'X4' area.
- Check to see that Weevil-Cide[®] has not piled up and that it is spread evenly to minimize contact between the individual tablets, pellets, and Gas Bags.
- Doors leading to the fumigated space should be closed, sealed, locked, and placarded with warning signs.
- g. The fumigation period usually lasts from 3 to 7 days, depending upon the temperature and humidity. Upon completion of the exposure period, windows, doors, vents, etc. should be opened and the fumigated structure allowed to aerate for at least two hours before entering. Remote monitoring is recommended prior to entering. When required, gas concentration readings may be taken using low level detector tubes or similar devices to ensure safety of personnel who reenter the treated area. Refer to the APPLICATOR AND WORKER EXPOSURE section in the Applicator's Manual.

- h. Collect the spent gas bags and Weevil-Cide®dust, and dispose of them, with or without further deactivation. Follow the recommendations given under DISPOSAL INSTRUCTIONS in this manual.
- i. Remove fumigation warning placards from the aerated structure.
- 7. Fumigation of Rail Cars, Containers, Trucks, Vans and Other Transport Vehicles
- a. General Information

Rail cars, containers, trucks, vans and other transport vehicles loaded with bulk raw agricultural commodities or other commodities approved for direct addition are treated in essentially the same way as any other flat storage facility. The dose may be scattered over the surface after loading has been completed or may be probed below the surface. Gas Bags are usually applied in vehicles on the boards or discs described below.

Catefully seal any vents, cracks, or other leaks. Remember, rail cars and containers shipped piggyback by rail may be fumigated in transit, but it is not legal to move trucks, trailers, vans etc. over public roads or highways until they are aerated. See PLACARDING OF FUMIGATED AREAS in the Applicator's Manual.

The shipper must provide advance notification to the consignee that treated commodities will be shipped. Proper handling of the rail cars at their destination is the responsibility of the consignee. The consignee must be familiar with the physical, chemical and toxicological properties of hydrogen phosphide (phosphine), worker exposure limits and symptoms and first aid treatment for hydrogen phosphide polosoning and must be knowledgeable in making gas concentration measurements. Unless prior arrangements have been made to return the rail cars containing the spent fumigant back to the shipper, consignees must also know proper procedures for deactivation and disposal of spent fumigant. Unaerated rail cars being returned in this manner must bear fumigation warning placards and be carefully sealed. It is the consignee's responsibility to aerate the car unless prior arrangements have been made to return the unaerated car directly to the shipper. Consignees must also ensure that industrial hygiene exposure limits are not exceeded and that the storage for the treated commodity is placarded if the airspace in and/or around the commodity contains more than 0.3 ppm hydrogen phosphide.

Weevil-Cide* Gas Bags are suited to furnigation of packaged commodities or bulk processed foods. They shall not be placed in or attached directly to commodity packages containing processed food. If placement of gas bags on the licer of a boxcar is not convenient, or if the vehicle is being furnigated in transit, they may be attached to a wall or other support. They may also be applied by taping the gas bags on cardboard with spacing between gas bags. Tape across the gas bag ends only. Specially designed discs or boards are also available for this purpose.

If these boards or discs are used, taking the gas bags is not necessary.

Instructions that follow suggest specific procedures for treatment of rail cars and containers when direct addition to the commonity is not used.

14

b. Procedures for Hopper Rail cars - Round Hatch

- Close and secure all hatch covers except those being utilized for the fumigation.
- 2 Seal all other openings. Fay particular attention to vents,

- Clean the flange lip of hatch (or hatches) being utilized. If the commodity extends into the throat of the hatch, force it away to the extent possible.
- 4. Open cans, and insert gas bags into the pockets, or tape the gas bags on the disc. Gas Bags must not be folded.
- 5. Place the loaded disc into position, gas bag side up.
- Secure the disc into place with tape.
- 7. Cover the hatch opening with "poly" sheeting before closing the cover.
- 8. Lower the cover into place and secure. Insert a "DANGER" placard into a clear plastic bag, and glue or otherwise affix it to the hatch cover.
- Insert 'DANGER" placards into clear plastic bags, and secure with glue, or otherwise affix near the ladder on each side of the car. Pre-glued, press-on envelopes are available for this purpose.
- c. Procedures for Hopper Rail Cars Slot Hatch
 - Fold the edges of a board to form a tray. The bbard is designed to "hang" in the hatch opening.
 - Open containers, and insert gas bags into pockets of the board. Gas Bags must not be folded.
 - Place the loaded board into position, gas bag side up.
 - 4. Secure into place with tape.
 - 5. Cover the entire hatch opening with "poly" sheeting.
 - 6. Lower the hatch covers.
 - 7. Inser: a "DANGER" placard into a clear plastic bag, and glue or otherwise affix t securely to the hatch cover.
 - Insen "DANGER" placards into a clear plastic bags and secure with glue, or otherwise affix them near the ladder on each side of the car. Pre-glued, press-on envelopes are available for this purpose.

d. Procedures for Box Cars

- Close and secure one of the doors. Seal all openings and joints. If needed, cault joints, and drape entire doorway with "poly" film, securing the edges to the inner wall, floor and ceiling with tape or suitable adhesive.
- Inspect the roof, floor and walls for holes and/or cracks. Seal all openings with either tape or caulking compound.
- 3. if needed, drape remaining doorway with polyethylene film before door is closed. Secure edges to door jambs and floor. Close door and secure. If doorway is draped with "poly", it may not be necessary to seal the door from the sutside. If doorway is not draped, seal all cracks, openings and leaky joins with masking tape and/or caulking compound from the outside.

15

- 4. Open cans, and insert gas bags into pockets of disc or board, or use tape to secure the gas bags.
- 5. Place the loaded disc or board onto the load, gas bag side up. Secure it into place with tape,
- 6. Or nail it to the wall.
- 7 Post "DANGER" placards by inserting into clear plastic bags and gluing or otherwise alfixing them to each door. Pre-glued envelopes are available for this purpose.

e. Procedures for Containers

Procedures for containers are essentially the same as box cars; except their doors tend to be more gas tight and they often have only a rear door which must be sealed after application is completed. If a refrigeration unit is present, it must be sealed from inside protecting it from phosphine damage.

Procedures for Receivers of Fumigated Rall Cars

1. General

Persons responsible for receiving rail cars which have been furnigated in transit must be familiar with the pertinent regulations, hazards, safety considerations, aeration and disposal procedures, etc. which apply to practices and situations enumerated in performing this function.

The appropriate sections of this applicator's manual should be reviewed as part of the training program for persons involved in receiving fumigated rail cars. These persons should be knowledgeable in the following areas:

- a. health hazards and symptoms of overexposure
- practical treatment for overexposed persons
- c. physical and chemical hazards
- d worker exposure limits
- e. techniques and requirements for monitoring
- odor of phosphine
- g. respiratory protection and protective pothing
- h. aeration and disposal
- i. placarding

2. Worker Exposure: Crew Size, Resolvatory Protection

When receiving rail cars in outdoor locations, certain sately procedures are not required, i.e. monitoring outdoors for worker exposure, a minimum crew size of 2 and the availability of respiratory equipment. However, in no case may the bost application worker be exposed to over 0.3 ppm as a ceiling concentration. Some facilities where rail

cars are received may be closed on more than one side, and the distinction between an indoor and outdoor operation is not clear cut. Worker exposure monitoring should be performed initially in these situations where exposure may be excessive.

3. Responsibilities of Consignees

Unless prior arrangements have been made to return unaerated rail cars containing the spent furnigant back to the shipper, the consignee receiving the furnigated rail car must:

- a. aerate the rait cars and verify that it contains 0.3 ppm PH, (phosphine) or less;
- b. remove the fumigation warning placards from the rail car, and
- Remove and dispose of the fumigant, unless pellets or tablets have been added directly to the commodity.

The consignee must also:

- d. ensure that the post-application worker exposure limit is not exceeded,
- e. transfer the fumigated commodity from the rail car, with or without prior aeration; and
- f. placard the new storage if it contains more than 0.3 ppm PH_s in or above the commodity mass.

8. Tarpaulin and Bunker Fumigations.

Use of plastic sheeting or tarpaulins to cover commodities is one of the easiest means for providing relatively gastight enclosures which are very well suited for fumigation. Polyethylene tarps are penetrated only very slowly by phosphine gas, and tight coverings are readily formed from the sheets. These enclosures may vary widely from a tarpaulin placed over a small stack of bagged commodity containing a few cubic feel to a plastic covered bunker storage capable of holding 600,000 bushels of grain or more.

An enclosure suitable for fumigation may be formed by covering bulk or packaged commodity with polyethylene sheeting. The sheets may be taped logether to provide a sufficient width of material to ensure that adequate sealing is obtained. If the flooring upon which the commodity rests is of wood or other porous material, it should be repositioned onto a tarpaulin prior to covering for fumigation. The plastic covering of the pile may be sealed to the floor using sand or water snakes or by shoveling soil or sand onto the ends of the plastic covering or by other suitable procedures. The "poly" covering should be reinforced by tape or other means around any sharp corners or edges in the stack to reduce the risk of tearing. Thinner polyethylene sheeting, about 2 mits., is suitable for most indoor tarp fumigations and for sealing windows, doors and other openings in structures. However, 4 mil. or thicker "poly" is more suitable for outdoor applications where wind or other mechanical stresses are likely to be encountered.

Tablets, pellets or gas bags may be applied to the tarped stack or bunker storage of bulk commodity through slits in the polyethylene covering. Probing or other means of dosing may be used. Avoid application of large amounts of Weevil-Cide® at any one point. The Weevil-Cide® should be added below the surface of the bulk commodity if condensation or other source of moisture is likely to form beneath the "poly". The slits in the covering should be carefully taped to prevent loss of gas once the dose has been applied. Weevil-Cide® Gas Bags are recommended for the treatment of bagged commodities and processed foods, atthough tablets and pellets on trays or sheets of paper may be used. Care should

be taken to ensure that the notyethylene sheeting is not allowed to cover the Weevil-Cide®, contining the gas, thus preventing contact with moist air

Distribution of phosphine gas is generally not a problem in the treatment of bagged commodities and packaged processed foods. However, fumigation of larger bunker storages containing bulk commodity will require proper application procedures to obtain adequate results.

See appropriate precautions if the fumigation is conducted indoors as opposed to outdoors. Indoor fumigation precautions are handled as any other situation where the application is made from outside the area being fumigated. Workers may occupy adjacent indoor areas, but they must be protected from overexposure to hydrogen phosphide by adequate sealing, phosphine monitoring, ventilation or as a last resort, respiratory equipment.

Do not walk on stacks during the fumigation.

Place "Danger" placards at conspicuous locations on the tarped stack or bunker only.

If concentrations in excess of 0.3 ppm are observed in adjacent indoor areas, the areas must be evacuated of unprotected workers and posted with "Danger" signs until this adjacent area is perated to 0.3 ppm or below.

- 9. Fumigation of Ships
- e. General Information
 - IMPORTANT shipboard, in-transit ship holds fumigation is also governed by U.S. Ceast Guard Regulation 46 CFR 147A. Refer to this regulation prior to fumination.
 - The Fumigation Handbook of the U.S. Department of Agriculture, Federal Grain Inspection Service (FGIS) contains additional procedures which must be followed if infested bulk grain is to be fumigated to avoid the designation "infested" by the FGIS, or to obtain a USDA phytosanitary inspection certification

b. Pre-voyage Fumigation Procedures

- Prior to furnigating a vessel for in-transit cargo furnigation, the master of the vessel or his representative and the furnigator must determine whether the vessel is suitably designed and configured to allow for safe occupancy by the ship's crew throughout the duration of the furnigation. If it is determined that the design and configuration of the vessel do not allow safe occupancy by the ship's crew throughout the duration of the furnigation, then the vessel will not be furnigated unless all crew members are removed from the vessel. The crew members will not be allowed to reoccup the vessel until the vessel has been properly aerated and a determination has been made by the master of the vessel and the furnigator that the vessel is safe for reoccupancy.
- 2. The person responsible for the fungation must notify the master of the vessel or this tep estimative of the requirements relating to personal protection equipment and detection equipment. Personal protection equipment means a NIOSH/ MSHA approved respirator or gas mask fitted with an approved canister for phosphine. The canister is approved for use up to 15 ppm. An SCBA or its

equivalent must be used above 15 ppm or at unknown concentrations. A person qualified in the use of this equipment must accompany the vessel with the cargo under fumigation. Emergency procedures, cargo ventilation, periodic monitoring and inspections and first aid measures must be discussed with and understood by the master of the vessel or his representative.

- 3. Seal all openings to the cargo hold or tank, and lock or otherwise secure all openings, manways, etc. which might be used to enter the hold. The over space pressure relief system of each tank aboard tankers must be sealed by closing the appropriate valves and sealing the openings into the overspace with gastight materials.
- Placard all entrances to the treated spaces with fumigation warning signs.
- 5. If the fumigation is not completed and the vessel aerated before the manned vessel leaves port, the person in charge of the vessel shall ensure that at least two units of personal protection equipment and one gas or vapor detection device, and a person qualified in their operation be on board the vessel during the voyage.
- 6. During the fumigation or until the manned vessel leaves port or the cargo is aerated, the person in charge of the fumigation shall ensure that a qualified person using gas or vapor detection equipment tests spaces adjacent to areas containing fumigated cargo and all regularly occupied spaces for fumigant leakage. If leakage of the fumigant is detected, the person in charge of the funigation shall take action to correct the leakage or shall inform the master of the vessel or his representative of the leakage so that corrective action can be taken.
- Review with the master or his representative, the precautions and procedures for the voyage.

c. Application Procedures for Bulk Dry Cargo Vessels and Tankers

- Apply tablets, pellets or gas bags by scattering uniformly over the commodity surface. Product may be shallow or deep probed into the commodity mass. Recirculation systems may be used to aid the penetration of phosphine throughout the commodity.
- Immediately after the application of the fumigant, close and secure all hatch covers, tank tops, butterworth valves, manways, etc.

d. In Transit Fumigation of Containers Aboard Ships

In transit fumigation of containers on ships is also governed by the U.S. Department of Transportation Regulation 49 CFR 176.76.

Application procedures for fumigation of raw commodities or processed foods in containers and other transport vehicles are described in the DIRECTIONS FOR USE section of the applicator's manual.

- e. Precautions and Procedures During Voyage
 - 1. Using appropriate gas detection equipment, monitor spaces adjacent to areas containing furnigated cargo and all regularly occupied areas for

fumigant leakage. If leakage is detected, the area should be evacuated of all personnel, ventilated and action taken to correct the leakage before allowing the area to be reoccupied.

 Do not enter fumigated areas except under emergency conditions. If necessary to enter the fumigated area, appropriate personal protection equipment must be used. Never enter fumigated areas alone. At least one other person, wearing personal protection equipment, should be available to assist in case of an emergency.

f. Precautions and Procedures During Discharge

- If necessary to enter holds prior to discharge, test spaces directly above grain surface for fumigant concentration, using appropriate gas detection and personal safety equipment. Do not allow entry to fumigated areas without personal safety equipment, unless fumigation concentrations are al safe levels, as indicated by a suitable detector.
- 2. It is the responsibility of the consignee to see that the spent furnigant, is disposed of properly and that industrial hygiene exposure limits are not exceeded during unloading of the ship or during subsequent transfer and storage of the treated commodity. Safety, aeration and disposal requirements in the United States are given herein as a guide. Consult regulations in the receiving country for local requirements.

g. Personal Protective Equipment and Monitoring

- Fully loaded holds on dry bulk carriers are considered an outdoor fumigation, and therefore monitoring and respiratory protection are not required during application.
- 2. NIOSH/MSHA approved respiratory protection must be available at the site in case it is needed during application to tanker holds and in partially filled holds if the hold must be entered for furnigant application. This respiratory protection must consist of a full face gas mask - phosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent. If an SCBA or its equivalent is not available at the application site, it must be available locally, for example, at a fire station or rescue squad.
- 3. If hydrogen phosphide is detected leaking into crew's quarters, housing or work areas, a minimum of two qualified persons on ship should wear the gas mask and canister described above while aerating the area and locating and sealing the leak.
- 4. Refer to the following sections a through 11 for additional required and recommended practices.

10. Fumigation of Barges

Barge fumigations are also regulated by U.S. Coast Guard regulation 46 CFR 147A as modified by U.S. Coast Guard Special Permit 2-75 This permit must be obtained prior to the fumigation and is available from: U.S. Coast Guard, Hazardous Branch, MTH-1, Washington, DC 20593-0001.

Leaks are a common cause of failures it the treatment of commodities aboard barges. Carefully inspect all hatch covers prior to application of Weevil-Cide[®] and seal, if necessary. Notify consignee if the barge is to be furnigated in transit. The consignee has the same responsibilities concerning aeration, monitoring, knowledge and disposal as does the rail car receiver.

11. Fumigations in Small Sealable Enclosures.

Excellent results may be attained in the treatment of small enclosures since it is often possible to control the fumigation and also to make the enclosure virtually gastight. Take care not to overdose, during these fumigations. A single pellet will treat a space of 1.4 to 10 cubic feet. From 6.9 to 50 cubic feet may be fumigated with a single Weevil-Cide[®] Tablet. A single gas bag will treat 77 to 500 cubic feet.

12. Treatment of Beehives, Supers And Other Beekeeping Equipment.

Weevil-Cide[•] Tablets, Pellets, and Gas Bags may be used for the control of the greater wax moth in stored beehives, supers and other beekeeping equipment and for the destruction of bees, Africanized bees, and diseased bees including those infested with tracheal miles and foulbrood. The recommended dosage for this use is 30-45 tablets, 150-225 pellets or 3 or 4 gas bags per 1000 cu.ft. Furnigations may be performed in chambers at almospheric pressure, under tarpaulins, etc. by using gas bags or placing tablets or pellets to trays or in moisture permeable envelopes. Do not add more than 2 tablets or 10 pellets to each envelope. Honey from treated hives or supers may only be used for bee food.

13. Burrowing Pest Control

a. List of Burrowing Pests.

Weevil-Cide[®] Tablets and Pellets may be used out of doors only for the control of the following burrowing rodents and moles: woodchucks and yellow belly marmots (rockchucks), prairie dogs (except Utah prairie dogs), Norway and roof rats, mice, ground squirrels, moles, voles, gophers and chipmunks.

b. Directions for Use

Add from 1 to 4 tablets or 5 to 20 pellets to each burrow opening. Then seal lightly by shoveling soil over the entrance. Place the tablets or pellets far enough down the burrow that the soil used to plug the burrow doesn't cover the tablets or pellets, slowing down their action. Where possible, subsurface tunnels or runways should be treated every 5 to 10 feet with a dose of 2 to 4 tablets or 10 to 20 pellets. Use lower rates in smaller burrows, in tight soils, under moist soil conditions and higher rates in larger burrows, in porous soils when soil moisture is low. In extremely dry or porous soil, it is sometimes not possible to obtain satisfactory results. This is particularly true in instances where the burrow systems are extensive such as moles or gophers. It is always better not to fumigate during extended periods of dry weather. Addition of several cups of water to the burrow prior to dosing with WeevII-Cide® may improve efficacy in some porous soils. Treat reopened burrows and fresh runways a second time 1 to 3 days after the initial treatment. WeevII-Cide® may be used out of doors only for control of burrowing pests. Do not use within 15 feet (5 meters) of inhabited structures. Do not apply to burrows which may open under or into occupied buildings. For use on all agricultural and noncropland areas.

c. Environmental Hazards

This product is very highly toxic to wildlife. Non-target organisms exposed to phosphine gas in burrows will be killed. Do not apply directly to water or wetlands (swamps, bogs,

marshes, and potholes). Do not contaminate water by cleaning of equipment or disposal of wastes.

d. Endangered Species Restrictions

The use of any pesticide in a manner that may kill or otherwise harm an endangered or threatened species or adversely modify their habitat is a violation of federal law. The use of this product is controlled to prevent death or harm to endangered or threatened species that occur in the following counties or elsewhere in their range.

STATE (REGIONAL U.S. FISH AND WILDLIFE OFFICE) SPECIES-COUNTY ARIZONA (Albuguerque, NM) * Black footed Ferret - Statewide CALIFORNIA (Portland, OR) San Joaquin Kit Fox-Fresho, Kern, Kings, Merced, Monterey, San Benito, San Luis Obispo, Santa Barbara, Tulare, Ventura Blunt-nosed Leopard Lizard-Fresho, Kern, Kings, Madera, Merced, Tulare COLORADO (Denver, CO) Black-footed Ferret - Statewide FLORIDA (Atlanta, GA) Eastern Indigo Snake - Statewide GEORGIA (Atlanta, GA) * Eastern Indigo Snake - Statewide KANSAS (Deriver, CO) * Black-looted Ferret - Statewide MONTANA (Deriver, CO) * Black-footed Ferret - Statewide NEBRASKA (Denver. CO) * Black-footed Ferret - Statewide NEW MEXICO (Albuquerque, NM) * Black-focted Ferret - Statewide NORTH DAKOTA (Derive), CO) Black footed Ferret - Statewide OKLAHOMA (Albuquerque, NM) * Black-footed Ferret - Statewide SOLITH DAKOTA (Deriver, CO) Black-focted Ferret - Statewide TEXAS (Albuquerque, NM) * Black-footed Ferret Statewide UFAH (Deriver, CC) * Desert Tortoise-Washington Black-footed Ferret - Statewide WYOMING (Demissr, CC). Black-footed Ferrel - Statewice

Use of this product in the above areas is prohibited without first contacting and obtaining permission from the endangered species specialist in the regional offices of the U.S. Fish and Wildlife Solvice (FWS) bearest you.

- e. Special Local Restrictions
 - North Chrolina Weevil-Cide* Tablets and Pellets may only be used for control
 of rats and mice in the state of North Carolina. Use against other pests is not
 permitted.

- Oktahoma A special permit for black-tailed prairie dog control by poisoning is required in Oklahoma. Contact the Oklahoma State Department of Wildlife Conservation to obtain this permit.
- Wisconsin A state permit is required for use of pesticides to control small mammals, except rats and nice. Contact your local Department of Natural Resources for information.
- Indiana Use of Weevil-Cide[®] Tablets and Pellets for mole control is not legal in the State of Indiana.
- Missouri A state permit is required for use of pesticides in Missouri to control small mammals, except rats and mice. Contact the Missouri Department of Conservation for information.
- Kansas A special permit for black-tailed prairie dog control by poisoning is required in Kansas. Contact the Kansas Dept. of Wildlife and Parks for information.
- Catifornia Use of Weevil-Cide® Tablets and Pellets for chipmunk control is not legal in the State of California.

SECTION 4

AERATION OF FUMIGATED COMMODITIES

A. Foods and Feeds

Tolerances for phosphine residues have been established at 0.1 ppm for animal feeds and 0.01 ppm for finished foods. To assure compliance with these tolerances; it is necessary to aerate these commodities for 48 hours prior to offering to the end use consumer.

B. Tobacco

Tobacco must be aerated for at least three-days (72 hours) when fumigated in hogsheads and for at least two days (48 hours) when fumigated in other containers. Tobacco fumigated in containers with plastic liners will probably require longer aeration periods to reach 0.3 ppm.

C. Alternatives

As an alternative to these aeration periods, each container of a treated commodity may be analyzed for residues using accepted analytical methods. If residues are less than tolerance levels, the commodity may be shipped to the consumer regardless of the above holding periods.

SECTION 5

PLACARDING OF FUMIGATED AREAS

The applicator must placard or post all entrances to the fumigated area with signs bearing.

 The signal word DANGER/PELIGRO and the SKULL AND CROSSBONES symbol in red.

- The statement, "Area and/or commodity under fumigation, DO NOT ENTER/ NO ENTRE."
- 3. The statement. "This sign may only be removed after the commodity is completely aerated (contains 0.3 ppm or less phosphine gas). If incompletely aerated commodity is transferred to a new site, the new site must also be placarded, and workers must not be exposed to more than 0.3 ppm phosphine.
- 4. The date and time fumigation begins and is completed.
- 5. Name of fumigant used.

6. Name, address and telephone number of the applicator.

All entrances to a furnigated area must be placarded. Where possible, placards should be placed in advance of the furnigation in order to keep unauthorized persons away. For the railroad hopper cars, placarding must be placed on both sides of the car near the ladders and on or next to the top hatches into which the furnigant is introduced.

Do not remove a placard until the treated commodity is completely aerated. To determine whether aeration is complete, each furnigated site or vehicle must be monitored and shown to contain 0.3 ppm or less phosphine gas in the air space around and when feasible, in the mass of the commodity. If 0.3 ppm or less phosphine is detected, the placard may be removed. However, if more than 0.3 ppm is detected, the placard must be transferred with the commodily to the new site. Workers who transfer or handle incompletely aerated commodity must be informed and appropriate measures must be taken (i.e. ventilation or respiratory protection) to prevent exposure from exceeding 0.3 ppm phosphine. It is recommended that the person removing the placard be knowledgeable in the physical, chemical and toxicological properties of phosphine; how to take gas readings; the exposure limits for phosphine; and symptoms of and first aid treatment for poisoning.

SECTION 6

PROTECTIVE CLOTHING

Wear dry gloves made of cotton or other material if contact with tablets, pellets, or their dust is likely. Wash hands after use. It is not necessary to wear gloves when handling gas bags.

SECTION 7

RESPIRATORY PROTECTION

A. WHEN RESPIRATORY PROTECTION MUST BE WORN

NIOSH/MSHA approved respiratory protection must be worn during exposure to concentrations in excess of permitted limits or when concentrations are unknown.

B. PERMISSIBLE GAS CONCENTRATION RANGES FOR RESPIRATORY PROTECTION DEVICES

A NIOSH/MSHA approved, full face gas mask - phosphilm cabilitier combination may be used at levels up to 15 ppm or to ascape from invels up to 1500 ppm. Above this level or in situations where the phosphille concentration is unknown, a NIOSH/MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used. The NIOSH/MSHA Pocket Guide, 8-85, DHEW/NIOSH 78-210, lists these and other types of approved respirators and the concentration limits at which they may be used.

C. REQUIREMENTS FOR AVAILABILITY OF RESPIRATORY PROTECTION

Respiratory protection must be available at the site of application in case it is needed when applying Weevil-Cide[®] from within the structure being fumigated. An approved full face gas mask – phosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent must be available at the site of application. If an SCBA or its equivalent is not available at the application site, it must be available locally, for example, at a fire station or rescue squad.

Respiratory protection need not be available for application from outside the area to be fumigated such as addition of tablets or pellets to automatic dispensing devices, etc., if exposures above the permitted exposure limit will not be encountered.

Respiratory protection need not be available for outdoor applications.

If monitoring equipment is not available on a farm and application cannot be done from outside the structure, an approved canister respirator must be worn during application from within the enclosed indoor area.

SECTION 8

GAS DETECTION EQUIPMENT

There are several reliable devices marketed. One type is the hand pump when used in conjunction with the appropriate detector tube. They are portable, simple devices and do not require intensive training or elaborate supporting equipment to operate. Furthermore, they are inexpensively adaptable to remote monitoring procedures and will measure concentrations of hydrogen phosphide in air in trace amounts on up. Use instructions are enclosed with each purchase.

Consult your local supplier of such equipment or contact your Weevll-Çide[®] distributor for more information.

SECTION 9

APPLICATOR AND WORKER EXPOSURE

A. HYDROGEN PHOSPHIDE EXPOSURE LIMITS

Exposure to hydrogen phosphide must not exceed the 8 hour TWA of 0.3 ppm for applicators and workers during application. Application is defined as the time period covering the opening of the first container, applying the appropriate dosage of fumigant and closing up the site to be fumigated. All persons in the treated site and in adjacent indoor areas are covered by this exposure standard.

After application is completed worker or applicator exposure must not exceed 0.3 ppm maximum concentration. Such exposures may occur because of leakage into enclosed areas from fumigation sites, during reentry or during transfer of unaerated commodity.

B. APPLICATION OF FUMIGANT

Depending upon temperature and humidity, Weevil-Cide® releases hydrogen phosphide (phosphine) gas slowly upon exposure to moisture from the air. This release is

sometimes slow enough to permit applicators to deposit lumigant in the desired areas and then vacate the premises without significant exposure to the gas. If the lumigator's exposure exceeds the 8 hour TWA of 0.3 ppm, approved respiratory protection must be worn. Gas concentration measurements for safety purposes must be made using low level detector tubes or other suitable low level detection equipment. See the "Industrial Hygiene Monitoring" section below.

It is often practical to wear respiratory protection from start to finish. This is particularly true when performing large space fumigations or when fumigating bulk stored commodities in flat storage buildings.

C. LEAKAGE FROM FUMIGATED SITES

Hydrogen phosphilde is highly mobile and given enough time may penetrate seemingly gastight materials such as concrete and cinder block. Therefore, adjacent enclosed areas likely to be occupied should be examined to ensure that significant leakage has not occurred. Sealing of the fumigated site and/or air flow in the occupied areas should be used to reduce exposure.

D, AERATION AND REENTRY

If the area is to be entered after fumigation, it must be aerated until the level of hydrogen phosphide gas is 0.3 ppm or below. The area or site must be monitored to ensure that liberation of gas from the treated commodity does not result in the development of unacceptable levels of hydrogen phosphide. Do not allow reentry into treated areas by any person before this time unless protected by an approved respirator.

E. HANDLING UNAERATED COMMODITIES

Transfer and processing of a treated commodity prior to complete aeration is permissible; however, workers must not be exposed to hydrogen phosphide in excess of the permitted exposure limit.

F. INDUSTRIAL HYGIENE MONITORING

It is recommended that hydrogen phosphide exposure be documented in an operation log or manual for each site and operation where exposure may occur. The purpose of this monitoring is to prevent excessive exposure and to determine when and where respiratory protection is required. This monitoring is mandatory although once exposures have been adequately characterized, subsequent monitoring is not routinely required. However, spot checks should be made occasionally, especially if conditions significantly change or an unexpected gartic odor is detected. Gas concentration measurements should be taken in the worker's breathing zone. Monitoring is not required outdoors.

G. ENGINEERING CONTROLS AND WORK PRACTICES

If initial monitoring shows that workers are exposed to concentrations in excess of the permitted exposure limits then ancineering controls (such as forced air ventilation) and/or appropriate work mantices should be used, where possible, in an attempt to reduce exposure to below permitted limits.

SECTION 10

STORAGE AND DISPOSAL

A. STORAGE

Containers should be stored in a dry, well ventilated area, away from heat and under lock and key. Post as a pesticide storage area. Do not contaminate water, food or feed by storing pesticides in the same areas used to store these commodities. Do not store in buildings where humans or domestic animals reside. Keep out of reach of children.

Weevil-Cide[®] Tablets and Pellets are supplied in resealable, aluminum flasks. Do not expose the product inside flasks to atmospheric moisture any longer than is necessary. Seal tightly before returning opened flasks to storage.

Tablet and petiet flasks should not be stored at sub-zero temperatures because this will increase the possibility of an ignition (flash) when opened.

The shelf life of Weevil-Cide® is virtually unlimited if the containers are tightly sealed.

8. DISPOSAL OF UNREACTED OR PARTIALLY REACTED WEEVIL-CIDE"

(From spills, leaking containers or other sources) : Unreacted or partially reacted aluminum phosphide is acutely hazardous. Improper disposal of these products is a violation of federal taw. If these products cannot be disposed of by ordinary use or according to the instructions that follow, contact your state pesticide or environmental control agency or the hazardous waste representative at the nearest EPA regional office for guidance. Do not contaminate water by disposal.

Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations.

FOR SPECIFIC INSTRUCTIONS CONCERNING SPILLS AND LEAKS, REFER TO SECTION 11.

C. DISPOSAL OF WEEVIL-CIDE® FOLLOWING A SPACE FUMIGATION

1. General

If properly exposed, the residual dust remaining after a furnigation will be a grayish white, spent, nonhazardous waste and will contain only a small amount of unreacted aluminum phosphide. However, residual dust from incompletely exposed aluminum phosphide (See "Exposure Guide" on page 7 of this manual.) will require special care. Confinement of <u>partially</u> spent aluminum phosphide as in a closed container or collection and storage of large quantities of the dust may result in a fire hazard. Small amounts of hydrogen phosphide may be given off from the partially reacted aluminum phosphide, and confinement of the gas may result in a flash.

2. Deactivation and Disposal of Weevil-Cide[®] Tablets and Pellets.

a. General

Unless it can be determined with certainty that the tablets or pellets are spent, they must be held for several days beyond the required exposure time prior to disposal, or the wet method of deactivation must be used. If the dust retains any of its greenish color, the wet method is recommended, Extension of the

furnigation period is the simplest method for further deactivation of "green" or partially spent product prior to ultimate disposal.

b. Dry Method

In open areas, small amounts (up to 5 flasks) of residual dust may be disposed of on site by burial or by spreading over the land surface away from inhabited buildings. Up to 3 flasks of this residual dust (4 to 7 lbs.) may be collected in a one gation bucket for holding or disposal. Larger amounts of residual dust may be collected in a porous cloth bag (burlap cotton, etc.) for holding and/or transportation to a suitable disposal site. Do not put more than one half case (7 flasks of tablets) or 7 flasks of pellets) of residual dust in each bag. Always transport these bags in an open vehicle. CAUTION: Do not use this method for dust that still retains some of its original greenish color. Never confine, dispose of or store residual dust in closed containers such as dumpsters, drums or plastic bags.

Spent residual dust from pellets or tablets may be collected and disposed of at a sanitary landfill, approved pesticide incinerator or other approved sites or by other procedures approved by federal, state and local authorities.

Do not dispose of dust in a tollet.

c. Wet Method

Fill an appropriate sized metal container 2/3 full with water. For each gallon of water add 1/4 cup of low sudsing detergent or surfactant. Use no less than 10 gallons of water/detergent solution for each case of spent material. Slowly pour the dust into the container as the water is stirred. Wear appropriate respiratory protection. DO NOT COVER THE CONTAINER AT ANY TIME. IF THE CONTAINER IS COVERED, THE PHOSPHINE BEING GENERATED WILL BE CONFINED AND MAY DECOMPOSE EXPLOSIVELY. This must be done outdoors or in front of an adequate fan that exhausts immediately outside.

Dispose of the water/dust mixture (slurry) (with or without preliminary pouring out of excess water) in a sanitary landfill or other suitable burial site approved by local authorities. Where permissible, the slurry may be poured out on the ground. The water from the slurry may be evaporated prior to disposal. After being held for 36 hours, it may be poured into a sanitary sewer if approved by local authorities.

d. Disposal of Empty Flasks

Method One: Triple rinse flasks and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of them in a sanitary landfill or other approved site or by other procedures approved by state and local authorities. The water from the rinsate may be evaporated prior to disposal. Dispose of rinsate or rinsate residue in a sanitary landfill or by other approved procedures. Small quantities can be poured out on the ground.

After being held for 36 hours the rinsate may be poured into a sanitary sewer if approved by local authorities.

Method, Twc., Rumove lids and place enjoty flasks in a secure location outdoors or in structure being fuminated until residue in flasks is reacted. Puncture and dispose of them in a salitary land. Iff or other approved site or by other procedures approved by state and local authorities. NOTE: It is permissible to tighten lids back in place on the triple rinsed or reacted empty flasks, place them in the original carton and ship them back to the distributor. They are not hazardous waste. Contact your distributor for information and approval.

D. DEACTIVATION AND DISPOSAL OF WEEVIL-CIDE® GAS BAGS

1. General

Unless it can be determined with certainty that the gas bags are spent, they must be deactivated as described below prior to disposal.

All the methods below may be used for deactivating used or unused Weevil-Cide[®] Gas Bags, regardless of the extent to which the aluminum phosphide has been consumed in the production of hydrogen phosphide.

2. Dry Deactivation

Collect gas bags, and place them into a secure, ventilated holding container. Store the gas bags until they are spent. It is recommended that unused or partially spent gas bags be spread out on the ground in a secure open area away from occupied buildings to be deactivated by atmospheric moisture. Care should be taken so that they are not carried away by the wind. Prior to final disposal, gas bags may be spread out in a single layer on the ground or concrete and covered with several inches of sand until they are spent. Gas Bags that have not been exposed for the minimum times specified in the exposure guide on page 7 should not be covered with sand. Dry deactivation is the recommended procedure for unused or partially spent gas bags. It in doubt concerning whether the gas bags are spent, contact your Weevil-Cide® distributor.

Ignition can occur if large numbers of incompletely reacted gas bags are contacted by liquid water. This can occur in open or perforated storage containers. Therefore, such storage should be out of doors in a relatively isolated area, protected from rain.

3. Wet Deactivation - Method One

Fill an appropriate sized container with water a few inches from the top. Submerge intact gas bags for 36 hours. A metal grid works well to keep gas bags submerged. Do not cover container. Wear appropriate respiratory protection. This must be done outdoors or in front of an adequate fan that exhausts outside. The water may be disposed of in a storm sewer, sanitary sewer or by pouring it out on the ground.

4. Wet Deactivation -- Method Two

Fill an appropriate sized metal container 2/3 full with water. For each gallon of water, add 1/4 cup of low sudsing detergent or surfactant. Use no less than 1 gallon of water/detergent solution for 60 gas bags. Open each gas bag and dump the contents into the container as the water is stirred. Wear appropriate respiratory protection. DO NOT COVER THE CONTAINER AT ANY TIME. IF THE CONTAINER IS COVERED, THE PHOSPHINE BEING GENERATED WILL BE CONFINED AND MAY DECOMPOSE EXPLOSIVELY. This must be done outdoors or in front of an adequate fan that exhausts immediately outside.

5. Disposal Procedures

In open areas, small amounts (up to 7.0 kg) of the spent gas bags may be disposed of on site by burial of the gas bags or by opening the gas bags and spreading the dust over the land surface away from inhabited buildings. and local authorities.

Do not dispose of dust in a toilet

if approved by local authorities.

They need not be rinsed.

hydrogen phosphide gas and could cause spontaneous ignition of the gas. If the spill is only a few minutes old and is not contaminated by other materials, collect the spillage and place it back into the original or other sound metal container and tightly seal. Seal punctures with foil tape. If possible, use immediately, CAUTION: AN IGNITION MAY OCCUR WHEN THESE CONTAINERS ARE REOPENED.

2. Weevil-Cide® Gas Bags

Since the formulation is placed in small, tough gas bags, a spill will be either gas bags or a small quantity of powder spilled from a punctured gas bag. Consequently, spills are not likely to constitute a frequent problem.

If the spill is more than a few minutes old or has been contaminated with water, gather it up and place it into an open top can and deactivate it immediately.

If on-site deactivation is not feasible, these open containers should be transported in open vehicles to a suitable area away from occupied buildings. Wet or dry deactivation may then be carried out.

3. WEEVIL-CIDE® TABLETS AND PELLETS

If the spilled material is contaminated or has begun to visibly decompose, gather it up and place it into open top, perforated gallon carls and process it immediately.

Do not add more than about one flask (2 to 3 lbs.) of spilled material to the bucket. If on-site deactivation is not feasible, these open containers should be quickly transported in open vehicles to a suitable area away from occupied buildings. Protect from rainfall but do not seal or cover cans. Wet or dry deactivation may then be carried out as described in the section immediately below.

- DEACTIVATION AND DISPOSAL OF UNREACTED TABLETS. PELLETS AND GAS E. BAGS
- 1 Wet Method

Transport material by hand or in open vehicles to open air away from occupied structures. Fill a drum 2/3 full with water.

Add 1/4 cup of low sudsing detergent or surfactant in each gallon of water. Each flask of lablets or pellets or the contents of 45 gas bags should be mixed with no less than 1 gallon of water/ detergent solution. Slowly pour the material into the water as it is stirred. After 5 flasks or the contents of 200 gas bags have been added to a 55 gallon drum of water, wait until bubbling is very slow before proceeding to add 5 more flasks or 200 gas bags. Repeat this procedure until the limit is reached. Concentration readings should be taken to ensure that inhalation exposure does not exceed the prescribed limits. Stir occasionally thereafter for at least 36 hours. Wear appropriate respiratory protection, DO NOT COVER THE CONTAINER, IF THE CONTAINER IS COVERED, THE HYDROGEN PHOSPHIDE BEING GENERATED WILL BE CONFINED AND WILL DECOMPOSE EXPLOSIVELY. The wet method of deactivation is the method of choice for quantities in excess of 5 flasks (10 to 15 pounds). It is safe to dispose of this slurry.

Dispose of the resulting deactivated slurry, with or without preliminary pouring out of excess water, at a landfill or other suitable burial site approved by local authorities. The water from the sturry may be evaporated prior to disposal. Where permissible, this slurry may be poured into a sanitary sewer or out onto the ground.

SECTION 11

Spent gas bags may also be collected and disposed of at a sanitary landfill, approved

pesticide incinerator or other approved sites or by other procedures approved by federal, state

Dispose of the water/dust mixture (slurry) (with or without preliminary pouring out of excess water) in a sanitary landfill or other suitable burial site approved by local authorities. The water

from the slurry may be evaporated prior to disposal. Where permissible, the slurry may be

poured out on the ground. After being held for 36 hours it may be poured into a sanitary sewer

Never confine partially spent gas bags or slurry in closed containers such as closed drums

Dispose of containers in a sanitary landfill or by other approved state or local procedures

Disposal of Emply Weevil-Cide® Gas Bag Containers

SPILL AND LEAK PROCEDURES

GENERAL Α.

or plastic bags.

6.

A spill, other than incidental to application or normal handling or punctured containers can produce high levels of gas, and therefore, attending personnel must wear an SCBA or its equivalent when the concentration of hydrogen phosphide gas is unknown. If the concentration is known; other NIOSH/ MSHA approved respiratory protection can be worn. Wear dry cloves made of cotton or other material when contact with the powdered formulation, pellets or tablets, is likely.

DAMAGE TO FIBERBOARD CASE Β.

Check metal containers. If they are damaged, handle as described below. If they are undamaged return them to cardboard cartons or other suitable packaging which complies with DOT regulations.

LEAKING PRODUCT CONTAINER PROCEDURES C.

If containers have been punctured or damaged causing a leak, the product may be immediately used, the containers may be temporarily repaired with aluminum tape, the furnigant may be transferred from the damaged containers to sound metal containers which should be sealed and properly labeled as aluminum phosphide, or it may be deactivated and disposed. See pages 27-30 of this manual tor deactivation and disposal procedures. Transport the damaged containers is an area suitable for pesticide storage for inspection. Further instructions and recommendations may be obtained, if required, from your distributor.

Handle empty, damaged containers as described in container disposal sections.

SPILL PROCEDURES Đ.

1. General

Do not flush spillage down drain with water. DO NOT use water at anytime to clean up a spill. Water in contact with unreacted aluminum phosphide will rapidly accelerate the production of

۰.

પ્ટ

4

2. Dry Method

J

See instructions in disposal section above.

NOTE: Never place pellets, tablets, their dust or the dust/water slurry in a confined container such as a closed drum or plastic bags. Any hydrogen phosphide generated will be confined and may decompose explosively.