



071653-00001-042099

Printed: 13:03:07 Friday, 21 May, 1999 # 59 / 2925

Systems Integration Group, Inc.

**PRECAUTIONARY STATEMENT
HAZARDS TO HUMANS
AND DOMESTIC ANIMALS**

WARNING

FIRST AID STATEMENT

Harmful if swallowed or absorbed through skin. Do not get into eyes, on skin or on clothing. Avoid breathing vapour. Use in well ventilated area.

IF SWALLOWED: Do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

IF INHALED: Remove to fresh air.

IF IN EYES: Flush with plenty of water and get immediate medical attention.

IF ON SKIN: Wash hands with vegetable oil or hand degreaser and then thoroughly with soap and water.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water, in areas where surface water is present or to intertidal area below the mean high water mark. Do not contaminate water when disposing of equipment wash waters. Do not discharge effluent containing this product into lakes, streams, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State water Board or regional EPA Office.

PHYSICAL OR CHEMICAL HAZARDS

Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation.

STORAGE AND DISPOSAL

Product will not freeze. Store at temperatures between 0° F and 120° F 18°C and 50°C. If product has been spilled, spread absorbent, pick up and place in containers. Do NOT STORE opened packages.

DISPOSAL: - Wrap any cut portion of COBRAWRAP™ and put into trash collection.

COBRAWRAP™

WOOD PRESERVATIVE COMMERCIAL

WOOD EXTERIOR SURFACE
WRAP FOR ABOVE OR BELOW
GROUND TREATMENT FOR
POLES, POSTS AND PILINGS

KEEP OUT OF REACH
OF CHILDREN
WARNING
COMBUSTIBLE
HARMFUL IF SWALLOWED
See other precautionary statements
on side panels

CONTAINS INGREDIENTS LISTED BELOW
SATURATED IN SYNTHETIC ABSORBENT CLOTH
ENSAPSULATED IN CHEMICAL AND VAPOUR
RESISTANT CONTAINERS WITH AN ADDITIONAL
CHEMICAL RESISTANT VAPOUR BARRIER
EXTERIOR.

ACTIVE INGREDIENT:

| | |
|-------------------------------------|-------|
| Copper naphthenate | |
| (2% copper as metal)..... | 17.80 |
| INERT INGREDIENTS | 82.20 |
| TOTAL | 100% |
| Net Contents: 19 oz. each 18" pouch | |

EPA Reg. No. 71653-1
EPA EST. NO. 71653-CAN-001

GENES + CAN INC.
#561 53016 Hwy 60
Acheson Industrial Park
Spruce Grove, AB T7X 8C6
(780)483-WALL (780)962-1000
FAX (780)962-1052

ACCEPTED
APR 20 1999
Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 71653-1

DIRECTIONS FOR USE:

FOR EXTERIOR USE ONLY

CONTINUOUS ROLL

COBRAWRAP™ containing copper naphthenate is intended for use only on poles, posts and pilings as a wood preservative treatment. **COBRAWRAP™** containing copper naphthenate provides protection against moisture, fungal rot and termite damage. This copper naphthenate wood preservative and insecticide will preserve, protect and seal wood surfaces that will be in contact with soil or concrete. Depending upon climatic conditions, species of wood to which applied, moisture and humidity, treatment extends service life several years.

PREPARATION AND APPLICATION

Wood should be clean, dry, well seasoned and free of bark. When using **COBRAWRAP™** as a groundline treatment excavate around wood to allow top of wrap to extend 2" (5cm) above groundline. Protect eyes and skin from contact.

Wire brush area 3" (7.5cm) above groundline and approximately 20" (50cm) below groundline removing dirt and decayed material.

Cut off sufficient length of **COBRAWRAP™** leaving 2" - 6" (5cm - 15cm) of wrap to serve as overlap. Lay on ground exposing the pouches of preservative. Peel off top layer exposing the leakable layer below. On the overlap portion leave a sufficient tail attached to the outermost edge forcing preservative to move back into wood zone for penetration.

Wrap proper length **COBRAWRAP™** around the pole with saturated pad against the pole and staple or tack firmly in place. Staple short side of the backing first and overwrap with longer edge. Allow wrap to extend 2" (5cm) above groundline.

Backfill excavation, tamping firmly.

pm 34 71653-1 4/20/99 page 1 of 1