U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460	EPA Reg. Number: 72304-6	Date of Issuance: NOV 2 2 1999	
NOTICE OF PESTICIDE: <u>x</u> Registration Reregistration		Term of Issuance: Until Reregistration	
(under F1FRA, as amended)	Nare of Pestic	ide Product:	
	PROTRAM™	PROTRAM™ 40	
Name and Address of Registrant (include ZIP Code):	•		
70 Mansell Court, Suite 230 Rosvell, GA 30076 Note: Changes in labeling differing in substance from that accepted by the Registration Division prior			
correspondence on this product always refer to the above EPA reg On the basis of information furnished by the registrant, the abo	istration number. ve named pestitude is he		
registered/seregisteration under the Federal Insecticide, Fungic Registratics is in no way to be construed as an endorsement or r In order to protect health and the environment, the Administrato cance) the registration of a pesticide in accordance with the Ac with the registration of a product under this Act is not to be c exclusive use of the name or to its use if it has been covered b	ecommendatic: of this pr- r, on his metion, may at it. The acceptance of an construed as giving the m	any time suspend or - y name in connection -	
This product is conditionally reg: FIFRA sec. 3(c)(7)(A) provided that you		rdance with	
 Submit and/or cite all data of for registration/reregistration of your 3(c)(5) or FIFRA sec. 4 when the Agency of similar products to submit such data 	r product under y requires all	FIFRA sec.	
2. Make the labeling changes 1: release the product for shipment:	isted below bef	ore you	
Adam Heyward, Product Manager (34)	Date:	22/1999	

EPA Reg. No. 72304-6

a. Add the phrase, "EPA Registration No. 72304-6".

S. Sheer St. British St. St.

Э

b. Delete the following uses (Millwork Wood Product, Textiles and Canvas)

c. Please note the active ingredient (3-Iodo-2-propynlbutyl carbamate) contain in this product is currently under reregistration. Therefore, additional labeling requirement will be required in the near future.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,

Adam Heyward Product Manager 34 Regulatory Management Branch II Antimicrobials Division (7510W)

Enclosure

PROTRAMTM 40 INDUSTRIAL FUNGICIDE

Security of the second seco

Active Ingredient:		
3-Iodo-2-propynl butyl carbamate	40%	
Other Ingredients	<u>60%</u>	
Total	100%	
Contains 3.88 lbs. active ingredient per gallon		

KEEP OUT OF REACH OF CHILDREN

DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes skin burns and irreversible eye damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, protective clothing, chemical-resistant (such as nitrile or butyl) gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing before reuse. Harmful if swallowed, inhaled, or adsorbed through skin. Avoid breathing vapor or spray mist. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

STATEMENT OF PRACTICAL TREATMENT (FIRST AID)

If in Eyes: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.

If on Skin: Wash with plenty of soap and water. Get medical attention.

If Swallowed: Call a physician or poison control center. Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, or gelatin mixture, or if these are not available, large quantities of water. Avoid alcohol. Do not give anything by mouth to an unconscious person.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.

Net Contents ____ Gallons

EPA Reg. No. 72304- A

EPA Est. No. 45359-NC-1

A start of the second second

to FFA Languer Datasti

NOV 2 2 1999

Manufactured for: Sostram Corporation Roswell, GA 30076

> Under the Federal Insecticide, Directicide, and Rodenticide Act as amended. In the periodide concerned under EFR Reg. No. 72304-6

Page 1 of 5

ENVIRONMENTAL HAZARD

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, ponds, streams, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact you State Water Board or Regional Office of the EPA.

STORAGE & DISPOSAL

PESTICIDE DISPOSAL

Keep container tightly closed when not in use. Do not reuse container. Do not store with strong oxidizing agents or strong (concentrated) acids. Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. For wastes, which cannot be disposed of by use according to label instructions, contact your local State Pesticide or environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration or, if allowed by state and local authorities, by burning. If burned stay out of smoke.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling. This formulation is not cleared by Federal Food, Drug and Cosmetic Act for use in manufactured food grade adhesive, paper and paper board products and paper coating.

Adhesives

ProtramTM 40 can be used as an additive to non-medical, non-food use natural and synthetic adhesive formulations and caulks to prevent the growth of fungal organisms in the material both in the wet state and in the dry film of the finished product. Recommended use levels are between 0.05 - 0.625% wet formulation weight. This product should be added toward the end of production cycle with good agitation to ensure a uniform distribution. For example, to inhibit the growth of mildew on a latex-based wall cover adhesive for a non-food area add 0.5% (5.1bs. of ProtramTM 40 per 1000 lbs. of latex-based adhesive formulation) of this product to the latex-based formulation.

Aqueous Metalworking, Cutting, Cooling, & Lubricating Concentrates

To inhibit the growth of fungi in an aqueous metalworking, cutting, cooling & lubricating concentrates add an amount that will give up to 2,500 ppm in the diluted fluid. The amount

required in the concentrate will depend on the end use dilution. For example, if the desired level of this product in the diluted fluid is 250 ppm, and the end use dilution of the fluid is 5%, then a 0.5% concentration of this product is required in the concentrate (250 ppm/0.05 = 5,000 ppm or 0.5%).

5

1

/

Aqueous Metalworking, Cutting, Cooling, & Lubricating Fluids

To inhibit the growth of fungi in an aqueous metalworking, cutting, cooling & lubricating fluids add up to 2,500 parts per million (0.25% v/v) of this product to the diluted fluid (1 quart per 100 gallons of solution or 2.5 liters per 1000 liters). This product may be added to the fluid at the time it is prepared (diluted) or to the reservoir (sump) containing the fluid after it is put into use. If it is added to the reservoir, the fluid should be circulated after addition to ensure mixing.

Canvas and Cordage

ProtramTM 40 may be used as a mildewcide in both aqueous and solvent based process formulations, which coat canvas and cordage. Typical use levels of this product will range from 0.05 - 2.5% of the process formulations used in the process of these canvases and cordages. This product should be added to the process formulation at the end of the production cycle with good agitation to prevent possible mechanical losses and to ensure a uniform distribution. As an example, to inhibit the growth of mildew on cotton canvas intended for a non-food area add 1.25% (12 lbs. ProtramTM 40 per 1000 lbs. of process formulation) of this product to the process formulation.

Inks

ProtramTM 40 may be used in aqueous-based ink solutions for protection of these solutions against attack by fungal organisms. It is recommended that this product be added at the end of the production cycle with good agitation. This product will generally impart protection when used at levels of 0.05 - 3.0% of active ingredient based on the formula weight.

Paints and Stains

ProtramTM 40, used in solvent and waterborne paints and stains, will inhibit the growth of mildew. Addition should be at the end of the manufacturing process and allowed to mix long enough to be adequately dispersed and should not be added to hot paint. Typical levels for protection against mildew on painted surfaces are 0.25 - 1.2% by weight on wet paint. For example, house paint with a wet density of 10 lbs. per gallon would use 2.5 - 12.0 lbs. of this product per 100 gallons of wet paint. Where the climate is severe and mildew growth is a major problem for painted surfaces, more would be required, as much as 2.0% by weight in the paint. For interior paint use, approximately half the exterior concentrations should be used, 0.1 - 0.6% by weight in the paint. Appropriate levels are best determined by field trials.

Plastics and Plastic Coatings

ProtramTM 40 may be used to prevent surface mildew growth on plastic items such as shower curtains, cable and wire insulation and sun umbrellas. Intended plastics include polymers such as PVC. Use levels of 0.1250 - 2.5% by weight of the plastic are generally adequate. This product should be dispersed in the plasticizer or color concentrate before it is incorporated into the resin to ensure a uniform distribution. Use of this product is not recommended if the heat of processing is above 350 °F for prolonged periods, nor should it be used in a plastic that will be in contact with food or medical device applications.

Paper Coatings

ProtramTM 40 may be used as a mildewcide in both aqueous and solvent-based coatings, which are applied to paper and cardboard substrates. This product can be used to prevent mold and mildew from growing on products such as: corrugated cardboard or soap wrappers, wall covers, non-food contact packaging materials, and non-food contact paper tapes. Use levels of this product range from 0.05 - 2.0% of this product by weight. This product should be added at the end of the production cycle and with good agitation to prevent possible mechanical losses and to ensure uniform distribution. As an example, to inhibit growth of mildew on corrugated cardboard intended for a non-food packaging add 1.25% (12.5 lbs. ProtramTM 40 per 1000 lbs. of coating material) of this product to the coating material formulation.

7

Textiles

ProtramTM 40 may be used as a mildewcide applied in both aqueous and solvent-based coatings or dyes, which are typical to the textile material processing. Typical end use applications of these materials can be carpet fibers and backings, canvas and cordage, drapes, shower curtains, etc. Not to be used in fabrics for human wear or direct skin contact. The product should be solubilized or stirred in the dye bath or polymer coating pan to minimize mechanical losses and \checkmark ensure a uniform distribution of the product. Use levels in the range of 0.05 - 2.5% by weight of the total processing formulation are typically adequate to prevent fungal growth. As an example, to inhibit the growth of mildew on cotton canvas intended for a non-food area add 1.25% (12.5 lbs. ProtramTM 40 per 1000 lbs. of dye bath) of this product the dye bath formulation.

Wood Preservation

ProtramTM 40 is a liquid designed for use as an additive to interior or exterior protective coatings to inhibit the growth of mildew on the film surface. It is also recommended as a wood preservative for use in above ground applications. All recommendations of use levels are in percentage by weight, and refer to this product. Dosage ranges are given for the various applications to indicate the approximate levels for a particular application. Exact levels of use should be determined by field trials.

ProtramTM 40 may be applied from solvent solutions or aqueous dispersions to new lumber, plywood, particle board, millwork, etc., to prevent the growth of mildew, sapstain and wood rot on these substrates. This product is recommended for use on wood in above ground use only.

Treating solutions may be prepared by diluting this product in alcohols or aromatic solvents or by dispersion in water. Levels of 0.25 - 3% of this product are suggested depending upon the severity of conditions for end use, and the extent of time that protection is required.

For freshly sawn lumber, a concentration of 0.5% of this product is suggested as a starting level. A one minute dip at ambient temperatures in a solution or aqueous dispersion containing 0.5% of this product should be adequate to control the development of mildew and sapstain organisms on the lumber. Because of the great variation in susceptibility of fresh sawn lumber relating to the type of wood, sawing and storage techniques, conditions of humidity, method of treatment, etc., it is usually necessary to carry out field tests to determine the most appropriate means of application and the optimum concentration of this product to be used within the range specified.

For best results, lumber should be treated within twenty-four hours after it is sawed. The lumber should be completely immersed in the treating bath, and the treating vat designed to permit casy immersion and removal, and to minimize spillage. The vat may be cleaned by emptying and rinsing with a suitable solvent or by use of a detergent solution. To add additional product while

treating, first prepare the proper solution or emulsion in a separate container (of wood, plastic, or stainless steel construction) and add to the treating vessel.

After treatment, lumber should be stacked in a properly maintained seasoning yard with good drainage so that no water will accumulate, in any area. The yard should be kept free from weeds and vegetation, which may hold moisture and promote growth of decay and stain producing fungi. All debris and lumber scraps should be removed from the area. A properly laid out yard should take advantage of prevailing winds to permit good air circulation. Main alleys should be at least 16 feet wide. Stack foundations should be sufficiently elevated to permit ready access of air to the pile, and allow water to drain off quickly.

Millwork

Í

This product is also recommended for use on millwork, including door and window frames, exterior siding, composite board, plywood and other construction lumber when it is important to prevent growth of mildew, sapstain and wood rot organisms on these materials. Wood treated with this product does not change in appearance and may be painted when dry. For applications of this type, this product may be applied by dipping, brushing or spraying. Levels of 0.25% may be used for mildew control.

To control rot and decay, do not use less than 0.5% as a concentration. Use this product in solution in a suitable solvent. Concentrations up to 2.0% are recommended depending upon the condition of the wood, the nature of the intended exposure and the length of protection desired.

When brushing, a single coat will usually suffice if the solution is applied liberally. This also pertains to spraying. Use of this product is not recommended for wood surfaces that may come in contact with food. Surfaces, which may be in continuous contact with skin, should be coated with a varnish or lacquer after treatment with this product. This product may also be used as an additive to stains to be applied to such materials as exterior siding, decks, lawn furniture, etc., in order to prevent the growth of fungal organisms. It is recommended that levels between 0.5 - 2.0% of this product by weight of the final formulation be added to these materials.

WARRANTY AND LIMITATIONS OF DAMAGES

CONDITIONS OF SALE: Sostram Corporation warrants that this product conforms to the chemical description stated on the label when used in accordance with the directions under normal conditions of use. This warranty does not extend to the use of this product contrary to label instructions, or under abnormal use conditions, or under conditions not reasonably foreseeable to Sostram. SOSTRAM DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF FITNESS OR MERCHANTABILITY. SOSTRAM SHALL NOT BE LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, AND SOSTRAM'S SOLE LIABILITY AND BUYER'S AND USER'S EXCLUSIVE REMEDY SHALL BE LIMITED TO THE REFUND OF THE PURCHASE PRICE. BUYER AND USER ACKNOWLEDGE AND ASSUME ALL RISKS AND LIABILITY RESULTING FROM HANDLING, STORAGE AND USE OF THIS PRODUCT. SOSTRAM DOES NOT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION CONCERNING THIS PRODUCT.