STATES TATES TO STATES TO

U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460 EPA Reg. Number:

Date of Issuance:

72304-7

NOV 2 2 1999

NOTICE OF PESTICIDE:

x Registration
Reregistration

Term of Issuance: Until Reregistration

(under FIFRA, as amended)

Name of Pesticide Product:

PROTRAM™ 20

Name and Address of Registrant (include ZIP Code):

Sostram Corporation 70 Mansell Court, Suite 230 Rosvell, GA 30076

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregisteration under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data or other material required for registration/reregistration of your product under FIFRA sec. 3(c)(5) or FIFRA sec. 4 when the Agency requires all registrants of similar products to submit such data.

and the second s

2. Make the labeling changes listed below before you release the product for shipment:

Signature of Approving Official:

Date

Adam Herward, Product Manager (34) Regulatory Management Branch II Antimicrobials Division (7510W)

Nov 22, 1999

EPA Form 8570-6

EPA Reg. No. 72304-7

- a. Add the phrase, "EPA Registration No. 72304-7".
- Delete the following uses (Millwork Wood Product, Textiles and Canvas)
- c. Please note the active ingredient (3-Iodo-2-propynl-butyl carbamate) contain in this product is currently under reregistration. Therefore, additional labeling requirement will be required in the near future.
- 3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,

Adam Heyward

Product Manager 34

Regulatory Management Branch II Antimicrobials Division (7510W)

Enclosure

1

PROTRAMTM 20 INDUSTRIAL FUNGICIDE

Active Ingredient:	
3-Iodo-2-propynl butyl carbamate	%
Other Ingredients	<u>%</u>
Total)%
Contains 1.73 lbs. active ingredient per gallon	

WARNING

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes skin irritation. Harmful if swallowed, adsorbed through the skin or inhaled. Causes moderate eye irritation. Do not get on skin, in eyes or on clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing before reuse.

STATEMENT OF PRACTICAL TREATMENT (FIRST AID)

If in Eyes: Flush with plenty of water. Call a physician if irritation persist.

If on Skin: Wash with plenty of soap and water. Get medical attention.

If Swallowed: Call a doctor or get medical attention. Do not induce vomiting or give anything by mouth to an unconscious person. Drink promptly a large quantity of milk, eggwhite, or gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.

Net Contents ____ Gallons

EPA Reg. No. 72304-

EPA Est. No. 45359-NC-1

ACCEPTED with COMMENTS In EPA Letter Dated:

Manufactured for: Sostram Corporation Roswell, GA 30076

NOV 2 2 1999

Under the Pederal Insecticide,
Furgacide, and Rodernicide Action
schedule, for the pesticide,
registered under EPA Reg. No. 112304-7

Page 1 of 5

ENVIRONMENTAL HAZARD

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, ponds, streams, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact you State Water Board or Regional Office of the EPA.

STORAGE & DISPOSAL

PESTICIDE DISPOSAL

Keep container tightly closed when not in use. Do not reuse container. Do not store with strong oxidizing agents or strong (concentrated) acids. Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. For wastes, which cannot be disposed of by use according to label instructions, contact your local State Pesticide or environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration or, if allowed by state and local authorities, by burning. If burned stay out of smoke.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling. This formulation is not cleared by Federal Food, Drug and Cosmetic Act for use in manufactured food grade adhesive, paper and paper board products and paper coating.

Adhesives

ProtramTM 20 can be used as an additive to non-medical, non-food use natural and synthetic adhesive formulations and caulks to prevent the growth of fungal organisms in the material both in the wet state and in the dry film of the finished product. Recommended use levels are between 0.1 – 1.25% wet formulation weight. This product should be added toward the end of production cycle with good agitation to ensure a uniform distribution. For example, to inhibit the growth of mildew on a latex-based wall cover adhesive for a non-food area add 1.0% (19 lbs. of ProtramTM 20 per 1000 lbs. of latex-based adhesive formulation) of this product to the latex-based formulation.

Aqueous Metalworking, Cutting, Cooling, & Lubricating Concentrates To inhibit the growth of fungi in an aqueous metalworking, cutting, cooling & intricating concentrates add an amount that will give up to 5,000 ppm in the diluted fluid. The amount required in the concentrate will depend on the end use dilution. For example, if the desired level of this product in the diluted fluid is 500 ppm, and the end use dilution of the fluid is 5%, then a

1.0% concentration of this product is required in the concentrate (500 ppm/0.05 = 10,000 ppm or 1.0%).

Aqueous Metalworking, Cutting, Cooling, & Lubricating Fluids

To inhibit the growth of fungi in an aqueous metalworking, cutting, cooling & lubricating fluids add up to 5,000 parts per million (0.5% v/v) of this product to the diluted fluid (0.5 gallons per 100 gallons of solution or 5 liters per 1000 liters). This product may be added to the fluid at the time it is prepared (diluted) or to the reservoir (sump) containing the fluid after it is put into use. If it is added to the reservoir, the fluid should be circulated after addition to ensure mixing.

Canvas and Cordage

ProtramTM 20 may be used as a mildewcide in both aqueous and solvent based process formulations, which coat canvas and cordage. Typical use levels of this product will range from 0.1-5% of the process formulations used in the process of these canvases and cordages. This product should be added to the process formulation at the end of the production cycle with good agitation to prevent possible mechanical losses and to ensure a uniform distribution. As an example, to inhibit the growth of mildew on cotton canvas intended for a non-food area add 2.5% (25 lbs. ProtramTM 20 per 1000 lbs. of process formulation) of this product to the process formulation.

Inks

)

ProtramTM 20 may be used in aqueous-based ink solutions for protection of these solutions against attack by fungal organisms. It is recommended that this product be added at the end of the production cycle with good agitation. This product will generally impart protection when used at levels of 0.05 - 3.0% of active ingredient based on the formula weight.

Paints and Stains

ProtramTM 20, used in solvent and waterborne paints and stains, will inhibit the growth of mildew. Addition should be at the end of the manufacturing process and allowed to mix long enough to be adequately dispersed and should not be added to hot paint. Typical levels for protection against mildew on painted surfaces are 0.5 – 2.4% by weight on wet paint. For example, house paint with a wet density of 10 lbs. per gallon would use 5 – 24.0 lbs. of this product per 100 gallons of wet paint. Where the climate is severe and mildew growth is a major problem for painted surfaces, more would be required, as much as 4.0% by weight in the paint. For interior paint use, approximately half the exterior concentrations should be used, 0.2 – 1.2% by weight in the paint. Appropriate levels are best determined by field trials.

Plastics and Plastic Coatings

ProtramTM 20 may be used to prevent surface mildew growth on plastic items such as shower curtains, cable and wire insulation and sun umbrellas. Intended plastics include polymers such as PVC. Use levels of 1.5 – 5.0% by weight of the plastic are generally adequate. This product should be dispersed in the plasticizer or color concentrate before it is incorporated into the resin to ensure a uniform distribution. Use of this product is not recommended if the rest of processing is above 350 °F for prolonged periods, nor should it be used in a plastic that will be in contact with food or medical device applications.

Paper Coatings

ProtramTM 20 may be used as a mildeweide in both aqueous and solvent-based coatings, which are applied to paper and cardboard substrates. This product can be used to prevent mold and mildew from growing on products such as: corrugated cardboard or soap wrappers, wall covers,

non-food contact packaging materials, and non-food contact paper tapes. Use levels of this product range from 0.1-3.75% of this product by weight. This product should be added at the end of the production cycle and with good agitation to prevent possible mechanical losses and to ensure uniform distribution. As an example, to inhibit growth of mildew on corrugated cardboard intended for a non-food packaging add 2.5% (25 lbs. Protram TM 20 per 1000 lbs. of coating material) of this product to the coating material formulation.

Textiles

ProtramTM 20 may be used as a mildewcide applied in both aqueous and solvent-based coatings or dyes, which are typical to the textile material processing. Typical end use applications of these materials can be carpet fibers and backings, canvas and cordage, drapes, shower curtains, etc. Not to be used in fabrics for human wear or direct skin contact. The product should be solubilized or stirred in the dye bath or polymer coating pan to minimize mechanical losses and ensure a uniform distribution of the product. Use levels in the range of 0.1 –5% by weight of the total processing formulation are typically adequate to prevent fungal growth. As an example, to inhibit the growth of mildew on cotton canvas intended for a non-food area add 2.5% (25 lbs. ProtramTM 20 per 1000 lbs. of dye bath) of this product the dye bath formulation.

Wood Preservation

ProtramTM 20 is a liquid designed for use as a wood preservative for use in above ground applications. All recommendations of use levels are in percentage by weight, and refer to this product. Dosage ranges are given for the various applications to indicate the approximate levels for a particular application. Exact level of use should be determined by field trials

ProtramTM 20 may be applied from solvent solutions or aqueous dispersions to new lumber, plywood, particle board, millwork, etc., to prevent the growth of mildew, sapstain and wood rot on these substrates. This product is recommended for use on wood in above ground use only.

Treating solutions may be prepared by diluting this product in alcohols or aromatic solvents or by dispersion in water. Levels of 0.5 - 6.0% of this product are suggested depending upon the severity of conditions for end use, and the extent of time that protection is required.

For freshly sawn lumber, a concentration of 1.0% of this product is suggested as a starting level. A one minute dip at ambient temperatures in a solution or aqueous dispersion containing 1.0% of this product should be adequate to control the development of mildew and sapstain organisms on the lumber. Because of the great variation in susceptibility of fresh sawn lumber relating to the type of wood, sawing and storage techniques, conditions of humidity, method of treatment, etc., it is usually necessary to carry out field tests to determine the most appropriate means of application and the optimum concentration of this product to be used within the range specified.

For best results, lumber should be treated within twenty-four hours after it is sawed. The lumber should be completely immersed in the treating bath, and the treating vat designed to permit easy immersion and removal, and to minimize spillage. The vat may be cleaned by emptying and rinsing with a suitable solvent or by use of a detergent solution. To add additional product while treating, first prepare the proper solution or emulsion in a separate container (of wood, plastic, or stainless steel construction) and add to the treating vessel.

After treatment, lumber should be stacked in a properly maintained seasoning yard with good drainage so that no water will accumulate, in any area. The yard should be kept free from weeds and vegetation, which may hold moisture and promote growth of decay and stain producing

ţ

fungi. All debris and lumber scraps should be removed from the area. A properly laid out yard should take advantage of prevailing winds to permit good air circulation. Main alleys should be at least 16 feet wide. Stack foundations should be sufficiently elevated to permit ready access of air to the pile, and allow water to drain off quickly.

Millwork

This product is also recommended for use on millwork, including door and window frames, exterior siding, composite board, plywood and other construction lumber when it is important to prevent growth of mildew, sapstain and wood rot organisms on these materials. Wood treated with this product does not change in appearance and may be painted when dry. For applications of this type, this product may be applied by dipping, brushing or spraying. Levels of 0.50% may be used for mildew control.

To control rot and decay, do not use less than 1.0% as a concentration. Use this product in solution in a suitable solvent. Concentrations up to 4.0% are recommended depending upon the condition of the wood, the nature of the intended exposure and the length of protection desired.

When brushing, a single coat will usually suffice if the solution is applied liberally. This also pertains to spraying. Use of this product is not recommended for wood surfaces that may come in contact with food. Surfaces, which may be in continuous contact with skin, should be coated with a varnish or lacquer after treatment with this product. This product may also be used as an additive to stains to be applied to such materials as exterior siding, decks, lawn furniture, etc., in order to prevent the growth of fungal organisms. It is recommended that levels between 1.0 – 4.0% of this product by weight of the final formulation be added to these materials.

WARRANTY AND LIMITATIONS OF DAMAGES

CONDITIONS OF SALE: Sostram Corporation warrants that this product conforms to the chemical description stated on the label when used in accordance with the directions under normal conditions of use. This warranty does not extend to the use of this product contrary to label instructions, or under abnormal use conditions, or under conditions not reasonably foreseeable to Sostram. SOSTRAM DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF FITNESS OR MERCHANTABILITY. SOSTRAM SHALL NOT BE LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, AND SOSTRAM'S SOLE LIABILITY AND BUYER'S AND USER'S EXCLUSIVE REMEDY SHALL BE LIMITED TO THE REFUND OF THE PURCHASE PRICE. BUYER AND USER ACKNOWLEDGE AND ASSUME ALL RISKS AND LIABILITY RESULTING FROM HANDLING, STORAGE AND USE OF THIS PRODUCT. SOSTRAM DOES NOT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION CONCERNING THIS PRODUCT.