4/1/2009



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

Eric Knipe President Princestone Corp. 9773 Santa Monica Blvd., #587 Beverly Hills, CA 90210

APR - 7 2009

Subject: Moldwash Wood Preservative/Mold Control EPA Registration No. 72468-3 Application Date: February 04, 2009 Receipt Date: March 08, 2009

Dear Mr. Knipe:

This acknowledges receipt of your notification, submitted under the provision of PR Notice 98-10, FIFRA section 3(c)9.

Proposed Notification

- Company name change from "Mold Free, Inc." to "Princestone Corp."
- Primary brand name change from "Moldwash Wood Preservative/Mold Control" to "PMC 360"

Based on a review of the material submitted, the following comments apply:

The Agency acknowledges your change of company name. The Primary brand name PMC 360 is acceptable. Please submit five (5) copies of your revised labeling to the Agency for review.

Should you have any questions concerning this letter, please contact me by telephone at (703) 308-6415 or email address at: <u>Lantz.Tracy@epa.gov</u> during the hours of 8:00 am to 3:30 pm EST. When submitting information or data in response to this letter, a copy of this letter should accompany the submission to facilitate processing.

Sincerely,

Tray Jast

Tracy Lantz (Acting) Product Manager (34) Regulatory Management Branch II Antimicrobials Division (7510P)

3~1

64

(.

{

Sector And Annual Sector Annual			Burb			70.0000	
SEPA Environmental Protoction Windington, 60 20			Ion Agency		Registration Amendment Other		OPP Intentition Humber
		Application for	Pestigide - 8	oction	1		
1. CompanysFroduct Number 72468-3			BPA Product Missioner Richard Gebken or Adam Hayward				
4, Company/Freduct (Flemat PIAC 360			Mar Id(Gebken) or 34 (Heyward)				
5. Nome and Address of Applicant Unclude 20 ⁹ Gode/ Princestone: Corp. 9773 Sama Monica Blvd, #587 Oeverty Hills, CA 90210			6. Expedized Review. In accordance with PIPAA Section 3(c)(3) (b)(8, my product is similar or identical in comparison and isosing to: 72468-3 (9) EPA Reg. No.				
Chest if the	in a nave address		Product New				tive/Mold Control
		Se					-
Amandment - Explain Resultation in respo Antheodon - Explain (1919) Stiller: Lies addition		Final printed initials to respect to Appropriate to Appropriate Catholic Inc. The Teo* Application. Other - Explain balance.					
stification of Primary Bri gulations at 40 CFR 152 oduct, 1 understand the	46 and no other ch	anges have been mi 18 U.S.C. Sec. 1081 (1	ide to the labeling see Page 2)				
		See	Hen - H				
Meterial Tids Produce Will	Contraction of States of States	and the second second second	La	1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919 - 1919			
id-finitionen Posteging	Usis Packaging	Tillera Privata	Schole Pankaging		2. Type of	•	
Yest *	Yes .	· · · · · · · · · · · · · · · · · · ·	Yes			Plattic	
Hite	Na.		Na			Öléni Panar	
Conditionation states	ti "Ver" Unit Paulaging wgt	No. per 8 M actualities Pecio	nga wgt Gint	943 617660		Other C	
Location of Net Contents (niorination onteiner	4. Oliviel Rousi Com	alerer f	Ē	On Label		nin Sinta biologia
Rommer in Which Label is . Custome Paint, Marguetato			Non - IV				ngeneratenske generatense gedensen oftense generatense oftense oftense oftense oftense generatense oftense oftense mannet Mannet av 1
			THE PARTY OF THE PARTY OF	CONTRACTOR OF CONTRACTOR	interest and the second	فينتعج وبارخمي الأطر	e No. (Include Area Code
k Knipa	allantin kay da satist pinin ini sangata ya	Preside	201			(310) 38	
i cardiy that the stater () acknowledge that even both ander applicable i	y knowingly fallinger a	Certification this form and di strad delanding statement n	hmocis Unises act ny ha panisinàlia d	Wis, aco y line or i	unate and con Ingrisonium	n gieta. Gr	6. Giere Appleanian Received (Blaimped)
Sigrature	$\langle 0$	a. Tide Preside	int	· .			
00		5. Den Febru	ary 4, 2009				
	ισου σιτ		ç a sızlı sığı didi i bak si alsibiy		PA File Copy	longinal	Vallow - Applicant (
εει ξι				••	÷		

p.3

2/6

Mold Free, Inc. 9601 Wilshire Bivd, Suite 620 Beverty Hills, CA 90210

(310) 383-3240 (310) 383-0055 evknipe@gmail.com

February 9, 2009

1. A state for multi dimensione state and a state of the state of the

- こうにうちのうにんないうと、みまびのであったうろうでき

Via Facsimile: (703) 305-7670 and Federal Express Mail

Ms. Kathleen O'Malley U.S. Environmental Protection Agency Document Processing Desk (AMED) Office of Pesticide Programs Room S4900, One Potomac Yard 2777 Crystal Drive Arlington, VA 22202

RE: Registration Numbers:

Request for Company Name Change and Product Name Change' 72468-3 Moldwash Wood Preservative/Mold Control (New Name: PMC 360[™])

Dear Ms. O'Malley:

This letter is to replace the letter I sent to Adrienne Turner (Document Processing Desk (NEWCO) dated February 4, 2009. Regarding the above captioned registration numbers, this is to notify you that the corporate name of Mold Free, Inc. has been changed to Princestone Corp. and remains under the same ownership of Eric Knipe (aka Eric Von Knipe) and there is no asset change. The product name Moldwash Wood Preservative/Mold Control has been changed to PMC 360TM.

The new address for Princestone Corp. is as follows:

New Corporate Name: Corporate Contacts: Contact Phone Number: Contact Email Addresses:

Official Mailing Address:

Princestone Corp. 9663 Santa Monica Blvd., #587 Beverly Hills, CA 90210

Eric Knipe (aka Eric von Knipe)

The old address was:

Mold Free, Inc. 9601 Wilshire Blvd., Suite 620 Beverly Hills, CA 90210

February 9, 2009

Princestone Corp.

(310) 383-0055 evknipe@gmail.com

C:CKsDocs:MoldFreeInc.2009OMalley020909

ffective Date:

Page Two EPA Form 8570-1

Company Product Number:

72468-3

New Company Product Name:

PMC 360 (formerly Moldwash Wood Preservative/Mold Control)

Name and Address of Applicant

Princestone Corp. (formerly Mold Free, Inc.) 9663 Santa Monica Blvd., #587 Beverly Hills, CA 90210

Section II (cont.)

to willfully make any false statements to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 98-10 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and <u>penalties under sections 12 and 14 of FIFRA</u>.

Eric Knipe, President Princestone Corp. Date : February 4, 2009

PMC 360™

Wood Preservative/Mold Control

For the preservation, protection and preventative treatment of wood against decay fungi *mold* and wood-destroying insects and for remedial control of such pests in infested wood.

Active Ingredient:

Disodium Octaborate Tetrahydrate	10% (12% BAE)*
(Na ₂ .B ₈ O ₁₃ .4H ₂ O)	. ,
Inert ingredients	90%

* 10% Disodium Octaborate Tetrahydrate active ingredient is equivalent to 12% Boric acid, Acid Equivalents-BAE

Keep out of reach of children

CAUTION

FIRST AID

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-tomouth if possible.
- Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a poison center or doctor, or going for treatment.

Precautionary statements:

Caution

Hazards to humans and domestic animals

72468-3

72468

Harmful if swallowed. Avoid contact civith eyes. Wash thoroughly after handling. Avoid contamination of food and feed. Do not leave container where children or animals may gain access.

PERSONAL PROTECTIVE EQUIPMENT: Applicators and other handlers must wear a long-sleeved shirt and long pants which cover the entire arm and leg skin surface, socks, water-resistant boots, chemical resistant gloves and chemical resistant protective eyewear – splash goggles are recommended. When applying this product in confined spaces such as craw, spaces and atticu, a veritilation exhaust system is recommended. If this is impractical, the use of a NIOSH approved respirator designed for dusts/mists is recommended. Crean spills and over-sorely with a clean damp for the use an absorbent. Dispose of spill as required by state guidelines and laws.

EPA Reg. No. EPA Est.

Manufactured by:

Princestone Corp. 9663 Santa Monica Blvd, #587 Beverly Hills, CA 90210

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. *Storage:* Store in a dry place. Do not store where children or animals may gain access.

Pesticide disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. *Container disposal:* Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Environmental hazards

*PMC 360™*solutions carelessly spilled or applied to cropland or growing plants, including trees and shrubs, may kill or seriously retard plant growth. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Target organisms

PMC 360TM is an effective treatment for wood against decay, fungi, common molds including brown (i.e. Poria), white, and wet rots.

Preparation of treatment solution

PMC 360TM is a ready-to-use solution that can be applied without any preparation of the solution.

If using as a foam: Simply add a surfactant/foaming agent to the solution. Typically 1-2 ounces of foaming agent added to the aqueous solution will produce foam with the desired expansion ratios of approximately 20 to 1 (approx. 20 gallons of foam per 1 gallon of *PMC 360TM* aqueous solution). *PMC 360TM* foam should be of a consistency that adheres to wood surfaces, so that run-off is minimized. Since each foam machine can produce different foams, refer to the manufacturer manuals and the surfactant's label for specific instructions.



Net contents ____ Gallons

Directions for use

It is a violation of Federal Law to use this $p_{\rm c}^\prime$, t in a manner inconsistent with its labeling.

General information

*PMC 360TM*is a ready-to-use solution with fungicidal/fungistatic properties. This product cannot be tank mixed with other products. This product will protect only treated wood and gypsum facing.

This product can be used in coatings to treat all interior and exterior wood structural components which when utilized will be protected from rain and not in direct contact with the ground. The treatment of lumber is permanent even after cutting and finishing providing the wood is not exposed to water for a prolonged period of time or in contact with the ground.

This product can be used for <u>preventative treatment</u> of wood in existing structures (before signs of infestation), for <u>pre-treatment</u> of wood during construction and for <u>remedial treatment</u> of wood infested with mold and fungus, as listed below.

PMC 360TM is recommended for wood and cellulose materials, in accordance with the specific treatment methods described herein. This product should be applied only to treat bare wood, plywood and particle board where an intact water repellent barrier such as paint, stain or a sealer is not present. **Do not apply to foam-board.**

PMC 360™ is effective for all interior and exterior wood that will be protected from excessive rain and not in direct contact with soil. Types of wood include, but are not limited to, all types of lumber, logs and plywood. Use of this product does not substitute for mechanical alteration, soil treatment or foundation treatment, but is merely a supplement.

This product is toxic to wood-destroying molds and fungi, but surface etching of treated wood by target organisms may occur. Application of *PMC 360TM*to control wood-destroying organisms must be part of an Integrated Pest Management (IPM) strategy. Current Princestone Corp. specifications and technical bulletins must be followed for all treatment methods.

Do not use to treat lumber that will contact soil or be exposed to leaching by weather.

Application

*PMC 360™*may be used as a solution or foam. For remedial control of mold, fungi and common molds attacking wood, or for protection of wood against future infestations, 2 applications of the PMC 360[™]aqueous solution are normally required.

Solutions

Apply solutions by brush or spray until the wood surface is thoroughly wet, at a rate of approximately 1 gallon per 200 square feet of wood surface area. Spray evenly using a medium or coarse spray at low pressure (20-30 psi). Best results and penetration will be obtained when ambient temperatures are above 55°F. Do not spray frozen wood, painted or waterproofed surfaces.

Foam

Apply foam so that all accessible wood surfaces are covered with foam at a rate of approximately 1 gallon per 200 square feet of wood surface area. Spray evenly using a medium or coarse spray at low pressure (20-30 psi). Where possible, place foam between wood joints or abutting wood surfaces. In wall voids, inject enough foam to contact *drywall and* wood surfaces of studs in the wall or the target area desired. Best results and penetration will be obtained when ambient temperatures are above 55°F. Do not foam frozen wood, painted or waterproofed surfaces.

Pressure processes

Pressure treatment procedures must rigidly adhere to the standards of Mold Free, Inc. and/or those of the American Wood Preservers' Association. If several species are being treated at once, choose the treating schedule for the most difficult to treat species.

Preventative treatment

Application of PMC 3607M solution and form will prevent infestation of mold and fungus.

Directions for use continued

Drilling and injection

Application may also be by drilling and then injecting the solution or foam under pressure into sound wood or until runoff is observed from entry/exit holes of infested wood. Injection holes (approximately $^{1}/_{8}$ inch diameter) should be drilled in the area of suspected infestation, preferably in a diamond pattern with the long axis (12-16 inches) along the grain and the short axis (4-6 inches) across. Drill holes approximately $^{3}/_{4}$ of the thickness of the beam. The solution is injected under pressure (65-70 psi) for 15-60 seconds in each hole. Please refer to Princestone Corp. technical bulletin for further details.

Remedial treatment

 $\it PMC~360^{\tau m}$ solution and foam will penetrate dry wood down to $\frac{1}{2}$ inch below treated surfaces.

Attics, crawlspaces and basements

Spray *PMC 360*TMto all accessible wood: rafters, trusses, top-plates, ceiling joists, plywood, particleboard, flooring, sub-floor etc. This application will control an infestation even when certain parts of the gallery are not directly sprayed. This has been a very effective technique in spot treating for control of mold and fungus.

Pre-treatment to wood - new construction

Spray or foam applications of *PMC 360*TMmay also be made to wood during construction. Apply solution to all accessible surfaces of bare wood at a rate of approximately 1 gallon per 200 square feet of wood surface area. Application should be performed after framing and roofing are in place and before drywall and insulation are installed. Avoid spraying electrical components. Protect wood from excessive rain.

Exterior wood

*PMC 360TM*can be applied to bare siding, trim or logs. Applications can be made by spray or pressure injection techniques. Painted or sealed wood can be treated by pressure injection or the sealing coat can be removed prior to application. Following treatment, exterior wood surfaces should be sealed. Wood should be completely dry before a sealing coat (paint, varnish or waterproofing seal) can be applied.

Decks

*PMC 360TM*can be used to treat wood decks. Prepare the deck by removing any dirt, debris or sealants that will interfere with the application and absorption of *PMC 360TM*. After the deck has dried (dry to the touch) two applications of *PMC 360TM*can then be applied to the wood. Protect any surrounding plants, ornamentals from accidental contact with the solution. Following treatment the deck should be allowed to dry before a sealing coat is applied.

PMC 360TMIS FOR NON-FOOD USE ONLY.

This product cannot be tank mixed with other products. In the home, remove or cover exposed food, food handling surfaces, and cooking utensils. Wash thoroughly after treatment and before reuse.

Do not use in any type of food processing plant (meat, poultry, shell egg, etc.) or food handling area. **DO NOT APPLY TO FOOD**. Do not use in cafeterias, kitchens, bakeries, meat packing plants, food processing plants, or any type of food handling establishment.

Do not apply in classrooms when in use. Do not use in aircraft cabins. Do not apply to patient rooms in hospitals and nursing homes while occupied.

Such applications are not a substitute for mechanical alteration, soil treatment or foundation treatment but are merely a supplement.

When spraying overhead interior areas of homes, apartment buildings and all other dwellings, cover or protect surfaces below the area being treated with plastic sheeting or other material which can be disposed of if contamination from dripping or splashing occurs.

Current Princestone Corp. specifications/technical bulletins should be followed for all treatment methods to ensure adequate chemical loadings in wood.

Notice Because of many varying conditions affecting use and opplication, manufacturer warns buyer that these may impair or vary the results or effects of the use of this product. In any event, complete prevention of decay by fund or other organisms is not guaranteed. Neither manufacturer nor seller shall be liable in respect to any injury or damages suffered by reason of the use of this product for a purplet on the label, or when used contrary to the directions or instructions hereon, nor with respect to breach of any warranty not expressly specified herein. Buyer accepts this material subject to these terms, and assumes all risk of usage and handling except when used or handled in accordance with this label. There are no express warranties on *Princestone Corp*, or implied warranties of merchantability or fitness for any particular purpose, except as specifically stated herein Manufacturer shall not be liable for any consequential damages based on the use of this product.