



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

February 8, 2018

Eric Y. Knipe
Pre-Chem Inc
9663 Santa Monica Blvd, #593
Beverly Hills, CA 90210

Subject: Notification per PRN 98-10 – *Removal of the following under Target Organisms:*
“such as”

Product Name: Flo-X/Moldwash/Wood Preservative/Mold Control

EPA Registration Number: 72468-7

Application Date: 12/26/17

Decision Number: 537783

Dear Mr. Knipe:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact me at 703-305-6440 or via email at grigsby.stacey@epa.gov .

Sincerely,

A handwritten signature in blue ink that reads "Stacey Grigsby".

Stacey Grigsby, Regulatory Risk Manager
Regulatory Management Branch II
Antimicrobials Division (7510P)

MASTER LABEL

FLO-X/MOLDWASH

Wood Preservative/Insect/Mold Control

For the preservation, protection and preventative treatment of wood against decay fungi *mold* and wood-destroying insects and for remedial control of such pests in infested wood.

Active Ingredient:

Disodium Octaborate Tetrahydrate 10% (12% BAE)*
(Na₂B₈O₁₃·4H₂O)

Inert ingredients 90%

Total 100%

* 10% Disodium Octaborate Tetrahydrate active ingredient is equivalent to 12% Boric acid. Acid Equivalents-BAE

KEEP OUT OF REACH OF CHILDREN

CAUTION

FIRST AID

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a poison center or doctor, or going for treatment.

Precautionary statements

Caution

Hazards to humans and domestic animals

Harmful if swallowed. Avoid contact with eyes. Wash thoroughly after handling and before eating, drinking, chewing gum, using tobacco, and using toilet. Avoid contamination of food and feed. Do not leave container where children or animals may gain access.

NOTIFICATION

72468-7

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

02/08/2018

PERSONAL PROTECTIVE EQUIPMENT RECOMMENDATION: Applicators and other handlers must wear a long-sleeved shirt and long pants which cover the entire arm and leg skin surface, socks, water-resistant boots, chemical resistant gloves and chemical resistant protective eyewear – splash goggles are recommended. When applying this product in confined spaces such as crawl spaces and attics, a ventilation exhaust system is recommended. If this is impractical, the use of a NIOSH approved respirator designed for dusts/mists is recommended. Clean spills and over-spray with a clean damp cloth or use an absorbent. Dispose of spill as required by state guidelines and laws.

EPA Reg. No. 72468-7
EPA Est. 66887-CA-007

Net contents _____ Gallons
Batch Code _____

Manufactured by: *PreChem, Inc* 9663 Santa Monica Boulevard, Suite 593
Beverly Hills, CA 90210

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Storage: Store in a dry place. Do not store where children or animals may gain access.

Pesticide disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container disposal: Non-refillable container, Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Environmental hazards

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

FLO-X/MOLDWASH solutions carelessly spilled or applied to cropland or growing plants, including trees and shrubs, may kill or seriously retard plant growth. Do not contaminate water by cleaning of equipment or disposal of wastes.

Target organisms

FLO-X/MOLDWASH is an effective treatment for wood against decay, fungi, common molds including brown (i.e. *Peria*), white, and wet rots and wood-boring insects **such as** termites, beetles and carpenter ants:

*Subterranean termites:

Heterotermes, Reticulitermes, Coptotermes (Formosan)

*Drywood Termites: Kalotermites, incisitermes

*Dampwood Termites: Zootermopsis

*Carpenter Ants: Camponotus

*"False" PowderPost Beetles: Bostrichidae

*Furniture and Deathwatch Beetles: Anobiidae

*Old House Borers: Longhorn beetles, Cerambycidae

*Ambrosia Beetles: Scolytidae

FLO-X/MOLDWASH is an effective treatment for cleaning surface mold and mildew on porous and non-porous surfaces such as ceramic, tiles, painted or varnished areas, metal framing, bathroom kitchen fixtures, fiberglass and vinyl.

Preparation of treatment solution

FLO-X/MOLDWASH is a ready-to-use solution that can be applied without any preparation of the solution.

If using as a foam: Simply add a surfactant/foaming agent to the solution. Typically 1-2 ounces of foaming agent added to the aqueous solution will produce foam with the desired expansion ratios of approximately 20 to 1 (approx. 20 gallons of foam per 1 gallon of *FLO-X/MOLDWASH* aqueous solution). *FLO-X/MOLDWASH* foam should be of a consistency that adheres to wood surfaces, so that run-off is minimized. Since each foam machine can produce different foams, refer to the manufacturer manuals and the surfactant's label for specific instructions.

Directions for use

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

General information

FLO-X/Moldwash is a ready-to-use solution with insecticidal, termiticidal and fungicidal properties. This product cannot be tank mixed with other products. This product will protect only treated wood and gypsum facing.

This product can be used in coatings to treat all interior and exterior wood structural components which when utilized will be protected from rain and not in direct contact with the ground. The treatment of lumber is permanent even after cutting and finishing providing the wood is not exposed to water for a prolonged period of time or in contact with the ground.

This product can be used for preventative treatment of wood in existing structures (before signs of infestation), for pre-treatment of wood during construction and for remedial treatment of wood infested with termites, carpenter ants, wood-boring beetle larvae and mold and fungus, as listed below.

FLO-X/Moldwash is recommended for wood and cellulose materials, in accordance with the specific treatment methods described herein. This product should be applied only to treat bare wood, plywood and particle board where an intact water repellent barrier such as paint, stain or a sealer is not present. **Do not apply to foam-board.**

FLO-X/Moldwash is effective for all interior and exterior wood that will be protected from excessive rain and not in direct contact with soil. Types of wood include, but are not limited to, all types of lumber, logs and plywood. **Use of this product does not substitute for mechanical alteration, soil treatment or foundation treatment, but is merely a supplement.**

This product is toxic to wood-destroying insects, molds and fungi, but surface etching of treated wood by target organisms may occur.

Application of *FLO-X/Moldwash* to control wood-destroying organisms must be part of an Integrated Pest Management (IPM) strategy. Current PreChem, Inc. specifications and technical bulletins must be followed for all treatment methods.

Do not use to treat lumber that will contact soil or be exposed to leaching by weather.

Application

FLO-X/Moldwash may be used as a solution or foam. For remedial control of mold, fungi and common molds attacking wood, or for protection of wood against future infestations, 2 applications of the *FLO-X/Moldwash* aqueous solution are normally required.

Solutions

Apply solutions by brush or spray until the wood surface is thoroughly wet, at a rate of approximately 1 gallon per 200 square feet of wood surface area. Spray evenly using a medium or coarse spray at low pressure (20-30 psi). Best results and penetration will be obtained when ambient temperatures are above 55°F. Do not spray frozen wood, painted or waterproofed surfaces.

Foam

Apply foam so that all accessible wood surfaces are covered with foam at a rate of approximately 1 gallon per 200 square feet of wood surface area. Spray evenly using a medium or coarse spray at low pressure (20-30 psi). Where possible, place foam between wood joints or abutting wood surfaces. In wall voids, inject enough foam to contact *drywall* and wood surfaces of studs in the wall or the target area desired. Best results and penetration will be obtained when ambient temperatures are above 55°F. Do not foam frozen wood, painted or waterproofed surfaces.

Pressure processes

Pressure treatment procedures must rigidly adhere to the standards of PreChem, Inc. and/or those of the American Wood Preservers' Association. If several species are being treated at once, choose the treating schedule for the most difficult to treat species.

Preventative treatment

Application of *FLO-X/Moldwash* solution and foam will prevent infestation of wood termites, carpenter ants, wood-boring beetles, mold and fungus.

Directions for use continued

Carpenter ants do not excavate treated surfaces and the eggs of wood-boring beetles laid on treated surfaces show reduced hatch rates; those larvae that do emerge die as they bore into the treated wood.

Drilling and injecting

Application may also be by drilling and then injecting the solution or foam under pressure into sound wood or until runoff is observed from entry/exit holes of infested wood. Injection holes (approximately 1/8 inch diameter) should be drilled in the area of suspected infestation, preferably in a diamond pattern with the long axis (12-16 inches) along the grain and the short axis (4-6 inches) across. Drill holes approximately 1/4 of the thickness of the beam. The solution is injected under pressure (65-70 psi) for 15-60 seconds in each hole. Please refer to PreChem, Inc. technical bulletin for further details.

Remedial treatment

FLO-X/Moldwash solution and foam will penetrate dry wood down to 1/2 inch below treated surfaces. Established infestations of termites and carpenter ants at greater depths may be controlled by drilling and injection of *FLO-X/Moldwash*. Beetle larvae at greater depths may not be immediately controlled by surface treatment, nor even by drilling and injection, but will eventually be killed by ingesting the *FLO-X/Moldwash* treated wood as they come to the surface to pupate.

Attics, crawlspaces and basements

Spray *FLO-X/Moldwash* to all accessible wood: rafters, trusses, top-plates, ceiling joists, plywood, particleboard, flooring, sub-floor etc. This application will control an infestation even when certain parts of the gallery are not directly sprayed. This has been a very effective technique in spot treating for control of drywood termites, mold and fungus.

Pre-treatment to wood – new construction

Spray or foam applications of *FLO-X/Moldwash* may also be made to wood during construction. Apply solution to all accessible surfaces of bare wood at a rate of approximately 1 gallon per 200 square feet of wood surface area. Application should be performed after framing and roofing are in place and before drywall and insulation are installed. Avoid spraying electrical components. Protect wood from excessive rain.

Exterior wood

FLO-X/Moldwash can be applied to bare siding, trim or logs. Applications can be made by spray or pressure injection techniques. Painted or sealed wood can be treated by pressure injection or the sealing coat can be removed prior to application. Following treatment, exterior wood surfaces should be sealed. Wood should be completely dry before a sealing coat (paint, varnish or waterproofing seal) can be applied.

Decks

FLO-X/Moldwash can be used to treat wood decks. Prepare the deck by removing any dirt, debris or sealants that will interfere with the application and absorption of *FLO-X/Moldwash*. After the deck has dried (dry to the touch) two applications of *FLO-X/Moldwash* can then be applied to the wood. Protect any surrounding plants, ornamentals from accidental contact with the solution. Following treatment the deck should be allowed to dry before a sealing coat is applied.

FLO-X/Moldwash is **FOR NON-FOOD USE ONLY.**

This product cannot be tank mixed with other products. In the home, remove or cover exposed food, food handling surfaces, and cooking utensils. Wash thoroughly after treatment and before reuse. Do not use in any type of food processing plant (meat, poultry, shell egg, etc.) or food handling area. **DO NOT APPLY TO FOOD.** Do not use in cafeterias, kitchens, bakeries, meat packing plants, food processing plants, or any type of food handling establishment. Do not apply in classrooms when in use. Do not use in aircraft cabins. Do not apply to patient rooms in hospitals and nursing homes while occupied.

Such applications are not a substitute for mechanical alteration, soil treatment or foundation treatment but are merely a supplement. When spraying overhead interior areas of homes, apartment buildings and all other dwellings, cover or protect surfaces below the area being treated with plastic sheeting or other material which can be disposed of if contamination from dripping or splashing occurs.

Current PreChem, Inc. specifications/technical bulletins should be followed for all treatment methods to ensure adequate chemical loadings in wood.

Notice Because of many varying conditions affecting use and application, manufacturer warns buyer that these may impair or vary the results or effects of the use of this product. In any event, complete prevention of decay by fungi or other organisms is not guaranteed. To the extent consistent with applicable law, neither manufacturer nor seller shall be liable in respect to any injury or damages suffered by reason of the use of this product for a purpose not indicated by the label, or when used contrary to the directions or instructions hereon, nor with respect to breach of any warranty not expressly specified herein. Buyer accepts this material subject to these terms, and assumes all risk of usage and handling except when used or handled in accordance with this label. To the extent consistent with applicable law, there are no express warranties on PreChem, Inc. or implied warranties of merchantability or fitness for any particular purpose, except as specifically