

PM 33

72679-1

12-3-99

104

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 2 460

EPA Reg. Number:

72679-1

Date of Issuance:

DEC 03 1999

NOTICE OF PESTICIDE:

- x Registration
Reregistration

Term of Issuance:

Conditional

Name of Pesticide Product:

Copper Paint No. 5
Green

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Shackelford-Porter Copper Paints, Inc.
P.O. Box 3456
Portsmouth, VA. 23701

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling change listed below before you release the product for shipment:

- a. Revise the EPA Registration Number to read, "EPA Reg. No. 72679-1".

Signature of Approving Official:

Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510C)

[Handwritten Signature]

Date:

DEC 03 1999

EPA Form 8570-6

CONCURRENCES

Table with columns for SYMBOL, SURNAME, and DATE.

page 2
EPA Reg. No. 72679-1

3. Submit copies of the revised final printed label for the record.

The Confidential Statement of Formula dated August 15, 1999 is acceptable.


4. Please refer to the enclosed chemistry science review. Note and correct the deficiencies in your Confidential Statement of Formula and resubmit to the Agency within 30 days.

A stamped copy of the label is enclosed for your records.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

If you have any questions concerning this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,



Marhsall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510C)

Enclosure

Best copy Available

SHACKELFORD PORTER

Copper Paints, Inc.

Anti-Fouling Speckle

Copper Paint No. 5

ACCEPTED
BY THE
EPA REGISTERED DATED

DEC 03 1999

For this pesticide
see the label for use, no

7-16-99-1

ACTIVE INGREDIENTS

CUPROUS OXIDE
INERT INGREDIENTS

TOTAL

100.00

(Copperate Metallizing 66189)

This Product Contains Petroleum Distillates

WARNING - Keep Out of Reach of Children

IF SWALLOWED: Drink promptly a large quantity of water. Avoid Alcohol. Get Medical Attention. **IF INHALED:** Remove to fresh air. Get Medical Attention. **IF ON SKIN:** Wash with plenty of soap and water. If irritation persists, Get Medical Attention. **EYES:** Flush with plenty of water for at least 15 minutes. Get Medical Attention. **SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.**

ONE GALLON

WARNING! COMBUSTIBLE.

DANGEROUS IF SWALLOWED.
See CAUTIONS elsewhere on label.

4024

ANTI-FOULING COPPER PAINT

SHACKELFORD PORTER

Copper Paints, Inc.

3.785 LITERS

SHACKELFORD PORTER

Copper Paints, Inc.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, goggles, cotton shirt, pants and hat. May be fatal if swallowed. Do not breathe vapors or spray mist while spraying paint or sanding boat. Wear a mask or respirator (only approved by the Mining, Enforcement and Safety Administration and the National Institute of Occupational Safety and Health). Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water. Use chemical equipment or disposal vessels. Do not allow wash water and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Do Not Store Near An Open Flame

STORAGE AND DISPOSAL

STORAGE - Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Store in a cool, dry area away from heat, sparks and flame.

PESTICIDE DISPOSAL - Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL - Dispose of container by triple rinsing (or equivalent) and recycling or reconditioning or puncturing and disposing of in a sanitary landfill, or by other approved state and local procedures. All burned sludge or sludge

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

This is a copper oxide pigmented coating formulation especially to prevent the attachment of both plant and animal fouling on boats, barges, crab pots, lobster traps and vessels immersed in both sea water and brackish water.

When used over steel or aluminum surfaces, a primer coating is required to prevent accelerated corrosion. The coating requires no primer when used directly over fibreglass or steel. Boat performance (two 12 coats are recommended). The theoretical coverage of the product is 40 sq. ft. per gallon. Let per gallon when applied in the recommended dry film thickness.

Do not spray the surface to be coated until the surface is clean and free of dirt, oil, grease, wax, and other contaminants. Wash with water and detergent. Rinse thoroughly. Do not use any other preparation or treatment to prevent oxidation.

Clean the surface to be coated. Remove all loose dirt, grease, oil, and other contaminants. Wash with water and detergent. Rinse thoroughly. Do not use any other preparation or treatment to prevent oxidation. Use for painting, spraying, or dipping. Do not use for surface preparation. Will result in unsatisfactory performance. Do not use in all dust, dirt, and other surface contaminants. Surface generated by the cleaning process prior to painting.

Mix the coating with the high speed emulsion. Shake (minimum 10 min). (6) Intended for use on steel, aluminum, and copper. Thin the even though coating is too thick to apply easily. Thin with mineral spirits or M.A. 2-Naphthol. Apply by roller, brush, or spray. Follow the instructions and apply the correct film thickness. Allow a minimum of 24 hours before painting over. Allow a minimum of 24 hours before unblocking.