

PM 33

72679-4

12-3-99

1 of 4

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 2 460

EPA Reg. Number:

Date of Issuance:

72679-4

DEC 03 1999

Term of Issuance:

Conditional

NOTICE OF PESTICIDE:

- x Registration
Reregistration

(under FIFRA, as amended)

Name of Pesticide Product:

Copper Paint No. 2
Green

Name and Address of Registrant (include ZIP Code):

Shackelford-Porter Copper Paints, Inc.
P.O. Box 3456
Portsmouth, VA. 23701

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling change listed below before you release the product for shipment:

- a. Revise the EPA Registration Number to read, "EPA Reg. No. 72679-4"

Signature of Approving Official:

Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510C)

Date:

DEC 03 1999

EPA Form 8570-6

CONCURRENCES

Table with columns for SYMBOL, SURNAME, and DATE, used for recording concurrences.

page 2  
EPA Reg. No. 72679-4

3. Submit copies of the revised final printed label for the record.

The Confidential Statement of Formula dated August 15, 1999 is acceptable.


4. Please refer to the enclosed chemistry science review. Note and correct the deficiencies in your Confidential Statement of Formula and resubmit to the Agency within 30 days.

A stamped copy of the label is enclosed for your records.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

If you have any questions concerning this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,



Marhsall Swindell  
Product Manager 33  
Regulatory Management Branch 1  
Antimicrobials Division (7510C)

Enclosure

Best copy Available

# SEACKILLFORD BORNER

REGISTERED TRADE NAME

Copper Paint No. 2

### ACTIVE INGREDIENTS

CUPROUS OXIDE .....	21.73%
INERT INGREDIENTS .....	78.27%
(Copper as Metallic) 21.73%	
TOTAL .....	100.00%

**This Product Contains Petroleum Distillates**

**WARNING - Keep Out Of Reach Of Children**

**IF SWALLOWED:** Drink promptly a large quantity of water. Avoid Alcohol. Get Medical Attention. **IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get Medical Attention. **IF ON SKIN:** Wash with plenty of soap and water. If irritation persists, Get Medical Attention. **IF IN EYES:** Flush with plenty of water for at least 15 minutes. Get Medical Attention.

**SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS**

ACCEPTED  
With COMMENTS  
EPA Letter Dated:

DEC 03 1999

Federal Insecticide,  
Fungicide and Rodenticide Act as  
applied to the pesticide,  
under EPA Reg. No.

72679-4

ONE GALLON

WARNING! COMBUSTIBLE.

DANGEROUS OR FATAL IF SWALLOWED.  
See CAUTIONS elsewhere on label.

3 of 4

# ANTI-FOULING COPPER PAINT

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS & DOMESTIC ANIMALS

#### WARNING

**CAUSES EYE IRRITATION.** Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing, such as gloves, long sleeved cotton shirt, overalls and hat. May be fatal if swallowed. Do not breathe vapor or spray mist while spraying paint or sanding boat surface. Wear a mask or respirator jointly approved by the Mine Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

#### ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water or cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

#### PHYSICAL or CHEMICAL HAZARDS

Do Not Use or Store Near An Open Flame

#### STORAGE AND DISPOSAL

**STORAGE:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Store in a cool, dry area away from heat or open flame.

**PESTICIDE DISPOSAL** - Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL** - Dispose of container by triple rinse (or equivalent) and recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures. If burned stay out of smoke.

## DIRECTIONS FOR USE

### IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

This is a cuprous oxide pigmented coating, formulated especially to prevent the attachment of both plant and animal fouling on boats, barges, crab pots, lobster pots, and vessels immersed in both sea water and "brackish" water.

When used over steel or aluminum surfaces, a primer coating is required to prevent accelerated corrosion. This coating requires no primer when used directly over fiberglass or wood. For optimum performance, two (2) coats are recommended. The theoretical coverage of this product is at least 400 square feet per gallon when applied to the recommended dry film thickness.

To prepare the surface coating, remove all old coating and fouling residue by either washing with high pressure water, scraping or by dry sanding. Be sure to use the proper protective equipment to prevent inhalation or ingestion of the paint dust generated.

Clean dry surface, free of scale, corrosion, dirt, grease, oil, marine fouling, or other foreign matter will provide the optimum performance of this coating when used for either complete coating or touch-up. Inadequate surface preparation will result in unsatisfactory performance. Be sure to remove all dust, debris and other surface contaminants that are generated by the cleaning process prior to painting.

Mix the coating with either a high speed mixer or paint shaker for minimum of five (5) minutes to insure complete pigment reincorporation. Thin in the event that the coating is too thick to apply easily. Thin with mineral spirits or VM & P Naphtha.

Apply by either brush, roller or spray. Be sure to follow mixing instructions and apply the correct film thickness. Allow a minimum of four (4) hours between coats and a minimum of two (2) hours before undocking vessel.

SHACKELFORD  
PORTER

Copper Paints, Inc.  
"Anti-Fouling Specialist"

3.785 LITERS

SHACKELFORD PORTER  
Copper Paints, Inc.

4/20/74